

ASSIGNMENT DAY-3 GIT

1. Create a private github repo named "i-am-a-git-noob"
2. Create a new repository on local in an empty directory (NOTE: do not clone)
Ques: What changes did you observe in the current directory after initializing local repo?
3. Point remote of your local git repo to the newly created repo on github
4. Print current git configs on terminal
5. Update git config with your name and email address (only for current repository)
6. Create a file named "test1.txt"
7. Added line with text "first line in file" in "test1.txt".
8. Push this file to your github repo.

```
vivswsyvora@MacBook-Air-de-VivswSyvora ~ % ls
Desktop      Library      Pictures  hello
Documents    Movies       Public    sample
Downloads    Music        bashrc

vivswsyvora@MacBook-Air-de-VivswSyvora ~ % cd Documents
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % mkdir i-am-a-git-noob
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % ls
i-am-a-git-noob  test-folder  test-repo
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % cd i-am-a-git-noob
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % ls
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git init
Initialized empty Git repository in /Users/vivswsyvora/Documents/i-am-a-git-noob/.git/
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % ls
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % ls -la
.      ..      .git
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git remote add origin
git@github.com:Vivswaan-Singh/i-am-a-git-noob.git
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git config --list
credential.helper=osxkeychain
init.defaultbranch=main
user.name=Vivsaan-Singh
user.email=vivswaan.singh@syvora.com
core.repositoryformatversion=0
core.filemode=true
core.bare=false
core.logallrefupdates=true
core.ignorecase=true
core.precomposeunicode=true
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git config user.name "Vivswaan Singh"
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git config user.email "vivswaan.singh@syvora.com"
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git config --list
credential.helper=osxkeychain
init.defaultbranch=main
user.name=Vivsaan-Singh
user.email=vivswaan.singh@syvora.com
core.repositoryformatversion=0
core.filemode=true
core.bare=false
core.logallrefupdates=true
core.ignorecase=true
core.precomposeunicode=true
remote.origin.url=git@github.com:Vivswaan-Singh/i-am-a-git-noob.git
```

```
remote.origin.fetch=+refs/heads/*:refs/remotes/origin/*
user.name=Vivswaan Singh
user.email=vivswaan.singh@syvora.com
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % echo "first line in file" > test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % ls
test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % cat test1.txt
first line in file
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git add test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git commit -m
error: switch `m' requires a value
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git commit -m "test1.txt file added."
[main (root-commit) 0bcff71] test1.txt file added.
 1 file changed, 1 insertion(+)
 create mode 100644 test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git push -u origin main
Enter passphrase for key '/Users/vivswsyvora/.ssh/id_ed25519':
Enumerating objects: 3, done.
Counting objects: 100% (3/3), done.
Writing objects: 100% (3/3), 246 bytes | 246.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0
To github.com:Vivswaan-Singh/i-am-a-git-noob.git
 * [new branch]    main -> main
branch 'main' set up to track 'origin/main'.
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob %
```

```

vivswsyvora@MacBook-Air-de-VivswSyvora ~ % cd Documents
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % mkdir i-am-a-git-noob
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % ls
i-am-a-git-noob test-folder test-repo
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % cd i-am-a-git-noob
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % ls
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git init
Initialized empty Git repository in /Users/vivswsyvora/Documents/i-am-a-git-noob/.git/
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % ls
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % ls -a
.
..
.git
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git remote add origin git@github.com:Vivswaan-Singh/i-am-a-git-noob.git
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git config --list
credential.helper=osxkeychain
init.defaultbranch=main
user.name=Vivswaan-Singh
user.email=vivswaan.singh@syvora.com
core.repositoryformatversion=0
core.filemode=true
core.bare=false
core.logallrefupdates=true
core.ignorecase=true
core.precomposeunicode=true
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git config user.name "Vivswaan Singh"
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git config user.email "vivswaan.singh@syvora.com"
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git config --list
credential.helper=osxkeychain
init.defaultbranch=main
user.name=Vivswaan-Singh
user.email=vivswaan.singh@syvora.com
core.repositoryformatversion=0
core.filemode=true
core.bare=false
core.logallrefupdates=true
core.ignorecase=true
core.precomposeunicode=true
remote.origin.url=git@github.com:Vivswaan-Singh/i-am-a-git-noob.git
remote.origin.fetch=+refs/heads/*:refs/remotes/origin/*
user.name=Vivswaan Singh
user.email=vivswaan.singh@syvora.com
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % echo "first line in file" > test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % ls
test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % cat test1.txt
first line in file
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git add test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git commit -m
error: switch 'm' requires a value
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git commit -m "test1.txt file added."
[main (root-commit) 0bcff71] test1.txt file added.
 1 file changed, 1 insertion(+)
 create mode 100644 test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git push -u origin main
Enter passphrase for key '/Users/vivswsyvora/.ssh/id_ed25519':
Enumerating objects: 3, done.
Counting objects: 100% (3/3), done.
Writing objects: 100% (3/3), 246 bytes | 246.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0
To github.com:Vivswaan-Singh/i-am-a-git-noob.git
 * [new branch]      main -> main
branch 'main' set up to track 'origin/main'.
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % █

```

9. Append line with text "second line in file" in "test1.txt".
10. Add file to the staging area.
11. Check the status of the file in all staging area
12. Append line with text "Third line in file" in "test1.txt". (Note status of files across different areas).
13. Remove "test1.txt" from the staging area.

```

vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % echo "second line in file" >> test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % cat test1.txt
first line in file
second line in file
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git status
On branch main
Your branch is up to date with 'origin/main'.
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)

```

modified: test1.txt

no changes added to commit (use "git add" and/or "git commit -a")

```
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git add test1.txt
```

```
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git status
```

On branch main

Your branch is up to date with 'origin/main'.

Changes to be committed:

(use "git restore --staged <file>..." to unstage)

modified: test1.txt

```
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % echo "third line in file" >> test1.txt
```

```
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git status
```

On branch main

Your branch is up to date with 'origin/main'.

Changes to be committed:

(use "git restore --staged <file>..." to unstage)

modified: test1.txt

Changes not staged for commit:

(use "git add <file>..." to update what will be committed)

(use "git restore <file>..." to discard changes in working directory)

modified: test1.txt

```
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git restore --staged test1.txt
```

```
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git status
```

On branch main

Your branch is up to date with 'origin/main'.

Changes not staged for commit:

(use "git add <file>..." to update what will be committed)

(use "git restore <file>..." to discard changes in working directory)

modified: test1.txt

no changes added to commit (use "git add" and/or "git commit -a")

```
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git add test.txt
```

fatal: pathspec 'test.txt' did not match any files

```
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git status
```

On branch main

Your branch is up to date with 'origin/main'.

Changes not staged for commit:

(use "git add <file>..." to update what will be committed)

(use "git restore <file>..." to discard changes in working directory)

modified: test1.txt

no changes added to commit (use "git add" and/or "git commit -a")

```

vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % echo "second line in file" >> test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % cat test1.txt
first line in file
second line in file
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git status
On branch main
Your branch is up to date with 'origin/main'.

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   test1.txt

no changes added to commit (use "git add" and/or "git commit -a")
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git add test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git status
On branch main
Your branch is up to date with 'origin/main'.

Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        modified:   test1.txt

vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % echo "third line in file" >> test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git status
On branch main
Your branch is up to date with 'origin/main'.

Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        modified:   test1.txt

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   test1.txt

vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git restore --staged test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git status
On branch main
Your branch is up to date with 'origin/main'.

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   test1.txt

no changes added to commit (use "git add" and/or "git commit -a")

```

14. Create commit with message "My First Commit"

15. Push commit to the remote repo

NOTE: checklist commits pushed to the remote

16. Update message of last commit "My First Commit" to "My Second Commit"
(without creating a new commit)

17. Push commit with the updated message to the remote repo

```

vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git add test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git status
On branch main
Your branch is up to date with 'origin/main'.
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        modified:   test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git commit -m "My First Commit"

```



```

[main 0ef0c95] My First Commit
1 file changed, 2 insertions(+)
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git push
Enter passphrase for key '/Users/vivswsyvora/.ssh/id_ed25519':
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 8 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 288 bytes | 288.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0
To github.com:Vivswaan-Singh/i-am-a-git-noob.git
0bcff71..0ef0c95 main -> main
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git commit --amend -m "My Second Commit"
[main 709a654] My Second Commit
Date: Fri May 16 12:07:08 2025 +0530
1 file changed, 2 insertions(+)
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git push --force
Enter passphrase for key '/Users/vivswsyvora/.ssh/id_ed25519':
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 8 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 292 bytes | 292.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0
To github.com:Vivswaan-Singh/i-am-a-git-noob.git
+ 0ef0c95...709a654 main -> main (forced update)
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob %

```

```

[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git add test1.txt
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git status
On branch main
Your branch is up to date with 'origin/main'.

Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        modified:   test1.txt

[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git commit -m "My First Commit"
[main 0ef0c95] My First Commit
1 file changed, 2 insertions(+)
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git push
[Enter passphrase for key '/Users/vivswsyvora/.ssh/id_ed25519':
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 8 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 288 bytes | 288.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0
To github.com:Vivswaan-Singh/i-am-a-git-noob.git
0bcff71..0ef0c95 main -> main
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git commit --amend -m "My Second Commit"
[main 709a654] My Second Commit
Date: Fri May 16 12:07:08 2025 +0530
1 file changed, 2 insertions(+)
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git push --force
[Enter passphrase for key '/Users/vivswsyvora/.ssh/id_ed25519':
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 8 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 292 bytes | 292.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0
To github.com:Vivswaan-Singh/i-am-a-git-noob.git
+ 0ef0c95...709a654 main -> main (forced update)
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob %

```

18. Check the difference between the last and second last commits.

```
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git log --oneline
709a654 (HEAD -> main, origin/main) My Second Commit
0bcff71 test1.txt file added.
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git diff 0bcff71 709a654
diff --git a/test1.txt b/test1.txt
index f581c70..f3c05a1 100644
--- a/test1.txt
+++ b/test1.txt
@@ -1 +1,3 @@
 first line in file
+second line in file
+third line in file
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git diff HEAD^ HEAD
diff --git a/test1.txt b/test1.txt
index f581c70..f3c05a1 100644
--- a/test1.txt
+++ b/test1.txt
@@ -1 +1,3 @@
 first line in file
+second line in file
+third line in file
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob %
```

```
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git log --oneline
709a654 (HEAD -> main, origin/main) My Second Commit
0bcff71 test1.txt file added.
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git diff 0bcff71 709a654

diff --git a/test1.txt b/test1.txt
index f581c70..f3c05a1 100644
--- a/test1.txt
+++ b/test1.txt
@@ -1 +1,3 @@
 first line in file
+second line in file
+third line in file
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git diff HEAD^ HEAD
diff --git a/test1.txt b/test1.txt
index f581c70..f3c05a1 100644
--- a/test1.txt
+++ b/test1.txt
@@ -1 +1,3 @@
 first line in file
+second line in file
+third line in file
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % █
```

19. Revert the last commit and check the updated commit logs history.
20. Append line with text "Fourth line in file" in "test1.txt" and commit it.
21. Update the last commit such that the "test1.txt" also contains "Fifth line in file" (without creating a new commit)
22. Push the updated commits to the remote repository

```

vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git log --oneline
709a654 (HEAD -> main, origin/main) My Second Commit
0bcff71 test1.txt file added.
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git revert HEAD
[main 11c9d1d] Revert "My Second Commit"
1 file changed, 2 deletions(-)
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git log --oneline
11c9d1d (HEAD -> main) Revert "My Second Commit"
709a654 (origin/main) My Second Commit
0bcff71 test1.txt file added.
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % echo "Fourth line in file" >> test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % cat test1.txt
first line in file
Fourth line in file
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git add test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git commit -m "Added fourth line"
[main a82453f] Added fourth line
1 file changed, 2 insertions(+)
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % echo "Fifth line in file" >> test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % cat test1.txt
first line in file
Fourth line in file
Fifth line in file
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git add test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git commit --amend --no-edit
[main 176d101] Added fourth line
Date: Fri May 16 12:22:37 2025 +0530
1 file changed, 3 insertions(+)
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git push --force
Enter passphrase for key '/Users/vivswsyvora/.ssh/id_ed25519':
Enumerating objects: 8, done.
Counting objects: 100% (8/8), done.
Delta compression using up to 8 threads
Compressing objects: 100% (3/3), done.
Writing objects: 100% (6/6), 560 bytes | 560.00 KiB/s, done.
Total 6 (delta 0), reused 0 (delta 0), pack-reused 0
To github.com:Vivswaan-Singh/i-am-a-git-noob.git
709a654..176d101 main -> main
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob %

```



```

[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git log --oneline
709a654 (HEAD -> main, origin/main) My Second Commit
0bcff71 test1.txt file added.
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git revert HEAD
[main 11c9d1d] ReverttttMy Second Commit"
 1 file changed, 2 deletions(-)
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git log --oneline
11c9d1d (HEAD -> main) ReverttttMy Second Commit"
709a654 (origin/main) My Second Commit
0bcff71 test1.txt file added.
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % echo "Fourth line in file
[dquote> " >> test1.txt
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % cat test1.txt
first line in file
Fourth line in file

[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git add test1.txt
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git commit -m "Added fourth line"
[main a82453f] Added fourth line
 1 file changed, 2 insertions(+)
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % echo "Fifth line in file" >> test1.txt
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % cat test1.txt
first line in file
Fourth line in file

Fifth line in file
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git add test1.txt
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git commit --amend --no-edit
[main 176d101] Added fourth line
Date: Fri May 16 12:22:37 2025 +0530
 1 file changed, 3 insertions(+)
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git push --force
[Enter passphrase for key '/Users/vivswsyvora/.ssh/id_ed25519':
Enumerating objects: 8, done.
Counting objects: 100% (8/8), done.
Delta compression using up to 8 threads
Compressing objects: 100% (3/3), done.
Writing objects: 100% (6/6), 560 bytes | 560.00 KiB/s, done.
Total 6 (delta 0), reused 0 (delta 0), pack-reused 0
To github.com:Vivswaan-Singh/i-am-a-git-noob.git
 709a654..176d101  main -> main
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % █

```

23. Append some content in "test1.txt" file

24. Pull all the content from remote repository to local repository

```

vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % echo "Some Appended Content" >> test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % cat test1.txt
first line in file
Fourth line in file
Fifth line in file
Some Appended Content
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git status
On branch main
Your branch is up to date with 'origin/main'.
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   test1.txt

no changes added to commit (use "git add" and/or "git commit -a")
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git pull
Enter passphrase for key '/Users/vivswsyvora/.ssh/id_ed25519':
Already up to date.
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % cat test1.txt
first line in file

```

Fourth line in file
Fifth line in file
Some Appended Content
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob %

```
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % echo "Some Appended Content" >> test1.txt
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % cat test1.txt
first line in file
Fourth line in file

Fifth line in file
Some Appended Content
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git status
On branch main
Your branch is up to date with 'origin/main'.

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   test1.txt

no changes added to commit (use "git add" and/or "git commit -a")
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % git pull
[Enter passphrase for key '/Users/vivswsyvora/.ssh/id_ed25519':
Already up to date.
[vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob % cat test1.txt
first line in file
Fourth line in file

Fifth line in file
Some Appended Content
vivswsyvora@MacBook-Air-de-VivswSyvora i-am-a-git-noob %
```

25. Clone the remote repository to some other directory in your local system.

```
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % ls
cloned-noob      i-am-a-git-noob  test-folder      test-repo
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % mkdir cloned-local-repo
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % ls
cloned-local-repo  i-am-a-git-noob  test-repo
cloned-noob        test-folder
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % cd cloned-local-repo
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-local-repo % ls
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-local-repo % git clone ~/Documents/i-am-a-git-noob
cloned-noob-repo
Cloning into 'cloned-noob-repo'...
done.
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-local-repo % ls
cloned-noob-repo
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-local-repo %
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-local-repo % cd cloned-noob-repo
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-noob-repo % ls
test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-noob-repo % ls -la
.      ..      .git      test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-noob-repo % cat test1.txt
first line in file
Fourth line in file
Fifth line in file
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-noob-repo % git remote -v
origin    /Users/vivswsyvora/Documents/i-am-a-git-noob (fetch)
```

origin /Users/vivswsyvora/Documents/i-am-a-git-noob (push)
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-noob-repo %

```
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % ls
cloned-noob    i-am-a-git-noob test-folder    test-repo
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % mkdir cloned-local-repo
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % ls
cloned-local-repo  i-am-a-git-noob    test-repo
cloned-noob        test-folder
vivswsyvora@MacBook-Air-de-VivswSyvora Documents % cd cloned-local-repo
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-local-repo % ls
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-local-repo % git clone ~/Documents/i-am-a-git-noob cloned-noob-repo
Cloning into 'cloned-noob-repo'...
done.
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-local-repo % ls
cloned-noob-repo
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-local-repo %
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-local-repo % cd cloned-noob-repo
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-noob-repo % ls
test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-noob-repo % ls -a
.      ..      .git      test1.txt
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-noob-repo % cat test1.txt
first line in file
Fourth line in file

Fifth line in file
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-noob-repo % git remote -v
origin /Users/vivswsyvora/Documents/i-am-a-git-noob (fetch)
origin /Users/vivswsyvora/Documents/i-am-a-git-noob (push)
vivswsyvora@MacBook-Air-de-VivswSyvora cloned-noob-repo % █
```

BY: Vivswaan Singh