


FISA 9 / 11

Contravantuiri si scoatem proptelele

~2 ore

CRITIC



| ST stalp | GR grinda | JO joista | DL dusumea | PO polita |  C1/C2 coltar

| CF diagonala

PIESE PENTRU ACEASTA ETAPA



CF

6

Contrafisa (offcut)
diagonale



H1

~18

Heco 8x200
3 / capat

SCULE

Fierastrau

Bormasina

Echer

● cap surub (fata vazuta)

● surub/piulita ascuns (pe spate)

→ directia de insurubare

oblic = la unghi (toe-screw)


Folosim **suruburi + buloane**, nu cuie. (Singurul cui e distantierul de 5 mm la dusumea.)

1


Masoara si taie capatul fiecarei contrafise (diagonala) pe potriveala.

ZOOM · CUM SE PRINDE

CAPAT pe stalp




DIRECTIE



H1 x3 / fiecare capat · fara coltar

2

Monteaza contravantuirile in planul stang, drept, fata si sub nasul consolei. La contrafisa de sub nas prinde-o pe LATERAL sau adauga un coltar — acolo lucreaza si la intindere. Platforma devine rigida.



contrafise CF


! CRITIC — opreste-te si verifica.

3


Prinde fiecare capat cu 3 suruburi H1.

ZOOM · CUM SE PRINDE

CAPAT pe stalp




DIRECTIE



H1 x3 / fiecare capat · fara coltar

4

SCOATE proptelele de la baza. Cele de la varful stalpilor inalti din spate RAMAN pana la peretii din Faza 2.



! CRITIC — opreste-te si verifica.

GATA CAND

- ☐ Diagonale pe toate planurile + sub consola
- ☐ 3 suruburi / capat
- ☐ Proptele baza scoase; varf raman