


FISA 4 / 11

Grinda din spate pe polite

~1 ora

CRITIC

2 persoane



stalp grinda joista dusumea polita coltar metal diagonala/proptea

PIESE PENTRU ACEASTA ETAPA



GR

1

Grinda glulam
90x200
grinda spate



C2

2

Coltar 90x90x65
coltar anti-smulgere



H1

~6

Heco 8x200
3 oblice / capat

SCULE

2 persoane


Bormasina

Nivela

- cap surub (fata vazuta)
- ⦿ surub/piulita ascuns (pe spate)
- ➔ directia de insurubare
- oblic** = la unghi (toe-screw)

Folosim **suruburi + buloane**, nu cuie. (Singurul cui e distantierul de 5 mm la dusumea.)


- 1 Ridicati in DOI grinda din spate si asezati-o pe cele doua polite. Sta pe polita — nu o tineti voi.



! CRITIC — opreste-te si verifica.

2

Verifica fata de sus la +2072 si orizontalitatea pe toata lungimea.




3


Prinde grinda de fiecare stalp cu 3 suruburi H1 oblice PLUS un coltar metalic in stalp si in grinda (anti-smulgere). Grinda nu trebuie sa se poata ridica de pe polita.

ZOOM • CUM SE PRINDE

LATERAL



DE SUS



H1 oblic in stalp • 2 buc • tin grinda lipita

! CRITIC — opreste-te si verifica.

GATA CAND

- ☐ Grinda pe ambele polite
- ☐ Fata sus la +2072
- ☐ Coltar anti-smulgere la fiecare capat
- ☐ Buloane polita REVERIFICATE dupa asezarea grinzii