Opponent-Aware Policy Gradient as Stochastic Approximation: Local Meta-MAPG Convergence and Restart Globalisation

Anonymous Authors[1]

Abstract

Policy-gradient methods in general stochastic games admit local convergence guarantees near stable Nash policies, but these guarantees are usually stated for independent policy-gradient fields that do not anticipate opponent learning. Opponent-aware methods such as LOLA and Meta-MAPG add terms that differentiate through the future learning of other agents, and empirically alter both adaptation and equilibrium selection. This paper gives a stochastic-approximation account of this mechanism. We show that finite-unroll Meta-MAPG estimators decompose into the base game-gradient field plus an annealed opponent-aware perturbation, martingale-difference noise, and summable truncation/modeling bias. Consequently, Giannou et al.'s local convergence theorem applies to Meta-MAPG near strategically stable Nash equilibria of the original game. We then add a restart mechanism: if reinitialisations have positive probability of landing in the local basin, the number of failed epochs is geometrically bounded and the restarted process converges almost surely after finitely many restarts. Small tabular experiments support the proof obligations: peer-learning terms change equilibrium selection, restart budget acts as an equilibrium-selection mechanism, basin maps expand under opponent-aware shaping, and estimator variance decreases with batch size.

1. Introduction

Learning in stochastic games is hard because each learner faces both an evolving environment and other learners whose policies change in response to the same data. Recent work by Giannou et al. (2022) showed that policy-gradient methods converge locally to stable Nash policies in general stochastic games under strategic stability and second-order sufficiency conditions. This result is a strong baseline, but the update it analyses treats opponent learning as part of the background stochastic process rather than as an object to be shaped.

Opponent-aware policy gradients address this missing dependence. LOLA differentiates through an opponent's anticipated update (Foerster et al., 2018a; Letcher et al., 2019). Meta-MAPG derives a meta-policy-gradient theorem with three terms: the current-policy gradient, an own-learning gradient, and a peer-learning gradient that captures how the agent's current behaviour changes the future policies of other agents (Kim et al., 2021). These terms matter empirically, but the convergence status of the resulting stochastic process is less clear than for standard PG.

We show that this gap can be closed locally. Our first contribution is an estimator decomposition: under bounded rewards, smooth policies, controlled unroll length, and standard sampling assumptions, the Meta-MAPG update is a stochastic approximation to the base game-gradient field plus controlled opponent-aware terms. For the convergence theorem, these terms are annealed so that the limiting stationary points remain the stable Nash equilibria of the original stochastic game; constant shaping is used only as a finite-time basin diagnostic. Sampling error remains a martingale difference with bounded conditional second moment.

Our second contribution is a restart globalisation of the local theorem. Local convergence cannot become unconditional without information about the basin of attraction; even normal-form games can contain cycles and multiple attractors. However, if restarts draw from a full-support distribution on a compact policy-parameter set, every epoch has a fixed positive probability of starting in the local basin. This gives an almost-sure finite-restart guarantee and an explicit expected restart bound. In this view, restart budget is not merely a rescue heuristic; it is an equilibrium-selection resource whose effectiveness depends on basin mass. Experiments in Stag Hunt and iterated Prisoner's Dilemma then test the precise claims the theorem uses: component ablations, restart-budget selection, basin volume, and estimator variance.

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the International Conference on Machine Learning (ICML). Do not distribute.

2. Setup

2.1. Stochastic Games

We consider finite discounted stochastic games

$$\mathcal{G} = (N, \mathcal{S}, \{\mathcal{A}_i\}_{i\in N}, P, \{r_i\}_{i\in N}, \rho, \gamma_{\text{disc}}),$$

with finite state space $\mathcal{S}$, finite action sets $\mathcal{A}_i$, transition kernel P, bounded rewards $|r_i| \le R_{\max}$, initial-state distribution ρ, and discount factor $\gamma_{\text{disc}} \in [0, 1)$. Each agent has a differentiable stationary Markov policy $\pi_{\phi_i}(a_i \mid s)$ with parameter $\phi_i \in \mathbb{R}^{d_i}$; the joint parameter is $\phi = (\phi_i)_{i=1}^N \in \mathbb{R}^d$. The value of agent i is

$$J_i(\phi) = \mathbb{E}_{\rho,\pi_\phi}\left[\sum_{t\ge 0} \gamma_{\text{disc}}^t r_i(s_t, a_t)\right],$$

and the standard game-gradient field is

$$v(\phi) = \left(\nabla_{\phi_i} J_i(\phi)\right)_{i=1}^N.$$

First-order stationary points of this field correspond to Nash policies under the gradient-dominance property used by Giannou et al. (2022); finite stochastic games possess stationary Nash equilibria (Fink, 1964).

Definition 2.1 (Stable Nash and SOS)**.** A Nash parameter ϕ^* is stable if

$$\langle v(\phi), \phi - \phi^* \rangle < 0$$

for all $\phi \ne \phi^*$ sufficiently close to ϕ^*. It is second-order stationary (SOS) if there exist $\mu > 0$ and $\rho > 0$ such that

$$\langle v(\phi), \phi - \phi^* \rangle \le -\mu \|\phi - \phi^*\|^2$$

whenever $\|\phi - \phi^*\| \le \rho$.

The SOS condition is the quantitative stability condition that yields an attracting neighbourhood and a rate in Giannou et al. (2022). We use it as the local anchor.

2.2. Meta-MAPG Field

Meta-MAPG views learning as a Markov chain of joint policy parameters $\phi_0, \dots, \phi_L$, where each inner transition is produced by a policy-gradient update. For agent i, Kim et al. (2021) decompose the meta-gradient into

$$G_i^{\text{MAPG}} = G_i^{\text{cur}} + G_i^{\text{own}} + G_i^{\text{peer}}.$$

The current term is the usual policy-gradient score term. The own-learning term differentiates through how ϕ_i^0 affects agent i's adapted parameters $\phi_i^{1:L}$. The peer-learning term differentiates through how ϕ_i^0 affects other agents' future parameters $\phi_{-i}^{1:L}$. The peer term is the Meta-MAPG analogue of LOLA-style opponent shaping; the own term is absent from pure LOLA.

We write the population opponent-aware field as

$$F_L(\phi) = v(\phi) + M_L^{\text{own}}(\phi) + M_L^{\text{peer}}(\phi),$$

where L is the unroll length. In the convergence theorem we use the annealed update

$$\phi_{n+1} = \text{Proj}_{\mathcal{K}}\left[\phi_n + \alpha_n\left(\hat{v}_n + \lambda_n \hat{M}_{L_n,n}\right)\right], \quad (1)$$

where $\mathcal{K} \subset \mathbb{R}^d$ is compact, $\hat{M}_{L_n,n}$ estimates the combined own/peer Meta-MAPG correction, and λ_n controls the asymptotic size of opponent-aware shaping. The compact projection can be replaced by any standard boundedness mechanism; it is stated explicitly to keep the stochastic approximation argument clean.

Definition 2.2 (Nash-consistent shaping)**.** Let U be a neighbourhood of a stable Nash set $\mathcal{N}$ of the base game-gradient field v. A scheduled opponent-aware correction $\lambda_n M_{L_n}$ is Nash-consistent on U if its contribution to the stochastic-approximation recursion is either summable,

$$\sup_{\phi\in U} \|\lambda_n M_{L_n}(\phi)\| \le \beta_n, \qquad \sum_n \alpha_n \beta_n < \infty,$$

so the limiting ODE on U is $\dot{\phi} = v(\phi)$, or else its non-vanishing limit field $v + M$ has exactly the same isolated SOS equilibria in U as v with the same local attracting neighbourhoods. The convergence theorem uses the first, annealed case; the second case only records when constant shaping is locally equilibrium-preserving.

3. Assumptions

The assumptions separate inherited stochastic-approximation conditions from the new Meta-MAPG estimator requirement.

Assumption 1 (Step sizes and bounded iterates)**.** The step sizes satisfy $\alpha_n > 0$, $\sum_n \alpha_n = \infty$, and $\sum_n \alpha_n^2 < \infty$. Iterates remain in a compact set $\mathcal{K}$, either by projection in (1) or by an equivalent stability mechanism.

Assumption 2 (Meta-MAPG estimator decomposition)**.** The scheduled correction $\lambda_n M_{L_n}$ is Nash-consistent in the sense of Theorem 2.2. Accordingly, there is a locally Lipschitz effective field F–equal to v in the annealed case, or to an equilibrium-preserving limit $v + M$ in the non-vanishing case–such that the sampled update $g_n = \hat{v}_n + \lambda_n \hat{M}_{L_n,n}$ satisfies

$$g_n = F(\phi_n) + \xi_{n+1} + b_n,$$

where $\{\xi_{n+1}\}$ is a martingale-difference sequence adapted to $\mathcal{F}_n$ with

$$\mathbb{E}[\xi_{n+1} \mid \mathcal{F}_n] = 0, \qquad \mathbb{E}[\|\xi_{n+1}\|^2 \mid \mathcal{F}_n] \le \sigma^2,$$

and $\|b_n\| \le C\beta_n$ with $\sum_n \alpha_n \beta_n < \infty$.

Assumption 3 (Annealing and truncation)**.** The unroll schedule L_n and shaping schedule λ_n are chosen so that finite-unroll bias, opponent-modeling error, and annealed shaping error are absorbed into the summable sequence β_n of Assumption 2. A concrete sufficient condition for the theorem is: M_{L_n} is uniformly bounded on $\mathcal{K}$, $\sum_n \alpha_n \lambda_n < \infty$, and the residual finite-unroll/modeling error ϵ_n satisfies $\sum_n \alpha_n \epsilon_n < \infty$. Then the opponent-aware correction is a transient shaping term and the limiting ODE remains the base game-gradient flow $\dot{\phi} = v(\phi)$.

Assumption 4 (Strategic stability)**.** The stable set $\mathcal{N}$ consists of isolated SOS Nash equilibria satisfying Theorem 2.1. In the non-annealed local geometry statement, the shaped field $F = v + \lambda M$ satisfies the analogous SOS condition around the same equilibrium.

Remark 3.1. The target of convergence is the original game's stable Nash set $\mathcal{N}$. Meta-objectives can have fixed points that differ from Nash equilibria if shaping is kept constant and allowed to dominate the original game. The theorem below is therefore an annealed or explicitly equilibrium-preserving statement; constant shaping is used for the finite-time basin geometry in Theorem 4.4, not as an asymptotic claim that arbitrary meta-game stationary points are Nash equilibria.

4. Main Result

Lemma 4.1 (Estimator decomposition and noise control)**.** *Under bounded rewards, twice differentiable policies with bounded score and Hessian on $\mathcal{K}$, and finite second moments of the likelihood-ratio estimators, the finite-unroll Meta-MAPG estimator satisfies Assumption 2. In particular, the current-policy, own-learning, and peer-learning components can each be written as a conditional mean plus a martingale-difference error; finite unroll and opponent-modeling truncation contribute the bias b_n.*

Lemma 4.2 (Local Meta-MAPG convergence)**.** *Suppose Assumptions 1–4 hold and no restarts occur. If ϕ_0 lies in the attracting neighbourhood of an SOS Nash equilibrium $\phi^* \in \mathcal{N}$, then*

$$\phi_n \to \phi^* \qquad \textit{almost surely.}$$

Moreover, under the quantitative bias and variance exponents of Giannou et al. (2022), the usual local squared-distance rate is inherited.

Theorem 4.3 (Restart globalisation of local Meta-MAPG convergence)**.** *Let $\{\phi_n\}$ be generated by (1) in independent restart epochs. Assume Assumptions 1–4. Let $\mathcal{B} \subset \mathcal{K}$ be the union of local attracting neighbourhoods furnished by Theorem 4.2, and let the restart distribution ν satisfy*

$$p_{\mathcal{B}} := \nu(\mathcal{B}) > 0.$$

If each epoch is independent and the local convergence theorem succeeds with conditional probability at least $1-\delta$ on $\mathcal{B}$, then the restarted process enters a successful epoch after finitely many restarts almost surely. If T is the index of the first successful epoch, then

$$\Pr(T > k) \le (1 - p_{\mathcal{B}}(1-\delta))^k, \qquad \mathbb{E}[T] \le \frac{1}{p_{\mathcal{B}}(1-\delta)}.$$

Consequently, after a finite random number of restarts, the process enters an epoch in which the local theorem applies and then converges almost surely to a stable Nash equilibrium in $\mathcal{N}$. This is a restart globalisation of a local convergence result, not a global contraction statement for the underlying vector field.

Proposition 4.4 (Certified basin enlargement)**.** *Fix an SOS Nash equilibrium ϕ^* with standard drift constant μ and local Lipschitz constant L_v. Let M denote the population Meta-MAPG correction and suppose the symmetric part of $DM(\phi^*)$ is negative semidefinite in the tangent cone with parameter $\mu_M > 0$. Then the constant-shaping field $F_\lambda = v + \lambda M$ has local drift constant*

$$\mu_\lambda \ge \mu + \lambda \mu_M + O(\lambda \|Dv(\phi^*)\|),$$

for sufficiently small $\lambda > 0$. In particular, the usual certified local radius, which scales as drift divided by local Lipschitz constant, increases whenever the reinforcement term dominates the Lipschitz change. This gives a sufficient local explanation for improved restart efficiency.

5. Proof Sketch

Step 1: estimator decomposition. This is the only step specific to Meta-MAPG. Using the Meta-MAPG theorem of Kim et al. (2021), the sampled gradient is split into current, own-learning, and peer-learning score-function terms. Under bounded rewards and bounded policy scores, each sample term has finite conditional variance; subtracting its conditional mean yields a martingale difference. Truncating the unroll at L_n and using an approximate opponent model introduce a bias b_n, controlled by the schedule in Assumption 3.

Step 2: summability. The bias and variance terms are checked against the stochastic-approximation conditions. Because $\sum_n \alpha_n^2 < \infty$, the square-integrable martingale noise is summable in the Robbins–Siegmund sense (Robbins & Monro, 1951; Robbins & Siegmund, 1971; Hall & Heyde, 1980). Because $\sum_n \alpha_n \beta_n < \infty$, the deterministic truncation bias is also summable.

Step 3: local theorem transfer. The Meta-MAPG update is mapped to Giannou et al.'s local PG template. In the annealed regime, the limiting field is Nash-consistent

in the strongest sense: stationary points in the local neighbourhood are the same stable Nash policies as in the base game-gradient field. The local Lyapunov recursion is therefore the same one used by Giannou et al. (2022), with extra summable forcing terms.

Step 4: local convergence. Theorem 4.2 follows by invoking the local attraction theorem for stable and SOS Nash policies. The proof does not require global monotonicity of the game; it is conditioned on the local basin, exactly as in the original theorem.

Step 5: restart globalisation. Restarts globalise this local guarantee in the usual product-space way. Each epoch is independent. Since the restart distribution assigns mass $p_{\mathcal{B}}$ to the attracting set and the local theorem succeeds with probability at least $1-\delta$, each epoch succeeds with probability at least $p_{\mathcal{B}}(1-\delta)$. The first successful epoch is dominated by a geometric random variable, which proves Theorem 4.3. The empirical basin maps in Section 6 illustrate why opponent-aware shaping can improve the constant in this bound by increasing $p_{\mathcal{B}}$.

6. Experiments

The experiments are intentionally small and theorem-facing. We use tabular Bernoulli policies in Stag Hunt and finite-horizon iterated Prisoner's Dilemma (IPD). For clarity, our Stag Hunt is a one-state, one-step, two-agent Markov game: each agent samples C or D from a Bernoulli policy, with row-player payoff matrix

	C	D
C	4	0
D	3	2

and the column-player payoff given by the transpose. Thus (C, C) is the payoff-dominant Nash equilibrium with social welfare 8, while (D, D) is the risk-dominant Nash equilibrium with social welfare 4. In the Stag Hunt figures, each coordinate is simply an agent's cooperation probability $p_i = \pi_i(C)$, and cooperative success means both final cooperation probabilities exceed 0.82.

Updates are sample-based: for a trajectory score $s_i = \nabla_{\phi_i} \log p_\phi(\tau)$ and return R_i, the base estimator is $\hat{g}_i = \frac{1}{B}\sum_b R_i^{(b)} s_i^{(b)}$. The own-learning term uses the likelihood-ratio Hessian estimator

$$\widehat{H}_{ii} = \frac{1}{B}\sum_b R_i^{(b)} \left(s_i^{(b)} s_i^{(b)\top} + \nabla^2_{\phi_i} \log p_\phi(\tau^{(b)}) \right),$$

and the peer-learning term uses the cross-score estimator

$$\widehat{C}_{ji} = \frac{1}{B}\sum_b R_j^{(b)} s_j^{(b)} s_i^{(b)\top}.$$



Figure 1. Component ablation. Peer-aware methods change equilibrium selection relative to standard PG and Meta-PG. In the 20-seed run, IPD cooperative convergence is 0% for PG/Meta-PG, 35% for peer-only, and 30% for full Meta-MAPG; full Meta-MAPG has the highest mean IPD return among the four methods.



Figure 2. Trajectory visualisation under PG and Meta-MAPG in Stag Hunt. Each curve shows the evolution of joint cooperation probabilities from one initialisation; green trajectories reach the payoff-dominant basin and red trajectories move toward the risk-dominant basin or miss the target. This is not a convergence proof; it visualises the finite-time change in local dynamics induced by the opponent-aware term and serves as the geometric bridge between the stochastic-approximation theorem and the restart-efficiency gains.

The implemented one-step correction is $\eta \widehat{H}_{ii}^\top \hat{g}_i$ for own learning and $\eta \widehat{C}_{ji}^\top \widehat{\nabla_{\phi_j} J_i}$ for peer learning. We compare standard PG, Meta-PG (no peer term), peer-only LOLA-style shaping (no own term), and full Meta-MAPG. Unless stated otherwise, reported summary experiments use 20 random seeds; run configuration and raw CSVs are in the experiment artifact directory.

The empirical claims are modest. The ablation primarily shows that peer-learning terms matter; it does not prove full Meta-MAPG dominates every LOLA-style variant in every game. The trajectory visualisation is finite-time mechanism evidence: it shows that opponent-aware shaping modifies the local flow in the same region where the basin map changes. The restart-budget and basin experiments are the direct support for Theorems 4.3 and 4.4: restarts turn local convergence into equilibrium search, and opponent-aware shaping improves that search by increasing the measured cooperative basin in Stag Hunt. The older restart-count statistic is retained in Table 1. The estimator sanity check in Section D is not a proof of Assumption 2; it is an implementation check that the sample estimator behaves in the predicted direction as batch size increases.



Figure 3. Basin visualisation in Stag Hunt. We discretise initial cooperation probabilities over a 21×21 grid and run sample-based updates without restarts. The cooperative basin covers 27.0% of grid points under PG and 47.4% under Meta-MAPG.



Figure 4. Restart budget as an equilibrium-selection mechanism in Stag Hunt. For each budget K, we report the best social welfare discovered across K independent restart attempts, averaged over 50 random seeds; bands show 95% confidence intervals. Dashed lines mark the payoff-dominant Nash equilibrium (welfare 8) and the risk-dominant Nash equilibrium (welfare 4). As K increases, restart search increasingly selects the payoff-dominant equilibrium; the effect is stronger under Meta-MAPG, consistent with opponent-aware shaping increasing entry into the cooperative basin. The inset shows payoff-dominant discovery probability.

7. Discussion

The result is local before it is global. Meta-MAPG inherits Giannou et al.'s stable-Nash theory only inside attracting neighbourhoods and only after the estimator has been placed in the stochastic-approximation form. Restarts remove dependence on a particular initialisation and can be used to search across equilibrium basins; selecting the best discovered endpoint then turns restart budget into a simple equilibrium-selection mechanism. Its expected complexity depends on the basin probability $p_{\mathcal{B}}$; opponent-aware shaping helps only when it increases this probability.

The assumptions are also substantive. The Meta-MAPG estimator must have bounded conditional variance, truncation schedules must make unroll bias summable, and asymptotic shaping must be Nash-consistent. Constant shaping is useful for basin geometry and finite-time behaviour, but a constant peer term can move the limiting fixed points in general-sum games. This is why the theorem separates annealed convergence from constant-shaping basin diagnostics.

Table 1. Main 20-seed summary. Cooperative success uses a minimum initial-state cooperation threshold of 0.82. Restart entries are shown only for PG and Meta-MAPG, the two methods used in the restart experiment.

Game	Method	Ablation success	Restart success	Restarts
ipd	Peer only	35%	–	–
ipd	Meta-MAPG	30%	85%	5.30
ipd	Meta-PG	0%	–	–
ipd	PG	0%	30%	10.70
stag hunt	Peer only	35%	–	–
stag hunt	Meta-MAPG	35%	100%	1.00
stag hunt	Meta-PG	30%	–	–
stag hunt	PG	30%	100%	1.65

The experiments are illustrative rather than definitive. They use matrix and tabular stochastic games because those are the environments in which the theorem's objects can be measured cleanly. Scaling the same decomposition to deep MARL requires better variance control, opponent modeling, and automatic differentiation through longer unrolls, for example with DiCE-style estimators (Foerster et al., 2018b). The conceptual message is narrower and, we think, useful: opponent-aware gradients can be analysed as stochastic approximation processes, and restart efficiency is the right global metric when the underlying convergence theorem is local.

This paper does not claim unconditional convergence of arbitrary opponent-aware learning in deep MARL. It shows that finite-unroll Meta-MAPG can be analysed within classical stochastic approximation under boundedness, smoothness, Nash-consistency, and summability conditions, and that local convergence can be globalised by independent restarts when local basin mass is positive.

A. Detailed Estimator Decomposition

For a sampled trajectory τ, write $S_i(\tau) = \nabla_{\phi_i} \log p_\phi(\tau)$ and $H_i(\tau) = \nabla^2_{\phi_i} \log p_\phi(\tau)$. The base likelihood-ratio estimator is $R_i(\tau)S_i(\tau)$ (Williams, 1992; Sutton & Barto, 2018). The one-step own-learning derivative follows from differentiating $J_i(\phi_i + \eta \nabla_{\phi_i} J_i, \phi_{-i})$:

$$\nabla_{\phi_i} J_i + \eta \left[\nabla^2_{\phi_i} J_i\right]^\top \nabla_{\phi_i} J_i.$$

The Hessian identity gives

$$\nabla^2_{\phi_i} J_i = \mathbb{E}\left[R_i(\tau)\left(S_i(\tau)S_i(\tau)^\top + H_i(\tau)\right)\right],$$

which is the estimator used in the experiments.

For the peer term, let agent j take one inner step $\phi'_j = \phi_j + \eta \nabla_{\phi_j} J_j$. Differentiating $J_i(\phi_i, \phi'_j)$ with respect to ϕ_i contributes

$$\eta \left[\nabla_{\phi_i} \nabla_{\phi_j} J_j\right]^\top \nabla_{\phi_j} J_i.$$

The mixed likelihood-ratio identity gives

$$\nabla_{\phi_i}\nabla_{\phi_j}J_j = \mathbb{E}\left[R_j(\tau)S_j(\tau)S_i(\tau)^\top\right],$$

which is the sample cross-score matrix used for the peer correction. Longer Meta-MAPG unrolls repeat this chain-rule structure across L inner updates; bounded derivatives on $\mathcal{K}$ allow the omitted tail and finite-modeling error to be collected in b_n.

B. Restart Argument

Let A_k be the event that restart epoch k starts in $\mathcal{B}$ and its local stochastic approximation path converges. By independence of restarts,

$$\Pr(A_k) \geq \nu(\mathcal{B})(1-\delta) = p_{\mathcal{B}}(1-\delta) =: p_\star > 0.$$

Thus

$$\Pr(T > k) = \Pr(A_1^c, \ldots, A_k^c) \leq (1-p_\star)^k.$$

This tail bound implies $\Pr(T < \infty) = 1$ and $\mathbb{E}[T] \leq 1/p_\star$. If the number of restarts counts failed epochs rather than the successful epoch itself, subtract one from this bound.

C. Experiment Reproducibility

All experiments can be regenerated with:

```
python3 experiments/run_meta_mapg_experiments.py
  --outdir artifacts/main \
  --seeds 20 \
  --steps 260 \
  --restart-steps 120 \
  --max-restarts 12 \
  --selection-budget 12 \
  --selection-seeds 50 \
  --selection-steps 120 \
  --trajectory-steps 140 \
  --trajectory-batch-size 384 \
  --trajectory-grid-size 5 \
  --batch-size 256 \
  --basin-batch-size 128 \
  --grid-size 21 \
  --basin-steps 120 \
  --reference-batch-size 120000 \
  --sanity-reps 80 \
  --own-coef 0.05 \
  --peer-coef 1.5 \
  --basin-peer-coef 2.0 \
  --selection-peer-coef 2.0 \
  --trajectory-peer-coef 2.0
```

The raw files are `ablation_summary.csv`, `restart_summary.csv`, `restart_selection.csv`, `trajectory_trace.csv`, `basin_map.csv`, and `estimator_sanity.csv` under `artifacts/main`. The code uses no exact gradients for updates; expected returns are computed only for logging and evaluation.



Figure 5. Estimator sanity check. At a fixed Stag Hunt parameter, the variance trace of the Meta-MAPG estimator decreases from 0.1272 at batch size 48 to 0.0062 at batch size 768. Bias is measured relative to a high-batch reference estimator, not an exact analytic gradient.

D. Estimator Sanity Check

References

Fink, A. M. Equilibrium in a stochastic n-person game. *Journal of Science of the Hiroshima University, Series A-I*, 28(1):89–93, 1964.

Foerster, J., Chen, R. Y., Al-Shedivat, M., Whiteson, S., Abbeel, P., and Mordatch, I. Learning with opponent-learning awareness. In *Proceedings of the 17th International Conference on Autonomous Agents and Multiagent Systems*, pp. 122–130, 2018a.

Foerster, J., Farquhar, G., Al-Shedivat, M., Rocktaschel, T., Xing, E., and Whiteson, S. DiCE: The infinitely differentiable monte carlo estimator. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 1524–1533, 2018b.

Giannou, A., Lotidis, K., Mertikopoulos, P., and Vlatakis-Gkaragkounis, E. V. On the convergence of policy gradient methods to nash equilibria in general stochastic games. In *Advances in Neural Information Processing Systems*, 2022.

Hall, P. and Heyde, C. C. *Martingale Limit Theory and Its Application*. Academic Press, 1980.

Kim, D.-K., Liu, M., Riemer, M., Sun, C., Abdulhai, M., Habibi, G., Lopez-Cot, S., Tesauro, G., and How, J. P. A policy gradient algorithm for learning to learn in multiagent reinforcement learning. In *Proceedings of the 38th International Conference on Machine Learning*, 2021.

Letcher, A., Foerster, J., Balduzzi, D., Rocktaschel, T., and Whiteson, S. Stable opponent shaping in differentiable games. In *International Conference on Learning Representations*, 2019.

Robbins, H. and Monro, S. A stochastic approximation method. *The Annals of Mathematical Statistics*, 22(3): 400–407, 1951.

Robbins, H. and Siegmund, D. A convergence theorem for non negative almost supermartingales and some applications. *Optimizing Methods in Statistics*, pp. 233–257, 1971.

Sutton, R. S. and Barto, A. G. *Reinforcement Learning: An Introduction*. MIT Press, 2 edition, 2018.

Williams, R. J. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine Learning*, 8:229–256, 1992.