

NetEngine 8000 M6

Universal Service Router

Overview

NetEngine 8000 M6 is an all-scenario converged bearer router for the cloud era. It's featured with 2U height, 220 mm depth, supports up to 160G port capacity and 6 service slots, flexibly adapts to different services, and supports 50GE/25GE/10GE/GE/ FE/CPOS/E1 interfaces. The compact design saves precious space resource, greatly reduces Capex, and protects the existing investment. Wide-temperature design enables it to be deployed in all scenarios. It also supports features such as SRv6, EVPN, network slicing, and 1588v2 high-precision clock which make it the best choice for multi-service convergence in the cloud era.

The product fully supports the future-oriented next-generation unified network SRv6 technology and can be used to build IP backbone, metro, mobile backhaul, and data center networks. It can be used for individual/enterprise cloud migration, inter-cloud interconnection, IoT, government and enterprise private lines, home broadband applications, and CDN. As a basic bearer protocol of the entire network, SRv6 implements end-to-end full-service bearer capabilities. SRv6 enables simplified protocols, large-scale networking, seamless integration, high reliability, integrated service chains, network and service programmability, and a full ecosystem.

The NetEngine 8000E series router integrates multiple functions, simplifies the network structure, provides rich service types, reliable service quality, and intelligent O&M. It leads the IP WAN to an intelligent network with self-driving driving, and continuously drives the business success of enterprise customers.

Product Highlights



NetEngine 8000 M6 (DC)



NetEngine 8000 M6 (AC)

Compact and Large-Capacity

- Size: 2U, 220 mm deep
- Capacity: 6 slots, 160 Gbps, up to 2 * 50GE/16 * 10GE/100 * GE

All-Scenario Platform

- 3-in-1 aggregation router: private line + IGW + DC-GW
- Various interfaces: E1/cPOS/PCM*/GE/10GE/25GE/50GE

Leading Capabilities

- SRv6/EVPN: Simplified protocols
- NP Architecture, to meet future evolution
- Industry-leading network slicing

Product Specifications

Property	CXP-160
Switching Capacity	320 Gbps
Forwarding Performance	72 Mpps
Maximum Board Capability	50 GE
Interface types	50GE/40GE/25GE/10GE/GE/FE/E1/cPOS/POS/V.35/X.21/V.24/C37.94&CoDir64K/FXS/FXO/E&M/RS232/RS485
Main Control Board	2, 1:1
Service Slots	6 (DC) 4 (AC)
Dimensions (W x D x H)	442mm x 220mm x 88.9mm(2U)
Typical Power Consumption	205.8 W
Voltage	DC: -48 V/-60 V; AC: 200 V to 240 V/100 V to127 V dual live wires, support 240 V HVDC
Clock	1588v2 and synchronous Ethernet clock
Temperature	DC: -40°C to +65°C (-40°F to +149°F); AC: -20°C to +55°C

 **NOTE** For details, see the corresponding product manual.

Product Features

Features of Huawei NetEngine 8000 M6 Series Routers

Feature	Description
L2	IEEE 802.1q, IEEE 802.1p, IEEE 802.3ad, IEEE 802.1ab, STP/RSTP/MSTP, G.8032, STP/RSTP, MSTP, L2 protocol transparent transmission, BPDU, LACP, VLAN, Bridge domain, L2TPv3, QinQ, MTU per port 9600 bytes
L3	OSPF/OSPF3, RIP/RIPng, IS-IS/IS-ISv6, BGP/BGP+, ACL, IPv4/IPv6, 6VPE, ARP, VLANIF, VXLAN
MEF	- E-LINE: EPL, EVPL - E-LAN: EP-LAN, EVP-LAN
IPv4	TCP/IP, for example, ICMP, IP, TCP, UDP, Socket (TCP/UDP/RAW IP), ARP Static DNS, DNS Client FTP Server, FTP Client TFTP Client DHCP Relay, DHCP Server Ping, Tracert, NQA IP policy-based routing Forwarding next hop based on traffic

Feature	Description
IPv4	IP policy-based route load balancing The QinQ interface (QinQ termination and dot1q termination) supports IPv4 load balancing. Enabling and disabling the rapid ping reply function based on interface boards Forcible fragmentation for packets with length greater than MTU and DF enabled MPLS-in-UDP tunnel egress
IPv6	IPv6 (ND) Path MTU (PMTU) TCP6 Ping IPv6 Tracert IPv6 Socket IPv6 DHCPv6 Relay Static IPv6 DNS TFTP IPv6 Client IP policy-based routing IPv6 ND fast reply
MPLS	LDP, RSVP-TE, seamless MPLS, Segment Routing MPLS, MPLS-TP
Multicast	IGMP, Static Multicast Routing, PIM-SM, PIM-SM/SSM, MBGP, MG MVPN, IPv4 Multicast, IPv6 multicast, BIERv6
SRv6	IS-IS for SRv6, OSPFv3 for SRv6, SRv6 TE Policy, SRv6 TE Policy Shortcut, SRv6 Flex- Algo, SRv6 SRH compression, SRv6 network slicing BGP for SRv6, SRv6 BE, SBFD for SRv6 BE, SRv6 TI-LFA FRR, SRv6 middle-node protection, SRv6 micro-loop avoidance, SRv6 OAM, SRv6 SFC, G-SRv6
L2VPN	PWE3/VLL, VPLS, VXLAN, VPWS, L2TPv3, BGP/MPLS IPv4/IPv6 VPN, PBB-EVPN, PBB VPLS, GRE
L3VPN	CE routers can access the L3VPN through L3 interfaces. Support static routes between CE and PE, BGP, RIPv1/v2, OSPF and IS-IS Inter-AS VPN, including RFC2547bis option A Inter-AS VPN, including RFC2547bis option B Inter-AS VPN, including RFC2547bis option C NG MVPN IPv6 VPN HoVPN Seamless MPLS BGP LSP entropy label Redirect to VPN L3VPN PIPE/Uniform mode L3VPN statistics

Feature	Description
EVPN	EVPN E-LAN/E-Line/E-Tree, EVPN L3VPN, EVPN VXLAN, PBB EVPN
Value added service	BNG/BRAS (IPoE/PPPoE), NAT/CGN, IPsec, MACsec, service awareness (SA)
Clock	NTP, Physical layer synchronization (SynE), 1588v2 ACR/ATR, G.8275.1, SMPTE-2059-2, CES ACR, Atom GPS 3.0
QoS	QPPB, DiffServ, 5-level HQoS, redirection, traffic classification & re-marking & scheduling
Reliability	IP FRR, LDP FRR, TE FRR, VPN FRR, BGP FRR, mLDP FRR, Bit-error-triggered protection switching
Maintainability	• A network management system (NMS) with a graphical user interface, which simplifies NE management, improves O&M capabilities, and facilitates network- wide or end-to-end performance monitoring and fault diagnosis. • Plug-and-play based on DHCP or DCN. The NMS can automatically detect and configure the newly connected devices, which helps to implement remote batch commissioning. • Directional Forwarding Detection (BFD), Ethernet OAM, MPLS OAM, and MPLS- TP OAM • Bandwidth association with microwave devices is supported. Bandwidth association simplifies QoS configurations and requirements on the microwave device, and the complex QoS logic is implemented on the NetEngine 8000 device. • Seamless MPLS • SNMP (v1/v2c/v3) • CLI • NETCONF • RMON • YANG • Telnet • AAA RADIUS and TACACS • IFIT, IP FPM, NQA, TWAMP, telemetry • BFD, VRRP • Ethernet OAM, IEEE 802.3ah, IEEE 802.1ag, Y.1731, ITU-T Y.1564 • Ethernet LPT • Syslog

Regulatory Compliance

Item	Description
Regulatory compliance	EMC
	• ANSI C63.4
	• AS/NZS CISPR 32
	• CISPR 24
	• CISPR 32
	• EN 55024
	• EN 55032
	• ETSI EN 300 386
	• ETSI ES 201 468
	• FCC CFR47 Part 15 Subpart B
	• ICES-003 Issue 6
	• ICES-GEN Issue 1
	• IEC 61000-3-2
	• IEC 61000-3-3
	• IEC 61000-4-11
	• IEC 61000-4-2
	• IEC 61000-4-29
	• IEC 61000-4-3
	• IEC 61000-4-4
	• IEC 61000-4-5
	• IEC 61000-4-6
	• IEC 61000-6-2
	• IEC 61000-6-4
	• VCCI-CISPR 32
	Environment
	• IEC 60068-2-30
	• IEC 60068-2-78
	• IEC 60068-2-14
	• IEC 60068-2-1
	• IEC 60068-2-2
	Safety
	• IEC/EN/UL/CSA 60950-1
	• IEC/EN 62368-1

Item	Description
	Environmental protection • 2011/65/EU & (EU)2015/863 (EU RoHS) • Regulation (EC) No.1907/2006 (REACH) • 2012/19/EU (WEEE) • 2006/66/EC & 2013/56/EU on batteries and accumulators

NOTE

- In the physical dimensions shown in the table, the width (W) does not include the rack-mounting ears.
- Temperature and humidity are measured at 1.5 m (4.92 ft.) above the ground and 0.4 m (1.31 ft.) in front of the cabinet. There should be no protection board on the front or back of the cabinet.
- "Short-term" refers to continuous working time that does not exceed 96 hours and accumulated working time per year that does not exceed 15 days. If the working time exceeds either of these values, it is considered "long-term".

Software Upgrade Paths.

Visit [Software Upgrade Paths](#) to get VRP software release version or patches

For More Information

For more information about the NetEngine 8000 M6 series router, visit <https://e.huawei.com> or contact us in the following ways:

Global service hotline: <https://e.huawei.com/en/service-hotline>

Logging in to the Huawei Enterprise technical support web: <https://support.huawei.com/enterprise/>

Sending an email to the customer service mailbox: support_e@huawei.com

Copyright © Huawei Technologies Co., Ltd. 2025. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

 HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address: Huawei Industrial Base Bantian,
Longgang Shenzhen 518129 People's
Republic of China

Website: www.huawei.com