



HPE Aruba Networking EC-XS SD-WAN Gateway

Product overview

The HPE Aruba Networking EC-XS SD-WAN Gateway is a very compact form factor thin edge branch gateway appliance that serves to build an SD-WAN fabric using zero touch provisioning. It supports Multiprotocol Label Switching (MPLS), 4G/5G/LTE, internet-based hybrid WAN datapath, and a control plane that is automated and secured by the HPE Aruba Networking SD-WAN Orchestrator centralized management software—providing policy-based virtual network segmentation and acceleration of on-premises and SaaS cloud applications.

Key features of the HPE Aruba Networking EC-XS SD-WAN Gateway include quiet operations and flexible mounting options. These features make it an ideal appliance for small branch and remote office environments with typical WAN bandwidth from 2 to 1000 Mbps (bidirectional).

Table 1. Technical specifications

HPE Aruba Networking EC-XS SD-WAN Gateway	
Capacity	
WAN bandwidth capacity (all features + encryption)	2 to 1000 Mbps (bidirectional)
Simultaneous connections	256,000
Recommended WAN optimization up to	250 Mbps
IDS/IPS capacity (Performant mode) up to	600 Mbps
IDS/IPS capacity (Inline mode) up to	300 Mbps
Resiliency	
Drives	Single
Power supplies	Single
Network	WAN link redundancy supported through business intent overlays with multiple link bonding options; LAN-side protection includes VRRP and BGP; Multiple IPSLA options included.
RAM	ECC memory
MTBF	162,171 hours (18.5 years)
Security	
Disk encryption	128-bit AES
Network encryption	IPSec (256-bit AES)
Connectivity	
LAN/WAN Ethernet	4x 10/100/1000 LAN/WAN (2 LAN / 2 WAN) as per IEEE 802.3i, 802.3u, 802.3ab, 802.1Q
Management	2x 10/100/1000; console port
Power	
Requirement	Input: 100 VAC–240 VAC / 50 Hz–60 Hz Max power consumption: 34W/116 BTU
Power supplies	Single adapter

Table 1. Technical specifications (continued)

HPE Aruba Networking EC-XS SD-WAN Gateway	
Dimensions	
Height	1.7 in (44 mm)
Width	9.4 in (240 mm)
Depth	7.9 in (200 mm)
Weight	3.5 lb (1.6 kg)
Regulatory	
EMC	FCC Part 15 Class B, EN 55022 Class B, VCCI Class B EN 61000-3-2/3-3, EN 55024
Safety	UL/cUL/60950, EN 60950
Environmental	
Temperature (operating)	0°C to 40°C (32°F to 104°F)
Temperature (storage)	-40°C to 65°C (-40° to 149°F)
Humidity (operating)	8%–90% relative humidity, non-condensing
Humidity (storage)	8%–95% relative humidity, non-condensing
Altitude (operating)	Up to 10,000 ft (3048m)
Altitude (storage)	Up to 40,000 ft (12,192m)
Management	
CLI	Full-featured CLI available over console port or SSH
UI/HTTPS	HPE Aruba Networking EdgeConnect SD-WAN Operating System includes a web user interface (WebUI) and REST API, which manages an individual appliance. HPE Aruba Networking SD-WAN Orchestrator provides centralized configuration, monitoring, and management of multiple HPE Aruba Networking EdgeConnect SD-WAN gateways. It also provides REST API and streaming notification service.
SNMP	SNMPv3
Secure access	SSH and HTTPS, supports PKI as per RFC 5280, RFC 6960, and RFC 7030
Logging	Secure syslog with configurable levels. email alerts
Authentication	Local database, RADIUS, TACACS+
Statistics	Graphing and monitoring, real time and historical; NetFlow and IPFIX supported

Table 2. Ordering information

Product type	HPE Aruba Networking SKU	Description
SD-WAN gateways		
	JM962A	HPE Aruba Networking EC-XS SD-WAN Gateway
	JM994A	HPE Aruba Networking EC-XS-NFR SD-WAN Gateway
	S3N70A	HPE Aruba Networking EC XS NAL SD-WAN Gateway
Accessories		
	JM995A	HPE Aruba Networking EC-XS Power Adapter
	JM996A	HPE Aruba Networking EC-XS A1 Power Adapter

Note: The regulatory model number for HPE Aruba Networking EC-XS SD-WAN Gateway with part number 201571 is FWA-ASP1012.

Note: The regulatory model number HPE Aruba Networking EC-XS SD-WAN Gateway with part number 201694 is NCA-1513A-SV1.

Learn more at

[HPE.com/us/en/aruba-edgeconnect-sd-wan.html](https://hpe.com/us/en/aruba-edgeconnect-sd-wan.html)

Visit HPE.com

[Chat now](#)

© Copyright 2025 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

a00110177ENW, Rev. 3

HEWLETT PACKARD ENTERPRISE

hpe.com

