```
CREATE DATABASE INTERNETSTORE;
USE INTERNETSTORE;
CREATE TABLE Clients
ClientsID int primary key not null auto_increment,
Name1 varchar(20),
LastName varchar(20),
Age int
);
CREATE TABLE Cities
CitiesID int primary key not null auto_increment,
cityName varchar(20),
Clientsid int,
foreign key (ClientsID) references Clients (ClientsID)
);
CREATE TABLE ClientsData
ClientsDataID int primary key not null auto_increment,
DataOfBird long,
DataOfRegistration long,
clientNumber long,
Clientsid int,
foreign key (ClientsID) references Clients(ClientsID)
);
CREATE TABLE Orders
OrdersID int primary key not null auto_increment,
NameOrders Varchar(20),
ClientsID int,
foreign key (ClientsID) references Clients(ClientsID)
);
```

```
CREATE TABLE Price
PriceID int primary key not null auto_increment,
Price int,
OrdersID int,
foreign key (OrdersID) references Orders(OrdersID)
);
CREATE TABLE Discounts
DiscountsID int primary key not null auto_increment,
NewPrice int,
PriceID int,
foreign key (PriceID) references Price(PriceID)
);
CREATE TABLE Delivery
DeliveryID int primary key not null auto_increment,
TypeDelivery varchar(20),
OrdersID int,
foreign key (OrdersID) references Orders(OrdersID)
);
INSERT INTO INTERNETSTORE.Clients (Name1, LastName, Age) VALUES
('Vlad', 'Strin', 27),
('Valera', 'Beyker', 37),
('Stiven', 'King', 47),
('Brus', 'Lee', 87),
('Katy', 'Stivensson', 97);
INSERT INTO INTERNETSTORE.Cities (cityName) VALUES
('Kyiv'),
('Lviv'),
('Odessa'),
```

```
('Kherson'),
('Vinnitsa');
INSERT INTO INTERNETSTORE. Clients Data (Data Of Bird, Data Of Registration, client Number) VALUES
('03.03.1983', '03.03,2000', '0678965412'),
('23.09.1981', '03.03,2010', '0678965412'),
('12.03,1982', '03.03,2020', '0678965412'),
('19.03,1983', '03.03,2019', '0678965412'),
('30.03,1984', '03.03,2017', '0678965412');
INSERT INTO INTERNETSTORE.Orders(NameOrders) VALUES
('Bag'),
('Tablet'),
('Phone'),
('Computer'),
('Laptop');
INSERT INTO INTERNETSTORE.Price(Price) VALUES
('11000'),
('22000'),
('33000'),
('50000'),
('90000');
INSERT INTO INTERNETSTORE. Discounts (NewPrice) VALUES
('10000'),
('20000'),
('30000'),
('45000'),
('80000');
INSERT INTO INTERNETSTORE. Delivery (TypeDelivery) VALUES
('Nova Pochta'),
('American Express'),
('Ukr Pochta'),
```

```
('Nova Pochta');

UPDATE internetstore.cities SET `Clientsid` = '1' WHERE (`CitiesID` = '1');

UPDATE internetstore.cities SET `Clientsid` = '2' WHERE (`CitiesID` = '2');

UPDATE internetstore.cities SET `Clientsid` = '3' WHERE (`CitiesID` = '3');

UPDATE internetstore.cities SET `Clientsid` = '4' WHERE (`CitiesID` = '4');

UPDATE internetstore.cities SET `Clientsid` = '5' WHERE (`CitiesID` = '5');
```