

Connecting the questionnaire to ekocentrs.lv

The AML/KYC client identification questionnaire is a standalone Next.js application. It is not installed inside Joomla and needs no changes to the site's code: it runs on its own subdomain, and an ordinary link leads to it from the site.

SITE	APPLICATION	SUBDOMAIN
Joomla 3.10.10	Next.js 16 / Node	anketa.ekocentrs.lv
CHANGES TO JOOMLA CODE		
none		

In short

1. The application is deployed to `anketa.ekocentrs.lv` on your server.
2. A link to it appears in the Joomla menu.
3. One page — `/izveidot` — needs to be closed off, however suits you best. Everything else stays public.

Two pages with opposite requirements

This is the one place that is easy to get wrong, which is why it comes first. The application has two pages, and they need the exact opposite of each other.

anketa.ekocentrs.lv

/izveidot

Agent page — creates links.
Must be closed.

↑
agents only

/aizpildit?d=...

Client questionnaire, opened from a link.
Must stay public.

↑
any client with the link

The restriction goes on the /izveidot path, not the whole subdomain.

If the protection is applied to the whole subdomain, clients can no longer fill in the questionnaire — they have no accounts and never will.

The client has no account and never will. An agent creates a link and sends it to the client, over WhatsApp for instance. All the transaction details are encoded in the link itself, so it has to open straight away, with no sign-in.

Who does what

TASK	OWNER
The application, PDF generation, link creation	Us — done
Deployment and TLS certificate	You
DNS record for the subdomain	You
Menu item on the site	You
Access restriction on <code>/izveidot</code>	You

Implementation steps

1

Deploying the application on your server

What it needs: Node.js 20+, git, and around 1 GB of free RAM (see the note below).

The source is in an open repository — no access keys needed, you can start straight away:

```
git clone https://github.com/VladislavSolims/ekocentrs-web-solutions.git anketa
cd anketa
# later updates need only:
git pull
```

```
npm ci
npm run build
npm start          # port 3000
```

One environment variable

Create `.env.local` in the project root with a single line:

```
AGENT_LOGIN=external
```

This says: access is handled by whatever sits in front of the application (step 4), and the application asks for no sign-in of its own. **There is deliberately no default** — with the variable unset the application refuses to serve `/izveidot` rather than quietly opening it to everyone.

Surviving a reboot

Example systemd service:

```
[Unit]
Description=Ekocentrs anketa
After=network.target

[Service]
WorkingDirectory=/var/www/anketa
ExecStart=/usr/bin/npm start
Restart=always
Environment=NODE_ENV=production

[Install]
WantedBy=multi-user.target
```

Example nginx block:

```
server {
    server_name anketa.ekocentrs.lv;
    location / {
        proxy_pass          http://127.0.0.1:3000;
        proxy_set_header    Host $host;
    }
}
```

```
proxy_set_header    X-Forwarded-Proto $scheme;  
}  
}
```

Worth knowing: the application launches headless Chromium to build the PDF. On your own server that needs system libraries (`libnss3` , `libatk-bridge2.0-0` , `libdrm2` , `libgbm1` , `libasound2`) and around 1 GB of free memory. If the PDF fails to generate, this is where to look — the rest of the application runs without them.

2

DNS record

Add the subdomain `anketa.ekocentrs.lv` :

```
anketa    A          <server IP>
```

A TLS certificate is required.

3

Link in the Joomla menu

Joomla admin → *Menus* → *Add New Menu Item* → type *External URL*:

```
URL:          https://anketa.ekocentrs.lv/izveidot  
Access level: Special (or your agents' level)
```

The access level only hides the link from other visitors — the real restriction is step 4.

No iframe. The agent page should not be embedded in an article as an `<iframe>` : some browsers block third-party cookies and the page will behave unpredictably. An iframe does not suit the client questionnaire either — all the transaction details live in the link's parameter, and they never reach the inside of an iframe.

4

Access restriction on `/izveidot`

We leave this to you — you know best what already works in your infrastructure. Nothing needs configuring on the application's side: it is built to sit behind any external restriction and asks for no sign-in of its own.

Three common options, in case they help:

- **Cloudflare Access** — free for up to 50 users, sign-in with a Google account, and the restriction can be placed on a specific path.
- **IP allowlist** for the office network — the simplest, but an agent cannot then work from home or from a phone.
- **HTTP Basic Auth** on `location /izveidot` — one password for all agents, two lines in the nginx config.

If something else suits you better, do it the way you think is right. The only condition is the one described at the top of this page: the restriction applies to `/izveidot` only, and `/aizpildit` stays public.

5

Checking it works

- An agent in the office opens the menu link → lands on the link-creation page.
- An outsider opens `anketa.ekocentrs.lv/izveidot` → does not get in.
- A client link `/aizpildit?d=...` opens anonymously — in another browser, on a phone, with no VPN and no account.
- A client fills the questionnaire in to the end and downloads the PDF.

When you are done

Two things are enough for us:

- confirmation that `anketa.ekocentrs.lv` exists and points where it should;
- a short note on how exactly `/izveidot` is protected — so we know what to tell an agent the first time they try to get in.

If anything is unclear, or something in your infrastructure calls for a different approach, write to us and we will adapt.