```
---Switch1----
  Spanning tree enabled protocol ieee
  Root ID Priority 4097
              Address
                          0ce5.5a03.0000
              This bridge is the root
              Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
  Bridge ID Priority 4097 (priority 4096 sys-id-ext 1)
Address 0ce5.5a03.0000
              Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
              Aging Time 300 sec
                    Role Sts Cost Prio.Nbr Type
Interface
______________
                    Desg FWD 4 128.1 Shr
Desg FWD 4 128.2 Shr
Desg FWD 4 128.3 Shr
Desg FWD 4 128.4 Shr
Desg FWD 4 128.5 Shr
Desg FWD 4 128.6 Shr
Desg FWD 4 128.7 Shr
Desg FWD 4 128.8 Shr
Desg FWD 4 128.8 Shr
Desg FWD 4 128.9 Shr
Gi0/0
Gi0/1
Gi0/2
Gi0/3
Gi1/0
Gi1/1
Gi1/2
Gi1/3
Gi2/0
----Switch2----
  Spanning tree enabled protocol ieee
  Root ID Priority 4097
Address 0ce5.5a03.0000
Cost 4
Port 1 (GigabitEthernet0/0)
              Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
  Bridge ID Priority 8193 (priority 8192 sys-id-ext 1)
Address 0c52.6d27.0000
              Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
              Aging Time 300 sec
             Role Sts Cost Prio.Nbr Type
Interface
______________
                    Root FWD 4 128.1 Shr
Altn BLK 4 128.2 Shr
Desg FWD 4 128.3 Shr
Desg FWD 4 128.4 Shr
Desg FWD 4 128.5 Shr
Desg FWD 4 128.6 Shr
Gi0/0
Gi0/1
Gi0/2
Gi0/3
Gi1/0
Gi1/1
                     Desg FWD 4
                                          128.6 Shr
                     Desg FWD 4
Gi1/2
                                          128.7 Shr
             Role Sts Cost Prio.Nbr Type
```

Gi1/3 Desg FWD 4 128.8 Shr

Interface

Gi2/0 Desg FWD 4 128.9 Shr ----Switch3----Spanning tree enabled protocol ieee Root ID Priority 4097
Address 0ce5.5a03.0000 Cost 4 Port 1 (GigabitEthernet0/0) Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec Bridge ID Priority 32769 (priority 32768 sys-id-ext 1) Address 0cf5.307b.0000 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec Aging Time 300 sec Role Sts Cost Prio.Nbr Type Root FWD 4 128.1 Shr
Altn BLK 4 128.2 Shr
Altn BLK 4 128.3 Shr
Altn BLK 4 128.4 Shr
Desg FWD 4 128.5 Shr
Desg FWD 4 128.6 Shr Gi0/0 Gi0/1 Gi0/2 Gi0/3 Gi1/0 Gi1/1 ----Switch4----Spanning tree enabled protocol ieee Root ID Priority 4097 Address 0ce5.5a03.0000
Cost 4
Port 1 (GigabitEthernet0/0) Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec Bridge ID Priority 32769 (priority 32768 sys-id-ext 1)
Address 0ca8.acc9.0000 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec Aging Time 300 sec Role Sts Cost Prio.Nbr Type Interface ______________ Root FWD 4 128.1 Shr Altn BLK 4 128.2 Shr Altn BLK 4 128.3 Shr Gi0/0 Gi0/1 Gi0/2 Altn BLK 4 128.4 Shr Desg FWD 4 128.5 Shr Desg FWD 4 128.6 Shr Gi0/3 Gi1/0 Gi1/1 ----Switch5---

Spanning tree enabled protocol ieee

Root ID Priority 4097
Address 0ce5.5a03.0000
Cost 4
Port 1 (GigabitEthernet0/0)

Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec

Bridge ID Priority 32769 (priority 32768 sys-id-ext 1)

Address 0cd4.8c41.0000

Hello Time $\,$ 2 sec $\,$ Max Age 20 sec $\,$ Forward Delay 15 sec

Aging Time 300 sec

Interface	Role Sts	Cost	Prio.Nbr	Туре
Gi0/0	Root FWD	4	128.1	Shr
Gi0/1	Altn BLK	4	128.2	Shr
Gi0/2	Altn BLK	4	128.3	Shr
Gi0/3	Altn BLK	4	128.4	Shr
Gi1/0	Desg FWD	4	128.5	Shr
Gi1/1	Desg FWD	4	128.6	Shr