MOBSF

ANDROID STATIC ANALYSIS REPORT



Мой ИМЭС (0.4.9)

File Name:	app-release.apk
Package Name:	com.example.vuz_app
Scan Date:	Nov. 2, 2026, 6:39 p.m.
App Security Score:	55/100 (MEDIUM RISK)
Grade:	B

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
1	12	2	2	1

FILE INFORMATION

File Name: app-release.apk
Size: 65.37MB
MD5: cb13e431db19ad96c6a0a492c068ab2a
SHA1: 96ddbcf12a8665734090fedd67c0daac1f043aa7
SHA256: 5c1962c55e40158023ee30baafee311d7f45a9a2bf1ab898ed3ab07238c72de3

APP INFORMATION

App Name: Мой ИМЭС
Package Name: com.example.vuz_app
Main Activity: com.example.vuz_app.MainActivity
Target SDK: 36
Min SDK: 26
Max SDK:
Android Version Name: 0.4.9
Android Version Code: 34

APP COMPONENTS

Activities: 8
Services: 6
Receivers: 8
Providers: 5
Exported Activities: 1
Exported Services: 0
Exported Receivers: 3
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
v3.1 signature: False
v3.2 signature: False
X.509 Subject: C=RU, ST=Unknown, L=Moscow, O=t3w1, OU=t3w1, CN=t3w1

Signature Algorithm: rsassa_pkcs1v15
Valid From: 2026-10-31 16:32:26+00:00
Valid To: 2054-03-18 16:32:26+00:00
Issuer: C=RU, ST=Unknown, L=Moscow, O=t3w1, OU=t3w1, CN=t3w1
Serial Number: 0xb96dfbeb99dd91fc
Hash Algorithm: sha256
md5: d5c4aca667aef56caa9e8a5d4986421d
sha1: bba62488ea35c048c3a907c2247bb2492e7f787c
sha256: 8fd39c61bfa8049392d92930ba059308ddd81a90c81bba4e6f93141633ea3d56
sha512: 2b8a8af279eab36d522b0cd8d25c65b26973afb7ef0b82e278af981d83a43ef9e15c6e7f393e6b37879e90693308749f91d6e37dbc32d5207645f2262de99de8
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 5170ddfd7bbc612aa6b423c624e0cf6199cc9d4a3f3fd546099c38435388f4a2
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.USE_BIOMETRIC	normal	allows use of device-supported biometric modalities.	Allows an app to use device supported biometric modalities.
android.permission.REQUEST_INSTALL_PACKAGES	dangerous	Allows an application to request installing packages.	Malicious applications can use this to try and trick users into installing additional malicious packages.
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.USE_FINGERPRINT	normal	allow use of fingerprint	This constant was deprecated in API level 28. Applications should request USE_BIOMETRIC instead.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.

PERMISSION	STATUS	INFO	DESCRIPTION
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
com.example.vuz_app.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	FINDINGS	DETAILS
cb13e431db19ad96c6a0a492c068ab2a.apk	Manipulator Found	Resources Confusion
cb13e431db19ad96c6a0a492c068ab2a.apk	Packer Found	DexGuard
classes.dex	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check SIM operator check
classes.dex	Compiler	r8

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

MANIFEST ANALYSIS

HIGH: 0 | WARNING: 5 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable Android version 8.0, minSdk=26]	warning	This application can be installed on an older version of android that has multiple vulnerabilities. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Activity-Alias (com.example.vuz_app.MainActivityDark) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
3	Broadcast Receiver (io.flutter.plugins.firebase.messaging.FlutterFirebaseMessagingReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
4	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
5	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

</> CODE ANALYSIS

HIGH: 1 | WARNING: 6 | INFO: 2 | SECURE: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	A/c.java A/g.java A0/c.java B/b.java B/f.java B/g.java B/i.java B/m.java B1/h.java C0/p.java C1/g.java C2/AbstractC0005e.java C2/AbstractServiceC0009i.java C2/C0012l.java C2/C0013m.java C2/C0014n.java C2/C0018s.java C2/C0024y.java C2/G.java C2/H.java C2/I.java C2/J.java C2/K.java C2/L.java C2/M.java C2/N.java C2/Q.java C2/S.java C2/T.java C2/U.java C2/W.java C2/Y.java F/AbstractC0029e.java F/C0027c.java F/C0042s.java F/P.java F/RunnableC0026b.java F0/k.java H/b.java H/m.java I/d.java I/e.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				I/f.java I/h.java I/i.java K1/d.java L1/a.java M/f.java N/a.java N/d.java N/m.java N1/g.java O1/e.java P0/k.java P2/a.java P2/c.java P2/d.java Q/C0079b.java Q/C0081d.java Q/C0094q.java Q/T.java Q/X.java Q/f0.java S/b.java T/h.java U2/A.java U2/C0109e.java U2/C0113i.java U2/l.java U2/m.java U2/n.java U2/p.java U2/r.java U2/v.java U2/z.java V/e.java V2/d.java V2/j.java W0/d.java W0/k.java W2/b.java W2/i.java X3/b.java Y1/b.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				Y1/c.java Z1/o.java Z2/a.java Z2/d.java com/dexterous/flutterlocalnotifications/ActionBroadcastReceiver.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/dexterous/flutterlocalnotifications/ScheduledNotificationReceiver.java com/pichillilorenzo/flutter_inappwebview_android/MyCookieManager.java com/pichillilorenzo/flutter_inappwebview_android/Util.java com/pichillilorenzo/flutter_inappwebview_android/chrome_custom_tabs/ChromeCustomTabsActivity.java com/pichillilorenzo/flutter_inappwebview_android/chrome_custom_tabs/CustomTabsHelper.java com/pichillilorenzo/flutter_inappwebview_android/in_app_browser/InAppBrowserActivity.java com/pichillilorenzo/flutter_inappwebview_android/in_app_browser/InAppBrowserManager.java com/pichillilorenzo/flutter_inappwebview_android/service_worker/ServiceWorkerManager.java com/pichillilorenzo/flutter_inappwebview_android/types/WebViewAssetLoaderExt.java com/pichillilorenzo/flutter_inappwebview_android/webview/JavaScriptBridgeInterface.java com/pichillilorenzo/flutter_inappwebview_android/webview/in_app_webview/DisplayListenerProxy.java com/pichillilorenzo/flutter_inappwebview_android/webview/in_app_webview/FlutterWebView.java com/pichillilorenzo/flutter_inappwebview_android/webview/in_app_webview/InAppWebView.java com/pichillilorenzo/flutter_inappwebview_android/webview/in_app_webview/InAppWebViewChromeClient.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/pichillilorenzo/flutter_inappwebview_android/webview/in_app_webview/InAppWebViewClient.java com/pichillilorenzo/flutter_inappwebview_android/webview/in_app_webview/InAppWebViewClientCompat.java com/pichillilorenzo/flutter_inappwebview_android/webview/in_app_webview/InputAwareWebView.java f2/m.java p000a/a.java p006b1/b.java p006b1/d.java p006b1/e.java p006b1/f.java p006b1/k.java p006b1/l.java p006b1/m.java p006b1/n.java p011c1/d.java p011c1/e.java p011c1/g.java p011c1/i.java p011c1/k.java p015d0/b.java p015d0/c.java p015d0/g.java p018e/A.java p020e1/j.java p022e3/a.java p022e3/k.java p022e3/o.java p024f0/d.java p025f1/c.java p025f1/f.java p025f1/j.java p025f1/k.java p025f1/p.java p025f1/q.java p025f1/s.java p025f1/w.java p026f3/a.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				p027g/i.java p034h2/g.java p038i1/a.java p041j/A.java p041j/AbstractActivityC0286k.java p041j/E.java p041j/r.java p041j/t.java p042j1/d.java p045k2/c.java p045k2/e.java p048l0/d.java p049l1/a.java p051l3/f.java p051l3/l.java p052m/h.java p052m/i.java p057n/g.java p057n/m.java p058n0/C0317u.java p058n0/H.java p058n0/Q.java p058n0/W.java p060n3/l.java p061o/AbstractC0324a0.java p061o/C0334f0.java p061o/C0358s.java p061o/C0362u.java p061o/F0.java p061o/I.java p061o/K0.java p061o/O.java p061o/S0.java p065o3/d.java p070p3/C0374a.java p070p3/I.java p075q3/f.java p076r/B.java p076r/h.java p076r/n.java p080s/h.java p080s/m.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				p090u1/a.java p098w0/s.java p100w2/c.java p103x1/b.java p104x2/c.java p108y2/c.java p109z/e.java p110z0/f.java u0/p.java
2	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/dexterous/flutterlocalnotifications/models/NotificationDetails.java com/pichillilorenzo/flutter_inappwebview_android/credential_database/URLCredentialContract.java com/pichillilorenzo/flutter_inappwebview_android/types/ClientCertResponse.java com/pichillilorenzo/flutter_inappwebview_android/types/HttpAuthResponse.java p080s/a.java
3	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	C2/C0012l.java C2/C0018s.java C2/U.java W0/i.java W0/j.java W0/k.java X0/j.java com/pichillilorenzo/flutter_inappwebview_android/credential_database/CredentialDatabaseHelper.java
4	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	I3/a.java I3/b.java I3/c.java J3/a.java p041j/RunnableC0288m.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
5	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	p065o3/d.java
6	The App uses the encryption mode CBC with PKCS5/PKCS7 padding. This configuration is vulnerable to padding oracle attacks.	high	CWE: CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-3	A/c.java p049l1/a.java
7	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	Z1/o.java p104x2/c.java p108y2/c.java
8	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	C1/g.java
9	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	p022e3/a.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	arm64-v8a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	arm64-v8a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__fwrite_chk', '__read_chk', '__write_chk', '__memcpy_chk', '__strcpy_chk', '__pread_chk', '__strlen_chk', '__memmove_chk', '__poll_chk', '__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	armeabi-v7a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	armeabi-v7a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	x86_64/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	x86_64/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__fwrite_chk', '__read_chk', '__write_chk', '__memcpy_chk', '__strcpy_chk', '__pread_chk', '__strlen_chk', '__memmove_chk', '__poll_chk', '__readlink_chk']	True info Symbols are stripped.

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00063	Implicit intent(view a web page, make a phone call, etc.)	control	A/c.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/pichillilorenzo/flutter_inappwebview_android/chrome_custom_tabs/ChromeCustomTabsActivity.java com/pichillilorenzo/flutter_inappwebview_android/chrome_custom_tabs/ChromeCustomTabsChannelDelegate.java com/pichillilorenzo/flutter_inappwebview_android/chrome_custom_tabs/CustomTabsHelper.java com/pichillilorenzo/flutter_inappwebview_android/chrome_custom_tabs/TrustedWebActivity.java com/pichillilorenzo/flutter_inappwebview_android/in_app_browser/InAppBrowserManager.java f2/m.java p011c1/e.java p080s/h.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	A/c.java com/pichillilorenzo/flutter_inappwebview_android/chrome_custom_tabs/TrustedWebActivity.java com/pichillilorenzo/flutter_inappwebview_android/in_app_browser/InAppBrowserManager.java f2/m.java p011c1/e.java
00036	Get resource file from res/raw directory	reflection	A/c.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/pichillilorenzo/flutter_inappwebview_android/chrome_custom_tabs/CustomTabsHelper.java f2/m.java p011c1/e.java
00022	Open a file from given absolute path of the file	file	M3/g.java S2/a.java W/O.java W/V.java Z2/b.java com/pichillilorenzo/flutter_inappwebview_android/process_global_config/ProcessGlobalConfigSettings.java p065o3/d.java

RULE ID	BEHAVIOUR	LABEL	FILES
00013	Read file and put it into a stream	file	C2/I.java F/AbstractC0029e.java V2/d.java W/D.java X3/b.java Y/e.java Z/f.java com/dexterous/flutterlocalnotifications/FlutterLocalNotifications Plugin.java com/pichillilorenzo/flutter_inappwebview_android/Util.java p022e3/a.java p048l0/d.java p048l0/i.java p098w0/s.java
00175	Get notification manager and cancel notifications	notification	com/dexterous/flutterlocalnotifications/FlutterLocalNotifications Plugin.java
00096	Connect to a URL and set request method	command network	C2/U.java com/pichillilorenzo/flutter_inappwebview_android/Util.java
00089	Connect to a URL and receive input stream from the server	command network	C2/U.java p108y2/c.java
00109	Connect to a URL and get the response code	network command	C2/U.java p108y2/c.java
00091	Retrieve data from broadcast	collection	C2/C0014n.java U2/l.java com/pichillilorenzo/flutter_inappwebview_android/chrome_custom_tabs/ActionBroadcastReceiver.java com/pichillilorenzo/flutter_inappwebview_android/chrome_custom_tabs/ChromeCustomTabsActivity.java com/pichillilorenzo/flutter_inappwebview_android/in_app_browser/InAppBrowserActivity.java p000a/a.java
00177	Check if permission is granted and request it	permission	F/AbstractC0029e.java
00125	Check if the given file path exist	file	X3/b.java p000a/a.java p049l1/a.java
00001	Initialize bitmap object and compress data (e.g. JPEG) into bitmap object	camera	com/pichillilorenzo/flutter_inappwebview_android/webview/in_app_webview/InAppWebViewChromeClient.java

RULE ID	BEHAVIOUR	LABEL	FILES
00123	Save the response to JSON after connecting to the remote server	network command	com/pichillilorenzo/flutter_inappwebview_android/Util.java
00030	Connect to the remote server through the given URL	network	com/pichillilorenzo/flutter_inappwebview_android/Util.java
00094	Connect to a URL and read data from it	command network	com/pichillilorenzo/flutter_inappwebview_android/Util.java
00003	Put the compressed bitmap data into JSON object	camera	com/pichillilorenzo/flutter_inappwebview_android/webview/in_app_webview/InAppWebView.java
00147	Get the time of current location	collection location	p041j/A.java
00075	Get location of the device	collection location	p041j/A.java
00115	Get last known location of the device	collection location	p041j/A.java
00046	Method reflection	reflection	p000a/a.java
00026	Method reflection	reflection	p000a/a.java
00014	Read file into a stream and put it into a JSON object	file	p022e3/a.java
00209	Get pixels from the latest rendered image	collection	U2/n.java
00210	Copy pixels from the latest rendered image into a Bitmap	collection	U2/n.java

FIREBASE DATABASES ANALYSIS

TITLE	SEVERITY	DESCRIPTION
Firebase Remote Config disabled	secure	Firebase Remote Config is disabled for https://firebaseremoteconfig.googleapis.com/v1/projects/530436436094/namespaces/firebase:fetch?key=AIzaSyDoaW7f-O090k5nDZfeZD_7MtHCaQMjYBo. This is indicated by the response: {'state': 'NO_TEMPLATE'}

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	6/25	android.permission.REQUEST_INSTALL_PACKAGES, android.permission.RECEIVE_BOOT_COMPLETED, android.permission.VIBRATE, android.permission.INTERNET, android.permission.WAKE_LOCK, android.permission.ACCESS_NETWORK_STATE
Other Common Permissions	1/44	com.google.android.c2dm.permission.RECEIVE

Malware Permissions:
Top permissions that are widely abused by known malware.

Other Common Permissions:
Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
t.me	ok	**IP:** 149.154.167.99 **Country:** United Kingdom of Great Britain and Northern Ireland **Region:** England **City:** Lowestoft **Latitude:** 52.475201 **Longitude:** 1.751590 **View:** Google Map
developer.android.com	ok	**IP:** 142.250.139.113 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.ibm.com	ok	**IP:** 23.39.213.36 **Country:** Indonesia **Region:** Jawa Timur **City:** Surabaya **Latitude:** -7.249170 **Longitude:** 112.750832 **View:** Google Map
firebaseinstallations.googleapis.com	ok	**IP:** 172.217.119.4 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
api.flutter.dev	ok	**IP:** 199.36.158.100 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
youtrack.jetbrains.com	ok	**IP:** 63.35.30.167 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
dartbug.com	ok	**IP:** 216.239.36.21 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
api.github.com	ok	**IP:** 140.82.114.6 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
192.168.1.10	ok	No Geolocation information available.
raw.githubusercontent.com	ok	**IP:** 185.199.110.133 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map
www.unicode.org	ok	**IP:** 172.67.74.23 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
github.com	ok	**IP:** 140.82.114.3 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
ns.adobe.com	ok	No Geolocation information available.
schemas.android.com	ok	No Geolocation information available.
192.168.137.1	ok	No Geolocation information available.
docs.flutter.dev	ok	**IP:** 199.36.158.100 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
eos.imes.su	ok	**IP:** 195.133.25.77 **Country:** India **Region:** Delhi **City:** New Delhi **Latitude:** 28.635759 **Longitude:** 77.224449 **View:** Google Map
www.w3.org	ok	**IP:** 104.18.23.19 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
issuetracker.google.com	ok	**IP:** 192.178.192.102 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.example.com	ok	**IP:** 172.66.147.243 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
firebase.google.com	ok	**IP:** 142.250.139.139 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

EMAILS

EMAIL	FILE
u0013android@android.com u0013android@android.com0	p011c1/j.java
authenticationscheme@17463476.fromstring	lib/arm64-v8a/libapp.so
appro@openssl.org	lib/arm64-v8a/libflutter.so

EMAIL	FILE
_list@0150898.empty	lib/armeabi-v7a/libapp.so
_growablelist@0150898._literal2	
_semanticsgeometry@27266271.root	
_growablelist@0150898._ofgrowabl	
_timer@1026248._internal	
dekanat@imes.su	
_growablelist@0150898._literal7	
_headervalue@17463476.parse	
_imagefilter@35065589.blur	
_colorfilter@35065589.lineartosr	
_growablelist@0150898.of	
_assertionerror@0150898._create	
_invocationmirror@0150898._withtype	
_growablelist@0150898._ofefficie	
_growablelist@0150898._ofother	
_link@16069316.fromrawpat	
_colorfilter@35065589.srgbtoline	
_imagefilter@35065589.fromcolorf	
_imagefilter@35065589.composed	
_growablelist@0150898._literal1	
storationinformation@39124995.fromserial	
_bytebuffer@8027147._new	
_growablelist@0150898._literal8	
_uri@0150898.notsimple	
_receiveportimpl@1026248.fromrawrec	
library@imes.su	
_growablelist@0150898._literal5	
_growablelist@0150898._literal3	
_nativesocket@16069316.normal	
_typeerror@0150898._create	
_hashcollisionnode@270137193.fromcollis	
_uri@0150898.directory	
ivanov@imes.su	
priem@imes.su	
_list@0150898._ofefficie	
androidstorage@18353248.implementa	
buh@imes.su	
_growablelist@0150898._literal4	
_assetmanifestbin@372287047.fromstanda	
_uri@0150898.file	
_list@0150898.of	
_future@5048458.immediatee	

EMAIL	FILE
_future@5048458.immediate _compressednode@270137193.single _list@0150898.generate ngstreamsubscription@5048458.zoned studsovet@imes.su _directory@16069316.fromrawpat _list@0150898._ofarray _httpparser@17463476.responsepa _growablelist@0150898._literal6 _list@0150898._ofgrowabl _growablelist@0150898.generate channelcontroller@18353248.implementa _growablelist@0150898._literal _list@0150898._ofother _file@16069316.fromrawpat support@imes.su authenticationscheme@17463476.fromstring _growablelist@0150898.withcapaci _timer@1026248.periodic _growablelist@0150898._ofarray _double@0150898.fromintege	
authenticationscheme@17463476.fromstring	lib/x86_64/libapp.so
appro@openssl.org	lib/x86_64/libflutter.so

HARDCODED SECRETS

POSSIBLE SECRETS
"google_api_key" : "AIzaSyDoaW7f-O090k5nDZfeZD_7MtHCaQMjYBo"
"google_crash_reporting_api_key" : "AIzaSyDoaW7f-O090k5nDZfeZD_7MtHCaQMjYBo"
VGhpcyBpcyB0aGUga2V5IGZvcihBIHNlY3XyZZBzdG9yYWdlIEFFUyBLZXkK

SCAN LOGS

Timestamp	Event	Error
2026-11-02 18:39:52	Generating Hashes	OK
2026-11-02 18:39:52	Extracting APK	OK

Timestamp	Event	Error
2026-11-02 18:39:52	Unzipping	OK
2026-11-02 18:39:52	Parsing APK with androguard	OK
2026-11-02 18:39:52	Extracting APK features using aapt/aapt2	OK
2026-11-02 18:39:53	Getting Hardcoded Certificates/Keystores	OK
2026-11-02 18:39:55	Parsing AndroidManifest.xml	OK
2026-11-02 18:39:55	Extracting Manifest Data	OK
2026-11-02 18:39:55	Manifest Analysis Started	OK
2026-11-02 18:39:55	Performing Static Analysis on: Мой ИМЭС (com.example.vuz_app)	OK
2026-11-02 18:40:00	Checking for Malware Permissions	OK
2026-11-02 18:40:00	Fetching icon path	OK
2026-11-02 18:40:00	Library Binary Analysis Started	OK
2026-11-02 18:40:00	Analyzing lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-11-02 18:40:00	Analyzing lib/arm64-v8a/libapp.so	OK
2026-11-02 18:40:00	Analyzing lib/arm64-v8a/libflutter.so	OK
2026-11-02 18:40:00	Analyzing lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-11-02 18:40:00	Analyzing lib/armeabi-v7a/libapp.so	OK
2026-11-02 18:40:00	Analyzing lib/armeabi-v7a/libflutter.so	OK
2026-11-02 18:40:01	Analyzing lib/x86_64/libdatastore_shared_counter.so	OK
2026-11-02 18:40:01	Analyzing lib/x86_64/libapp.so	OK
2026-11-02 18:40:01	Analyzing lib/x86_64/libflutter.so	OK
2026-11-02 18:40:01	Reading Code Signing Certificate	OK
2026-11-02 18:40:01	Running APKiD 3.2.0	OK
2026-11-02 18:40:06	Detecting Trackers	OK
2026-11-02 18:40:06	Decompiling APK to Java with JADX	OK
2026-11-02 18:40:16	Converting DEX to Smali	OK
2026-11-02 18:40:16	Code Analysis Started on - java_source	OK

Timestamp	Event	Error
2026-11-02 18:40:17	Android SBOM Analysis Completed	OK
2026-11-02 18:40:19	Android SAST Completed	OK
2026-11-02 18:40:19	Android API Analysis Started	OK
2026-11-02 18:40:22	Android API Analysis Completed	OK
2026-11-02 18:40:22	Android Permission Mapping Started	OK
2026-11-02 18:40:24	Android Permission Mapping Completed	OK
2026-11-02 18:40:24	Android Behaviour Analysis Started	OK
2026-11-02 18:40:27	Android Behaviour Analysis Completed	OK
2026-11-02 18:40:27	Extracting Emails and URLs from Source Code	OK
2026-11-02 18:40:28	Email and URL Extraction Completed	OK
2026-11-02 18:40:28	Extracting String data from APK	OK
2026-11-02 18:40:29	Extracting String data from SO	OK
2026-11-02 18:40:30	Extracting String data from Code	OK
2026-11-02 18:40:30	Extracting String values and entropies from Code	OK
2026-11-02 18:40:32	Performing Malware check on extracted domains	OK
2026-11-02 18:41:03	Saving to Database	OK

Report Generated by - MobSF v4.6.4

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.