

UDP

Generated by Doxygen 1.16.1



<b>1 udp</b>	<b>1</b>
<b>2 Topic Index</b>	<b>3</b>
2.1 Topics	3
<b>3 Directory Hierarchy</b>	<b>5</b>
3.1 Directories	5
<b>4 Class Index</b>	<b>7</b>
4.1 Class List	7
<b>5 File Index</b>	<b>9</b>
5.1 File List	9
<b>6 Topic Documentation</b>	<b>11</b>
6.1 work for udp	11
6.1.1 Detailed Description	13
6.1.2 Macro Definition Documentation	13
6.1.2.1 PACKED	13
6.1.3 Typedef Documentation	13
6.1.3.1 udp_pack_t	13
6.1.4 Function Documentation	13
6.1.4.1 add_byte_udp_pack()	13
6.1.4.2 add_date_udp_pack()	14
6.1.4.3 calculate_checksum_udp_pack()	15
6.1.4.4 checksum_compute()	15
6.1.4.5 destroy_udp_pack()	15
6.1.4.6 get_data_hex_udp_pack()	16
6.1.4.7 get_data_udp_pack()	16
6.1.4.8 get_interface_udp_pack()	17
6.1.4.9 get_ip_address_destantion_udp_pack()	18
6.1.4.10 get_ip_address_source_udp_pack()	18
6.1.4.11 get_mac_address_destantion_udp_pack()	19
6.1.4.12 get_mac_address_source_udp_pack()	20
6.1.4.13 get_pack_udp_pack()	20
6.1.4.14 get_port_destantion_udp_pack()	21
6.1.4.15 get_port_source_udp_pack()	21
6.1.4.16 get_size_data_udp_pack()	22
6.1.4.17 inet_mac()	23
6.1.4.18 inet_port()	24
6.1.4.19 init_udp_pack()	24
6.1.4.20 print_udp_pack()	25
6.1.4.21 send_udp_pack()	25
6.1.4.22 set_data_udp_pack()	26

6.1.4.23 set_file_data_udp_pack()	26
6.1.4.24 set_input_data_udp_pack()	27
6.1.4.25 set_interface_udp_pack()	27
6.1.4.26 set_ip_address_destantion_udp_pack()	28
6.1.4.27 set_ip_address_source_udp_pack()	28
6.1.4.28 set_mac_address_destantion_udp_pack()	29
6.1.4.29 set_mac_address_source_udp_pack()	29
6.1.4.30 set_port_destantion_udp_pack()	30
6.1.4.31 set_port_source_udp_pack()	30
6.1.4.32 set_size_udp_pack()	31
6.1.4.33 sum_compute()	31
6.1.5 Variable Documentation	32
6.1.5.1 PACKED	32
<b>7 Directory Documentation</b>	<b>33</b>
7.1 udp_lib Directory Reference	33
<b>8 Class Documentation</b>	<b>35</b>
8.1 pseudo_header Struct Reference	35
8.1.1 Detailed Description	35
8.1.2 Member Data Documentation	35
8.1.2.1 dest_address	35
8.1.2.2 placeholder	35
8.1.2.3 protocol	36
8.1.2.4 source_address	36
8.1.2.5 udp_length	36
8.2 udp_head Struct Reference	36
8.2.1 Detailed Description	36
8.2.2 Member Data Documentation	37
8.2.2.1 m_checksum	37
8.2.2.2 m_length	37
8.2.2.3 m_port_destantion	37
8.2.2.4 m_port_source	37
8.3 udp_pack Struct Reference	37
8.3.1 Detailed Description	38
8.3.2 Member Data Documentation	38
8.3.2.1 m_data	38
8.3.2.2 m_ethhdr	38
8.3.2.3 m_head	38
8.3.2.4 m_interface	38
8.3.2.5 m_iphdr	38
<b>9 File Documentation</b>	<b>39</b>

---

9.1 main.c File Reference . . . . .	39
9.1.1 Function Documentation . . . . .	39
9.1.1.1 main() . . . . .	39
9.2 README.md File Reference . . . . .	39
9.3 udp_lib/udp.c File Reference . . . . .	39
9.3.1 Detailed Description . . . . .	42
9.3.2 Macro Definition Documentation . . . . .	42
9.3.2.1 HEAD_ETH . . . . .	42
9.3.2.2 HEAD_IP . . . . .	42
9.3.2.3 HEAD_PSEUDO . . . . .	42
9.3.2.4 HEAD_UDP . . . . .	42
9.3.2.5 HEAD_UDP_IP . . . . .	42
9.3.2.6 MAX_SIZE_DATA . . . . .	42
9.3.2.7 MIN . . . . .	42
9.3.2.8 NULL_CHECKSUM . . . . .	43
9.4 udp_lib/udp.h File Reference . . . . .	43
9.4.1 Detailed Description . . . . .	44
9.5 udp.h . . . . .	44
<b>Index</b>	<b>47</b>



# Chapter 1

## udp





## Chapter 2

# Topic Index

### 2.1 Topics

Here is a list of all topics with brief descriptions:

work for udp . . . . . [11](#)



## Chapter 3

# Directory Hierarchy

### 3.1 Directories

udp_lib	33
udp.c	39
udp.h	43



## Chapter 4

# Class Index

### 4.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">pseudo_header</a>		
	Struct <a href="#">pseudo_header</a> for calculate checksum for UDP package . . . . .	<a href="#">35</a>
<a href="#">udp_head</a>		
	Struct is header UDP pack . . . . .	<a href="#">36</a>
<a href="#">udp_pack</a>		
	Struct is UDP package . . . . .	<a href="#">37</a>



# Chapter 5

## File Index

### 5.1 File List

Here is a list of all files with brief descriptions:

<a href="#">main.c</a> . . . . .	39
<a href="#">udp_lib/udp.c</a>	
Code file for work udp package . . . . .	39
<a href="#">udp_lib/udp.h</a>	
Header file for work udp package . . . . .	43





# Chapter 6

## Topic Documentation

### 6.1 work for udp

Group function for work udp package.

#### Classes

- struct [udp\\_head](#)  
*Struct is header UDP pack.*
- struct [udp\\_pack](#)  
*Struct is UDP package.*
- struct [pseudo\\_header](#)  
*Struct [pseudo\\_header](#) for calculate checksum for UDP package.*

#### Macros

- #define [PACKED](#) \_\_attribute\_\_((packed))

#### Typedefs

- typedef struct [udp\\_pack](#) \* [udp\\_pack\\_t](#)  
*UDP packet descriptor.*

#### Functions

- static uint16\_t [inet\\_port](#) (const char \*const port)  
*Function support for parsing port.*
- static void [set\\_size\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const uint16\_t size)  
*Function raw write size UDP package.*
- static uint32\_t [sum\\_compute](#) (void \*ptr, uint16\_t nbytes)  
*Function calculate sum in big endian.*
- static uint16\_t [checksum\\_compute](#) (uint32\_t sum)  
*Function calculating from sum big endian to checksum big endian.*

- static void [calculate\\_checksum\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function calculate checksum for ip header and UDP package.*
- static void \* [get\\_pack\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function raw get pointer on UDP package.*
- static void \* [inet\\_mac](#) (const char \*const mac\_address)  
*Function return mac address in big endian.*
- [udp\\_pack\\_t](#) [init\\_udp\\_pack](#) (void)  
*Function for create object UDP package.*
- ssize\_t [set\\_port\\_source\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const port)  
*Function for setting source port in UDP package.*
- ssize\_t [set\\_port\\_destantion\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const port)  
*Function for setting destantion port in UDP package.*
- ssize\_t [set\\_ip\\_address\\_source\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const ip)  
*Function for setting source ip address in UDP package.*
- ssize\_t [set\\_ip\\_address\\_destantion\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const ip)  
*Function for setting destantion ip address in UDP package.*
- uint16\_t [get\\_size\\_data\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function give size data in UDP package.*
- ssize\_t [add\\_date\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, void \*data, uint16\_t size)  
*Function addition data in UDP package.*
- ssize\_t [set\\_data\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, void \*data, const uint16\_t size)  
*Function overriding data in UDP package.*
- ssize\_t [add\\_byte\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const uint8\_t byte)  
*Function addition byte in UDP package.*
- ssize\_t [set\\_input\\_data\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function read data from stdin in UDP package.*
- ssize\_t [set\\_file\\_data\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const file\_name)  
*Function read data from file in UDP package.*
- ssize\_t [set\\_interface\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const interface)  
*Function for pick interface to send UDP package.*
- ssize\_t [send\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function to send UDP package.*
- char \* [get\\_mac\\_address\\_source\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function getting mac address for source.*
- char \* [get\\_mac\\_address\\_destantion\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function setting mac address for destantion.*
- ssize\_t [set\\_mac\\_address\\_source\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const mac\_address)  
*Function setting mac address for source.*
- ssize\_t [set\\_mac\\_address\\_destantion\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const mac\_address)  
*Function setting mac address for destantion.*
- char \* [get\\_interface\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function for getting interface.*
- char \* [get\\_port\\_source\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function for getting port source.*
- char \* [get\\_port\\_destantion\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function for getting port destantion.*
- char \* [get\\_ip\\_address\\_source\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function for getting ip address source.*
- char \* [get\\_ip\\_address\\_destantion\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function for getting ip address destantion.*
- char \* [get\\_data\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)

*Function for getting data.*

- char \* [get\\_data\\_hex\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)

*Function for getting data hex.*

- ssize\_t [print\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)

*Function print all info about udp pack.*

- void [destroy\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)

*Function free UDP package.*

## Variables

- struct [udp\\_head](#) [PACKED](#)

### 6.1.1 Detailed Description

Group function for work udp package.

### 6.1.2 Macro Definition Documentation

#### 6.1.2.1 PACKED

```
struct pseudo\_header PACKED __attribute__((packed))
```

### 6.1.3 Typedef Documentation

#### 6.1.3.1 udp\_pack\_t

```
typedef struct udp\_pack* udp\_pack\_t
```

UDP packet descriptor.

The primary type for working with the library. All functions accept this pointer as an argument.

### 6.1.4 Function Documentation

#### 6.1.4.1 add\_byte\_udp\_pack()

```
ssize_t add_byte_udp_pack (
    udp\_pack\_t pack,
    const uint8_t byte)
```

Function addition byte in UDP package.

#### Note

You must call [init\\_udp\\_pack](#) before this.

#### Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

in	byte	Addition byte in UDP package.
----	------	-------------------------------

### Returns

0 or -1 on error. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
set_date_udp_pack(pack, 'n');
set_date_udp_pack(pack, '\0');
get_not_udp_pack:
destroy_udp_pack(pack);
```

#### 6.1.4.2 add\_date\_udp\_pack()

```
ssize_t add_date_udp_pack (
    udp_pack_t pack,
    void * data,
    uint16_t size)
```

Function addition data in UDP package.

### Note

You must call [init\\_udp\\_pack](#) before this.

### Parameters

in, out	<i>pack</i>	UDP package for work.
in	<i>data</i>	Addition data in UDP package.
in	<i>size</i>	Size addition data for UDP package.

### Returns

0 or -1 on error. Usage example.

```
ssize_t ret = 0;
const char * const message = "Hello, world";
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
add_date_udp_pack(pack, message, strlen(message));
get_not_udp_pack:
destroy_udp_pack(pack);
```

#### 6.1.4.3 calculate\_checksum\_udp\_pack()

```
void calculate_checksum_udp_pack (
    udp_pack_t pack) [static]
```

Function calculate checksum for ip header and UDP package.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

##### Note

This function is private. Not used outside [udp\\_lib/udp.c](#)

#### 6.1.4.4 checksum\_compute()

```
uint16_t checksum_compute (
    uint32_t sum) [static]
```

Function calculating from sum big endian to checksum big endian.

##### Parameters

in	<i>sum</i>	Sum in big endian.
----	------------	--------------------

##### Returns

Checksum in big endian.

##### Note

This function is private. Not used outside [udp\\_lib/udp.c](#)

#### 6.1.4.5 destroy\_udp\_pack()

```
void destroy_udp_pack (
    udp_pack_t pack)
```

Function free UDP package.

##### Note

You must call [init\\_udp\\_pack](#) before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work. Usage example.
---------	-------------	--------------------------------------

```

ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
// other code whit using udp_pack_t
get_not_udp_pack:
destroy_udp_pack(pack);
```

#### 6.1.4.6 get\_data\_hex\_udp\_pack()

```
char * get_data_hex_udp_pack (  
    udp_pack_t pack)
```

Function for getting data hex.

##### Note

You must call `init_udp_pack` before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

##### Returns

Data hex in UDP package or NULL pointer on error. Usage example.

```
ssize_t ret = 0;  
udp_pack_t pack = init_udp_pack();  
if (pack == NULL) {  
    ret = -1;  
    goto get_not_udp_pack;  
}  
{  
    char * data = get_data_hex_udp_pack(pack);  
    if (data == NULL) {  
        ret = -1;  
        goto get_not_data_hex_udp_pack;  
    }  
    // other code whit udp_pack_t  
}  
// other code whit udp_pack_t  
get_not_data_hex_udp_pack:  
get_not_udp_pack:  
destroy_udp_pack(pack);
```

#### 6.1.4.7 get\_data\_udp\_pack()

```
char * get_data_udp_pack (  
    udp_pack_t pack)
```

Function for getting data.

##### Note

You must call `init_udp_pack` before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

**Returns**

Data in UDP package. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
{
    void * data = get_data_udp_pack(pack);
    // other code whit udp_pack_t
}
// other code whit udp_pack_t
get_not_udp_pack:
destroy_udp_pack(pack);
```

**6.1.4.8 get\_interface\_udp\_pack()**

```
char * get_interface_udp_pack (
    udp_pack_t pack)
```

Function for getting interface.

**Note**

You must call [init\\_udp\\_pack](#) before this.

You can call [set\\_interface\\_udp\\_pack](#) before this.

**Parameters**

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

**Returns**

String or NULL pointer is fail. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
ret = set_interface_udp_pack(pack, "lo");
if (ret == -1)
    goto setting_not_interface;
{
    char * interface = NULL;
    interface = get_interface_udp_pack(pack);
    if (interface == NULL)
        getting_not_interface;
    // other code whit udp_pack_t
}
// other code whit udp_pack_t
getting_not_interface:
setting_not_interface:
get_not_udp_pack:
destroy_udp_pack(pack);
```

#### 6.1.4.9 `get_ip_address_destantion_udp_pack()`

```
char * get_ip_address_destantion_udp_pack (
    udp_pack_t pack)
```

Function for getting ip address destantion.

##### Note

You must call `init_udp_pack` before this.

You can call `set_ip_address_destantion_udp_pack` before this.

##### Parameters

<code>in, out</code>	<code>pack</code>	UDP package for work.
----------------------	-------------------	-----------------------

##### Returns

String or NULL pointer is fail. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
ret = set_ip_address_source_udp_pack(pack, "127.0.0.1");
if (ret == -1)
    goto setting_not_ip_destantion;
{
    char * ip_address = NULL;
    ip_address = get_ip_destantion_udp_pack(pack);
    if (ip_address == NULL)
        getting_not_ip_address;
    // other code whit udp_pack_t
}
// other code whit udp_pack_t
getting_not_ip_address:
setting_not_ip_address:
get_not_udp_pack:
destroy_udp_pack(pack);
```

#### 6.1.4.10 `get_ip_address_source_udp_pack()`

```
char * get_ip_address_source_udp_pack (
    udp_pack_t pack)
```

Function for getting ip address source.

##### Note

You must call `init_udp_pack` before this.

You can call `set_ip_address_source_udp_pack` before this.

##### Parameters

<code>in, out</code>	<code>pack</code>	UDP package for work.
----------------------	-------------------	-----------------------



**Returns**

String or NULL pointer is fail. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
ret = set_ip_address_source_udp_pack(pack, "127.0.0.1");
if (ret == -1)
    goto setting_not_ip_address;
{
    char * ip_address = NULL;
    ip_address = get_ip_address_source_udp_pack(pack);
    if (ip_source == NULL)
        getting_not_ip_address;
    // other code whit udp_pack_t
}
// other code whit udp_pack_t
getting_not_ip_address:
setting_not_ip_address:
get_not_udp_pack:
destroy_udp_pack(pack);
```

**6.1.4.11 get\_mac\_address\_destantion\_udp\_pack()**

```
char * get_mac_address_destantion_udp_pack (
    udp_pack_t pack)
```

Function setting mac address for destantion.

**Note**

You must call [init\\_udp\\_pack](#) before this.

You can call [set\\_mac\\_address\\_destantion\\_udp\\_pack](#) before this.

**Parameters**

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

**Returns**

String or NULL pointer is fail. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
ret = set_mac_address_destantion_udp_pack(pack, "ff:ff:ff:ff:ff:ff");
if (ret == -1)
    goto setting_not_mac_address;
{
    char * mac_address = NULL;
    mac_address = get_mac_address_destantion_udp_pack(udp_pack pack);
    // other code whit udp_pack_t
}
// other code whit udp_pack_t
setting_not_mac_address:
get_not_udp_pack:
destroy_udp_pack(pack);
```

#### 6.1.4.12 `get_mac_address_source_udp_pack()`

```
char * get_mac_address_source_udp_pack (
    udp_pack_t pack)
```

Function getting mac address for source.

##### Note

You must call `init_udp_pack` before this.

You can call `set_mac_address_source_udp_pack` before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

##### Returns

String or NULL pointer is fail. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
ret = set_mac_address_source_udp_pack(pack, "ff:ff:ff:ff:ff:ff");
if (ret == -1)
    goto setting_not_mac_address;
{
    char * mac_address = NULL;
    mac_address = get_mac_address_source_udp_pack(pack);
    // other code whit udp_pack_t
}
// other code whit udp_pack_t
setting_not_mac_address:
get_not_udp_pack:
destroy_udp_pack(pack);
```

#### 6.1.4.13 `get_pack_udp_pack()`

```
void * get_pack_udp_pack (
    udp_pack_t pack) [static]
```

Function raw get pointer on UDP package.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

##### Returns

Getting UDP package.

##### Note

This function is private. Not used outside `udp_lib/udp.c`

#### 6.1.4.14 get\_port\_destantion\_udp\_pack()

```
char * get_port_destantion_udp_pack (  
    udp_pack_t pack)
```

Function for getting port destantion.

##### Note

You must call `init_udp_pack` before this.

You can call `set_port_destantion_udp_pack` before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

##### Returns

String or NULL pointer is fail. Usage example.

```
ssize_t ret = 0;  
udp_pack_t pack = init_udp_pack();  
if (pack == NULL) {  
    ret = -1;  
    goto get_not_udp_pack;  
}  
ret = set_port_destantion_udp_pack(pack, "8001");  
if (ret == -1)  
    goto setting_not_port_destantion;  
{  
    char * port_destantion = NULL;  
    port_destantion = get_port_destantion_udp_pack(pack);  
    if (port_destantion == NULL)  
        getting_not_port_destantion;  
    // other code whit udp_pack_t  
}  
// other code whit udp_pack_t  
getting_not_port_destantion:  
setting_not_port_destantion:  
get_not_udp_pack:  
destroy_udp_pack(pack);
```

#### 6.1.4.15 get\_port\_source\_udp\_pack()

```
char * get_port_source_udp_pack (  
    udp_pack_t pack)
```

Function for getting port source.

##### Note

You must call `init_udp_pack` before this.

You can call `set_port_source_udp_pack` before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

## Returns

String or NULL pointer is fail. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
ret = set_port_source_udp_pack(pack, "8003");
if (ret == -1)
    goto setting_not_port_source;
{
    char * port_source = NULL;
    port_source = get_port_source_udp_pack(pack);
    if (port_source == NULL)
        getting_not_port_source;
    // other code whit udp_pack_t
}
// other code whit udp_pack_t
getting_not_port_source:
setting_not_port_source:
get_not_udp_pack:
destroy_udp_pack(pack);
```

### 6.1.4.16 get\_size\_data\_udp\_pack()

```
uint16_t get_size_data_udp_pack (
    udp_pack_t pack)
```

Function give size data in UDP package.

Function for getting size data.

## Note

You must call [init\\_udp\\_pack](#) before this.

## Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

## Returns

size data in UDP package. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
get_size_data_udp_pack(pack);
get_not_udp_pack:
destroy_udp_pack(pack);
```

## Note

You must call [init\\_udp\\_pack](#) before this.

You can call [set\\_data\\_udp\\_pack](#) before this.

You can call [add\\_data\\_udp\\_pack](#) before this.

You can call [add\\_symbol\\_udp\\_pack](#) before this.

## Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

**Returns**

Length data in UDP package. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
{
    uint16_t size_data = get_size_data_udp_pack(pack);
    // other code whit udp_pack_t
}
// other code whit udp_pack_t
getting_not_size_data:
get_not_udp_pack:
destroy_udp_pack(pack);
```

Function give size data in UDP package.

**Note**

You must call `init_udp_pack` before this.

You can call `set_data_udp_pack` before this.

You can call `add_data_udp_pack` before this.

You can call `add_symbol_udp_pack` before this.

**Parameters**

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

**Returns**

Length data in UDP package. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
{
    uint16_t size_data = get_size_data_udp_pack(pack);
    // other code whit udp_pack_t
}
// other code whit udp_pack_t
getting_not_size_data:
get_not_udp_pack:
destroy_udp_pack(pack);
```

**6.1.4.17 inet\_mac()**

```
void * inet_mac (
    const char *const mac_address) [static]
```

Function return mac address in big endian.

**Parameters**

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

**Returns**

Getting buffer mac address.

**Note**

This function is private. Not used outside [udp\\_lib/udp.c](#)

**6.1.4.18 inet\_port()**

```
uint16_t inet_port (
    const char *const port) [static]
```

Function support for parsing port.

**Parameters**

in	<i>port</i>	Port in string format.
----	-------------	------------------------

**Returns**

Port for big indian architect.

**Note**

This function is private. Not used outside [udp\\_lib/udp.c](#)

**6.1.4.19 init\_udp\_pack()**

```
udp_pack_t init_udp_pack (
    void )
```

Function for create object UDP package.

**Note**

You must call [destroy\\_udp\\_pack](#) after this.

**Returns**

pointer or null on error. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
// other code whit using udp_pack_t
get_not_udp_pack:
destroy_udp_pack(pack);
```

#### 6.1.4.20 print\_udp\_pack()

```
ssize_t print_udp_pack (  
    udp_pack_t pack)
```

Function print all info about udp pack.

##### Note

You must call [init\\_udp\\_pack](#) before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

##### Returns

0 or -1 on error. Usage example.

```
ssize_t ret = 0;  
udp_pack_t pack = init_udp_pack();  
if (pack == NULL) {  
    ret = -1;  
    goto get_not_udp_pack;  
}  
ret = print_udp_pack(pack);  
if (ret)  
    goto print_not_udp_pack;  
// other code whit udp_pack_t  
print_not_udp_pack:  
get_not_udp_pack:  
destroy_udp_pack(pack);
```

#### 6.1.4.21 send\_udp\_pack()

```
ssize_t send_udp_pack (  
    udp_pack_t pack)
```

Function to send UDP package.

##### Note

You must call [init\\_udp\\_pack](#) before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

##### Returns

0 or -1 on error. Usage example.

```
ssize_t ret = 0;  
udp_pack_t pack = init_udp_pack();  
if (pack == NULL) {  
    ret = -1;  
    goto get_not_udp_pack;  
}  
send_udp_pack(pack);  
get_not_udp_pack:  
destroy_udp_pack(pack);
```

#### 6.1.4.22 `set_data_udp_pack()`

```
ssize_t set_data_udp_pack (
    udp_pack_t pack,
    void * data,
    const uint16_t size)
```

Function overriding data in UDP package.

##### Note

You must call `init_udp_pack` before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
in	<i>data</i>	New data in UDP package.
in	<i>size</i>	Size new data for UDP package.

##### Returns

0 or -1 on error. Usage example.

```
ssize_t ret = 0;
const char * const message = "Hello, world";
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
set_data_udp_pack(pack, message, strlen(message));
get_not_udp_pack:
destroy_udp_pack(pack);
```

#### 6.1.4.23 `set_file_data_udp_pack()`

```
ssize_t set_file_data_udp_pack (
    udp_pack_t pack,
    const char *const file_name)
```

Function read data from file in UDP package.

##### Note

You must call `init_udp_pack` before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
in	<i>file_name</i>	File name for read in UDP pack.

##### Returns

0 or -1 on error. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
set_file_data_udp_pack(pack, "Hello.txt");
get_not_udp_pack:
destroy_udp_pack(pack);
```



#### 6.1.4.24 set\_input\_data\_udp\_pack()

```
ssize_t set_input_data_udp_pack (  
    udp_pack_t pack)
```

Function read data from stdin in UDP package.

##### Note

You must call `init_udp_pack` before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

##### Returns

0 or -1 on error. Usage example.

```
ssize_t ret = 0;  
udp_pack_t pack = init_udp_pack();  
if (pack == NULL) {  
    ret = -1;  
    goto get_not_udp_pack;  
}  
set_input_data_udp_pack(pack);  
get_not_udp_pack:  
destroy_udp_pack(pack);
```

#### 6.1.4.25 set\_interface\_udp\_pack()

```
ssize_t set_interface_udp_pack (  
    udp_pack_t pack,  
    const char *const interface)
```

Function for pick interface to send UDP package.

##### Note

You must call `init_udp_pack` before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
in	<i>interface</i>	Interface to send UDP pack.

##### Returns

0 or -1 on error. Usage example.

```
ssize_t ret = 0;  
udp_pack_t pack = init_udp_pack();  
if (pack == NULL) {  
    ret = -1;  
    goto get_not_udp_pack;  
}  
set_interface_udp_pack(pack, "lo");  
get_not_udp_pack:  
destroy_udp_pack(pack);
```

#### 6.1.4.26 set\_ip\_address\_destantion\_udp\_pack()

```
ssize_t set_ip_address_destantion_udp_pack (
    udp_pack_t pack,
    const char *const ip)
```

Function for setting destantion ip address in UDP package.

##### Note

You must call `init_udp_pack` before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
in	<i>ip</i>	Destination ip address to send.

##### Returns

0 or -1 on error. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
ret = set_ip_address_destantion_udp_pack(pack, "127.0.0.1");
if (ret == -1)
    goto setting_not_ip_address;
// other code whit udp_pack_t
setting_not_ip_address:
get_not_udp_pack:
destroy_udp_pack(pack);
```

#### 6.1.4.27 set\_ip\_address\_source\_udp\_pack()

```
ssize_t set_ip_address_source_udp_pack (
    udp_pack_t pack,
    const char *const ip)
```

Function for setting source ip address in UDP package.

##### Note

You must call `init_udp_pack` before this.

##### Parameters

in, out	<i>pack</i>	UDP package for work.
in	<i>ip</i>	Source ip to send.

**Returns**

0 or -1 on error. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
ret = set_ip_address_source_udp_pack(pack, "127.0.0.1");
if (ret == -1)
    goto set_not_ip_address;
// other code whit udp_pack_t
set_not_ip_address:
get_not_udp_pack:
destroy_udp_pack(pack);
```

**6.1.4.28 set\_mac\_address\_destantion\_udp\_pack()**

```
ssize_t set_mac_address_destantion_udp_pack (
    udp_pack_t pack,
    const char *const mac_address)
```

Function setting mac address for destantion.

**Note**

You must call `init_udp_pack` before this.

**Parameters**

in, out	<i>pack</i>	UDP package for work.
in	<i>mac_address</i>	String is mac address destantion.

**Returns**

0 or -1 on error. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
ret = set_mac_address_destantion_udp_pack(pack, "ff:ff:ff:ff:ff:ff");
if (ret == -1)
    goto setting_not_mac_address;
// other code whit udp_pack_t
setting_not_mac_address:
get_not_udp_pack:
destroy_udp_pack(pack);
```

**6.1.4.29 set\_mac\_address\_source\_udp\_pack()**

```
ssize_t set_mac_address_source_udp_pack (
    udp_pack_t pack,
    const char *const mac_address)
```

Function setting mac address for source.

**Note**

You must call `init_udp_pack` before this.

**Parameters**

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

in	<i>mac_address</i>	String is mac address source.
----	--------------------	-------------------------------

### Returns

0 or -1 on error. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
ret = set_mac_address_source_udp_pack(pack, "ff:ff:ff:ff:ff:ff");
if (ret == -1)
    goto setting_not_mac_address;
// other code whit udp_pack_t
setting_not_mac_address:
get_not_udp_pack:
destroy_udp_pack(pack);
```

#### 6.1.4.30 set\_port\_destantion\_udp\_pack()

```
ssize_t set_port_destantion_udp_pack (
    udp_pack_t pack,
    const char *const port)
```

Function for setting destantion port in UDP package.

### Note

You must call [init\\_udp\\_pack](#) before this.

### Parameters

in, out	<i>pack</i>	UDP package for work.
in	<i>port</i>	Destination port to send.

### Returns

0 or -1 on error. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
set_port_destantion_udp_pack(pack, "8003");
get_not_udp_pack:
destroy_udp_pack(pack);
```

#### 6.1.4.31 set\_port\_source\_udp\_pack()

```
ssize_t set_port_source_udp_pack (
    udp_pack_t pack,
    const char *const port)
```

Function for setting source port in UDP package.

### Note

You must call [init\\_udp\\_pack](#) before this.

### Parameters

in, out	<i>pack</i>	UDP package for work.
---------	-------------	-----------------------

in	<i>port</i>	Source port to send.
----	-------------	----------------------

**Returns**

0 or -1 on error. Usage example.

```
ssize_t ret = 0;
udp_pack_t pack = init_udp_pack();
if (pack == NULL) {
    ret = -1;
    goto get_not_udp_pack;
}
set_port_source_udp_pack(pack, "8001");
get_not_udp_pack:
destroy_udp_pack(pack);
```

**6.1.4.32 set\_size\_udp\_pack()**

```
void set_size_udp_pack (
    udp_pack_t pack,
    const uint16_t size) [static]
```

Function raw write size UDP package.

**Parameters**

in, out	<i>pack</i>	UDP package for work.
in	<i>size</i>	New size UDP package.

**Note**

This function is private. Not used outside [udp\\_lib/udp.c](#)

**6.1.4.33 sum\_compute()**

```
uint32_t sum_compute (
    void * ptr,
    uint16_t nbytes) [static]
```

Function calculate sum in big endian.

**Parameters**

in	<i>ptr</i>	Buffer for calculating sum in big endian.
in	<i>nbytes</i>	Size buffer for calculating sum.

**Returns**

Sum buffer in big endian.

**Note**

This function is private. Not used outside [udp\\_lib/udp.c](#)

## 6.1.5 Variable Documentation

### 6.1.5.1 PACKED

```
struct pseudo_header PACKED
```

## Chapter 7

# Directory Documentation

### 7.1 udp\_lib Directory Reference

#### Files

- file [udp.c](#)  
*Code file for work udp package.*
- file [udp.h](#)  
*Header file for work udp package.*





# Chapter 8

## Class Documentation

### 8.1 `pseudo_header` Struct Reference

Struct `pseudo_header` for calculate checksum for UDP package.

#### Public Attributes

- `uint32_t` `source_address`
- `uint32_t` `dest_address`
- `uint8_t` `placeholder`
- `uint8_t` `protocol`
- `uint16_t` `udp_length`

#### 8.1.1 Detailed Description

Struct `pseudo_header` for calculate checksum for UDP package.

##### Note

This struct is private. Not used outside `udp_lib/udp.c`

#### 8.1.2 Member Data Documentation

##### 8.1.2.1 `dest_address`

```
uint32_t pseudo_header::dest_address
```

Destination ip addresses

##### 8.1.2.2 `placeholder`

```
uint8_t pseudo_header::placeholder
```

Placeholder is 0x00.

### 8.1.2.3 protocol

```
uint8_t pseudo_header::protocol
```

Constant protocol.

### 8.1.2.4 source\_address

```
uint32_t pseudo_header::source_address
```

Source ip addresses

### 8.1.2.5 udp\_length

```
uint16_t pseudo_header::udp_length
```

Length UDP package.

The documentation for this struct was generated from the following file:

- [udp\\_lib/udp.c](#)

## 8.2 udp\_head Struct Reference

Struct is header UDP pack.

### Public Attributes

- uint16\_t [m\\_port\\_source](#)
- uint16\_t [m\\_port\\_destantion](#)
- uint16\_t [m\\_length](#)
- uint16\_t [m\\_checksum](#)

### 8.2.1 Detailed Description

Struct is header UDP pack.

#### Note

This struct is private. Not used outside [udp\\_lib/udp.c](#)

## 8.2.2 Member Data Documentation

### 8.2.2.1 m\_checksum

```
uint16_t udp_head::m_checksum
```

Calculated software checksum

### 8.2.2.2 m\_length

```
uint16_t udp_head::m_length
```

Length udp pack

### 8.2.2.3 m\_port\_destantion

```
uint16_t udp_head::m_port_destantion
```

Port destantion

### 8.2.2.4 m\_port\_source

```
uint16_t udp_head::m_port_source
```

Port source

The documentation for this struct was generated from the following file:

- [udp\\_lib/udp.c](#)

## 8.3 udp\_pack Struct Reference

Struct is UDP package.

### Public Attributes

- char [m\\_interface](#) [IFNAMSIZ]
- struct ethhdr [m\\_ethhdr](#)
- struct iphdr [m\\_iphdr](#)
- struct [udp\\_head](#) [m\\_head](#)
- uint8\_t [m\\_data](#) [MAX\_SIZE\_DATA]

### 8.3.1 Detailed Description

Struct is UDP package.

#### Note

This struct is private. Not used outside [udp\\_lib/udp.c](#)

### 8.3.2 Member Data Documentation

#### 8.3.2.1 m\_data

```
uint8_t udp_pack::m_data[MAX_SIZE_DATA]
```

Data in UDP package.

#### 8.3.2.2 m\_ethhdr

```
struct ethhdr udp_pack::m_ethhdr
```

Ethernet header start UDP package.

#### 8.3.2.3 m\_head

```
struct udp\_head udp_pack::m_head
```

UDP header

#### 8.3.2.4 m\_interface

```
char udp_pack::m_interface[IFNAMSIZ]
```

Name ethernet interface.

#### 8.3.2.5 m\_iphdr

```
struct iphdr udp_pack::m_iphdr
```

IP header

The documentation for this struct was generated from the following file:

- [udp\\_lib/udp.c](#)

# Chapter 9

## File Documentation

### 9.1 main.c File Reference

```
#include "udp_lib/udp.h"
#include <getopt.h>
#include <stddef.h>
#include <string.h>
```

#### Functions

- int [main](#) (int argc, char \*\*argv)

#### 9.1.1 Function Documentation

##### 9.1.1.1 main()

```
int main (
    int argc,
    char ** argv)
```

### 9.2 README.md File Reference

### 9.3 udp\_lib/udp.c File Reference

Code file for work udp package.

```
#include "udp_lib/udp.h"
#include <stdint.h>
#include <string.h>
#include <stdlib.h>
#include <stdio.h>
```

```
#include <sys/ioctl.h>
#include <sys/stat.h>
#include <unistd.h>
#include <fcntl.h>
#include <errno.h>
#include <stddef.h>
#include <net/if.h>
#include <linux/if_packet.h>
#include <net/ethernet.h>
#include <arpa/inet.h>
#include <sys/socket.h>
#include <netinet/ip.h>
```

## Classes

- struct [udp\\_head](#)  
*Struct is header UDP pack.*
- struct [udp\\_pack](#)  
*Struct is UDP package.*
- struct [pseudo\\_header](#)  
*Struct [pseudo\\_header](#) for calculate checksum for UDP package.*

## Macros

- #define [PACKED](#) \_\_attribute\_\_((packed))
- #define [HEAD\\_ETH](#) sizeof(struct ethhdr)
- #define [HEAD\\_UDP](#) sizeof(struct [udp\\_head](#))
- #define [HEAD\\_IP](#) sizeof(struct iphdr)
- #define [HEAD\\_UDP\\_IP](#) ([HEAD\\_IP](#) + [HEAD\\_UDP](#))
- #define [MAX\\_SIZE\\_DATA](#) (0xFFFF - [HEAD\\_UDP\\_IP](#))
- #define [NULL\\_CHECKSUM](#) 0x0000
- #define [MIN](#)(left, right)
- #define [HEAD\\_PSEUDO](#) sizeof(struct [pseudo\\_header](#))

## Functions

- [udp\\_pack\\_t init\\_udp\\_pack](#) (void)  
*Function for create object UDP package.*
- static uint16\_t [inet\\_port](#) (const char \*const port)  
*Function support for parsing port.*
- ssize\_t [set\\_port\\_source\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const port)  
*Function for setting source port in UDP package.*
- ssize\_t [set\\_port\\_destantion\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const port)  
*Function for setting destantion port in UDP package.*
- ssize\_t [set\\_ip\\_address\\_source\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const ip)  
*Function for setting source ip address in UDP package.*
- ssize\_t [set\\_ip\\_address\\_destantion\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const ip)  
*Function for setting destantion ip address in UDP package.*
- static void [set\\_size\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const uint16\_t size)  
*Function raw write size UDP package.*

- uint16\_t [get\\_size\\_data\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function for getting size data.*
- ssize\_t [add\\_date\\_udp\\_pack](#) (udp\_pack\_t pack, void \*data, const uint16\_t size)  
*Function addition data in UDP package.*
- ssize\_t [set\\_data\\_udp\\_pack](#) (udp\_pack\_t pack, void \*data, uint16\_t size)  
*Function overriding data in UDP package.*
- ssize\_t [add\\_byte\\_udp\\_pack](#) (udp\_pack\_t pack, uint8\_t byte)  
*Function addition byte in UDP package.*
- ssize\_t [set\\_input\\_data\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function read data from stdin in UDP package.*
- ssize\_t [set\\_file\\_data\\_udp\\_pack](#) (udp\_pack\_t pack, const char \*const file\_name)  
*Function read data from file in UDP package.*
- static uint32\_t [sum\\_compute](#) (void \*ptr, uint16\_t nbytes)  
*Function calculate sum in big endian.*
- static uint16\_t [checksum\\_compute](#) (uint32\_t sum)  
*Function calculating from sum big endian to checksum big endian.*
- static void [calculate\\_checksum\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function calculate checksum for ip header and UDP package.*
- ssize\_t [set\\_interface\\_udp\\_pack](#) (udp\_pack\_t pack, const char \*const interface)  
*Function for pick interface to send UDP package.*
- static void \* [get\\_pack\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function raw get pointer on UDP package.*
- ssize\_t [send\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function to send UDP package.*
- static void \* [inet\\_mac](#) (const char \*const mac\_address)  
*Function return mac address in big endian.*
- ssize\_t [set\\_mac\\_address\\_source\\_udp\\_pack](#) (udp\_pack\_t pack, const char \*const mac\_address)  
*Function setting mac address for source.*
- ssize\_t [set\\_mac\\_address\\_destantion\\_udp\\_pack](#) (udp\_pack\_t pack, const char \*const mac\_address)  
*Function setting mac address for destantion.*
- char \* [get\\_ip\\_address\\_source\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function for getting ip address source.*
- char \* [get\\_ip\\_address\\_destantion\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function for getting ip address destantion.*
- char \* [get\\_interface\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function for getting interface.*
- char \* [get\\_mac\\_address\\_source\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function getting mac address for source.*
- char \* [get\\_mac\\_address\\_destantion\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function setting mac address for destantion.*
- char \* [get\\_port\\_destantion\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function for getting port destantion.*
- char \* [get\\_port\\_source\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function for getting port source.*
- ssize\_t [print\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function print all info about udp pack.*
- char \* [get\\_data\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function for getting data.*
- void [destroy\\_udp\\_pack](#) (udp\_pack\_t pack)  
*Function free UDP package.*

## Variables

- struct `udp_head` `PACKED`

### 9.3.1 Detailed Description

Code file for work udp package.

#### Author

Vladsanin777

### 9.3.2 Macro Definition Documentation

#### 9.3.2.1 HEAD\_ETH

```
#define HEAD_ETH sizeof(struct ethhdr)
```

#### 9.3.2.2 HEAD\_IP

```
#define HEAD_IP sizeof(struct iphdr)
```

#### 9.3.2.3 HEAD\_PSEUDO

```
#define HEAD_PSEUDO sizeof(struct pseudo_header)
```

#### 9.3.2.4 HEAD\_UDP

```
#define HEAD_UDP sizeof(struct udp_head)
```

#### 9.3.2.5 HEAD\_UDP\_IP

```
#define HEAD_UDP_IP (HEAD_IP + HEAD_UDP)
```

#### 9.3.2.6 MAX\_SIZE\_DATA

```
#define MAX_SIZE_DATA (0xFFFF - HEAD_UDP_IP)
```

#### 9.3.2.7 MIN

```
#define MIN(  
    left,  
    righth)
```

#### Value:

```
((left) < ((typeof(left))righth)) ? (left) : ((typeof(left))righth))
```



### 9.3.2.8 NULL\_CHECKSUM

```
#define NULL_CHECKSUM 0x0000
```

## 9.4 udp\_lib/udp.h File Reference

Header file for work udp package.

```
#include <stdint.h>
#include <stdlib.h>
```

### Typedefs

- typedef struct [udp\\_pack](#) \* [udp\\_pack\\_t](#)  
*UDP packet descriptor.*

### Functions

- [udp\\_pack\\_t](#) [init\\_udp\\_pack](#) (void)  
*Function for create object UDP package.*
- ssize\_t [set\\_port\\_source\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const port)  
*Function for setting source port in UDP package.*
- ssize\_t [set\\_port\\_destantion\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const port)  
*Function for setting destantion port in UDP package.*
- ssize\_t [set\\_ip\\_address\\_source\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const ip)  
*Function for setting source ip address in UDP package.*
- ssize\_t [set\\_ip\\_address\\_destantion\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const ip)  
*Function for setting destantion ip address in UDP package.*
- uint16\_t [get\\_size\\_data\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function give size data in UDP package.*
- ssize\_t [add\\_date\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, void \*data, uint16\_t size)  
*Function addition data in UDP package.*
- ssize\_t [set\\_data\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, void \*data, const uint16\_t size)  
*Function overriding data in UDP package.*
- ssize\_t [add\\_byte\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const uint8\_t byte)  
*Function addition byte in UDP package.*
- ssize\_t [set\\_input\\_data\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function read data from stdin in UDP package.*
- ssize\_t [set\\_file\\_data\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const file\_name)  
*Function read data from file in UDP package.*
- ssize\_t [set\\_interface\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack, const char \*const interface)  
*Function for pick interface to send UDP package.*
- ssize\_t [send\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function to send UDP package.*
- char \* [get\\_mac\\_address\\_source\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)  
*Function getting mac address for source.*
- char \* [get\\_mac\\_address\\_destantion\\_udp\\_pack](#) ([udp\\_pack\\_t](#) pack)

- Function setting mac address for destantion.*
- ssize\_t [set\\_mac\\_address\\_source\\_udp\\_pack](#) (udp\_pack\_t pack, const char \*const mac\_address)
- Function setting mac address for source.*
- ssize\_t [set\\_mac\\_address\\_destantion\\_udp\\_pack](#) (udp\_pack\_t pack, const char \*const mac\_address)
- Function setting mac address for destantion.*
- char \* [get\\_interface\\_udp\\_pack](#) (udp\_pack\_t pack)
- Function for getting interface.*
- char \* [get\\_port\\_source\\_udp\\_pack](#) (udp\_pack\_t pack)
- Function for getting port source.*
- char \* [get\\_port\\_destantion\\_udp\\_pack](#) (udp\_pack\_t pack)
- Function for getting port destantion.*
- char \* [get\\_ip\\_address\\_source\\_udp\\_pack](#) (udp\_pack\_t pack)
- Function for getting ip address source.*
- char \* [get\\_ip\\_address\\_destantion\\_udp\\_pack](#) (udp\_pack\_t pack)
- Function for getting ip address destantion.*
- char \* [get\\_data\\_udp\\_pack](#) (udp\_pack\_t pack)
- Function for getting data.*
- char \* [get\\_data\\_hex\\_udp\\_pack](#) (udp\_pack\_t pack)
- Function for getting data hex.*
- ssize\_t [print\\_udp\\_pack](#) (udp\_pack\_t pack)
- Function print all info about udp pack.*
- void [destroy\\_udp\\_pack](#) (udp\_pack\_t pack)
- Function free UDP package.*

### 9.4.1 Detailed Description

Header file for work udp package.

Author

Vladsanin777

## 9.5 udp.h

[Go to the documentation of this file.](#)

```

00001
00006
00007 #include <stdint.h>
00008 #include <stdlib.h>
00009
00015
00019 struct udp_pack;
00020
00026 typedef struct udp_pack * udp_pack_t;
00027
00045 udp_pack_t init_udp_pack(void);
00046
00066 ssize_t set_port_source_udp_pack(udp_pack_t pack, const char * const port);
00067
00087 ssize_t set_port_destantion_udp_pack(udp_pack_t pack, const char * const port);
00088
00112 ssize_t set_ip_address_source_udp_pack( \
00113     udp_pack_t pack, const char * const ip);
00114
00138 ssize_t set_ip_address_destantion_udp_pack( \
00139     udp_pack_t pack, const char * const ip);
00140
00159 uint16_t get_size_data_udp_pack(udp_pack_t pack);

```

```
00160
00182 ssize_t add_data_udp_pack(udp_pack_t pack, void * data, uint16_t size);
00183
00205 ssize_t set_data_udp_pack(udp_pack_t pack, void * data, \
00206     const uint16_t size);
00207
00228 ssize_t add_byte_udp_pack(udp_pack_t pack, \
00229     const uint8_t byte);
00230
00249 ssize_t set_input_data_udp_pack(udp_pack_t pack);
00250
00270 ssize_t set_file_data_udp_pack( \
00271     udp_pack_t pack, const char * const file_name);
00272
00292 ssize_t set_interface_udp_pack( \
00293     udp_pack_t pack, const char * const interface);
00294
00313 ssize_t send_udp_pack(udp_pack_t pack);
00314
00343 char * get_mac_address_source_udp_pack(udp_pack_t pack);
00344
00373 char * get_mac_address_destantion_udp_pack(udp_pack_t pack);
00374
00398 ssize_t set_mac_address_source_udp_pack(udp_pack_t pack, \
00399     const char * const mac_address);
00400
00424 ssize_t set_mac_address_destantion_udp_pack(udp_pack_t pack, \
00425     const char * const mac_address);
00426
00458 char * get_interface_udp_pack(udp_pack_t pack);
00459
00491 char * get_port_source_udp_pack(udp_pack_t pack);
00492
00524 char * get_port_destantion_udp_pack(udp_pack_t pack);
00525
00557 char * get_ip_address_source_udp_pack(udp_pack_t pack);
00558
00590 char * get_ip_address_destantion_udp_pack(udp_pack_t pack);
00591
00618 uint16_t get_size_data_udp_pack(udp_pack_t pack);
00619
00642 char * get_data_udp_pack(udp_pack_t pack);
00643
00671 char * get_data_hex_udp_pack(udp_pack_t pack);
00672
00695 ssize_t print_udp_pack(udp_pack_t pack);
00696
00714 void destroy_udp_pack(udp_pack_t pack);
00715
```



# Index

add\_byte\_udp\_pack  
    work for udp, [13](#)

add\_date\_udp\_pack  
    work for udp, [14](#)

calculate\_checksum\_udp\_pack  
    work for udp, [14](#)

checksum\_compute  
    work for udp, [15](#)

dest\_address  
    pseudo\_header, [35](#)

destroy\_udp\_pack  
    work for udp, [15](#)

get\_data\_hex\_udp\_pack  
    work for udp, [15](#)

get\_data\_udp\_pack  
    work for udp, [16](#)

get\_interface\_udp\_pack  
    work for udp, [17](#)

get\_ip\_address\_destantion\_udp\_pack  
    work for udp, [17](#)

get\_ip\_address\_source\_udp\_pack  
    work for udp, [18](#)

get\_mac\_address\_destantion\_udp\_pack  
    work for udp, [19](#)

get\_mac\_address\_source\_udp\_pack  
    work for udp, [19](#)

get\_pack\_udp\_pack  
    work for udp, [20](#)

get\_port\_destantion\_udp\_pack  
    work for udp, [20](#)

get\_port\_source\_udp\_pack  
    work for udp, [21](#)

get\_size\_data\_udp\_pack  
    work for udp, [22](#)

HEAD\_ETH  
    udp.c, [42](#)

HEAD\_IP  
    udp.c, [42](#)

HEAD\_PSEUDO  
    udp.c, [42](#)

HEAD\_UDP  
    udp.c, [42](#)

HEAD\_UDP\_IP  
    udp.c, [42](#)

inet\_mac  
    work for udp, [23](#)

inet\_port  
    work for udp, [24](#)

init\_udp\_pack  
    work for udp, [24](#)

m\_checksum  
    udp\_head, [37](#)

m\_data  
    udp\_pack, [38](#)

m\_ethhdr  
    udp\_pack, [38](#)

m\_head  
    udp\_pack, [38](#)

m\_interface  
    udp\_pack, [38](#)

m\_iphdr  
    udp\_pack, [38](#)

m\_length  
    udp\_head, [37](#)

m\_port\_destantion  
    udp\_head, [37](#)

m\_port\_source  
    udp\_head, [37](#)

main  
    main.c, [39](#)

main.c, [39](#)

main, [39](#)

MAX\_SIZE\_DATA  
    udp.c, [42](#)

MIN  
    udp.c, [42](#)

NULL\_CHECKSUM  
    udp.c, [42](#)

PACKED  
    work for udp, [13](#), [32](#)

placeholder  
    pseudo\_header, [35](#)

print\_udp\_pack  
    work for udp, [24](#)

protocol  
    pseudo\_header, [35](#)

pseudo\_header, [35](#)

    dest\_address, [35](#)

    placeholder, [35](#)

    protocol, [35](#)

    source\_address, [36](#)

    udp\_length, [36](#)

README.md, [39](#)

- send\_udp\_pack
  - work for udp, [25](#)
- set\_data\_udp\_pack
  - work for udp, [25](#)
- set\_file\_data\_udp\_pack
  - work for udp, [26](#)
- set\_input\_data\_udp\_pack
  - work for udp, [26](#)
- set\_interface\_udp\_pack
  - work for udp, [27](#)
- set\_ip\_address\_destantion\_udp\_pack
  - work for udp, [27](#)
- set\_ip\_address\_source\_udp\_pack
  - work for udp, [28](#)
- set\_mac\_address\_destantion\_udp\_pack
  - work for udp, [29](#)
- set\_mac\_address\_source\_udp\_pack
  - work for udp, [29](#)
- set\_port\_destantion\_udp\_pack
  - work for udp, [30](#)
- set\_port\_source\_udp\_pack
  - work for udp, [30](#)
- set\_size\_udp\_pack
  - work for udp, [31](#)
- source\_address
  - pseudo\_header, [36](#)
- sum\_compute
  - work for udp, [31](#)
- udp, [1](#)
- udp.c
  - HEAD\_ETH, [42](#)
  - HEAD\_IP, [42](#)
  - HEAD\_PSEUDO, [42](#)
  - HEAD\_UDP, [42](#)
  - HEAD\_UDP\_IP, [42](#)
  - MAX\_SIZE\_DATA, [42](#)
  - MIN, [42](#)
  - NULL\_CHECKSUM, [42](#)
- udp\_head, [36](#)
  - m\_checksum, [37](#)
  - m\_length, [37](#)
  - m\_port\_destantion, [37](#)
  - m\_port\_source, [37](#)
- udp\_length
  - pseudo\_header, [36](#)
- udp\_lib Directory Reference, [33](#)
- udp\_lib/udp.c, [39](#)
- udp\_lib/udp.h, [43](#), [44](#)
- udp\_pack, [37](#)
  - m\_data, [38](#)
  - m\_ethhdr, [38](#)
  - m\_head, [38](#)
  - m\_interface, [38](#)
  - m\_iphdr, [38](#)
- udp\_pack\_t
  - work for udp, [13](#)
- add\_byte\_udp\_pack, [13](#)
- add\_date\_udp\_pack, [14](#)
- calculate\_checksum\_udp\_pack, [14](#)
- checksum\_compute, [15](#)
- destroy\_udp\_pack, [15](#)
- get\_data\_hex\_udp\_pack, [15](#)
- get\_data\_udp\_pack, [16](#)
- get\_interface\_udp\_pack, [17](#)
- get\_ip\_address\_destantion\_udp\_pack, [17](#)
- get\_ip\_address\_source\_udp\_pack, [18](#)
- get\_mac\_address\_destantion\_udp\_pack, [19](#)
- get\_mac\_address\_source\_udp\_pack, [19](#)
- get\_pack\_udp\_pack, [20](#)
- get\_port\_destantion\_udp\_pack, [20](#)
- get\_port\_source\_udp\_pack, [21](#)
- get\_size\_data\_udp\_pack, [22](#)
- inet\_mac, [23](#)
- inet\_port, [24](#)
- init\_udp\_pack, [24](#)
- PACKED, [13](#), [32](#)
- print\_udp\_pack, [24](#)
- send\_udp\_pack, [25](#)
- set\_data\_udp\_pack, [25](#)
- set\_file\_data\_udp\_pack, [26](#)
- set\_input\_data\_udp\_pack, [26](#)
- set\_interface\_udp\_pack, [27](#)
- set\_ip\_address\_destantion\_udp\_pack, [27](#)
- set\_ip\_address\_source\_udp\_pack, [28](#)
- set\_mac\_address\_destantion\_udp\_pack, [29](#)
- set\_mac\_address\_source\_udp\_pack, [29](#)
- set\_port\_destantion\_udp\_pack, [30](#)
- set\_port\_source\_udp\_pack, [30](#)
- set\_size\_udp\_pack, [31](#)
- sum\_compute, [31](#)
- udp\_pack\_t, [13](#)
- work for udp, [11](#)