





```
Router(config) #access-list 1 permit 192.168.0.0 0.0.0.255
Router(config) #ip nat pool white-address 100.10.11.77 100.10.11.99 netmask 255.255.255.0
Router(config) #ip nat inside source list 1 pool white-address
Router(config) #int fa0/0
Router(config-if) #ip nat inside
Router(config-if) #ip t fa0/1
Router(config-if) #ip nat outside
```

```
C:\>ping 100.10.10.2

Pinging 100.10.10.2 with 32 bytes of data:

Reply from 100.10.10.2: bytes=32 time<1ms TTL=254

Reply from 100.10.10.2: bytes=32 time=4ms TTL=254

Reply from 100.10.10.2: bytes=32 time<1ms TTL=254

Reply from 100.10.10.2: bytes=32 time<1ms TTL=254

Ping statistics for 100.10.10.2:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 4ms, Average = 1ms
```

```
Router#show ip nat translation
                                        Outside local
Pro Inside global Inside local
                                                           Outside global
icmp 100.10.11.77:5
                     192.168.0.2:5
                                        100.10.10.2:5
                                                           100.10.10.2:5
                     192.168.0.2:6
                                        100.10.10.2:6
                                                           100.10.10.2:6
icmp 100.10.11.77:6
icmp 100.10.11.77:7
                     192.168.0.2:7
                                        100.10.10.2:7
                                                           100.10.10.2:7
icmp 100.10.11.77:8
                     192.168.0.2:8
                                        100.10.10.2:8
                                                           100.10.10.2:8
```