

Agile

Containers

DevOps
Automation

DevOps Linux

DevOps Services

Languages

Network

Scripting

Security

Solutions

Virtualization

Windows

Glib Examples

Go Examples

Javascript
Examples

D4D Examples

APIs

Bash Associative Array

Bash Functions

Bash Regex

Bash *

Color Distance [↗](#)Shell Problems [↗](#)

Shell-Scripting

awk

packages.json [↗](#)

sed



Bash Functions Cheat Sheet

[Edit Cheat Sheet ↗](#)**See also** [Bash](#)

Declaring Functions

Note: the () after the function name is optional.

```
my_func() {  
    printf "Hello!\n"  
}  
  
# Call it with  
my_func
```

Passing Parameters

Note: Bash doesn't support prototyping, parameter types or references.

```
my_func() {  
    printf "Hello %s %s\n" "$1" "$2"  
}  
  
my_func "literal 1" "$var2"
```

It is good style to "shift" parameters like this

```
my_func() {  
    param1=$1; shift  
    param2=$1; shift  
  
    printf "Hello %s %s\n" "$param1" "$param2"  
}
```

Return Values

You can return **numbers only**! Similar to program exit codes, functions have return codes. Check below to see how to return data from a function.

CHEAT SHEETS

Agile

APIs

Containers

Bash Associative Array

DevOps
Automation**Bash Functions**

Bash Regex

Bash *

Color Distance [🔗](#)

DevOps Linux

Shell Problems [🔗](#)

DevOps Services

Shell-Scripting

Languages

awk

packages.json [🔗](#)

Network

sed

Scripting

Security

Solutions

Virtualization

Windows

Glib Examples

Go Examples

Javascript
Examples

DHD Examples

```
my_func() {  
    return 1  
}  
  
my_func  
  
# Check return code  
if [ $? -ne 0 ]; then  
    printf "Return code: %d\n" $?  
fi
```

Returning data from a function

The best way to return data is catching the functions STDOUT using `\$()`

```
my_func() {  
    printf "Some output lines\nLine2\nLine3\n"  
}  
  
output=$(my_func)
```

[Comment on Disqus](#)