

# sed cheatsheet

Proudly sponsored by

**Segment** Send data to any tool without having to implement a new API every time.

*ethical* ad by CodeFund

Here's some hints on using sed.

## In place replacements

In GNU sed: use `-i` without arg.

```
sed -i -e 's/foo/bar/' example.md
```

In OSX, `-i ''` is required.

```
sed -i '' -e 's/foo/bar/' example.md
```

## File regions

Print until a certain line is met

```
sed '/begin api/q'
```

Print until a certain line is met, but not that line

```
sed '/^# begin/, $d'
```


Print everything after a given line

```
sed -n '/end api/, $p'
```



**0 Comments** for this cheatsheet. [Write yours!](#)

Search 381+ cheatsheets



Over 381 curated cheatsheets, by developers for developers.

Devhints home

## Other CLI cheatsheets

Cron  
cheatsheet

Homebrew  
cheatsheet

httpie  
cheatsheet

adb (Android Debug  
Bridge)  
cheatsheet

## Top cheatsheets

Elixir  
cheatsheet

ES2015+  
cheatsheet

React.js  
cheatsheet

Vimdiff  
cheatsheet

composer  
cheatsheet

Fish shell  
cheatsheet

Vim  
cheatsheet

Vim scripting  
cheatsheet