AML LAB



Name-Anmol

Batch-20 AIML

Sap-590011794

Submitted to-Prof. Sahinur Laskar

Index

1	Data Processing using Python Lib
2	Predicting House Prices using linear Regression
3	Predicting Stock Prices using linear Regression
4	Customer Churn Prediction using Linear regression
5	Spam Email Detection Model
6	Credit Risk Assesment model
7	Anomaly Detection model
8	Student Performance level analysis model

1)Data processing using Python libararies

Using pandas to plot and clean data

Using matplotlib and seaborn to plt the outputs

EXE-2

Step-0 Data Processing

Python libraries such as pandas, matplotlib, and seaborn were used to handle and visualize the dataset. Pandas was used for loading, inspecting, and cleaning the data, while matplotlib and seaborn were used to generate plots that help analyze relationships between variables and understand patterns in the dataset.

Step-1 Problem Defination

The objective of this experiment is to build a machine learning model that can predict house prices using the given dataset. The dataset contains features such as area, number of bedrooms, location, and other property attributes. Since price is a continuous numeric value, this problem is a regression task. The model must learn how these features influence price and estimate it accurately.

Step-2 Data understanding

Using functions like df.head() and df.info(), the dataset structure was examined. Each row represents a house, and each column represents a feature describing that house.

The dataset contains:

Numerical features : Area, Bedrooms, Bathrooms, Age, Parking, Balcony, etc.

Categorical features : Location and Furnished

The target variable is Price, which is denoted as y, and the remaining features are used as input variables x. Since machine learning models require numeric input, categorical features must be encoded before training.

Step-3 Data Processing

Categorical variables such as Location and Furnished were converted into numerical format using one-hot encoding. This creates new columns such as:

- Location_Urban
- Location_Rural
- Furnished_Yes

This transformation was done using the get_dummies() function. Numerical features were already in usable format and therefore did not require modification. This preprocessing step ensures the dataset is suitable for machine learning algorithms. This aligns with the preprocessing stage of the pipeline where raw data is transformed into model-ready numerical form

Step-4 Data Selection and Model Training

As discussed earlier, Price was selected as the target variable (y), and all other columns were selected as input features (x). For demonstration purposes, the model was trained on the full dataset instead of splitting into training and testing sets.

The model chosen was Linear Regression, since the dependent variable is continuous. Regression models are specifically designed to predict numeric outputs, unlike classification models which predict categories.

Step 5-Prediction

After training, the model was used to generate predictions using the .predict() function. By providing input feature values (X), the model calculates estimated house prices based

on the learned relationship between features and target variable.

Step-6 Evaluation

The model performance was evaluated using:

Mean Squared Error (MSE) -- measures average squared difference between predicted and actual prices

R^2 Score - measures how well the model explains variation in price .

The obtained values showed MSE close to zero and R^2 close to 1, indicating that the model fit the training data extremely well. According to regression evaluation theory, lower MSE

Additionally, the results were visualized using a scatter plot to compare predicted prices with actual prices, allowing visual inspection of model accuracy.

Predicting Housing Prices: Develop a regression model to predict house prices based on features like location, size, and amenities. italicized text

```
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn import linear_model as lm
from sklearn.metrics import mean_squared_error, r2_score
```

```
df=pd.read_csv('/content/drive/MyDrive/Housing_Price_Dataset_120_Records.csv')
print(df.head())
```

```
  HouseID  Location  Area_sqft  Bedrooms  Bathrooms  Balcony  Parking  \
0    H001     Rural       1028         1          3        0        0
1    H002     Rural       2316         1          4        0        0
2    H003     Urban       1834         1          2        2        2
3    H004     Urban       1719         3          1        0        2
4    H005  Suburban       1118         2          3        0        0

   Age_Years Furnished   Price
0          5       Yes   55.84
1          3       Yes  103.88
2         23        No   86.42
3         14        No   96.77
4         13       Yes   63.94
```

Data Preprocessing

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 120 entries, 0 to 119
Data columns (total 10 columns):
 #   Column     Non-Null Count  Dtype
---  ------     --------------  -----
 0   HouseID    120 non-null    object
 1   Location   120 non-null    object
 2   Area_sqft  120 non-null    int64
 3   Bedrooms   120 non-null    int64
 4   Bathrooms  120 non-null    int64
 5   Balcony    120 non-null    int64
 6   Parking    120 non-null    int64
 7   Age_Years  120 non-null    int64
 8   Furnished  120 non-null    object
 9   Price      120 non-null    float64
dtypes: float64(1), int64(6), object(3)
memory usage: 9.5+ KB
```

```
pd.Index(['HouseID','Location','Area_sqft','Bedrooms','Bathrooms','Balcony','Parking','Age_Years','Furnished','Price'])
```

```
Index(['HouseID', 'Location', 'Area_sqft', 'Bedrooms', 'Bathrooms', 'Balcony',
       'Parking', 'Age_Years', 'Furnished', 'Price'],
      dtype='object')
```

```
df=pd.get_dummies(df,columns=['Furnished','Location'],drop_first=False)
```

```
df.head()
```

	HouseID	Area_sqft	Bedrooms	Bathrooms	Balcony	Parking	Age_Years	Price	Furnished_No	Furnished_Yes	Location_Rural
0	H001	1028	1	3	0	0	5	55.84	False	True	True
1	H002	2316	1	4	0	0	3	103.88	False	True	True
2	H003	1834	1	2	2	2	23	86.42	True	False	False
3	H004	1719	3	1	0	2	14	96.77	True	False	False
4	H005	1118	2	3	0	0	13	63.94	False	True	False

```
reg=lm.LinearRegression()
reg.fit(df[['Area_sqft','Bedrooms','Bathrooms','Balcony','Parking','Age_Years','Furnished_Yes','Location_Suburban','Locatio
```

```
▾ LinearRegression
LinearRegression()
```

```
import pickle
with open('model_pickle','wb') as f:
  pickle.dump(reg,f)
```

```
y_pred = reg.predict(df[['Area_sqft','Bedrooms','Bathrooms','Balcony','Parking','Age_Years','Furnished_Yes','Location_Subur
mse = mean_squared_error(df.Price, y_pred)
r2 = r2_score(df.Price, y_pred)
print(f'Mean Squared Error: {mse}')
print(f'R^2 Score: {r2}')
```

```
Mean Squared Error: 6.344966032873642e-27
R^2 Score: 1.0
```

```
plot = sns.scatterplot(x=df.Price, y=y_pred)
plot.set_xlabel('Actual Prices')
plot.set_ylabel('Predicted Prices')
```

```
Text(0, 0.5, 'Predicted Prices')
```



EXE-3

Step-0 Libraries Used

Several Python libraries were used to perform data handling, model training, evaluation, and visualization for stock price prediction.

NumPy: was used for numerical operations and array manipulation required during model input preparation.

Pandas: was used for loading the dataset, filtering stock data, converting date formats, and creating new features such as the numerical time variable (Days).

Matplotlib and **Seaborn:** were used for visualization to plot stock price trends and analyze the distribution of values.

Scikit-learn: was used to implement machine learning functionality. The train_test_split module was used to divide data into training and testing sets, the LinearRegression model was used for prediction, and evaluation metrics such as **Mean Squared Error** and **R^2 score** were used to assess model performance.

Pickle: was used to save the trained model so it can be reused later without retraining.

Step-1 Problem Definition

The objective of this experiment is to develop a time series prediction model to forecast stock prices. The dataset contains historical stock data including Date, Open, High, Low, Close prices, and Volume for different companies. Since the output variable (stock price) is numeric and changes over time, this is a regression-based time series prediction problem.

Step-2 Data Understanding

The dataset was loaded using pandas and inspected to understand its structure. Each row represents a stock record for a specific date, and each column represents a feature describing that day's market performance.

The dataset contains the following attributes:

- Date → trading day
- Stock → company ticker symbol
- Open, High, Low, Close → price values
- Volume → number of shares traded

As shown in the dataset, the data contains multiple stocks such as AAPL and TSLA ,For modeling purposes, only one stock (AAPL) was selected so that a single time series could be analyzed.

Step-3 Data Preprocessing

The Date column was converted into datetime format to enable time-based calculations. A new feature called Days was created by subtracting the minimum date from each date value. This converts time into numerical form representing the number of days since the start of the dataset.

This step is necessary because machine learning models cannot directly process date values; they require numerical inputs.

Step-4 Feature Selection, Model Selection and Training

In this step, the input (X) was taken as the Days column, which represents time in numeric form, and the output (y) was selected as the closing stock price.

The dataset was divided into training and testing sets using an 80:20 ratio. Shuffling was disabled so that the chronological

order of dates remains unchanged. This is important for time-series data because predictions should always be made using past values to estimate future ones.

A Linear Regression model was chosen for this task because the target variable is continuous. The model was trained using the training data, where it learned the relationship between time and stock price by fitting a line that minimizes prediction error. After training, the model parameters were stored so that it could later be reused without retraining.

Step-6 Prediction

After training, the model was used to predict stock prices for the test dataset. The predictions generated represent estimated closing prices based solely on time progression.

As shown in the output, the predicted values form a continuous decreasing trend, indicating the model learned a linear relationship

Step-7 Evaluation

Model performance was evaluated using two regression metrics:

- Mean Squared Error (MSE):Measures average squared difference between predicted and actual values. Lower values indicate better performance.

- R^2 Score:Measures how well the model explains variance in the data. Values closer to 1 indicate better fit.

From the results :

MSE is approx.= 3072

R^2 is approx.= -11.21

The negative R^2 indicates the model performs poorly and does not fit the data well. This occurs because stock prices follow nonlinear patterns, while linear regression can only model straight-line relationships.

Predicting Stock Prices: Develop a time series prediction model to forecast stock prices.

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn import linear_model as lm
from sklearn.metrics import r2_score,mean_squared_error
import pickle
```

```
df=pd.read_csv('/content/drive/MyDrive/stock_price_timeseries_dataset.csv')
df
```

	Date	Stock	Open	High	Low	Close	Volume
0	2020-01-01	AAPL	173.80	174.75	173.68	174.43	8204212
1	2020-01-02	AAPL	176.01	177.59	174.07	177.55	2766891
2	2020-01-03	AAPL	177.57	178.37	176.62	176.71	5721339
3	2020-01-06	AAPL	176.01	177.58	171.33	171.73	9242680
4	2020-01-07	AAPL	171.85	172.20	170.69	170.82	4416664
...	...	...	...	...	...	...	...
6520	2024-12-25	TSLA	225.09	225.21	221.66	223.18	9701165
6521	2024-12-26	TSLA	222.07	222.87	220.31	220.32	6045143
6522	2024-12-27	TSLA	219.94	221.69	218.38	219.57	8512677
6523	2024-12-30	TSLA	219.54	220.33	216.70	217.33	9137479
6524	2024-12-31	TSLA	216.47	219.61	216.19	218.41	2097124

6525 rows × 7 columns

Next steps: Generate code with df New interactive sheet

```
df_stock=df[df['Stock']=='AAPL']
df_stock.head()
```

	Date	Stock	Open	High	Low	Close	Volume
0	2020-01-01	AAPL	173.80	174.75	173.68	174.43	8204212
1	2020-01-02	AAPL	176.01	177.59	174.07	177.55	2766891
2	2020-01-03	AAPL	177.57	178.37	176.62	176.71	5721339
3	2020-01-06	AAPL	176.01	177.58	171.33	171.73	9242680
4	2020-01-07	AAPL	171.85	172.20	170.69	170.82	4416664

Next steps: Generate code with df_stock New interactive sheet

```
df_stock['Date']=pd.to_datetime(df_stock['Date'])
df_stock.info()
```

```
<class 'pandas.core.frame.DataFrame'>
Index: 1305 entries, 0 to 1304
Data columns (total 7 columns):
 #   Column  Non-Null Count  Dtype
---  ------  --------------  -----
 0   Date    1305 non-null   datetime64[ns]
 1   Stock   1305 non-null   object
 2   Open    1305 non-null   float64
 3   High    1305 non-null   float64
 4   Low     1305 non-null   float64
 5   Close   1305 non-null   float64
 6   Volume  1305 non-null   int64
dtypes: datetime64[ns](1), float64(4), int64(1), object(1)
memory usage: 113.9+ KB
```

```
/tmp/ipython-input-31740583.py:1: SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame.
Try using .loc[row_indexer,col_indexer] = value instead

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view
  df_stock['Date']=pd.to_datetime(df_stock['Date'])
```

```
df_stock['Days']=(df_stock['Date']-df_stock['Date'].min())
df_stock
```

```
/tmp/ipython-input-1482232864.py:1: SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame.
Try using .loc[row_indexer,col_indexer] = value instead

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view
  df_stock['Days']=(df_stock['Date']-df_stock['Date'].min())
```

	Date	Stock	Open	High	Low	Close	Volume	Days
0	2020-01-01	AAPL	173.80	174.75	173.68	174.43	8204212	0 days
1	2020-01-02	AAPL	176.01	177.59	174.07	177.55	2766891	1 days
2	2020-01-03	AAPL	177.57	178.37	176.62	176.71	5721339	2 days
3	2020-01-06	AAPL	176.01	177.58	171.33	171.73	9242680	5 days
4	2020-01-07	AAPL	171.85	172.20	170.69	170.82	4416664	6 days
...	...	...	...	...	...	...	...	...
1300	2024-12-25	AAPL	207.96	210.35	206.18	208.42	4510463	1820 days
1301	2024-12-26	AAPL	208.69	214.63	207.23	213.99	4335705	1821 days
1302	2024-12-27	AAPL	213.99	217.12	212.77	216.24	2601207	1822 days
1303	2024-12-30	AAPL	216.62	217.17	213.72	215.53	7203690	1825 days
1304	2024-12-31	AAPL	215.26	218.50	215.06	217.00	5083372	1826 days

1305 rows × 8 columns

Next steps: Generate code with df_stock New interactive sheet

```
x=df_stock['Days']
y=df_stock['Close']
```

```
x_train,x_test,y_train,y_test=train_test_split(x,y,test_size=0.2,shuffle=False)
```

```
model=lm.LinearRegression()
model.fit(x_train.dt.days.values.reshape(-1,1), y_train)
with open('model_pickle','wb') as f:
  pickle.dump(model,f)
```

```
y_pred=model.predict(x_test.dt.days.values.reshape(-1,1))
y_pred
```

```
       150.49573228, 150.47262862, 150.40331765, 150.380214  ,
       150.35711034, 150.33400669, 150.31090303, 150.24159206,
       150.21848841, 150.19538475, 150.17228109, 150.14917744,
       150.07986647, 150.05676281, 150.03365916, 150.0105555 ,
       149.98745185, 149.91814088, 149.89503722, 149.87193357,
       149.84882991, 149.82572625, 149.75641529, 149.73331163,
       149.71020797, 149.68710432, 149.66400066, 149.59468969,
       149.57158604, 149.54848238, 149.52537873, 149.50227507,
       149.4329641 , 149.40986045, 149.38675679, 149.36365313,
       149.34054948, 149.27123851, 149.24813485, 149.2250312 ,
       149.20192754, 149.17882389, 149.10951292, 149.08640926,
       149.06330561, 149.04020195, 149.01709829, 148.94778733,
       148.92468367, 148.90158001, 148.87847636, 148.8553727 ,
       148.78606173, 148.76295808, 148.73985442, 148.71675077,
       148.69364711, 148.62433614, 148.60123249, 148.57812883,
       148.55502517, 148.53192152, 148.46261055, 148.43950689,
       148.41640324, 148.39329958, 148.37019593, 148.30088496,
       148.2777813 , 148.25467765, 148.23157399, 148.20847033,
       148.13915937, 148.11605571, 148.09295205, 148.0698484 ,
       148.04674474, 147.97743377, 147.95433012, 147.93122646,
```

```
       146.84353463, 146.82223097, 146.79914752, 146.77604566,
       146.75294001, 146.68362904, 146.66052538, 146.63742173,
       146.61431807, 146.59121441, 146.52190345, 146.49879979,
       146.47569613, 146.45259248, 146.42948882, 146.36017785,
       146.3370742 , 146.31397054, 146.29086689, 146.26776323,
       146.19845226, 146.17534861, 146.15224495, 146.12914129,
       146.10603764, 146.03672667, 146.01362301, 145.99051936,
       145.9674157 , 145.94431205, 145.87500108, 145.85189742,
       145.82879377, 145.80569011, 145.78258645, 145.71327549,
       145.69017183, 145.66706817, 145.64396452, 145.62086086,
       145.55154989, 145.52844624, 145.50534258, 145.48223893,
       145.45913527, 145.3898243 , 145.36672065, 145.34361699,
       145.32051333, 145.29740968, 145.22809871, 145.20499505,
       145.1818914 , 145.15878774, 145.13568409, 145.06637312,
       145.04326946, 145.02016581, 144.99706215, 144.97395849,
       144.90464753, 144.88154387, 144.85844021, 144.83533656,
       144.8122329 , 144.74292193, 144.71981828, 144.69671462,
       144.67361097, 144.65050731, 144.58119634, 144.55809269,
       144.53498903, 144.51188537, 144.48878172, 144.41947075,
       144.39636709, 144.37326344, 144.35015978, 144.32705613,
       144.25774516, 144.2346415 , 144.21153785, 144.18843419,
       144.16533053, 144.09601957, 144.07291591, 144.04981225,
       144.0267086 , 144.00360494, 143.93429397, 143.91119032,
       143.88808666, 143.86498301, 143.84187935, 143.77256838,
       143.74946473, 143.72636107, 143.70325741, 143.68015376,
       143.61084279, 143.58773913, 143.56463548, 143.54153182,
       143.51842817, 143.4491172 , 143.42601354, 143.40290989,
       143.37980623, 143.35670257, 143.28739161, 143.26428795,
       143.24118429, 143.21808064, 143.19497698, 143.12566601,
       143.10256236])
```

```
mse=mean_squared_error(y_test,y_pred)
mse
```

```
3072.378496877529
```

```
r2=r2_score(y_test,y_pred)
r2
```

```
-11.213999810715315
```

```
plt.scatter(x_test.dt.days,y_test)
plt.xlabel('Time')
plt.ylabel('Price')
```

```
Text(0, 0.5, 'Price')
```



EX-4

Step-0 Libraries Used

Pandas: is used to load and analyze data.

NumPy: is used for numerical operations.

Matplotlib and Seaborn: are used for plotting graphs.

Scikit-learn: is used for train test split, model training, prediction, and evaluation.

Pickle: is used to save the trained model for later use.

Step-1 Problem Definition

The goal is to predict whether a customer will churn or not using customer information such as age, subscription type, payment method, and charges. Since the output is either 0 or 1, this is a binary classification problem.

Step-2 Data Understanding

The dataset was loaded and checked using head() and info() to understand structure. Each row represents a customer and each column represents a feature.

The dataset contains numerical features such as age, tenure, charges, and support tickets, and categorical features such as gender, subscription type, payment method, and contract type. The target column is Churn.

Step-3 Data Processing

The CustomerID column was removed because it is only an identifier and does not help prediction. Categorical columns were converted into numerical form using one-hot encoding so that the model can understand them.

Step-4 Feature Selection and Model Training

All columns except Churn were selected as input (x), and Churn was selected as output (y). The dataset was split into training and testing sets in 80:20 ratio. A Logistic Regression model was chosen because it is suitable for binary classification. The model was trained on training data to learn patterns between customer features and churn.

Step-5 Prediction

After training, predictions were generated using the test data. The model outputs either 0 (not churn) or 1 (churn) based on learned patterns.

Step-6 Evaluation

The model performance was evaluated using accuracy, precision, recall, and F1 score. The accuracy was about 0.75, which shows the model performs reasonably well. However, precision and recall were lower, meaning the model has difficulty correctly identifying churn customers.

A confusion matrix was plotted to visualize prediction performance and to see correct and incorrect classifications.

Step-7 Feature Impact

A graph of model coefficients was plotted to see which features influence churn prediction the most. Features related to subscription type, payment method, and contract duration showed strong impact.

Customer Churn Prediction: Develop a model to predict customer churn in a subscription-based business.

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score,precision_score,recall_score,f1_score,confusion_matrix
import pickle
```

```
df=pd.read_csv('/content/drive/MyDrive/customer_churn_dataset.csv')
df.head()
```

	CustomerID	Gender	Age	Tenure_Months	SubscriptionType	MonthlyCharges	TotalCharges	PaymentMethod	SupportTickets	Co
0	CUST1000	Male	49	54	Standard	99.33	4912.77	Net Banking	1	
1	CUST1001	Female	56	8	Standard	12.01	604.59	Debit Card	2	
2	CUST1002	Male	66	27	Basic	57.62	2019.39	Cash	4	
3	CUST1003	Male	69	27	Premium	97.08	4848.88	Credit Card	7	
4	CUST1004	Male	49	34	Standard	54.69	4334.26	Credit Card	9	

Next steps: Generate code with df | New interactive sheet

```
print("Shape:",df.shape)
df.info()
df.describe()
```

```
Shape: (200, 11)
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 200 entries, 0 to 199
Data columns (total 11 columns):
 #   Column            Non-Null Count  Dtype
---  ------            --------------  -----
 0   CustomerID        200 non-null    object
 1   Gender            200 non-null    object
 2   Age               200 non-null    int64
 3   Tenure_Months     200 non-null    int64
 4   SubscriptionType  200 non-null    object
 5   MonthlyCharges    200 non-null    float64
 6   TotalCharges      200 non-null    float64
 7   PaymentMethod     200 non-null    object
 8   SupportTickets    200 non-null    int64
 9   ContractType      200 non-null    object
 10  Churn             200 non-null    int64
dtypes: float64(2), int64(4), object(5)
memory usage: 17.3+ KB
```

	Age	Tenure_Months	MonthlyCharges	TotalCharges	SupportTickets	Churn
count	200.000000	200.000000	200.000000	200.000000	200.000000	200.000000
mean	44.405000	31.925000	51.348250	2536.105100	4.505000	0.285000
std	15.353816	16.390933	27.570371	1408.107184	2.967153	0.452547
min	18.000000	1.000000	6.380000	72.930000	0.000000	0.000000
25%	32.750000	21.000000	27.335000	1292.312500	2.000000	0.000000
50%	46.000000	32.000000	50.530000	2537.170000	4.000000	0.000000
75%	56.000000	46.250000	73.062500	3753.577500	7.000000	1.000000
max	69.000000	58.000000	99.970000	4984.530000	9.000000	1.000000

```
sns.countplot(x='Churn',data=df)
plt.title("Churn Distibution")
plt.show()
```




```
df=df.drop("CustomerID",axis=1)
df=pd.get_dummies(df,drop_first=True)
df.head()
```

	Age	Tenure_Months	MonthlyCharges	TotalCharges	SupportTickets	Churn	Gender_Male	SubscriptionType_Premium	Subscript
0	49	54	99.33	4912.77	1	0	True	False	
1	56	8	12.01	604.59	2	0	False	False	
2	66	27	57.62	2019.39	4	0	True	False	
3	69	27	97.08	4848.88	7	0	True	True	
4	49	34	54.69	4334.26	9	1	True	False	

Next steps: Generate code with df New interactive sheet

```
X=df.drop(["Churn"],axis=1)
y=df["Churn"]
X.head(),y.head()
```

```
(   Age  Tenure_Months  MonthlyCharges  TotalCharges  SupportTickets  \
 0   49            54           99.33       4912.77               1
 1   56             8           12.01        604.59               2
 2   66            27           57.62       2019.39               4
 3   69            27           97.08       4848.88               7
 4   49            34           54.69       4334.26               9

    Gender_Male  SubscriptionType_Premium  SubscriptionType_Standard  \
 0         True                     False                       True
 1        False                     False                       True
 2         True                     False                      False
 3         True                      True                      False
 4         True                     False                       True

    PaymentMethod_Credit Card  PaymentMethod_Debit Card  \
 0                      False                     False
 1                      False                      True
 2                      False                     False
 3                       True                     False
 4                       True                     False

    PaymentMethod_Net Banking  PaymentMethod_UPI  ContractType_One Year  \
 0                       True              False                  False
 1                      False              False                  False
 2                      False              False                  False
 3                      False              False                  False
 4                      False              False                   True

    ContractType_Two Year
 0                   True
 1                   True
 2                   True
 3                   True
 4                  False  ,
 0    0
```

```
1    0
2    0
3    0
4    1
Name: Churn, dtype: int64)
```

```
X_train,X_test,y_train,y_test=train_test_split(X,y,test_size=0.2,random_state=50)
print("Train size:",X_train.shape)
print("Test size:",X_test.shape)
```

```
Train size: (160, 14)
Test size: (40, 14)
```

```
model=LogisticRegression(max_iter=1000)
model.fit(X_train,y_train)
with open("model","wb") as f:
    pickle.dump(model,f)
```

```
/usr/local/lib/python3.12/dist-packages/sklearn/linear_model/_logistic.py:465: ConvergenceWarning: lbfgs failed to converge
STOP: TOTAL NO. OF ITERATIONS REACHED LIMIT.

Increase the number of iterations (max_iter) or scale the data as shown in:
    https://scikit-learn.org/stable/modules/preprocessing.html
Please also refer to the documentation for alternative solver options:
    https://scikit-learn.org/stable/modules/linear_model.html#logistic-regression
  n_iter_i = _check_optimize_result(
```

```
y_pred=model.predict(X_test)
y_pred
```

```
array([0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0,
       0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0])
```

```
cm=confusion_matrix(y_test,y_pred)

sns.heatmap(cm,annot=True,fmt='d')
plt.xlabel("Predicted")
plt.ylabel("Actual")
plt.title("Confusion Matrix")
plt.show()
```




```
print("Accuracy:",accuracy_score(y_test,y_pred))
print("Precision:",precision_score(y_test,y_pred))
print("Recall:",recall_score(y_test,y_pred))
print("F1 Score:",f1_score(y_test,y_pred))
```

```
Accuracy: 0.8
Precision: 0.6666666666666666
Recall: 0.2222222222222222
F1 Score: 0.3333333333333333
```

Ex-5

Step-0 Libraries Used

Pandas is used to load and handle the dataset.
NumPy helps with numerical operations.
Matplotlib and Seaborn are used to plot graphs and visualize results.
Scikit-learn is used for train-test splitting, text vectorization, model training, prediction, and evaluation.
CountVectorizer is used to convert text into numerical feature vectors so machine learning algorithms can process email text.
Metrics module from sklearn is used to calculate accuracy, precision, recall, F1 score, ROC-AUC score, and confusion matrix.
Pickle is used to save the trained model so it can be reused later without retraining.

Step-1 Problem Definition

The goal of this experiment is to build a system that can detect whether an email is spam or not. This helps automatically filter unwanted messages. Since the output has only two values (spam or ham), this is a binary classification problem. The model needs to learn patterns in email text that differentiate spam from normal emails.

Step-2 Data Understanding

The dataset was loaded and checked using functions like head(), info(), and value_counts() to understand its structure. Each row represents one email and the columns represent its label and message text.The dataset contains 500 emails and 2 columns label and text.
The label column contains spam and ham values. The dataset is balanced, meaning both classes appear almost equally. Balanced data helps models learn properly and prevents bias toward one class.

Step-3 Data Processing

The labels were converted into numbers by mapping:

ham to 0
spam to 1

This conversion is necessary because machine learning algorithms work only with numerical values. After that, the text column was taken as input (X) and the label column as output (y). This prepares the dataset for model training.

Step-4 Feature Extraction and Training

The dataset was split into training and testing sets in 80:20 ratio so that the model trains on one part and is tested on unseen data. This ensures the model is evaluated on data it has not seen before.The email text was converted into numerical vectors using CountVectorizer. This method counts how many times each word appears and uses those counts as features. Machine learning models cannot understand text directly, so text must be converted into numbers.

The output shows:

Training matrix size → (400, 83)
Testing matrix size → (100, 83)
This means 83 unique words were used as features for classification.

Five models were trained:

Naive Bayes: works well for text data because it calculates probability of words appearing in spam or ham messages.
Logistic Regression: a linear classifier that predicts probability of spam.
SVM: finds the best boundary that separates spam and non-spam emails.
Decision Tree: creates rule-based decisions using words as conditions.
Random Forest: combines multiple decision trees to improve prediction accuracy and reduce errors.

Each model learns word patterns that indicate spam or normal email.

Step-5 Prediction

After training, the models predicted labels for the test emails. The output values were 0 or 1 representing ham or spam. This step checks how well the trained models perform on unseen data.

Step-6 Evaluation

The models were evaluated using multiple metrics:

Accuracy = overall correctness

Precision = correctness of predicted spam

Recall = ability to detect actual spam

F1 Score = balance between precision and recall

All models achieved values of 1.0, meaning they classified every test email correctly.

The confusion matrix confirms this result. It shows that all ham emails and all spam emails were predicted correctly with zero errors. The diagonal values represent correct predictions, and the absence of off-diagonal values indicates no misclassification.

The ROC-AUC score was also 1.0, which indicates perfect classification performance and perfect separation between spam and ham classes.

Step-7 Best Model Selection

The best model was selected based on F1 score. Since all models performed equally well, Naive Bayes was selected as the best model because it is simple, fast, and specially suited for text classification tasks.

The selected model was saved using pickle so that it can be reused later without retraining. Saving the model preserves its learned parameters. The saved model was then loaded again and used for prediction and visualization to verify that it produces the same results as the original trained model.

Exp 5. Spam Email Detection: Build a spam email filter using text classification algorithms and perform comparative analysis. (Naïve Bayes, Logistic Regression, Support Vector Machine, Decision Tree, Random Forest)

Note: Use Evaluation Metrics (Accuracy, Precision, Recall, F1-Score for binary classification), (ROC-AUC, Accuracy, Precision, Recall, Weighted / Macro/ Micro Average F1-Score for Multiclassification task) and Confusion Matrix.

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.feature_extraction.text import CountVectorizer
from sklearn.naive_bayes import MultinomialNB
from sklearn.linear_model import LogisticRegression
from sklearn.svm import SVC
from sklearn.tree import DecisionTreeClassifier
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import accuracy_score,precision_score,recall_score,f1_score,confusion_matrix,classification_report,roc_auc_score
import pickle
```

```
df=pd.read_csv('/content/drive/MyDrive/spam_email_500_samples.csv')
df.head()
```

	label	text
0	spam	Free entry in 2 million dollar contest. Click ...
1	spam	Act now! This offer is valid for today only.
2	spam	Get cheap medicines online without prescriptio...
3	ham	Lunch at 1 PM works for me.
4	ham	Thank you for your assistance.

Next steps: Generate code with df New interactive sheet

```
df.info()
df.describe()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 500 entries, 0 to 499
Data columns (total 2 columns):
 #   Column  Non-Null Count  Dtype
---  ------  --------------  -----
 0   label   500 non-null    object
 1   text    500 non-null    object
dtypes: object(2)
memory usage: 7.9+ KB
```

	label	text
count	500	500
unique	2	20
top	spam	Get cheap medicines online without prescriptio...
freq	250	40

```
df['label']=df['label'].map({'ham':0,'spam':1})
df.head()
```

	label	text
0	1	Free entry in 2 million dollar contest. Click ...
1	1	Act now! This offer is valid for today only.
2	1	Get cheap medicines online without prescriptio...
3	0	Lunch at 1 PM works for me.
4	0	Thank you for your assistance.

Next steps: Generate code with df New interactive sheet

```
X=df['text']
y=df['label']
```

```
X_train,X_test,y_train,y_test=train_test_split(X,y,test_size=0.2,random_state=0)
```

```
cv=CountVectorizer(stop_words='english')
X_train=cv.fit_transform(X_train)
X_test=cv.transform(X_test)
print("Training matrix shape:",X_train.shape)
print("Testing matrix shape:",X_test.shape)
```

```
Training matrix shape: (400, 83)
Testing matrix shape: (100, 83)
```

```
models={"Naive Bayes":MultinomialNB(),
        "Logistic Regression":LogisticRegression(max_iter=100),
        "SVM":SVC(probability=True),
        "Decision Tree":DecisionTreeClassifier(),
        "Random Forest":RandomForestClassifier()
        }
```

```
results=[]
for name,model in models.items():
    model.fit(X_train,y_train)
    pred=model.predict(X_test)
    acc=accuracy_score(y_test,pred)
    pre=precision_score(y_test,pred)
    rec=recall_score(y_test,pred)
    f1=f1_score(y_test,pred)
    results.append([name,acc,pre,rec,f1])
results_df=pd.DataFrame(results,columns=["Model","Accuracy","Precision","Recall","F1"])
results_df
```

	Model	Accuracy	Precision	Recall	F1
0	Naive Bayes	1.0	1.0	1.0	1.0
1	Logistic Regression	1.0	1.0	1.0	1.0
2	SVM	1.0	1.0	1.0	1.0
3	Decision Tree	1.0	1.0	1.0	1.0
4	Random Forest	1.0	1.0	1.0	1.0

Next steps: Generate code with results_df New interactive sheet

```
results_df.plot(x="Model",y="F1",kind="bar")
plt.title("Model Comparison (F1 Score)")
plt.ylabel("Score")
plt.show()
```




```
best_name=results_df.sort_values("F1",ascending=False).iloc[0,0]
best_model=models[best_name]
print("Best Model:",best_name)
```

```
Best Model: Naive Bayes
```

```
with open("spam_email_classifier.pkl","wb") as f:
    pickle.dump(best_model,f)
```

```
pred=best_model.predict(X_test)
cm=confusion_matrix(y_test,pred)
sns.heatmap(cm,annot=True,fmt="d")
```

```
<Axes: >
```




```
probs=best_model.predict_proba(X_test)[:,1]
print("ROC AUC:",roc_auc_score(y_test,probs))
```

```
ROC AUC: 1.0
```

```
print(classification_report(y_test,pred))
```

```
              precision    recall  f1-score   support

           0       1.00      1.00      1.00        56
           1       1.00      1.00      1.00        44

    accuracy                           1.00       100
   macro avg       1.00      1.00      1.00       100
weighted avg       1.00      1.00      1.00       100
```

Ex-6

Step-0 Libraries Used

Pandas: is used to load and handle the dataset.
NumPy: helps in numerical operations.
Matplotlib and Seaborn: are used to visualize class distribution and model comparison graphs.
Scikit-learn: is used for train-test splitting, label encoding, model training, and evaluation. LogisticRegression, RandomForestClassifier, and XGBClassifier are used as classification models.
The metrics module: is used to calculate Accuracy, Precision, Recall, F1 (weighted, macro, micro), ROC-AUC, and Confusion Matrix.
Pickle: is used to save the trained best model for future use without retraining.

Step-1 Problem Definition

The objective of this experiment is to build a credit scoring model that classifies loan applicants into risk categories based on historical financial information.Since the output variable Credit_Risk contains multiple categories (High, Medium, Low), this is a multiclass classification problem.The goal is to compare different classification models and select the best-performing one.

Step-2 Data Understanding

The dataset contains 500 records and 11 columns
Important columns include:

- Age
- Annual_Income
- Employment_Years
- Credit_Score
- Loan_Amount
- Loan_Term_Months
- Existing_Loans_Count
- Debt_to_Income_Ratio
- Late_Payments_Last_2Yrs
- Credit_Risk (Target Variable)

The target column Credit_Risk is categorical (object type)
A countplot was generated to visualize the distribution of risk classes This helps understand class imbalance before training models.

Step-3 Data Processing

The target column Credit_Risk was converted into numerical format using LabelEncoder, because machine learning algorithms require numerical input.The Applicant_ID column was dropped since it is only an identifier and does not contribute to prediction.Features (X) were separated from the target (y).

Step-4 Train-Test Split and Model Training

The dataset was split using:
train_test_split(test_size=0.2, random_state=0)

This means:80% data used for training,20% data used for testing

Three models were trained:

- **Logistic Regression:**Linear model for classification.Performs well when classes are linearly separable.
- **Random Forest:**Ensemble of multiple decision trees.Reduces overfitting and improves stability.
- **XGBoost:**Gradient boosting algorithm. Builds trees sequentially to correct previous errors. Known for high performance in structured data.

Step-5 Model Evaluation and Comparative Analysis

Each model was evaluated using:

- Accuracy
- Precision (weighted)
- Recall (weighted)
- F1_weighted
- F1_macro
- F1_micro

Model Accuracy:

- Logistic Regression=0.68
- Random Forest=0.99
- XGBoost=1.00

XGBoost achieved perfect classification performance.

Step-6 Prediction

The confusion matrix shows:

- Class 0 = 70 correctly predicted
- Class 1 = 4 correctly predicted
- Class 2 = 26 correctly predicted

No misclassifications occurred.

The classification report confirms precision, recall, and F1-score of 1.00 for all classes
This indicates perfect separation of risk categories.

Step-7 Best Model Selection and Model Saving

The best model was selected based on highest F1_weighted score:
Best Model: XGBoost
The trained best model was saved using pickle:
pickle.dump(best_model,f)

Saving the model ensures:

- No need to retrain
- Reproducibility
- Deployment readiness

The saved model can later be loaded and used for predictions.

Exp 6: Credit Risk Assessment: Build a credit scoring model to assess the creditworthiness of applicants using historical financial data and perform comparative analysis (Logistic Regression, Random Forest, XGBoost)

Note: Use Evaluation Metrics (Accuracy, Precision, Recall, F1-Score for binary classification), (ROC-AUC, Accuracy, Precision, Recall, Weighted / Macro/ Micro Average F1-Score for Multiclassification task) and Confusion Matrix

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from sklearn.linear_model import LogisticRegression
from sklearn.ensemble import RandomForestClassifier
from xgboost import XGBClassifier
from sklearn.metrics import accuracy_score,precision_score,recall_score,f1_score,confusion_matrix,roc_auc_score,classificat
import pickle
```

```
df=pd.read_csv('/content/drive/MyDrive/credit_risk_assessment_500_samples.csv')
df.head()
```

	Applicant_ID	Age	Annual_Income	Employment_Years	Credit_Score	Loan_Amount	Loan_Term_Months	Existing_Loans_Count	De
0	1	59	153267	28	818	196649	12	2	
1	2	49	232745	0	436	175354	60	0	
2	3	35	974945	19	797	662297	48	3	
3	4	63	307164	29	776	831725	48	0	
4	5	28	685626	6	893	498625	60	3	

Next steps: Generate code with df New interactive sheet

```
print(df.shape)
df.info()
df.describe()
```

```
(500, 11)
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 500 entries, 0 to 499
Data columns (total 11 columns):
 #   Column                   Non-Null Count  Dtype
---  ------                   --------------  -----
 0   Applicant_ID             500 non-null    int64
 1   Age                      500 non-null    int64
 2   Annual_Income            500 non-null    int64
 3   Employment_Years         500 non-null    int64
 4   Credit_Score             500 non-null    int64
 5   Loan_Amount              500 non-null    int64
 6   Loan_Term_Months         500 non-null    int64
 7   Existing_Loans_Count     500 non-null    int64
 8   Debt_to_Income_Ratio     500 non-null    float64
 9   Late_Payments_Last_2Yrs  500 non-null    int64
 10  Credit_Risk              500 non-null    object
dtypes: float64(1), int64(9), object(1)
memory usage: 43.1+ KB
```

1 to 8 of 8 entries Filter

index	Applicant_ID	Age	Annual_Income	Employment_Years	Credit_Score	Loan_Amount	Loan_Term_M
count	500.0	500.0	500.0	500.0	500.0	500.0	
mean	250.5	43.116	827131.654	14.702	596.394	521385.53	
std	144.4818327679989	12.733216939456186	384829.8617613202	8.713497925183917	171.33979518731104	281799.5141543726	17.117037182
min	1.0	21.0	150404.0	0.0	300.0	55901.0	
25%	125.75	32.0	506262.25	7.0	452.0	266621.75	
50%	250.5	44.0	833427.5	15.5	602.0	533640.0	
75%	375.25	53.0	1148353.0	22.0	732.25	765362.5	
max	500.0	64.0	1498464.0	29.0	898.0	999621.0	

Show 100 per page
Like what you see? Visit the data table notebook to learn more about interactive tables.

```
sns.countplot(x="Credit_Risk",data=df)
plt.title("Risk Class Distribution")
plt.show()
```




```
le=LabelEncoder()
df["Credit_Risk"]=le.fit_transform(df["Credit_Risk"])
```

```
df=df.drop("Applicant_ID",axis=1)
```

```
X=df.drop("Credit_Risk",axis=1)
y=df["Credit_Risk"]
```

```
X_train,X_test,y_train,y_test=train_test_split(X,y,test_size=0.2,random_state=0)
```

```
models={
    "Logistic Regression":LogisticRegression(max_iter=1000),
    "Random Forest":RandomForestClassifier(),
    "XGBoost":XGBClassifier(eval_metric="mlogloss")
    }
```

```
results=[]
for name,model in models.items():
    model.fit(X_train,y_train)
    pred=model.predict(X_test)
    acc=accuracy_score(y_test,pred)
    pre=precision_score(y_test,pred,average="weighted")
    rec=recall_score(y_test,pred,average="weighted")
    f1w=f1_score(y_test,pred,average="weighted")
    f1m=f1_score(y_test,pred,average="macro")
    f1mi=f1_score(y_test,pred,average="micro")
    results.append([name,acc,pre,rec,f1w,f1m,f1mi])
results_df=pd.DataFrame(results,columns=[
"Model","Accuracy","Precision","Recall",
"F1_weighted","F1_macro","F1_micro"])
results_df
```

```
/usr/local/lib/python3.12/dist-packages/sklearn/linear_model/_logistic.py:465: ConvergenceWarning: lbfgs failed to converge
STOP: TOTAL NO. OF ITERATIONS REACHED LIMIT.

Increase the number of iterations (max_iter) or scale the data as shown in:
    https://scikit-learn.org/stable/modules/preprocessing.html
Please also refer to the documentation for alternative solver options:
    https://scikit-learn.org/stable/modules/linear_model.html#logistic-regression
  n_iter_i = _check_optimize_result(
```

	Model	Accuracy	Precision	Recall	F1_weighted	F1_macro	F1_micro
0	Logistic Regression	0.68	0.699529	0.68	0.683579	0.431938	0.68
1	Random Forest	0.99	0.990370	0.99	0.989380	0.946092	0.99
2	XGBoost	1.00	1.000000	1.00	1.000000	1.000000	1.00

Next steps: Generate code with results_df New interactive sheet

```
results_df.plot(x="Model",y="F1_weighted",kind="bar")
plt.title("Model Comparison")
```

```
plt.ylabel("Score")
plt.show()
```




```
best_name=results_df.sort_values("F1_weighted",ascending=False).iloc[0,0]
best_model=models[best_name]
print("Best Model:",best_name)
```

```
Best Model: XGBoost
```

```
with open("best_model.pkl","wb") as f:
    pickle.dump(best_model,f)
```

```
pred=best_model.predict(X_test)
cm=confusion_matrix(y_test,pred)
sns.heatmap(cm,annot=True,fmt='d')
plt.title("Confusion Matrix")
plt.show()
```




```
print(classification_report(y_test,pred))
```

```
              precision    recall  f1-score   support

           0       1.00      1.00      1.00        70
           1       1.00      1.00      1.00         4
           2       1.00      1.00      1.00        26
```

```
    accuracy                           1.00       100
   macro avg       1.00      1.00      1.00       100
weighted avg       1.00      1.00      1.00       100
```

Exe-7

Step-0 Libraries Used

Pandas: is used to load and manage the dataset.
NumPy: is used for numerical operations and label conversion.
Matplotlib and Seaborn: are used to visualize data distribution, model comparison, and confusion matrix.
Scikit-learn: is used for scaling data, train-test splitting, model implementation, and evaluation metrics.
IsolationForest, LocalOutlierFactor, and OneClassSVM: are used as anomaly detection models.
Metrics: such as Accuracy, Precision, Recall, F1 Score, ROC-AUC, and Confusion Matrix are used to evaluate performance.
Pickle: is used to save the best-performing model for future reuse.

Step-1 Problem Definition

The objective of this experiment is to detect anomalies (outliers) in a dataset. In real world scenarios, anomaly detection is used in fraud detection, intrusion detection, and fault monitoring.

The dataset contains two numerical features and a target column Anomaly_Label, where:

- 0 = Normal data
- 1 = Anomaly

Since the output has two classes, this is a binary classification problem, but the models used are unsupervised anomaly detection algorithms.

Step-2 Data Understanding

The dataset contains 500 rows and 3 columns

- Feature_1
- Feature_2
- Anomaly_Label

The dataset is imbalanced:

- Most records are normal (0)
- Very few records are anomalies (1)

confirms that anomalies are rare, which is typical in anomaly detection problems.
This imbalance makes accuracy alone unreliable, so precision, recall, and F1-score become important.

Step-3 Data Preprocessing

The features were separated:

- X = df[["Feature_1","Feature_2"]]
- y = df["Anomaly_Label"]

Since anomaly detection models are distance-based or boundary-based, feature scaling is necessary.
StandardScaler was used to normalize data so that both features contribute equally to distance calculations.

After scaling, the dataset was split:

- 80% = Training
- 20% = Testing

Step-4 Model Training

Three anomaly detection models were implemented:

1. Isolation Forest

Works by randomly selecting features and splitting values.
Anomalies are easier to isolate and require fewer splits.
Uses contamination parameter to define expected anomaly proportion.

2. Local Outlier Factor (LOF)

Detects anomalies by comparing local density of a point to its neighbors.
Points with significantly lower density are marked as anomalies.

3. One-Class SVM

Creates a boundary around normal data points.
Points outside the boundary are considered anomalies.

Since these are unsupervised models, they were trained using only feature data (X_train).

Predictions returned values:

- -1 = anomaly
- 1 = normal

These were converted to:

-1 = 1 (anomaly)
1 = 0 (normal)

to match the dataset labels.

Step-5 Model Evaluation and Comparative Analysis

The models were evaluated using:

- Accuracy
- Precision
- Recall
- F1 Score
- ROC-AUC

Model	F1 Score
Isolation Forest	0.727
Local Outlier Factor	0.000
One-Class SVM	0.316

Isolation Forest performed best overall.

Interpretation:

- Isolation Forest achieved high recall (1.0), meaning it detected all anomalies.
- LOF failed to detect anomalies properly.
- One-Class SVM detected some anomalies but with lower performance.

clearly shows Isolation Forest having the highest F1 score.

Step-6 Confusion Matrix Analysis

The confusion matrix for Isolation Forest shows:

Actual	Predicted Normal	Predicted Anomaly
Normal	86	6
Anomaly	0	8

Interpretation:

- 86 normal points correctly identified
- 8 anomalies correctly detected
- 6 normal points incorrectly classified as anomalies (False Positives)
- 0 anomalies missed (False Negatives)

This means the model successfully detected all anomalies but slightly over-flagged some normal points.

In anomaly detection, missing anomalies (false negatives) is more critical than false positives, so this result is acceptable.

Step-7 Best Model Selection and Model Saving

The best model was selected based on highest F1 score:
Best Model: Isolation Forest

The trained model was saved using pickle:
pickle.dump(best_model,f)

Saving the model ensures:

- No need to retrain
- Faster deployment
- Reproducibility

The saved model can later be loaded and used for anomaly detection on new data.

Exp 7: Anomaly Detection: Implement an anomaly detection system for detecting outliers in data (e.g., fraud detection) and perform comparative analysis. (Isolation Forest, Local Outlier Factor, One-Class SVM)

Note: Use Evaluation Metrics (Accuracy, Precision, Recall, F1-Score for binary classification), (ROC-AUC, Accuracy, Precision, Recall, Weighted / Macro/ Micro Average F1-Score for Multiclassification task) and Confusion Matrix.

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler
from sklearn.ensemble import IsolationForest
from sklearn.neighbors import LocalOutlierFactor
from sklearn.svm import OneClassSVM
from sklearn.metrics import accuracy_score,precision_score,recall_score,f1_score,confusion_matrix,roc_au
import pickle
```

```
df=pd.read_csv('/content/drive/MyDrive/anomaly_detection_dataset_500_samples.csv')
df.head()
```

	Feature_1	Feature_2	Anomaly_Label
0	43.259073	53.716320	0
1	43.815246	43.397717	0
2	46.942411	42.966695	0
3	48.911594	55.493884	0
4	52.575238	69.263657	0

Next steps: Generate code with df New interactive sheet

```
print(df.shape)
df.info()
df.describe()
```

```
(500, 3)
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 500 entries, 0 to 499
Data columns (total 3 columns):
 #   Column         Non-Null Count  Dtype
---  ------         --------------  -----
 0   Feature_1      500 non-null    float64
 1   Feature_2      500 non-null    float64
 2   Anomaly_Label  500 non-null    int64
dtypes: float64(2), int64(1)
memory usage: 11.8 KB
```

	Feature_1	Feature_2	Anomaly_Label
count	500.000000	500.000000	500.000000
mean	52.422862	52.573850	0.060000
std	10.600455	10.641964	0.237725
min	33.793663	38.490394	0.000000
25%	47.027724	47.097147	0.000000
50%	50.447020	50.566493	0.000000
75%	53.827497	54.163940	0.000000
max	95.539911	95.402821	1.000000

```
sns.countplot(x="Anomaly_Label",data=df)
plt.title("Normal vs Anomaly Count")
```

```
plt.show()
```




```
X=df[["Feature_1","Feature_2"]]
y=df["Anomaly_Label"]
```

```
sc=StandardScaler()
X_scaled=sc.fit_transform(X)
```

```
X_train,X_test,y_train,y_test=train_test_split(X_scaled,y,test_size=0.2,random_state=0)
```

```
models={
"Isolation Forest":IsolationForest(contamination=0.1,random_state=0),
"Local Outlier Factor":LocalOutlierFactor(novelty=True),
"One-Class SVM":OneClassSVM(nu=0.1)
}
```

```
results=[]
for name,model in models.items():
    model.fit(X_train)
    pred=model.predict(X_test)
    pred=np.where(pred==-1,1,0)
    acc=accuracy_score(y_test,pred)
    pre=precision_score(y_test,pred)
    rec=recall_score(y_test,pred)
    f1=f1_score(y_test,pred)
    auc=roc_auc_score(y_test,pred)
    results.append([name,acc,pre,rec,f1,auc])
results_df=pd.DataFrame(results,columns=["Model","Accuracy","Precision","Recall","F1","ROC_AUC"])
results_df
```

	Model	Accuracy	Precision	Recall	F1	ROC_AUC
0	Isolation Forest	0.94	0.571429	1.000	0.727273	0.967391
1	Local Outlier Factor	0.88	0.000000	0.000	0.000000	0.478261
2	One-Class SVM	0.87	0.272727	0.375	0.315789	0.644022

Next steps: Generate code with results_df New interactive sheet

```
results_df.plot(x="Model",y="F1",kind="bar")
plt.title("Model Comparison")
```

```
plt.ylabel("Score")
plt.show()
```




```
best=results_df.sort_values("F1",ascending=False).iloc[0,0]
best_model=models[best]
print("Best Model:",best)
```

```
Best Model: Isolation Forest
```

```
with(open("best_model.pkl","wb")) as f:
    pickle.dump(best_model,f)
```

```
pred=best_model.predict(X_test)
pred=np.where(pred==-1,1,0)
cm=confusion_matrix(y_test,pred)
sns.heatmap(cm,annot=True,fmt='d')
plt.title("Confusion Matrix -"+best)
plt.show()
```


Confusion Matrix -Isolation Forest
86
6
0
8
0
1
0
1
80
70
60
50
40
30
20
10
0