DRIFT V2 — Drift as a Live Elastic Recovery Signal for Runtime Stability Governance

Author: Rafael Felippe Voigt
Research Series: Voigtian Field Research Series
Type: Scientific Paper — Version 2 (Empirical Expansion)
Version: v2.0 Canonical
Recommended Distribution: Zenodo • SSRN • ResearchGate • National Library
VOIGT, R. F. (2026). ***DRIFT — Temporal Drift Applied to the Voigtian Field.*** Zenodo.
https://doi.org/10.5281/zenodo.18233534
SSRN: https://papers.ssrn.com/sol3/papers.cfm?abstract_id=6168911
Canonical DOI: https://doi.org/10.5281/zenodo.18249999
Manifest Volume II DOI: https://doi.org/10.5281/zenodo.19474931
ORCID: https://orcid.org/0009-0001-1091-8398
ResearchGate: https://www.researchgate.net/publication/401969333_VCore_-Temporal_Governance_Framework_Time_as_an_Asset_A_Universal_Metric_for_the_Temporal_Cost_of_Decisions

"Runtime stability is not the absence of pressure, but the ability to reconstruct coherence before structural rupture."

Abstract

Traditional drift models have historically focused on deviation from baseline states across data systems, machine learning pipelines, and infrastructure configuration layers. While useful for detecting divergence, these approaches rarely capture the elastic recovery behavior of a live computational runtime under stress.

This paper introduces **DRIFT V2**, the empirical evolution of the VCore drift model, in which drift is formalized as a **live elastic recovery signal** capable of quantifying not only baseline distance, but also return velocity, persistence, and the structural memory of system recovery after perturbation.

The model is supported by long-running real-world observations from VCore OS under production conditions, integrating a multi-engine runtime architecture, critical regime transitions, elastic baseline reconstruction, and anticipation-driven historical recovery.

The result is a scientific-operational grammar in which drift becomes a measurable proxy for host elasticity, rupture proximity, regime transition dynamics, and future runtime governance for autonomous AI agents.

Keywords: Drift, Runtime Stability, Elastic Recovery, Baseline Memory, Inertia Coupling, Nano Collapse, Predictive Observability, VCore API, Agent Governance, Computational Elasticity

1. Introduction

Drift has long existed as a concept in data science, machine learning, and infrastructure observability. However, most implementations reduce drift to a static notion of deviation.

The VCore framework expands this interpretation.

In live runtime environments, deviation alone is insufficient. What truly matters is whether the system can **coherently reconstruct its baseline after pressure**, and how much structural reserve is consumed during that recovery.

This paper proposes that drift must be treated as a **dynamic host elasticity function**, rather than merely a divergence metric.

2. The Core Problem

Conventional drift models answer a limited question:

How far did the system move away from baseline?

But they do not answer:

- How quickly can it recover?
- How much structural memory remains?
- Is the deformation temporary or persistent?
- Is the host approaching saturation?
- How close is the runtime to Nano collapse?

This creates an **observability gap in the invisible interval before visible failure**.

3. Limitations of Traditional Drift

Current drift approaches usually focus on:

- concept drift
- data drift
- schema drift
- configuration drift

These models lack coupling with:

- runtime inertia
- elastic reserve
- regime transitions
- critical recurrence
- collapse trajectory

As a result, they remain weak for **machine structural stability governance**.

4. The VCore Elastic Drift Model

The VCore model redefines drift as:

the measurable elastic memory of system recovery under real runtime stress

This introduces five dimensions of interpretation.

4.1 Baseline Distance

How far the host moved away from the coherent baseline.

4.2 Return Velocity

How quickly the host reconstructs coherence.

4.3 Persistence

Whether deformation remains after load removal.

4.4 Inertia Coupling

How drift interacts with the damping capacity of the host.

4.5 Regime Transition

How drift contributes to transitions between:

- Healthy
- Elevated
- Stressed
- Nano Critical

5. Empirical Runtime Evidence

VCore OS has been operating continuously in real environments under controlled updates and authentic runtime perturbations.

Observed evidence includes:

- long-running production runtime behavior
- real update cycles
- critical Nano regime transitions
- automatic historical reconstruction
- elastic baseline recovery after burst loads
- recurrence-aware structural memory

These observations validate that drift behaves not only as deviation, but as **live elastic deformation and recovery memory**.

6. Nano Collapse and Critical Anticipation

One of the strongest empirical validations occurs in the **Nano regime**.

When the host approaches Nano, the predictive reconstruction layer automatically rebuilds:

- critical history
- recurrence intervals
- structural persistence
- burst fatigue memory

This demonstrates that drift can be used as an **early collapse precursor signal**, especially when persistence rises while inertia falls.

7. API Productization Layer

The first commercial expression of DRIFT V2 is the **VCore Stability API**.

At the product layer, drift becomes a governance-grade intelligence field consumable by external platforms:

```
{
  "runtime_state": "...",
  "elastic_drift": "...",
  "coherence_score": "..."
}
```

This allows enterprise systems, dashboards, and autonomous orchestration platforms to consume drift as a **machine elasticity intelligence signal**.

8. Extension for AI Agent Governance

The next expansion layer applies DRIFT V2 to autonomous AI agents.

Here, drift evolves into:

- tool drift
- decision drift
- context entropy drift
- execution recovery coherence

This positions VCore as a:

runtime governance layer for AI agents

where elastic recovery is measured across decision chains, tool loops, execution coherence, and structural saturation.

9. Conclusion

DRIFT V2 extends the traditional meaning of drift beyond deviation.

Within the VCore framework, drift becomes a **live elastic recovery signal**, capable of measuring:

- host structural memory
- coherence return
- degradation persistence
- regime transitions
- Nano collapse proximity
- agent execution instability

Its scientific and commercial relevance lies in transforming a classical concept into a **governance-grade metric for computational elasticity and predictive runtime stability**.

This makes DRIFT V2 one of the foundational pillars of the **VCore API**, future enterprise tiers, and autonomous runtime governance.

Final Thesis

Drift is no longer merely the measure of deviation. It is the measurable elastic memory of a living computational baseline under real runtime stress.

RAFAEL FELIPPE
VOIGT:04395796940

Assinado de forma digital por RAFAEL FELIPPE VOIGT:04395796940
Dados: 2026.04.12 16:03:18 -03'00'

“The Voigtian Field transforms invisible degradation into empirical laws for living baseline reconstruction.”