

	FILE DETAILS				SUBSTRATE		HARDWARE		POWER		
	PRODUCT NAME:								Spec. Tolerance: ±10% (Vp,Ip)		
			9W 18V 221x257mm			221x257mm	Male 3.5x1.1mm 260mm		Cell Supplier:Solar World		
	DWG. NO. 9_18_221x257_R			x257_R5			WIRE COLOR: Red		Cell: Efficell M C4 3BB 4.59W		
	DWG. TYPE:				COLOR:	·	WIRE NO.		Cell Efficiency:+19%		
Voltaic			Р	roduction		Silver / Charcoal	Wire	e 17	MC	36	pcs
	SCALE:	UNITS:	TOLERANCE:	SHEET:	COATING:		STRAIN RELIEF:		Voc	23.1	V
	1:2.5	MM	±0.1mm	1/1		Urethane		etal	Vp	19.4	V
	CREATI	ED BY: TK	9	DATE: 2016/5/25	TAPE:	3mm + 4mm Black	SCREWS: C-MPSCRS028X0079-k	(M#	mAsc	490	mA
This document contains proprietary information	REV.	CHANGE:		CHK'D BY:	-	-	NUTS:	CIVIT	mAp	460	mA
and should not be copied or shared without the consent of Voltaic Systems.	5		2017/7/20	SM	1 40.50	85*C [-40*F - 185*F]		one	Wp	8.9	W