

NOTES:

- 1. Total Panel Thickness (not including screws): 4.8mm ± 0.2mm

- Weight: 70.9g [2.5oz]
 Waterproof Rating: IP67
 All materials RoHS compliant
 Tape over all electrical connections

	FILE DETAILS			SUBSTRATE		HARDWARE	POWER		
	PRODUC					WIRE:	Spec. Tolerance: ±10% (Vp,Ip)		
	1W 6V 113x89mm					Male 3.5x1.1mm 260mm	Cell Supplier: Solar World		
Voltain Paris	DWG. NO. 1_6_113x89_R1			MATERIAL: 3.0mm A	AL-Plastic Composite	WIRE COLOR:		Cell: Efficell M C4 3BB 4.59W	
	DWG. TYPE:		COLOR:		WIRE NO.	Cell Efficiency:+19.1%			
			Production		Silver / Charcoal	Wire 17	MC	12	pcs
	SCALE: UN	NITS: TOLERANG	E: SHEET:	COATING:		STRAIN RELIEF:	Voc	7.7	V
		<u>MM ±0.1m</u>			Urethane	None	Vp	6.5	V
	CREATED		DATE:	TAPE:		SCREWS:	mAsc	190	mA
This document contains proprietary information	REV. CH	TK ANGE: DATE:	2017/7/6 CHK'D BY:	TEMP. RAN	3mm + 4mm Black	C-MPSCRS028X0079-KM# NUTS:	mAp	180	mA
and should not be copied or shared without the consent of Voltaic Systems.	1		SM		85*C [-40*F - 185*F]		Wp	1.2	W