



#### NOTES:

1. All materials RoHS compliant
2. Tape over all electrical connections
3. Total Panel Thickness (not including screws): 4.5-5.0mm

	FILE DETAILS				SUBSTRATE		HARDWARE		POWER		
	PRODUCT NAME: <b>6W 6V 175x220.5mm</b>				SIZE: 175x220.5mm		WIRE: Male 3.5x1.1mm 260mm		Spec. Tolerance: ±10% (Vp,Ip)		
	DWG. NO. 6_6_175x220.5_R1				MATERIAL: 3.0mm AL-Plastic Composite		WIRE COLOR: Red		Cell Supplier: Solar World		
	DWG. TYPE: Production				COLOR: Silver / Charcoal / Orange		WIRE NO. Wire 17		Cell Efficiency: +19%		
	SCALE: UNITS: TOLERANCE: SHEET: 1:2.5 MM ±0.1mm 1/1				COATING: Urethane		STRAIN RELIEF: Metal		MC	12	pcs
	CREATED BY: DATE: TK 2017/7/20				TAPE: 3mm + 4mm Black		SCREWS: C-MPSCRS028X0079-KM#		Voc	7.7	V
	REV. CHANGE DATE CHK'D BY				TESTING: -40°C - 85°C [-40°F - 185°F]		NUTS: None		Vp	6.5	V
	1								mAsc	990	mA
									mAp	930	mA
									Wp	6.0	W

This document contains proprietary information and should not be copied or shared without the consent of Voltaic Systems.