



NOTES:

1. All materials RoHS compliant
2. Tape over all electrical connections
3. Total Panel Thickness (not including screws): 4.5-5.0mm



FILE DETAILS				SUBSTRATE		HARDWARE		POWER		
PRODUCT NAME: 1W 6V 113x89mm				SIZE: 113x89mm		WIRE: Male 3.5x1.1mm 260mm		Spec. Tolerance: ±10% (Vp,Ip)		
DWG. NO. 1_6_113x89_R1				MATERIAL: 3.0mm AL-Plastic Composite		WIRE COLOR: Red		Cell Supplier: Solar World		
DWG. TYPE: Production				COLOR: Silver / Charcoal		WIRE NO. Wire 17		Cell Efficiency: +19.1%		
SCALE: UNITS: TOLERANCE: SHEET: 1:1.5 MM ±0.1mm 1/1				COATING: Urethane		STRAIN RELIEF: None		MC	12	pcs
CREATED BY: DATE: TK 2017/7/6				TAPE: 3mm + 4mm Black		SCREWS: C-MPSCRS028X0079-KM#		Voc	7.7	V
REV. CHANGE: DATE: CHK'D BY: 1				TEMP. RANGE: -40°C - 85°C [-40°F - 185°F]		NUTS: None		Vp	6.5	V
								mAsc	190	mA
								mAp	180	mA
								Wp	1.2	W