

Lab 09

Name: Vorng Viseth

ID: IDTB110230

1. Write a query to find the name (first_name, last_name) and the salary of the employees who have a higher salary than the employee whose last_name='Bull'.

```
select concat(first_name, ' ', last_name) as name, salary from employees where salary  
> (select salary from employees where last_name = 'Bull');
```

2. Write a query to find the name (first_name, last_name) of all employees who works in the IT department.

```
select concat(first_name, ' ', last_name) as name from employees where  
department_id = ( select department_id from departments where department_name =  
                  'IT' );
```

3. Write a query to find the name (first_name, last_name) of the employees who have a manager and worked in a USA based department.

```
select concat(first_name, ' ', last_name) as name from employees where manager_id is  
not null and department_id in ( select department_id from departments where  
location_id in ( select location_id from locations where country_id = 'US' ) );
```

4. Write a query to find the name (first_name, last_name) of the employees who are managers

```
select concat(first_name, ' ', last_name) as name from employees where employee_id  
in (select manager_id from employees);
```

5. Write a query to find the name (first_name, last_name), and salary of the employees whose salary is greater than the average salary.

```
select concat(first_name, ' ', last_name) as name, salary from employees where salary  
> ( select avg(salary) from employees );
```

6. Write a query to find the name (first_name, last_name), and salary of the employees whose salary is equal to the minimum salary for their job grade.

```
select concat(first_name, ' ', last_name) as name, salary, job_id from employees e
where salary = ( select min_salary from jobs j where e.job_id = j.job_id );
```

7. Write a query to find the name (first_name, last_name), and salary of the employees who earns more than the average salary and works in any of the IT departments.

```
select concat(first_name, ' ', last_name) as name, salary from employees where salary
> ( select avg(salary) from employees ) and department_id in (select department_id
from departments where department_name = 'IT');
```

8. Write a query to find the name (first_name, last_name), and salary of the employees who earns more than the earning of Mr. Bell.

```
select concat(first_name, ' ', last_name) as name, salary from employees where salary
> (select salary from employees where last_name = 'Bell');
```

9. Write a query to find the name (first_name, last_name), and salary of the employees who earn the same salary as the minimum salary for all departments.

```
select concat(first_name, ' ', last_name) as name, salary from employees where salary
= ( select min(salary) from employees );
```

10. Write a query to find the name (first_name, last_name), and salary of the employees whose salary is greater than the average salary of all departments.

```
select concat(first_name, ' ', last_name) as name, salary from employees where salary
> ( select avg(salary) from employees );
```

11. Write a query to find the name (first_name, last_name) and salary of the employees who earn a salary that is higher than the salary of all the Shipping Clerk (JOB_ID = 'SH_CLERK'). Sort the results of the salary of the lowest to highest.

```
select concat(first_name, ' ', last_name) as name, salary from employees where salary
> ALL ( select salary from employees where job_id = 'SH_CLERK' ) order by salary asc;
```

12. Write a query to find the name (first_name, last_name) of the employees who are not supervisors

```
select concat(first_name, ' ', last_name) as name from employees where employee_id  
not in ( select distinct manager_id from employees where manager_id is not null );
```

13. Write a query to display the employee ID, first name, last name, and department names of all employees

```
select e.employee_id, e.first_name, e.last_name, (select d.department_name from  
departments d where d.department_id = e.department_id) as department_name from  
employees e;
```

14. Write a query to display the employee ID, first name, last name, salary of all employees whose salary is above average for their departments.

```
select e.employee_id, e.first_name, e.last_name, e.salary from employees e where  
e.salary > ( select avg(salary) from employees where e.department_id =  
department_id );
```

15. Write a query to fetch even numbered records from employees table.

```
SELECT * FROM employees WHERE MOD(employee_id, 2) = 0;
```

16. Write a query to find the 5th maximum salary in the employees table.

```
select distinct salary from employees order by salary desc limit 1 offset 4;
```

17. Write a query to find the 4th minimum salary in the employees table.

```
select distinct salary from employees order by salary desc limit 1 offset 3;
```

18. Write a query to select last 10 records from a table.

```
select * from ( select * from employees order by employee_id desc limit 10 ) as  
at_least_10 order by employee_id asc;
```

19. Write a query to list the department ID and name of all the departments where no employee is working.

```
select department_id, department_name from departments where department_id not  
in ( select department_id from employees );
```

20. Write a query to get 3 maximum salaries.

```
select distinct salary from employees order by salary desc limit 3;
```

21. Write a query to get 3 minimum salaries.

```
select salary from ( select distinct salary from employees order by salary asc limit 3 ) as  
salary order by salary desc;
```

22. Write a query to get nth max salaries of employees.