

1. CHECKLIST BELT CONVEYOR (Excel)

IMMEDIATE ACTIONS:

Equipment:

Frequency:

Operator/Mechanic:

If ✕ detected:

TB01

Weekly

High Priority: Stop immediately.

High Priority: Schedule repair within 24h.

Date:

A. VISUAL VERIFICATIONS (Running)

Item	**Verification**	**Criteria**	✓ OK	✕ NOK	**Observations**
	1 Belt alignment	Belt doesn't shift laterally (>2 cm)			
	2 Scraper condition	Uniform contact, no material accumulation			
	3 Support rollers	Rotate freely, no adhered material			
	4 Material leaks	No material accumulation on sides or base			
	5 Gearmotor	No oil leaks			
B. SOUND VERIFICATIONS (Running)					
	1 Support rollers	No abnormal noises (squeaking, impacts)			
	2 Gearmotor	No irregular or excessive humming			
	3 Belt	No friction noises with structure			
C. MANUAL VERIFICATIONS (Stopped)					
	1 Belt wear	No cuts or cracks on surface			
	2 Rollers (drive, driven)	No axial clearances, smooth rotation			
	3 Oil level (gearmotor)	Between MIN/MAX marks			
	4 Bearing condition	No axial/radial play			
	5 Belt tension	Maximum deflection 2-3 cm when pressing			

2. CHECKLIST CEMENT SCREW CONVEYOR

****IMMEDIATE ACTIONS:****

If **X** detected:

****High Priority:**** Stop immediately.

****High Priority:**** Schedule repair within 24h.

****Equipment:****

SCREW_CEM01

****Frequency:****

Weekly

****Date:****

****Operator/Mechanic:****

****A. VISUAL VERIFICATIONS (Running)****

****Item****

****Verification****

****Criteria****

1 Cement leaks

No accumulation in joints or connections

2 Gearmotor and coupling

No oil leaks, no misalignments

3 Greasing points

Visible and accessible grease fittings

4 Screw structure

No deformations or corrosion

****B. SOUND VERIFICATIONS (Running)****

1 Screw friction

No metallic noises (screw vs. casing)

2 Gearmotor

No excessive vibrations or humming

3 Couplings

No clicking or impact sounds

****C. MANUAL VERIFICATIONS (Stopped)****

1 Screw wear

Clearance <5 mm between screw and casing

2 Couplings

No excessive clearances

3 Oil level (gearmotor)

Between MIN/MAX marks

4 Bearing condition

No axial/radial play

5 Critical points lubrication

Complete greasing (if applicable)

[illegible]

**