arXiv:submit/8334597 [cs.CV] 14 Nov 2026

FDAM: A Frequency-Direction-Aware Multi-Task Framework for Pavement Crack Grid Localization

Haiyang Xu[1] Bin Pan[1,*] Mengze Wang[1] Qiaoying Qu[1] Zhenwei Shi[2]

[1]School of Statistics and Data Science, LEBPS, KLMDASR, LPMC, AAIS, NITFID, Nankai University

[2]Department of Aerospace Intelligent Science and Technology, School of Astronautics, Beihang University

Abstract

Pavement crack grid localization remains challenging for thin and tiny cracks due to weak visual cues and background interference. Box detection often misses these cracks, while supervised semantic segmentation faces limited pixel-wise annotations and high labeling costs. In this paper, we propose a Frequency-Direction-Aware Multi-Task framework (FDAM) with box detection and grid classification branches. The core grid classification branch comprises Frequency-Domain Enhancement (FDE) and Directional Feature Refinement (DFR). FDE adaptively weights spectral bands and fuses reconstructed features with spatial features. DFR captures thin crack patterns through multi-scale strip convolutions, direction-sensitive modulation, and feature recalibration. Sparse positive cells and ambiguous local predictions motivate adaptive grid supervision. Adaptive Importance Reweighting emphasizes uncertain predictions and local label transitions, with focal supervision for all cells. Our contribution is to couple the box detection and grid classification branches through shared feature learning for pavement crack grid localization. We validate FDAM on our RoadDistress2026 dataset of thin and tiny cracks and further evaluate it on the public datasets Crack500 and DeepCrack. The code is available at https://github.com/Lab-PANbin/FDAM.

1. Introduction


Pavement crack detection identifies surface cracks and their spatial distribution for road condition assessment [2, 35]. We focus on pavement crack grid localization for thin and tiny cracks. We use thin to describe narrow apparent widths, whereas tiny describes limited spatial extent relative to the image. These image-space characteristics, together with pavement textures and shadows, make reliable localization challenging [8].

Existing methods represent cracks using bounding boxes or pixel-wise masks. Transformer-based detectors predict categories and instance extents through set prediction [16, 17, 37, 52]. Convolutional segmentation aggregates multi-scale features [1, 46, 55], while lightweight and attention-based designs refine crack details [25, 50, 54]. Transformers [28, 31, 45] and state space models [9, 11, 32, 53] extend contextual modeling. Multiscale and hybrid architectures integrate local detail with broader context [10, 12, 43, 44], with further refinement through structural modeling and feature mixing [13, 41, 49, 56]. Spectral processing provides complementary features for restoration and segmentation [4, 20, 47, 51]. Directional models encode oriented cracks [3], while strip convolutions capture elongated objects in remote sensing [48].

However, weak crack cues, costly annotations, and imbalanced supervision still challenge thin and tiny crack localization. Bounding boxes can contain substantial background, while fully supervised segmentation requires precise pixel-wise masks. Weakly supervised methods reduce annotation demands [14, 15, 18, 21] but still need to distinguish weak cracks from the background. Although tailored losses and focal loss address foreground-background imbalance [26, 29, 39], sparse positive grid cells and ambiguous label transitions remain challenging. Reliable grid localization therefore requires stronger crack representations and effective supervision across the image.

Grid occupancy provides this local representation and has an engineering basis in pavement assessment. China's *Highway Performance Assessment Standard* (JTG 5210–2018) classifies longitudinal and transverse asphalt pavement cracks as low-severity when the main crack width does not exceed $3\ \mathrm{mm}$. Its automated assessment of the Pavement Surface Condition Index uses occupied $0.1\ \mathrm{m} \times 0.1\ \mathrm{m}$ grids to estimate distress area [34]. Inspired by this practice and prior joint box-grid learning [22], we combine instance localization and local occupancy prediction for thin and tiny cracks. Our grids operate in image coordinates without a prescribed physical size. Fig. 1 illustrates the task and its complementary labels.

To address this challenge, we propose FDAM, a



(a) Crack detection and segmentation

(b) Pavement crack grid localization

Figure 1. Illustration of pavement crack localization tasks and labels. (a) Crack detection and segmentation. Detection and pixel-wise segmentation labels are shown for a wide crack. (b) Pavement crack grid localization for thin and tiny cracks. From left to right: input image and crack detail, detection label, and grid label. The full-image grid defines regular classification units, and cells with highlighted boundaries indicate crack presence.

Frequency–Direction-Aware Multi-Task framework that couples box detection and grid classification through shared feature learning. A shared backbone and hybrid encoder support a transformer-based detection branch [16] and the core grid classification branch. Within the grid branch, Frequency-Domain Enhancement (FDE) adaptively weights spectral bands, while Directional Feature Refinement (DFR) captures elongated crack structures. Adaptive Importance Reweighting emphasizes uncertain predictions and local grid-label transitions while retaining focal supervision over all cells. During inference, class-aware box-grid association filters grid predictions using detection categories and spatial overlap. Experiments on our newly constructed RoadDistress2026 dataset of thin and tiny cracks and the public Crack500 and DeepCrack datasets evaluate the framework and its components.

Our main contributions are summarized as follows:

- We develop a multi-task framework for pavement crack grid localization of thin and tiny cracks through shared box and grid feature learning.
- We design a grid classification branch combining adaptive spectral weighting and directional feature refinement to strengthen weak crack representations.
- We introduce adaptive importance reweighting for grid focal supervision, emphasizing uncertain predictions and local label transitions while retaining supervision over all cells.

2. Related Work

2.1. Crack Detection and Segmentation

Automated pavement analysis spans distress evaluation [6], crack localization [7], quantification [36], and learned distress recognition [5]. Transformer-based detectors predict object categories and boxes through set prediction [16, 17, 37, 52]. For pixel-wise crack prediction, convolutional networks aggregate hierarchical and multiscale features [1, 46, 55]. Lightweight designs and attention-based integration improve efficiency and feature representation [23, 25, 50, 54]. Transformers capture contextual dependencies through attention [28, 31, 45]. Selective state space modeling [9] also supports long-range interactions in recent crack segmentation networks [11, 32, 53].

Preserving spatial detail remains essential for weak crack representations. High-resolution multiscale features support semantic segmentation [10], while crack-specific architectures integrate local detail with broader context [12, 43, 44]. Other methods explore convolution-transformer integration [41], convolutional and state space features [13], topology-aware modeling [56], and global-local feature mixing [49]. These approaches advance dense crack prediction, but fully supervised segmentation requires precise pixel-wise annotations.

2.2. Frequency and Directional Feature Modeling

Spectral and directional representations provide complementary cues for recovering weak structures. Frequency-domain processing has been explored in image inpainting [4] and crack segmentation under shadows [51]. Related work investigates high-frequency refinement for weakly supervised segmentation [47] and frequency-aware decoding for thin cracks [20]. Directional modeling represents cracks as oriented sub-cracks [3], while strip convolutions capture elongated objects in remote sensing images [48]. These studies motivate combining spectral and directional cues in our grid classification branch. Because cracks and pavement textures can share frequency components, we combine input-dependent spectral weighting with directional refinement.

2.3. Weak Supervision and Loss Reweighting

Annotation requirements and foreground sparsity motivate alternative supervision strategies. Weakly supervised crack analysis uses coarse annotations or generated labels to reduce dependence on precise masks [14, 15, 18, 21]. Loss

design has also been investigated for imbalanced crack segmentation [26, 39]. Focal loss reduces the contribution of well-classified examples [29]. Our supervision operates on category-specific grid occupancy. Adaptive Importance Reweighting uses prediction uncertainty and local grid-label transitions to weight focal loss while supervising all entries. These transitions describe coarse occupancy changes without requiring pixel-wise crack boundaries.

3. Methodology

We formulate pavement crack grid localization as joint instance detection and category-wise grid occupancy prediction. FDAM couples shared feature learning with spectral enhancement, directional refinement, and adaptive grid supervision.

3.1. Overall Framework

Given an input image $\mathbf{I} \in \mathbb{R}^{3\times H\times W}$, a backbone and hybrid encoder produce three shared feature maps $\{\mathbf{F}_l\}_{l=1}^{3}$. The two branches predict

$$\mathcal{D}_{\text{raw}} = \{(\hat{\mathbf{p}}_i, \hat{\mathbf{b}}_i)\}_{i=1}^{N_q}, \quad \mathbf{Z} \in \mathbb{R}^{C_g\times H_g\times W_g}, \tag{1}$$

where N_q is the query count, and $\hat{\mathbf{p}}_i$ and $\hat{\mathbf{b}}_i$ denote category scores and normalized boxes. $\mathbf{Z}$ contains category-specific grid logits, where $Z_c(u, v)$ predicts the presence of category c in cell (u, v) before sigmoid activation. The C_g categories share an $H_g \times W_g$ grid.

As shown in Fig. 2, both branches learn from shared features while retaining task-specific prediction heads. The detection branch follows DEIMv2 [16], using a transformer decoder and Hungarian matching for set prediction. We retain its classification, box regression, and auxiliary losses in $\mathcal{L}_{\text{det}}$. Training minimizes

$$\mathcal{L} = \mathcal{L}_{\text{det}} + \lambda_{\text{grid}}\mathcal{L}_{\text{grid}}, \tag{2}$$

where λ_{grid} balances the objectives. Both losses update the shared backbone and encoder.

3.2. Grid Classification Branch

Pointwise projections and bilinear resizing align the shared features to C channels and the coarsest encoder resolution (H_g, W_g). Concatenation and convolution produce the fused feature $\mathbf{F}_g$. Fig. 3 shows the subsequent enhancement and prediction stages. Detailed operators are given in Supplementary Sec. A.

3.2.1. Frequency-Domain Enhancement

Thin and tiny cracks produce spatial variations across multiple frequency bands, which may also contain pavement textures and noise. FDE therefore learns input-dependent spectral weights. Let $\mathcal{F}_r$ denote the orthonormal real Fourier transform. Four disjoint radial masks M_k receive weights

$$\begin{aligned} \boldsymbol{\omega} &= \text{Softmax}(\phi_b(\text{GAP}(\mathbf{F}_g))), \\ M_b &= \sum_{k=1}^{4} \omega_k M_k, M_f = M_b \odot (1 + \chi_f M_d), \end{aligned} \tag{3}$$

where GAP denotes global average pooling, $M_d \in [0, 1]$ is a learned axis-modulation mask, and $\chi_f \in \{0, 1\}$ specifies whether it is enabled.

The masks are shared across channels. Spectral reconstruction and gated fusion give

$$\begin{aligned} \mathbf{F}_f &= \mathcal{F}_r^{-1}[(1 + \lambda_f M_f) \odot \mathcal{F}_r(\mathbf{F}_g)], \\ \mathbf{G}_f &= \sigma(\phi_g(\mathbf{F}_g \| \mathbf{F}_f)), \\ \mathbf{F}_{\text{e}} &= \mathbf{F}_g + \mathbf{G}_f \odot (\mathbf{F}_f - \mathbf{F}_g), \end{aligned} \tag{4}$$

where λ_f is learned, σ is sigmoid, $\|$ denotes channel concatenation, and $\odot$ denotes element-wise multiplication.

The spatial gate is broadcast across channels. Since $\|M_f\|_\infty \le 2$, the correction satisfies

$$\|\mathbf{F}_{\text{e}} - \mathbf{F}_g\|_F \le 2|\lambda_f| \, \|\mathbf{F}_g\|_F. \tag{5}$$

Thus, $|\lambda_f|$ controls the relative correction magnitude for each input, and $\lambda_f = 0$ recovers the input. Mask construction and the derivation appear in Supplementary Sec. B.

3.2.2. Directional Feature Refinement

DFR captures elongated crack patterns through multiscale strip convolutions, directional modulation, and feature recalibration. Given the input feature $\mathbf{F}_{\text{in}}$, each DFR stage applies parallel $1 \times k$ and $k \times 1$ convolutions with $k \in \{3, 7, 11\}$, followed by concatenation, normalization, and activation to obtain $\mathbf{A}$. Axis-wise pooling produces attention maps $\mathbf{T}_h, \mathbf{T}_v$, while global pooling predicts softmax weights a_h, a_v. The directional update is

$$\begin{aligned} \mathbf{A}_d &= \mathbf{A} \odot (a_h \mathbf{T}_h + a_v \mathbf{T}_v), \\ \mathbf{F}_{\text{out}} &= \mathbf{F}_{\text{in}} + \text{GN}(\text{Conv}_{1\times1}(\mathbf{A}_d)). \end{aligned} \tag{6}$$

where GN denotes group normalization. The residual connection preserves the input features while incorporating the directional refinement.

Applying N_b independently parameterized stages to $\mathbf{F}_{\text{e}}$ yields $\mathbf{F}_r$. Two complementary spatial maps reweight equal channel groups, followed by channel recalibration:

$$\begin{aligned} \mathbf{F}_s &= (\mathbf{F}_{r,1} \odot \mathbf{S}_1) \| (\mathbf{F}_{r,2} \odot \mathbf{S}_2), \\ \mathbf{F}_d &= \mathbf{F}_s \odot \sigma(\psi_c(\text{GAP}(\mathbf{F}_s))). \end{aligned} \tag{7}$$

where the maps satisfy $\mathbf{S}_1 + \mathbf{S}_2 = 1$ at each location. The channel groups are learned partitions without prescribed orientations. Spatial dropout and a pointwise classifier produce $\mathbf{Z}$. Supplementary Sec. A.2 specifies the attention, recalibration, and prediction operators.




Figure 2. Overview of FDAM for pavement crack grid localization. The training procedure jointly optimizes a box detection branch and a grid classification branch through shared feature learning. The inference procedure applies class-aware box-grid association to refine grid predictions using detection categories and spatial overlap.

3.3. Adaptive Importance Reweighting

Grid supervision emphasizes uncertain predictions and local label transitions while retaining supervision over every category-cell entry. Grid annotations are stored separately from detection boxes. Their transformed centers and eight offsets are projected onto the prediction grid to form $\mathbf{Y} \in \{0,1\}^{C_g \times H_g \times W_g}$. Categories are encoded independently, allowing multiple labels per cell. Supplementary Sec. C.1 details target construction.

For training, let $\bar{\mathbf{Z}} = \mathrm{clip}(\mathbf{Z}, -20, 20)$ and $\mathbf{P} = \sigma(\bar{\mathbf{Z}})$. Define

$$\begin{aligned} \mathbf{U} &= 1 - |2\mathbf{P} - 1|, \\ \mathbf{T} &= \mathrm{Dilate}_{k_t}(\mathbf{Y}) - \mathrm{Erode}_{k_t}(\mathbf{Y}), \\ \mathbf{W}_{\mathrm{AIR}} &= \mathrm{StopGrad}(1 + \lambda_u \mathbf{U} + \lambda_t \mathbf{T}). \end{aligned} \tag{8}$$

Uncertainty peaks at $P = 0.5$, and $\mathbf{T}$ marks coarse grid-label transitions rather than pixel-wise crack boundaries. StopGrad prevents differentiation through the weighting rule. The grid objective uses binary focal loss [29]:

$$\mathcal{L}_{\mathrm{grid}} = \frac{\sum_j W_{\mathrm{AIR},j}\, \ell_{\mathrm{focal}}(P_j, Y_j)}{\max(1, N_+)}, N_+ = \sum_j Y_j, \tag{9}$$

where $j = (b, c, u, v)$ indexes the local mini-batch.

With $\lambda_u = \lambda_t = 1$, the weights satisfy $1 \le W_j \le 3$. Relative to the unit-weight objective $\mathcal{L}_0$,

$$\frac{\partial \mathcal{L}_{\mathrm{grid}}}{\partial \bar{Z}_j} = W_{\mathrm{AIR},j} \frac{\partial \mathcal{L}_0}{\partial \bar{Z}_j}. \tag{10}$$

The weights preserve each clipped-logit's gradient sign while scaling its magnitude by a bounded positive factor. The focal formulation, hyperparameters, and derivation are provided in Supplementary Sec. C.2.

3.4. Inference Procedure

A single forward pass produces both outputs. Decoded detections with scores $s^d > \tau_d$ form $\mathcal{D}$. Each grid cell selects its highest-scoring category from $\sigma(\mathbf{Z})$ and is retained as a candidate when $s^g \ge \tau_g$. After mapping both outputs to original-image coordinates and a common category space, association retains

$$\mathcal{G}^* = \left\{ g \in \mathcal{G} \;\middle|\; \begin{array}{l} \exists d \in \mathcal{D} :\ \hat{c}^g = \hat{c}^d, \\ |\mathbf{b}^g \cap \mathbf{b}^d| > 0 \end{array} \right\}. \tag{11}$$

Association only filters grid candidates and preserves their scores. If $\mathcal{D} = \varnothing$, then $\mathcal{G}^* = \varnothing$. Grid-only inference returns the unassociated set $\mathcal{G}$. Box average precision uses decoded detections independently of the association threshold. Supplementary Sec. D and Algorithm 1 give the complete procedure.

4. Experiments

We evaluate box detection and grid classification on RoadDistress2026, Crack500, and DeepCrack, followed by component and task ablations. Additional evaluations stratified by instance extent and mask width, together with qualitative comparisons, are provided in Sec. E of the supplementary material.

4.1. Datasets and Annotation Preparation

RoadDistress2026. Our dataset contains 13,000 images at 4656×2657 pixels: 9,100 for training, 2,600 for validation, and 1,300 for testing. Longitudinal cracks (LC) and transverse cracks (TC) are labeled on a 20×37 grid. Positive cells carry category and instance labels; each detection box encloses one instance's cells.




Figure 3. Grid classification branch with Frequency-Domain Enhancement and Directional Feature Refinement. Spatial dimensions illustrate a 640 × 640 input.

Public Benchmarks. Crack500 contains 500 mask-labeled images [46], processed into 1,896 training, 348 validation, and 1,124 test samples. DeepCrack contains 537 images of diverse surfaces [55], split into 375/53/109 images for training/validation/testing.

For both datasets, boxes enclose 8-connected mask components with at least three foreground pixels. Grid annotations are derived separately using 20 × 20-pixel reference cells on a 640 × 640 plane, scaled to the original image size and rounded to integer pixels. These annotation cells differ from the network's 20 × 20 output grid, whose cells cover 32 × 32 input pixels. Annotation regions map to the output grid through the nine-point projection in Section 3.3, with $\delta_g = 0.125$. FDAM uses the derived boxes and grid regions. Segmentation baselines use dense masks.

4.2. Experimental Setup

4.2.1. Training Settings

FDAM uses PyTorch 2.2.2 on an Intel Xeon E5-2680 workstation with two 24 GB NVIDIA RTX 3090 GPUs. AdamW uses $\beta_1 = 0.9$, $\beta_2 = 0.999$, warm-up, and a flat-cosine schedule. Backbones use pretrained DINOv3 representations. DeepCrack and its ablations share COCO-pretrained DEIMv2 initialization and seed zero. Training applies ImageNet normalization, photometric and geometric augmentation, scheduled Mosaic/MixUp, and multiscale resizing. The grid head uses four frequency bands and dropout 0.1. Grid loss parameters are $\alpha_f = 0.5$ and $\gamma_f = 1.5$. AIR uses $\lambda_u = \lambda_t = 1$ and $k_t = 3$.

4.2.2. Model Selection and Inference

Validation-selected checkpoints and thresholds are frozen for testing with exponential-moving-average weights. Joint and detection-only models are selected by box AP. Grid-only uses foreground grid F1. Both joint outputs use the same checkpoint. On public datasets, thresholds maximize validation foreground grid F1, including for segmentation baselines. Joint models use $\tau_g = 0.45$ and $\tau_d = 0.30$. DeepCrack Grid-only uses $\tau_g = 0.50$.

Joint inference retains grid cells overlapping same-category detections with positive area. Grid-only uses raw grids. Box AP is evaluated independently of grid association. RoadDistress2026 uses $\tau_d = \tau_g = 0.5$ for quantitative joint inference. All three datasets retain grid candidates with $s^g \geq \tau_g$ and detection candidates with $s^d > \tau_d$.

4.2.3. Evaluation Protocol

Comparisons include eight box detectors, five segmentation methods, and GCBD [22] under identical splits. Box detection uses COCO AP over IoU thresholds 0.50:0.05:0.95, AP_{50}, and AP_{75}. RoadDistress2026 reports category-wise grid precision, recall, and confidence-ranked cell AP after box association, without an IoU sweep. On public datasets, FDAM probabilities are thresholded directly on its output grid. Precision, recall, F1, and IoU use the confusion matrix aggregated over all test cells. Overall metrics average background and crack equally. Crack Only denotes foreground metrics. All accuracy values are percentages.

Table 1. Box detection on Crack500 and DeepCrack. All methods use the same mask-derived box annotations. Best and second-best metric values are **bold** and underlined, respectively.

Method	Crack500					DeepCrack				
	Params (M)	GFLOPs	AP	AP_{50}	AP_{75}	Params (M)	GFLOPs	AP	AP_{50}	AP_{75}
YOLOv12 [40]	26	99	18.8	33.8	18.2	26	99	32.8	52.0	32.6
YOLO26 [38]	25	96	18.0	33.1	17.1	25	96	33.2	52.3	36.3
RT-DETR [52]	36	100	19.8	34.1	19.6	36	100	35.8	52.0	36.3
RT-DETRv2 [33]	36	100	19.9	33.9	20.0	36	100	30.2	44.7	30.6
RT-DETRv3 [42]	31	92	18.6	31.7	18.5	31	92	26.7	39.5	28.7
RT-DETRv4 [27]	31	91	20.1	34.8	20.0	31	91	25.6	40.6	24.5
DEIM [17]	31	92	20.4	35.0	20.3	31	92	36.9	54.7	37.7
DEIMv2 [16]	10	25	21.3	35.4	21.0	18	52	37.6	55.5	37.3
FDAM (Ours)	12	29	**21.8**	**36.6**	**21.8**	22	56	**39.8**	**57.3**	**40.7**

Table 2. Box detection on RoadDistress2026. FDAM uses only the detection branch in this comparison. LC and TC denote longitudinal and transverse cracks. Best and second-best metric values are **bold** and underlined, respectively.

Method	Params (M)	GFLOPs	LC			TC			All		
			AP	AP_{50}	AP_{75}	AP	AP_{50}	AP_{75}	AP	AP_{50}	AP_{75}
YOLOv12 [40]	26	281	15.6	38.5	8.8	16.5	40.4	11.0	16.1	39.5	9.9
YOLO26 [38]	25	248	15.1	34.4	11.1	15.9	38.1	10.5	15.5	36.3	10.8
RT-DETR [52]	36	254	15.4	38.7	8.8	15.9	42.9	7.2	15.7	40.8	8.0
RT-DETRv2 [33]	36	254	15.0	37.1	10.3	16.5	42.8	9.1	15.8	40.0	9.7
RT-DETRv3 [42]	43	157	15.5	39.1	8.8	15.3	39.2	9.8	15.4	39.2	9.3
RT-DETRv4 [27]	31	224	19.9	50.2	12.7	19.1	50.0	11.2	19.5	50.1	12.0
DEIM [17]	31	230	19.6	47.4	12.8	18.6	47.2	11.4	19.1	47.3	12.1
DEIMv2 [16]	32	242	19.9	48.8	12.6	19.1	50.0	11.7	19.5	49.4	12.2
FDAM (Ours)	35	248	**20.2**	**51.1**	**13.5**	**19.8**	**51.1**	**12.2**	**20.0**	**51.1**	**12.9**

Table 3. Joint box–grid comparison on RoadDistress2026. FDAM uses the multitask model with both detection and grid branches. All denotes the average over LC and TC. Grid AP is class-wise average precision without an IoU sweep. Best and second-best metric values are **bold** and underlined, respectively.

Task	Method	Params (M)	GFLOPs	LC			TC			All		
				AP	AP_{50}	AP_{75}	AP	AP_{50}	AP_{75}	AP	AP_{50}	AP_{75}
Box	GCBD [22]	56	117	7.6	25.5	4.0	13.4	41.8	3.6	10.5	33.7	3.8
	FDAM (Ours)	35	248	**17.7**	**44.5**	**12.4**	**19.6**	**46.3**	**13.0**	**18.7**	**45.4**	**12.7**
				P	R	AP	P	R	AP	P	R	AP
Grid	GCBD [22]	56	117	44.0	61.6	46.7	53.5	55.6	51.3	48.8	58.6	49.0
	FDAM (Ours)	35	248	**59.3**	**68.8**	**65.6**	**62.0**	**69.1**	**67.3**	**60.7**	**69.0**	**66.5**

4.2.4. Input Resolution and Complexity

The public-dataset comparisons in Table 1 use 640×640 inputs. RoadDistress2026 comparisons in Tables 2 and 3 use 1024×1024 inputs. In Table 4, GFLOPs use each method's input resolution: 256×256 for SimCrack and MSFAF-Net, 512×512 for SCSegamba and MixerCSeg, and 640×640 for FDAM. CCMamba's GFLOPs cover one 384×384 sliding window, excluding additional windows per image.




Figure 4. Qualitative comparison of GCBD and the joint FDAM model on RoadDistress2026 for box detection and grid localization.

Table 4. Grid classification results for pavement crack grid localization on Crack500 and DeepCrack under a common grid protocol. Overall metrics are macro-averaged over background and crack. Segmentation baselines use dense mask supervision, while FDAM uses derived box and grid annotations. Params and GFLOPs are given as Crack500/DeepCrack when they differ. Best and second-best metric values are **bold** and underlined, respectively.

Method	Params (M)	GFLOPs	Crack500								DeepCrack							
			Overall				Crack Only				Overall				Crack Only			
			mP	mR	mF1	mIoU	P	R	F1	IoU	mP	mR	mF1	mIoU	P	R	F1	IoU
SimCrack [19]	299	146	84.3	86.2	85.2	75.7	72.3	77.2	74.7	59.6	89.0	86.5	87.7	79.2	82.4	76.0	79.0	65.3
SCSegamba [32]	2.8	18	90.5	90.6	90.5	83.4	83.5	83.8	83.7	71.9	94.2	89.6	91.7	85.2	91.8	80.5	85.8	75.1
MixerCSeg [53]	2.5	3	89.9	90.3	90.1	82.8	82.4	83.5	82.9	70.9	90.6	89.0	89.8	82.2	84.7	80.7	82.6	70.4
CCMamba [30]	89	41	90.3	91.4	90.8	83.9	82.9	85.7	84.3	72.8	**95.7**	91.3	93.3	87.8	**94.4**	83.4	88.6	79.5
MSFAF-Net [24]	5.5	28	87.0	88.6	87.8	79.4	77.1	81.1	79.1	65.4	87.5	85.5	86.4	77.3	79.5	74.4	76.9	62.4
FDAM (Ours)	12/22	29/56	**91.5**	**92.7**	**92.1**	**85.8**	**84.9**	**87.8**	**86.3**	**76.0**	93.7	**93.7**	**93.7**	**88.5**	89.3	**89.4**	**89.4**	**80.8**

4.3. Comparison with Existing Methods

4.3.1. Box Detection on Public Benchmarks

Table 1 shows that FDAM achieves 21.8/39.8 AP on Crack500/DeepCrack, exceeding the strongest baselines by 0.5/2.2 percentage points and leading in AP_{50} and AP_{75}.

4.3.2. Box Detection on RoadDistress2026

In Table 2, the detection-only configuration reaches 20.0 AP, 51.1 AP_{50}, and 12.9 AP_{75}, leading for both LC and TC. The joint model in Table 3 performs both box detection and grid classification, achieving 18.7 box AP and 66.5 grid AP. Fig. 4 presents qualitative comparisons of the detection and grid-classification results between the two methods.

4.3.3. Comparison on Pavement Crack Grid Localization

Table 4 compares FDAM with segmentation methods after converting their predictions to grids. FDAM leads all eight metrics on Crack500, with mF1/mIoU of 92.1/85.8, exceeding CCMamba by 1.3/1.9 percentage points. On DeepCrack, FDAM achieves the highest mF1/mIoU of 93.7/88.5. Relative to CCMamba, higher crack recall (89.4 versus 83.4) offsets lower precision (89.3 versus 94.4), yielding higher crack F1/IoU of 89.4/80.8. Fig. 5 shows qualitative comparisons under the same grid protocol.

4.4. Ablation Studies

DeepCrack ablations share the backbone, split, initialization, and training settings except for the component or task removed. Both joint outputs use one validation-selected checkpoint. Table 5 reports task and component ablations with all detection and grid metrics.

Adaptive Importance Reweighting. AIR increases box AP from 37.8 to 39.8 and grid mIoU from 84.0 to 88.5. Higher grid macro recall, 93.7 versus 87.4, offsets lower




Figure 5. Qualitative comparison of grid localization on Crack500 and DeepCrack. Each row shows an input image, grid ground truth, and predictions from the compared methods. Segmentation outputs are converted to the common grid representation.

Table 5. Task and component ablations on DeepCrack. Grid metrics average background and crack. Best and second-best metric values are **bold** and underlined, respectively.

Configuration	Box Detection			Grid Classification			
	AP	AP_{50}	AP_{75}	mP	mR	mF1	mIoU
Detection-only	35.5	51.1	36.8	–	–	–	–
Grid-only	–	–	–	93.8	**94.5**	**94.2**	**89.2**
Joint w/o FDE	38.4	54.7	40.4	93.3	93.6	93.4	88.0
Joint w/o DFR	38.6	54.1	38.7	93.3	93.4	93.4	87.9
Joint w/o AIR	37.8	54.8	38.7	**95.6**	87.4	90.9	84.0
Full FDAM	**39.8**	**57.3**	**40.7**	93.7	93.7	93.7	88.5

macro precision and raises mF1 from 90.9 to 93.7. AIR is enabled in the grid-only and full joint models.

Task branches. The joint model improves detection AP from 35.5 to 39.8 over detection-only. This gain suggests that grid supervision benefits detection through shared features, while box predictions provide category and spatial constraints for grid predictions during inference, highlighting their complementary roles. Grid-only achieves higher mF1/mIoU, 94.2/89.2 versus 93.7/88.5. However, this comparison does not isolate a multitask trade-off. Joint models use box-AP checkpoint selection and associated grids, whereas grid-only uses foreground-F1 selection and raw grids.

Feature enhancement. Removing FDE reduces box AP/grid mIoU from 39.8/88.5 to 38.4/88.0. Removing DFR reduces them to 38.6/87.9. Both components improve the measured detection and grid scores under these settings.

4.4.1. Effect of the Grid Loss Weight

Table 6 compares $\lambda_{\text{grid}} \in \{0.5, 1.0, 2.0\}$ on DeepCrack with other training settings fixed. Each setting uses a checkpoint selected by validation box AP for both tasks and validation-selected grid thresholds frozen for testing. The setting $\lambda_{\text{grid}} = 1.0$ achieves the highest box AP and grid mIoU among the tested values. Grid mF1 varies from 93.5 to 93.7 across these settings.

Table 6. Effect of the grid loss weight on DeepCrack. Grid metrics are macro-averaged over background and crack. All results are percentages. Best and second-best metric values are **bold** and underlined, respectively.

λ_{grid}	Box Detection			Grid Localization			
	AP	AP_{50}	AP_{75}	mP	mR	mF1	mIoU
0.5	37.7	55.2	38.1	93.5	93.5	93.5	88.1
1.0	**39.8**	**57.3**	**40.7**	**93.7**	93.7	**93.7**	**88.5**
2.0	38.2	54.7	38.6	93.4	**93.9**	**93.7**	88.4

5. Conclusion

We present FDAM for pavement crack grid localization of thin and tiny cracks. The framework couples box detection and grid classification through shared features. Spectral and directional enhancement strengthen grid representations, while adaptive importance reweighting emphasizes uncertain predictions and label transitions. Experiments on RoadDistress2026, Crack500, and DeepCrack demonstrate the effectiveness of the framework and its components. Fixed grids limit geometric detail, and missed detec-

tions can suppress valid cells during box-grid association.

LLM Usage Statement

We used ChatGPT for language polishing and grammatical correction. All technical content and conclusions were developed and verified solely by the authors.

Acknowledgment

The work was supported by the National Key Research and Development Program of China under Grant 2022YFA1003800, the National Natural Science Foundation of China under the Grant 62571273, Grant 62125102 and Grant U24B20177, and the Natural Science Foundation of Tianjin under the Grant 25JCLMJC01090.

References

[1] Zaid Al-Huda, Bo Peng, Riyadh Nazar Ali Algburi, Mugahed A Al-antari, Rabea AL-Jarazi, Omar Al-maqtari, and Donghai Zhai. Asymmetric dual-decoder-U-Net for pavement crack semantic segmentation. *Automation in Construction*, 156:105138, 2023. 1, 2

[2] H Ayman and Mohamed W Fakhr. Recent computer vision applications for pavement distress and condition assessment. *Automation in Construction*, 146:104664, 2023. 1

[3] Zhuangzhuang Chen, Jin Zhang, Zhuonan Lai, Guanming Zhu, Zun Liu, Jie Chen, and Jianqiang Li. The devil is in the crack orientation: A new perspective for crack detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 6653–6663, 2023. 1, 2

[4] Tianyi Chu, Jiafu Chen, Jiakai Sun, Shuobin Lian, Zhizhong Wang, Zhiwen Zuo, Lei Zhao, Wei Xing, and Dongming Lu. Rethinking fast Fourier convolution in image inpainting. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 23195–23205, 2023. 1, 2

[5] Hongwen Dong, Kechen Song, Qi Wang, Yunhui Yan, and Peng Jiang. Deep metric learning-based for multi-target few-shot pavement distress classification. *IEEE Transactions on Industrial Informatics*, 18(3):1801–1810, 2022. 2

[6] Hongwen Dong, Kechen Song, Yanyan Wang, Yunhui Yan, and Peng Jiang. Automatic inspection and evaluation system for pavement distress. *IEEE Transactions on Intelligent Transportation Systems*, 23(8):12377–12387, 2022. 2

[7] Yuchuan Du, Shan Zhong, Hongyuan Fang, Niannian Wang, Chenglong Liu, Difei Wu, Yan Sun, and Mang Xiang. Modeling automatic pavement crack object detection and pixel-level segmentation. *Automation in Construction*, 150: 104840, 2023. 2

[8] Lili Fan, Shen Li, Ying Li, Bai Li, Dongpu Cao, and Fei-Yue Wang. Pavement cracks coupled with shadows: A new shadow-crack dataset and a shadow-removal-oriented crack detection approach. *IEEE/CAA Journal of Automatica Sinica*, 10(7):1593–1607, 2023. 1

[9] Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces. In *First Conference on Language Modeling*, 2024. 1, 2

[10] Jiaqi Gu, Hyoukjun Kwon, Dilin Wang, Wei Ye, Meng Li, Yu-Hsin Chen, Liangzhen Lai, Vikas Chandra, and David Z Pan. Multi-scale high-resolution vision transformer for semantic segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12094–12103, 2022. 1, 2

[11] Yubin Gu, Boyang Hou, Yuan Meng, Wenting Luo, Jiayi Ji, and Xiaoshuai Sun. CrackSSM: Reviving SSMs for crack segmentation via dynamic scanning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10721–10730, 2026. 1, 2

[12] Feng Guo, Yu Qian, Jian Liu, and Huayang Yu. Pavement crack detection based on transformer network. *Automation in Construction*, 145:104646, 2023. 1, 2

[13] Chengjia Han, Handuo Yang, and Yaowen Yang. Enhancing pixel-level crack segmentation with visual Mamba and convolutional networks. *Automation in Construction*, 168: 105770, 2024. 1, 2

[14] Tiejun He, Huaen Li, Zhendong Qian, Chenyi Niu, and Ruihua Huang. Research on weakly supervised pavement crack segmentation based on defect location by generative adversarial network and target re-optimization. *Construction and Building Materials*, 411:134668, 2024. 1, 2

[15] Sheng Huang, Wenhao Tang, Guixin Huang, Luwen Huangfu, and Dan Yang. Weakly supervised patch label inference networks for efficient pavement distress detection and recognition in the wild. *IEEE Transactions on Intelligent Transportation Systems*, 24(5):5216–5228, 2023. 1, 2

[16] Shihua Huang, Yongjie Hou, Longfei Liu, Xuanlong Yu, and Xi Shen. Real-time object detection meets DINOv3. *arXiv preprint arXiv:2509.20787*, 2025. 1, 2, 3, 6

[17] Shihua Huang, Zhichao Lu, Xiaodong Cun, Yongjun Yu, Xiao Zhou, and Xi Shen. DEIM: DETR with improved matching for fast convergence. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 15162–15171, 2025. 1, 2, 6

[18] Yuki Inoue and Hiroto Nagayoshi. Weakly-supervised crack detection. *IEEE Transactions on Intelligent Transportation Systems*, 24(11):12050–12061, 2023. 1, 2

[19] Achref Jaziri, Martin Mundt, Andres Fernandez, and Visvanathan Ramesh. Designing a hybrid neural system to learn real-world crack segmentation from fractal-based simulation. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 8636–8646, 2024. 7

[20] Siheon Joo, Seokhwan Kim, and Hongjo Kim. Frequency-aware crack segmentation network (FACS-net) and crack topology loss (CT-loss) for thin cracks. *Automation in Construction*, 182:106719, 2026. 1, 2

[21] Jacob König, Mark David Jenkins, Mike Mannion, Peter Barrie, and Gordon Morison. Weakly-supervised surface crack segmentation by generating pseudo-labels using localization with a classifier and thresholding. *IEEE Transactions on Intelligent Transportation Systems*, 23(12):24083–24094, 2022. 1, 2

[22] Bao-Luo Li, Yu Qi, Jian-Sheng Fan, Yu-Fei Liu, and Cheng Liu. A grid-based classification and box-based detection fusion model for asphalt pavement crack. *Computer-Aided*

Civil and Infrastructure Engineering, 38(16):2279–2299, 2023. 1, 5, 6

[23] Kai Li, Jie Yang, Siwei Ma, Bo Wang, Shanshe Wang, Yingjie Tian, and Zhiquan Qi. Rethinking lightweight convolutional neural networks for efficient and high-quality pavement crack detection. *IEEE Transactions on Intelligent Transportation Systems*, 25(1):237–250, 2024. 2

[24] Xi Li, Yu-Qi Wang, Qiang Zhou, Hua-Kun Luo, and You-Lin Chen. MSFAF-Net: A multi-scale frequency-attentive fusion network for pavement crack detection. *IEEE Transactions on Intelligent Transportation Systems*, 2026. 7

[25] Jia Liang, Xingyu Gu, Dong Jiang, and Qipeng Zhang. CNN-based network with multi-scale context feature and attention mechanism for automatic pavement crack segmentation. *Automation in Construction*, 164:105482, 2024. 1, 2

[26] Jia Liang, Qipeng Zhang, and Xingyu Gu. Lightweight convolutional neural network driven by small data for asphalt pavement crack segmentation. *Automation in Construction*, 158:105214, 2024. 1, 3

[27] Zijun Liao, Yian Zhao, Xin Shan, Yu Yan, Chang Liu, Lei Lu, Xiangyang Ji, and Jie Chen. RT-DETRv4: Painlessly furthering real-time object detection with vision foundation models. *arXiv preprint arXiv:2510.25257*, 2025. 6

[28] Chunmian Lin, Daxin Tian, Xuting Duan, and Jianshan Zhou. TransCrack: Revisiting fine-grained road crack detection with a transformer design. *Philosophical Transactions of the Royal Society A*, 481(2254):20220172, 2023. 1, 2

[29] Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 2980–2988, 2017. 1, 3, 4

[30] Binghao Liu, Qi Zhao, Chunlei Wang, Hongbo Xie, and Hong Zhang. CCMamba: A multi-head criss-cross Mamba for pavement crack segmentation. *IEEE Transactions on Intelligent Transportation Systems*, 2026. 7

[31] Huajun Liu, Xiangyu Miao, Christoph Mertz, Chengzhong Xu, and Hui Kong. CrackFormer: Transformer network for fine-grained crack detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 3783–3792, 2021. 1, 2

[32] Hui Liu, Chen Jia, Fan Shi, Xu Cheng, and Shengyong Chen. SCSegamba: Lightweight structure-aware vision Mamba for crack segmentation in structures. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 29406–29416, 2025. 1, 2, 7

[33] Wenyu Lv, Yian Zhao, Qinyao Chang, Kui Huang, Guanzhong Wang, and Yi Liu. RT-DETRv2: Improved baseline with bag-of-freebies for real-time detection transformer. *arXiv preprint arXiv:2407.17140*, 2024. 6

[34] Ministry of Transport of the People's Republic of China. Highway performance assessment standard. Technical Report JTG 5210–2018, Ministry of Transport of the People's Republic of China, Beijing, China, 2018. 1

[35] Ning Pan, Hao Liu, Difei Wu, Chenglong Liu, and Yuchuan Du. Spatiotemporal matching method for tracking pavement distress using high-frequency detection data. *Computer-Aided Civil and Infrastructure Engineering*, 38(16):2257–2278, 2023. 1

[36] Zhihao Pan, Jinchao Guan, Xu Yang, Kang Fan, Jeremy CH Ong, Ningqun Guo, and Xin Wang. One-stage 3D profile-based pavement crack detection and quantification. *Automation in Construction*, 153:104946, 2023. 2

[37] Yansong Peng, Hebei Li, Peixi Wu, Yueyi Zhang, Xiaoyan Sun, and Feng Wu. D-FINE: Redefine regression task in DETRs as fine-grained distribution refinement. In *International Conference on Learning Representations*, pages 44015–44031, 2025. 1, 2

[38] Ranjan Sapkota, Rahul Harsha Cheppally, Ajay Sharda, and Manoj Karkee. YOLO26: Key architectural enhancements and performance benchmarking for real-time object detection. *arXiv preprint arXiv:2509.25164*, 2025. 6

[39] Thitirat Siriborvornratanakul. Pixel-level thin crack detection on road surface using convolutional neural network for severely imbalanced data. *Computer-Aided Civil and Infrastructure Engineering*, 38(16):2300–2316, 2023. 1, 3

[40] Yunjie Tian, Qixiang Ye, and David Doermann. YOLOv12: Attention-centric real-time object detectors. In *Advances in Neural Information Processing Systems*, pages 78433–78457, 2025. 6

[41] Jin Wang, Zhigao Zeng, Pradip Kumar Sharma, Osama Alfarraj, Amr Tolba, Jianming Zhang, and Lei Wang. Dual-path network combining CNN and transformer for pavement crack segmentation. *Automation in Construction*, 158: 105217, 2024. 1, 2

[42] Shuo Wang, Chunlong Xia, Feng Lv, and Yifeng Shi. RT-DETRv3: Real-time end-to-end object detection with hierarchical dense positive supervision. In *2025 IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, pages 1628–1636. IEEE, 2025. 6

[43] Shaozhang Xiao, Kaikai Shang, Ken Lin, Qingguo Wu, Hanzhu Gu, and Zhengwei Zhang. Pavement crack detection with hybrid-window attentive vision transformers. *International Journal of Applied Earth Observation and Geoinformation*, 116:103172, 2023. 1, 2

[44] Yang Xu, Wei Liang, Guanqiu Qi, Yuanyuan Li, Peiyong Wang, Qiuzhuo Liu, Hui Xu, and Zhiqin Zhu. DRCNet: A dual-stream multi-scale information retention network for crack segmentation. *Expert Systems with Applications*, page 132575, 2026. 1, 2

[45] Zhengsen Xu, Haiyan Guan, Jian Kang, Xiangda Lei, Lingfei Ma, Yongtao Yu, Yiping Chen, and Jonathan Li. Pavement crack detection from CCD images with a locally enhanced transformer network. *International Journal of Applied Earth Observation and Geoinformation*, 110:102825, 2022. 1, 2

[46] Fan Yang, Lei Zhang, Sijia Yu, Danil Prokhorov, Xue Mei, and Haibin Ling. Feature pyramid and hierarchical boosting network for pavement crack detection. *IEEE Transactions on Intelligent Transportation Systems*, 21(4):1525–1535, 2020. 1, 2, 5

[47] Ziqian Yang, Xinqiao Zhao, Xiaolei Wang, Quan Zhang, and Jimin Xiao. FFR: Frequency feature rectification for weakly supervised semantic segmentation. In *2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 30261–30270. IEEE, 2025. 1, 2

[48] Xinbin Yuan, Zhaohui Zheng, Yuxuan Li, Xialei Liu, Li Liu, Xiang Li, Qibin Hou, and Ming-Ming Cheng. Strip R-CNN: Large strip convolution for remote sensing object detection. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 12259–12267, 2026. 1, 2

[49] Hang Zhang, Allen A Zhang, Zishuo Dong, Anzheng He, Yang Liu, You Zhan, and Kelvin CP Wang. Robust semantic segmentation for automatic crack detection within pavement images using multi-mixing of global context and local image features. *IEEE Transactions on Intelligent Transportation Systems*, 25(9):11282–11303, 2024. 1, 2

[50] Tianjie Zhang, Donglei Wang, Amanda Mullins, and Yang Lu. Integrated APC-GAN and AttuNet framework for automated pavement crack pixel-level segmentation: A new solution to small training datasets. *IEEE Transactions on Intelligent Transportation Systems*, 24(4):4474–4481, 2023. 1, 2

[51] Yingchao Zhang and Cheng Liu. Crack segmentation using discrete cosine transform in shadow environments. *Automation in Construction*, 166:105646, 2024. 1, 2

[52] Yian Zhao, Wenyu Lv, Shangliang Xu, Jinman Wei, Guanzhong Wang, Qingqing Dang, Yi Liu, and Jie Chen. DETRs beat YOLOs on real-time object detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 16965–16974, 2024. 1, 2, 6

[53] Zilong Zhao, Zhengming Ding, Pei Niu, Wenhao Sun, and Feng Guo. MixerCSeg: An efficient mixer architecture for crack segmentation via decoupled Mamba attention. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 17969–17978, 2026. 1, 2, 7

[54] Guijie Zhu, Jiacheng Liu, Zhun Fan, Duan Yuan, Peili Ma, Meihua Wang, Weihua Sheng, and Kelvin CP Wang. A lightweight encoder–decoder network for automatic pavement crack detection. *Computer-Aided Civil and Infrastructure Engineering*, 39(12):1743–1765, 2024. 1, 2

[55] Qin Zou, Zheng Zhang, Qingquan Li, Xianbiao Qi, Qian Wang, and Song Wang. DeepCrack: Learning hierarchical convolutional features for crack detection. *IEEE Transactions on Image Processing*, 28(3):1498–1512, 2019. 1, 2, 5

[56] Xin Zuo, Yu Sheng, Jifeng Shen, and Yongwei Shan. Topology-aware Mamba for crack segmentation in structures. *Automation in Construction*, 168:105845, 2024. 1, 2

FDAM: A Frequency-Direction-Aware Multi-Task Framework for Pavement Crack Grid Localization

Supplementary Material

A. Detailed Architecture

A.1. Feature Aggregation and Detection

The shared encoder produces feature maps $\mathbf{F}_l \in \mathbb{R}^{C_l \times H_l \times W_l}$ at three scales. For channel width C divisible by 32, pointwise projections ϕ_l and bilinear interpolation align them to $(H_g, W_g) = (H_3, W_3)$:

$$\begin{aligned} \mathbf{Q}_l &= \mathrm{Resize}_{H_g,W_g}(\phi_l(\mathbf{F}_l)), \\ \mathbf{F}_g &= \delta(\mathrm{GN}[\mathrm{Conv}_{3\times3}(\mathbf{Q}_1 \| \mathbf{Q}_2 \| \mathbf{Q}_3)]) \,. \end{aligned} \tag{A.1}$$

where δ is SiLU.

The detection decoder progressively updates N_q queries from the shared encoder features. Prediction heads produce class scores and normalized boxes. Hungarian matching establishes one-to-one assignments to ground-truth instances, and the original detection losses are retained.

A.2. Directional Refinement and Prediction

For each refinement stage, six convolution branches use $\mathcal{K} = \{3, 7, 11\}$:

$$\begin{aligned} \mathbf{A}_h &= \mathop{\Vert}_{k\in\mathcal{K}} \mathrm{Conv}_{1\times k}(\mathbf{F}_{\mathrm{in}}), \\ \mathbf{A}_v &= \mathop{\Vert}_{k\in\mathcal{K}} \mathrm{Conv}_{k\times 1}(\mathbf{F}_{\mathrm{in}}), \\ \mathbf{A} &= \delta(\mathrm{GN}(\mathbf{A}_h \| \mathbf{A}_v)). \end{aligned} \tag{A.2}$$

The six branches jointly output C channels. Each receives $\lfloor C/6 \rfloor$ channels, with the remainder assigned to the earlier branches in concatenation order. Symmetric padding preserves spatial dimensions.

Direction-sensitive feature modulation uses

$$\begin{aligned} \mathbf{T}_h &= \sigma(\phi_h(\mathrm{Avg}_H(\mathbf{A}))), \\ \mathbf{T}_v &= \sigma(\phi_v(\mathrm{Avg}_W(\mathbf{A}))), \\ [a_h, a_v] &= \mathrm{Softmax}(\phi_d(\mathrm{GAP}(\mathbf{A}))). \end{aligned} \tag{A.3}$$

The maps have shapes $C \times 1 \times W_g$ and $C \times H_g \times 1$ and are broadcast over the missing spatial dimension. Each of ϕ_h, ϕ_v consists of pointwise projections $C \to \max(\lfloor C/4 \rfloor, 32) \to C$, with SiLU between them. The mapping ϕ_d is a pointwise projection from C to two outputs.

The resulting maps enter Eq. 6. Because $a_h + a_v = 1$ and the attention maps lie in $(0, 1)$, $|\mathbf{A}_d| \le |\mathbf{A}|$ element-wise before residual projection. This property does not bound the entire residual block.

After N_b stages, spatial recalibration predicts

$$[\mathbf{S}_1, \mathbf{S}_2] = \mathrm{Softmax}(\psi_s(\mathbf{F}_r)). \tag{A.4}$$

The mapping ψ_s applies a depthwise 3×3 convolution, a pointwise projection to $C/4$ channels, eight-group normalization, SiLU, and a two-output pointwise projection. The channel mapping ψ_c in Eq. 7 uses pointwise projections $C \to C/4 \to C$ with SiLU.

All spatial and channel gates are broadcast over the corresponding dimensions when multiplied with features. The final head computes

$$\mathbf{Z} = \mathrm{Conv}^{\mathrm{cls}}_{1\times1}(\mathrm{Dropout2D}(\mathbf{F}_d)), \mathbf{P} = \sigma(\mathbf{Z}). \tag{A.5}$$

Independent sigmoid probabilities permit multiple positive categories per training cell. Inference retains only the highest-scoring category.

B. Spectral Masks and Correction Bound

B.1. Frequency Coordinates and Masks

The orthonormal real Fourier transform stores $\mathbf{X} = \mathcal{F}_r(\mathbf{F}_g)$ with $W_f = \lfloor W_g/2 \rfloor + 1$ columns. Indices satisfy $0 \le \xi < H_g$ and $0 \le \eta < W_f$. Mask coordinates follow the implementation:

$$\begin{aligned} f_h(\xi) = \frac{\tilde{\xi}}{H_g}, f_w(\eta) &= \frac{\eta}{2W_f - 1}, \\ \tilde{\xi} &= \begin{cases} \xi, & \xi \le \lfloor H_g/2 \rfloor, \\ \xi - H_g, & \text{otherwise.} \end{cases} \end{aligned} \tag{B.1}$$

These coordinates construct masks and do not redefine the Fourier transform frequencies. In particular, the width denominator is $W_g + 1$ for even W_g and W_g for odd W_g. Writing $q(\xi, \eta) = \sqrt{f_h(\xi)^2 + f_w(\eta)^2}$ gives

$$\begin{aligned} r(\xi, \eta) &= \frac{q(\xi, \eta)}{\max_{\xi',\eta'} q(\xi', \eta') + \epsilon}, \\ M_k &= \mathbb{1}\left[\frac{k-1}{4} \le r < \frac{k}{4}\right]. \end{aligned} \tag{B.2}$$

The four radial intervals are equally spaced and disjoint. All maxima cover retained frequency bins, and $\epsilon = 10^{-8}$. The band predictor ϕ_b uses pointwise projections $C \to \max(\lfloor C/4 \rfloor, 16) \to 4$ with SiLU. Softmax makes the weights positive and sum to one, hence $0 \le M_b \le 1$.

When frequency-axis modulation is enabled, its mask is

$$\begin{aligned} [a_h^f, a_v^f] &= \mathrm{Softmax}([\theta_h, \theta_v]), \\ D(\xi, \eta) &= a_h^f |f_h(\xi)| + a_v^f |f_w(\eta)|, \\ M_d(\xi, \eta) &= \frac{D(\xi, \eta)}{\max_{\xi',\eta'} D(\xi', \eta') + \epsilon}. \end{aligned} \tag{B.3}$$

The learned scalars θ_h, θ_v are initialized to 0.5 and shared across inputs and channels. The configuration flag χ_f in Eq. 3 enables or disables this term. The spectral scale λ_f is unconstrained and initialized to 0.1. The fusion mapping ϕ_g uses pointwise projections $2C \to \max(\lfloor C/4 \rfloor, 16) \to 1$ with SiLU. Its sigmoid output is a spatial gate shared across channels. The real gain preserves a nonzero coefficient's phase wherever $1 + \lambda_f M_f > 0$.

The implementation evaluates the orthonormal transform using real cosine and sine matrices, including the conjugate-frequency multiplicities required by the inverse transform.

B.2. Bound on the Spectral Correction

Let $\mathcal{F}$ denote the orthonormal full complex Fourier transform, and let $\widehat{M}_f$ be the conjugate-symmetric extension of M_f. The radial and absolute-axis masks preserve the required symmetry. The reconstruction residual is

$$\mathbf{R} = \mathbf{F}_f - \mathbf{F}_g = \lambda_f \mathcal{F}^{-1}(\widehat{M}_f \odot \mathcal{F}(\mathbf{F}_g)). \tag{B.4}$$

Parseval's identity and $\|\widehat{M}_f\|_\infty \le 1 + \chi_f$ imply

$$\begin{aligned} \|\mathbf{R}\|_F &= |\lambda_f| \, \|\widehat{M}_f \odot \mathcal{F}(\mathbf{F}_g)\|_F \\ &\le (1 + \chi_f)|\lambda_f| \, \|\mathbf{F}_g\|_F. \end{aligned} \tag{B.5}$$

Since every gate value lies in $(0, 1)$,

$$\|\mathbf{F}_e - \mathbf{F}_g\|_F = \|\mathbf{G}_f \odot \mathbf{R}\|_F \le \|\mathbf{R}\|_F \le 2|\lambda_f| \, \|\mathbf{F}_g\|_F. \tag{B.6}$$

Disabling axis modulation gives the tighter factor $|\lambda_f|$. The argument uses the full spectrum, avoiding an unweighted half-spectrum interpretation of Parseval's identity. This is a per-input correction bound rather than a bound on sensitivity to input perturbations.

C. Grid Supervision

C.1. Grid Target Construction

Grid regions are stored separately from detection boxes and undergo the same geometric transformations as the image. Each transformed region has a grid category c and normalized coordinates (c_x, c_y, w, h). Starting from $\mathbf{Y} = \mathbf{0}$, project nine points:

$$\begin{aligned} v &= \lfloor (c_x + d_x \delta_g w) W_g \rfloor, \\ u &= \lfloor (c_y + d_y \delta_g h) H_g \rfloor, \end{aligned} \qquad d_x, d_y \in \{-1, 0, 1\}, \tag{C.1}$$

where $\delta_g = 0.125$. Valid indices set $Y_c(u, v) = 1$, and repeated projections are merged. The implementation casts projected coordinates to integers, which agrees with the floor expression for nonnegative projected positions. Out-of-range indices are ignored. Categories remain independent, and fully annotated images without positive regions retain all-negative targets. Fig. 6 illustrates this construction and the subsequent weighting procedure.




Figure 6. Grid target construction and adaptive importance reweighting. (a) Nine-point projection converts transformed grid annotations into binary category-wise targets. (b) Prediction uncertainty and target transitions determine detached weights for focal supervision over all grid entries.

C.2. Loss Formulation and Gradient Properties

For probability p and binary target y, binary focal loss is

$$\begin{aligned} p_t &= yp + (1 - y)(1 - p), \\ \alpha_t &= y\alpha_f + (1 - y)(1 - \alpha_f), \\ \ell_{\text{focal}}(p, y) &= -\alpha_t (1 - p_t)^{\gamma_f} \log p_t. \end{aligned} \tag{C.2}$$

We use $\alpha_f = 0.5$, $\gamma_f = 1.5$, $\lambda_u = \lambda_t = 1$, and $k_t = 3$. Logits are clipped to $[-20, 20]$ before training probabilities and focal weights are computed. Numerically, the logarithmic term is evaluated using binary cross-entropy with logits, multiplied by the focal and class factors.

Dilation and erosion operate independently on each category using $k_t \times k_t$ neighborhoods, unit stride, and valid locations at image borders. Thus, $U_j \in [0, 1]$ and $T_j \in \{0, 1\}$. The implementation also clips importance weights to $[1, 10]$, which is inactive under the stated coefficients because $1 \le W_j \le 3$. Let $N = \max(1, N_+)$ and define

$$\mathcal{L}_0 = \frac{1}{N} \sum_j \ell_{\text{focal}}(P_j, Y_j). \tag{C.3}$$

Nonnegative focal losses yield

$$\mathcal{L}_0 \le \mathcal{L}_{\text{grid}} \le 3\mathcal{L}_0. \tag{C.4}$$

Because the weights are detached and N depends only on targets,

$$\frac{\partial \mathcal{L}_{\text{grid}}}{\partial \bar{Z}_j} = \frac{W_j}{N} \frac{\partial \ell_{\text{focal}}(P_j, Y_j)}{\partial \bar{Z}_j} = W_j \frac{\partial \mathcal{L}_0}{\partial \bar{Z}_j}. \tag{C.5}$$

The resulting sign preservation applies to individual clipped logits. For raw logits, the chain rule additionally includes the clipping derivative, which is zero outside the clipping interval. The property does not imply that the full parameter gradient retains its direction or that optimization is guaranteed to converge. Every category-cell entry remains in the loss, and setting $\lambda_u = \lambda_t = 0$ recovers $\mathcal{L}_0$.

D. Detailed Inference Procedure

D.1. Decoding and Category Alignment

Let $\mathbf{I}_0 \in \mathbb{R}^{3\times H_0 \times W_0}$ be the original image, and let $\mathcal{T}$ denote input preprocessing. The detector's original postprocessor decodes its configured query outputs and restores boxes to original-image coordinates. Category maps κ_d and κ_g map detection labels and grid channels to the same semantic category space. The decoded set $\mathcal{D}_0$ is retained for box average precision. Association uses the subset with scores strictly greater than τ_d.

Grid probabilities are computed as $\mathbf{P} = \sigma(\mathbf{Z})$. Each cell selects the highest-scoring category over all output channels, with ties resolved by the smallest channel index. The grid threshold uses $s^g \geq \tau_g$ on RoadDistress2026, Crack500, and DeepCrack. Under direct resizing, cell (u, v) maps to

$$\mathbf{b}^g_{uv} = \left[\frac{vW_0}{W_g}, \frac{uH_0}{H_g}, \frac{(v+1)W_0}{W_g}, \frac{(u+1)H_0}{H_g} \right]. \tag{D.1}$$

Indices are zero-based. For other supported preprocessing, the corresponding inverse geometric mapping replaces Eq. D.1.

D.2. Association and Complete Algorithm

For $\mathbf{b} = [x_1, y_1, x_2, y_2]$, two boxes have positive intersection area if both intersection side lengths are positive. Boundary touching alone does not qualify. This is equivalent to the original rule $\text{IoA}(g, d) > 0$, where $\text{IoA}(g, d) = |\mathbf{b}^g \cap \mathbf{b}^d| / (|\mathbf{b}^g| + \epsilon)$. No grid-cell expansion or positive overlap-ratio threshold is used.

Algorithm 1 specifies decoding and association for direct resizing. Grid-only mode returns unassociated predictions from the grid branch. Association never substitutes a lower-scoring category when the highest-scoring one has no matching detection. It preserves detection outputs and all retained grid scores. If there are no accepted detections, joint mode returns an empty grid set, whereas grid-only mode remains independent of detections. Box average precision is computed from $\mathcal{D}_0$ before the association confidence cutoff.

Algorithm 1 Class-Aware Box–Grid Association

Input: Original image $\mathbf{I}_0$; preprocessing $\mathcal{T}$; model $\mathcal{M}$; thresholds τ_d, τ_g; category maps κ_d, κ_g; inference mode m.
Output: Detections $\mathcal{D}$ and grid output $\mathcal{G}_{\text{out}}$.

$\mathbf{I} \leftarrow \mathcal{T}(\mathbf{I}_0)$.
$(\mathcal{D}_{\text{raw}}, \mathbf{Z}) \leftarrow \mathcal{M}(\mathbf{I})$.
$\mathcal{D}_0 \leftarrow \text{Decode}(\mathcal{D}_{\text{raw}}, \mathcal{T}^{-1}, \kappa_d)$.
$\mathcal{D} \leftarrow \{d \in \mathcal{D}_0 \mid s^d > \tau_d\}$.
Set $\mathbf{P} \leftarrow \sigma(\mathbf{Z})$ and $\mathcal{G} \leftarrow \varnothing$.
for $u = 0, \ldots, H_g - 1$ **do**
  for $v = 0, \ldots, W_g - 1$ **do**
    $c \leftarrow \min \arg\max_j P_j(u, v)$.
    $s \leftarrow P_c(u, v)$.
    if $s \geq \tau_g$ **then**
      Compute $\mathbf{b}^g$ using Eq. (D.1).
      $g \leftarrow (\mathbf{b}^g, s, \kappa_g(c))$.
      $\mathcal{G} \leftarrow \mathcal{G} \cup \{g\}$.
    end if
  end for
end for
if $m =$ grid-only **then**
  return $\mathcal{D}, \mathcal{G}$.
end if
Initialize $\mathcal{G}^* \leftarrow \varnothing$.
for each grid candidate $g \in \mathcal{G}$ **do**
  for each detection $d \in \mathcal{D}$ with $\hat{c}^d = \hat{c}^g$ **do**
    $\Delta_x \leftarrow \min(x_2^g, x_2^d) - \max(x_1^g, x_1^d)$.
    $\Delta_y \leftarrow \min(y_2^g, y_2^d) - \max(y_1^g, y_1^d)$.
    if $\Delta_x > 0$ and $\Delta_y > 0$ **then**
      $\mathcal{G}^* \leftarrow \mathcal{G}^* \cup \{g\}$.
      break.
    end if
  end for
end for
return $\mathcal{D}, \mathcal{G}^*$.

E. Experiments

We test whether FDAM improves grid localization for tinier crack instances on RoadDistress2026 and thinner crack components on Crack500 and DeepCrack. This *thin* describes narrow width in image coordinates, while *tiny* describes limited instance extent. Stratified recall identifies missed positive grid cells within each group. Overall precision and F1 check whether higher recall comes at the cost of additional false positives. A qualitative comparison further illustrates the complementary box and grid representations.

E.1. Annotation-Defined Stratification

RoadDistress2026 uses annotated boxes because verified masks are unavailable. For a box of size $w \times h$ in an image of size $W \times H$, we define its relative extent as

$$e = \max\left(\frac{w}{W}, \frac{h}{H}\right). \tag{E.1}$$

This measures instance extent rather than crack width. For Crack500 and DeepCrack, we extract 8-connected components with at least three pixels from the original ground-truth masks. For component C, its relative width proxy is

$$r(C) = \frac{\mathrm{median}_{p \in \mathrm{Skel}(C)}\, 2\,\mathrm{EDT}_C(p)}{\min(H, W)}, \tag{E.2}$$

where Skel denotes skeletonization and EDT_C is the Euclidean distance to background. Masks are neither resized nor dilated before measurement. This digital proxy has discretization bias: a one-pixel-wide strip has a proxy width of two pixels. It does not measure physical width.

For each dataset, we estimate two boundaries from training annotations alone, using percentiles at $33\frac{1}{3}\%$ and $66\frac{2}{3}\%$. These boundaries, q_1 and q_2, remain fixed for test evaluation. Values $x \le q_1$, $q_1 < x \le q_2$, and $x > q_2$ define the lower, middle, and upper groups, respectively. We call them Tiny, Medium, and Large for instance extent, and Thin, Medium, and Thick for the width proxy.

Equal measurements remain in the same group, so group sizes may differ. Specifically, $r(C) \le q_1^r$ defines the thin group on each public dataset, while $e \le q_1^e$ defines the tiny group on RoadDistress2026 used to examine performance on tiny crack instances. The superscripts indicate the measurement, and the boundaries are estimated independently for each dataset. These relative groups operationalize width and extent for this analysis. They imply neither universal size thresholds nor a correspondence to physical crack width. RoadDistress2026 boxes support extent analysis only and cannot establish whether a crack is physically thin.

E.2. Evaluation Protocol

We retain the existing project splits, checkpoints, and fixed inference settings. The test sets contain 1,300 RoadDistress2026, 1,124 Crack500, and 109 DeepCrack images. RoadDistress2026 uses direct resizing to 1024×1024 and a 32×32 grid. FDAM uses a grid threshold of $\tau_g = 0.5$ on RoadDistress2026 and $\tau_g = 0.45$ on the public datasets. GCBD uses $\tau_g = 0.35$ for unassociated grids and $\tau_g = 0.15$ for associated output. Both detection methods use $\tau_d = 0.30$. Grid scores satisfy $s_g \ge \tau_g$, whereas detection scores satisfy $s_d > \tau_d$. Association requires positive overlap with a same-category box. On Crack500, the pixel thresholds are 0.25 for SCSegamba and 0.35 for MixerCSeg. Both use 0.05 on DeepCrack. Segmentation probabilities are bilinearly resized to 640×640 and thresholded. At least 1% foreground occupancy marks a cell positive in the 20×20 grid. These comparisons therefore include conversion and operating-point differences. We report the recomputed outputs at these fixed settings.

Grid-group membership is assigned to source annotation regions before the original nine-point target projection. Mixed or unresolved cells, including those involving excluded small components, are omitted only from stratified recall. They remain in overall metrics. The assigned proportions of positive category-cell entries are 99.70%, 98.04%, and 98.19%, respectively. Within each group, recall is the fraction of ground-truth positive category-cell entries correctly predicted as positive. RoadDistress2026 averages recall over longitudinal and transverse crack categories. Public-dataset recall concerns the single crack class. Overall RoadDistress2026 scores also average these two categories. Overall precision and F1 include background false positives without averaging the background class. Box recall uses confidence-ordered, same-category matching at $\mathrm{IoU} \ge 0.50$ before grouping ground-truth instances. It measures recall at a fixed threshold, not AP.

E.3. Stratified Results

On RoadDistress2026, associated FDAM exceeds GCBD's separately selected grid output by 5.17 percentage points in small-extent grid recall. Fig. 7 additionally shows small-extent box recall of 43.40% versus 3.77%. These results concern instance extent, not actual crack width. However, association reduces FDAM's overall grid F1 from 64.53% to 64.24% and small-extent grid recall from 46.97% to 44.50%.

FDAM preserves more positive grid responses in the relative Thin groups of both public datasets. As shown in Fig. 8, its gains over SCSegamba are 11.45 percentage points on Crack500 and 15.61 on DeepCrack. These point-estimate gains exceed those in the medium and thick groups. Overall foreground F1 is also higher, although DeepCrack precision is lower than SCSegamba's. These observations do not establish statistical significance or attribute the gains to individual modules.

E.4. Qualitative Comparison

Fig. 9 compares GCBD and FDAM on a transverse-crack example from RoadDistress2026. Box predictions describe the overall instance extent, while grid predictions represent local crack occupancy. The enlarged grid views expose differences in cell coverage that are difficult to inspect in the full images. This example illustrates the complementary spatial representations used for pavement crack grid localization. Stratified quantitative results are reported in Table 7, and broader dataset-wide comparisons are provided

Table 7. Grid recall within each annotation-defined group and overall grid performance, in percent. RoadDistress2026 groups reflect instance extent, whereas public-dataset groups reflect relative mask width. GCBD (grid) uses unassociated predictions. GCBD (box–grid) and all FDAM results use class-aware box–grid association. The grid thresholds for these output modes are fixed separately as specified in Sec. E.2. Best and second-best metric values are **bold** and underlined, respectively. Rankings are computed separately within each dataset.

	Recall within each group			Overall grid performance		
RoadDistress2026						
Method	Tiny	Medium	Large	Precision	Recall	F1
GCBD (grid)	39.32	58.07	61.47	48.77	58.61	52.95
GCBD (box–grid)	6.53	23.24	31.93	44.33	26.67	32.96
FDAM (Ours)	**44.50**	**60.90**	**72.25**	**61.28**	**67.51**	**64.24**
Crack500						
Method	Thin	Medium	Thick	Precision	Recall	F1
SCSegamba	73.72	84.44	86.03	83.51	83.84	83.67
MixerCSeg	72.71	84.79	85.69	82.31	83.59	82.95
FDAM (Ours)	**85.17**	**88.16**	**88.28**	**84.89**	**87.84**	**86.34**
DeepCrack						
Method	Thin	Medium	Thick	Precision	Recall	F1
SCSegamba	70.84	81.01	83.29	**91.83**	80.50	85.79
MixerCSeg	67.67	80.53	84.91	84.61	80.64	82.58
FDAM (Ours)	**86.45**	**88.43**	**90.64**	89.35	**89.43**	**89.39**




Figure 7. RoadDistress2026 box recall across relative instance extents at score > 0.30 and IoU ≥ 0.50. N counts annotated instances within each group. Error bars denote 95% image-bootstrap intervals.

in the main paper.




Figure 8. Grid recall across annotation-defined strata. RoadDistress2026 uses relative instance extent, whereas Crack500 and DeepCrack use the ground-truth mask width proxy. The protocols are specified in Sec. E.2. N counts positive category-cell entries within each group. Error bars denote 95% image-bootstrap intervals.




Figure 9. Qualitative comparison of pavement crack grid localization on RoadDistress2026. Rows show GT, GCBD predictions, and FDAM predictions. Columns show box labels or predictions, grid labels or predictions, and enlarged views of the grid results. Magenta denotes transverse cracks (TC). The enlarged views facilitate inspection of local crack occupancy.