# Constructing a ROCKS Cluster

Ryan Wojtyla

February 24, 2019

# 1 Preparation

Preparation is key before attempting to build a ROCKS cluster; there are many steps to take care of beforehand.

### 1.1 Backup Data

One of the most important preliminary steps is to first backup all the data on the devices that are being updated. I backed up the contents of the CE, minus /mnt and /cvmfs, the SE, and both the server and data partitions of NAS-0 onto NAS-1. For the CE and SE, /mnt was excluded because I don't want to backup both of the NASs' data onto NAS-1. /cvmfs was excluded for the CE because it is externally mounted from CERN, thus eliminating the need for a local backup. Unlike the CE and SE, NAS-0 does not have NAS-1 mounted, so the rsync command had to remotely copy the NAS-0 files from the CE. Since there is already an older backup of NAS-0 on NAS-1 and there is not enough space on NAS-1 to fully copy another backup of NAS-0, all of the newer files on NAS-0 were manually copied into the old backup of NAS-0, effectively updating it.

- Backup the CE (command run while logged into the CE):
  - rsync -av --exclude '/mnt\*' --exclude '/cvmfs' / /mnt/nas1/CEBackup-20180
- Backup the SE (command run while logged into the SE):
  - rsync -av --exclude '/mnt' / /mnt/nas1/SEBackup-20180803

- Backup the server partition of NAS-0 (command run while logged into the CE):
  - rsync -av --exclude '/nas0' root@10.1.255.234:/ /mnt/nas1/nas0-bak-201807

Ideally, the entirety of one compute node would also be backed up at this point, but due to catastrophic hardware failures preventing the nodes from being run (one of the big Tripplite UPSs AND the APC UPS have failed, leaving me with only one UPS), I'm going to come back to them later.

### 1.2 Create Boot Drives

Once all of the data is secure, the ISO images of the ROCKS rolls can be downloaded and installed. The necessary ROCKS rolls, available here, are:

- kernel
- base
- core
- CentOS
- Updates-CentOS
- ganglia
- htcondor

These ISO images may be directly placed on a formated USB using the dd command. The computer-given name of the USB drive of the form /dev/sd? (/dev/disk? on MacOS) must be determined. On Linux, the lsblk command may be used to discover this proper name. On Mac, the "Disk Utility" application may be used.

To create the bootable USB, the dd command may be used. The USB must be first unmounted, sudo umount /dev/sd?, then the following command may be run: sudo dd bs=4M if=INPUT-FILE.iso of=/dev/sd? conv=fdatasync (for MacOS: sudo dd bs=4m if=INPUT-FILE.iso of=/dev/disk? && sync). The bs option determines the block size of each packet transferred at a time, the input file is the ISO file of the image to be copied,

and the output file is the name of the USB to be made bootable. Both the conv=fdatasync and && sync parts of the commands ensure that all data has been written before the next packet is sent.

Since coming across eight USBs may be a challenge, the USBs will be created as they are needed. The first USB to be made is the one containing the "kernel" roll.

Actually, the firmware doesn't support booting from USB, so I need to go get DVDs because CDs are too small.

All the rolls were burnt onto separate DVDs except for the large "CentOS" roll, which is more than 7GB, larger than the 4.7GB discs.

### 1.3 Ensure NAS-1 Remains Operational

Because NAS-1 does not need to be updated, and since everyone needs to access their data on it, it must be kept running and accessible during the rebuild process. Since NAS-1 has never technically been part of the cluster with ROCKS, it is independently addressable via its own IP address. This independent addressability permits NAS-1 to be mounted and ssh-ed into without the rest of the cluster. It just needs to be left on and connected to the router.

# 2 Installation

### 2.1 Kernel Installation

The instructions say to first use the "kernel" disc. The CE was turned on so that the optical drive has power to open, the disc was quickly inserted, and the CE was allowed to continue booting. It automatically booted into the disc, and it applies checks before continuing.

Once it has finished booting, the system language must be selected. After that, regional information, such as timezone, is entered.

# 2.2 Network Configuration

Select Network & Host Name.

Now, the network must be configured. The option for the 10GB/s ethernet connection is turned on.

Next, the "Configure..." button is selected. Under the "IPv4 Settings" tab, the "Method" is set to *Manual*, and the IP of the CE, 163.118.42.1, is entered. The netmask, an arbitrary range of IPs for the network, is set to 25 in order to encompass the IP range 163.118.42.1-163.118.42.127. The gateway is the IP address of the router through which the computer is connected to the network. It was found by ssh-ing into NAS-1 and running ip route, which displays the default gateway IP, 163.118.42.126, and the IP of NAS-1, itself. Provide a DNS server of 8.8.8.8 so that the cluster will recognize its hostname and allow the internet to work. Under the "IPv6 Settings" tab, the "Method" is set to *Link-Local Only*.

With this information entered, the *Save* button is pressed. The ethernet connection may be switched on as before, and the "Current host name" in the bottom right of the screen should read "uscms1.fltech-grid3.fit.edu", the cluster's hostname. If it reads something else, enter the correct hostname on the bottom left of the screen. Once everything here is completed, *Done* may be selected.

With network configuration out of the way, all the previously grayed-out options are now full of color! Now the local network needs to be configured. Select *Cluster Private Network*.

The "Private Cluster Interface" dropdown menu is a list of the ethernet ports, similar to the list for selecting the public network connection. Since the 10GB/s connection is used for the public connection, the normal ethernet port, usually of the form enp6s0f0, is used for the private connection. Refer back to the "Network & Hostname" section to see which port is occupied, and select that one in the "Private Cluster Interface" dropdown menu. All the other fields should not need to be altered; the default settings are fine and expected.

### 2.3 Rolls

Now the rolls can be installed! Select "ROCKS ROLLS". Here, rolls may be installed remotely from the ROCKS website. Select *List Available Rolls* to generate the roll list. Select the following rolls:

- base
- CentOS
- core

- ganglia
- htcondor
- kernel
- perl
- python
- Updates-CentOS-<version>

Once all the desired rolls are selected, select Add Selected Rolls. After the rolls appear in the "Selected Rolls" section, select Done.

If no network rolls can be found, change "Network Roll" to "CD/DVD" Roll, and just install the "kernel" roll. The other rolls may be installed later.

### 2.4 Cluster Configuration

Select  $CLUSTER\ CONFIG$  to configure the cluster. The fields are filled as follows:

Cluster Name	USCMS-FIT-Grid
Contact	<administrator email=""></administrator>
Project URL	https://research.fit.edu/hep/hohlmann-research-group/grid-
Latitude/Longitude	N28.0622 W80.6237
Certificate Organization	Florida Institute of Technology
Certificate Locality	Melbourne
Certificate State	Florida
Certificate Country	US
NTP Servers	pool.ntp.org

After the fields have been verified to be correct, select *Done*.

# 2.5 Partitioning

Now the CE must be partitioned. Select *INSTALLATION DESTINA-TION*. Select the larger of the two drives (the smaller one is the hot spare and it is NOT TO BE TOUCHED), and select *I will configure partitioning*.

under "Other Storage Options". Select *Done* to be kicked over to Anaconda's partitioning system.

First, the old partition, the CentOS 6 one, was selected, then removed by selecting the "-" at the bottom of the window and checking the box for deleting all file systems. Then the *Click here to create them automatically* option was selected.

The created /home partition was renamed to /export, because NAS-0 is what holds our home directories, and it was given 100 GiB. The default /boot and swap partitions were left untouched, the /var partition was created and given 100 GiB, and the / partition was allocated the remainder of the available space, 256.76 GiB.

Once everything is together, select *Done* and carefully review the changes. If the changes are correct, select *Accept Changes*.

### 2.6 Commit

If everything is undoubtedly confirmed (to the best of your ability), and you're absolutely ready to destroy everything and build it back up, say a quick prayer to your deity of choice and select *Begin Installation*. WARNING: there is no "confirm" to *Begin Installation* 

Create a root password when prompted, and do NOT setup a user.

After the installation is complete, reboot as per the instructions. After reboot do not enter any further configuration; simply continue. When presented with the login prompt, login as root. Congratulations! ROCKS has been installed onto the CE!

### 3 Unification

Now that ROCKS is installed onto the CE, it can be installed onto the other cluster components so that they may be brought into the fold.

#### 3.1 Nodes

To begin, login to the CE as root and run insert-ethers, the program that routes network traffic from the nodes to the ROCKS database for processing. From the menu, select *Compute*. The "Inserted Applicances" screen

that appears should initially be blank; nodes must be turned on for them to be recognized and configured.

Insert the ROCKS Kernel disc into the first node, compute-1-0, and restart it. compute-1-0 should appear in the "Inserted Applicances" menu. The () in the rightmost column will be blank for now. A star, \*, will appear between them when the node requests a kickstart file from the CE. The node will boot into the Anaconda installation for ROCKS 7.

#### 3.1.1 Installing ROCKS onto a Compute Node

The CE hosts a kickstart file that the nodes use to configure their installation. In order to fetch this file on startup, the nodes must be configured for PXE network booting. This is achieved by ensuring PXE is at the top of the boot order in the BIOS.

NOTE: If the CE is on while this is being completed, when the nodes restart, they will immediately grab the kickstart file from the CE regardless if insert-ethers is running or not. If this is undesired behavior, shutdown the CE before configuring the nodes.

To enter a node's BIOS, spam the DELETE key on start up until "Entering SETUP" is displayed. To modify the boot order, navigate to the "Boot" tab and follow the on screen directions to place PCI BEV: IBA GE Slot 0400 v1236 (the ethernet port connected to the router; ethernet device enp4s0f0) in slot 1. Slot 2 should be the CD drive, IDE CD, and slot 3 should be the regular hard drive, PCI SCSI. The remaining boot options can be excluded. Once these changes have been made, Save and Exit.

Now that the boot order of all the nodes has been corrected, we're going to reinstall ROCKS onto the CE.

# 4 Configuration

### 4.1 Enable SSH

ssh communication with the cluster is paramount in its efficient administration. Upon initial installation, the sshd service ought to already be running. This can be verified with service sshd status. If it's not running, it can easily set up after a quick internet search.

### 4.2 Automatic Mounting of Key Components

# 5 Troubleshooting

### 5.1 Boot Loader Install Failed

During installation, the boot loader failed to install. Selecting *no* on the dialogue box will present an "unknown error" screen with a log and a debug option. Selecting "debug" kicks the screen over to the terminal screen.

Navigating to the "program-log" tab, the following errors may be found after the installer attempted to run grub2-install --no-floppy /dev/sda:

- grub2-install: warning: Attempting to install GRUB to a disk with multiple partition labels. This is not supported yet...
- grub2-install: error: embedding is not possible, but this is required for cross-disk install.

The decision to try to install to /dev/sda is strange because according to fdisk -l /dev/sda and fdisk -l /dev/sdb, run in the "shell" tab, reveal that /dev/sdb1 is marked for boot, whereas no such marking is present in the single part of /dev/sda.

Trying to run grub2-install --no-floppy /dev/sda and grub2-install --no-floppy /dev/sdb produces the same result: grub2-install: error: /usr/lib/grub/i386-pc/modinfo.sh doesn't exist. Please specify --target or --directory. Investigating that path, /usr/lib/grub comes up empty. To find where that file is actually located, since it has to be somewhere if the installer is running that command, I ran find / -name modinfo.sh. It appears in two places: /mnt/sysimage/boot/grub2/i386-pc/modinfo.sh and /mnt/sysimage/usr/lib/grub/i386-pc/modinfo.sh.

I'm trying to run the installer's command again while specifying the location of the file it needs: grub2-install --no-floppy --directory='/mnt/sysimage/boot/grub2/dev/sda. Now it says: grub2-install: error: cannot open '/mnt/sysimage/boot/grub2/No such file or directory.. Hmm, let's see if that file exists anywhere with: find / -name kernel.img. Ahh, it's at /mnt/sysimage/usr/lib/grub/i386-pc/kernel.it's run the installer's command again, but the directory will be changed to /mnt/sysimage/usr/lib/grub/i386-pc: grub2-install --no-floppy --directory='/mnt/sysimage/usr/lib/grub/i386-pc' /dev/sda. Ah ha!

Now I'm getting the same error as the installer! Let's try with /dev/sdb:

grub2-install --no-floppy --directory='/mnt/sysimage/usr/lib/grub/i386-pc/dev/sdb. Ohh! Installation finished. No error reported.!

Since the installer crashed, the CE needs to be rebooted. Be sure to swiftly eject the disc when it first begins to power on so that it tries to boot normally. It will boot to grub rescue mode because, while grub is installed, it is not configured correctly.

Running the ls command in grub rescue will show that there are two drives, (hd0) and (hd1), and set will reveal that it is trying to boot into (hd0). Running ls (hd0) will show that its file system is unknown, while ls (hd1) shows a recognizable one, such as ext2. The file system of (hd0) is unknown because it is the hot spare for the RAID; grub is trying to boot into the hot spare, just as it was trying to do during installation.

The set command said that the variable prefix was set to (hd0)/boot/grub2 and root was set to hd0. To point those at the right place I ran the following two commands:

- set prefix=(hd1)/boot/grub2
- set root=hd1

Instructions online say after fixing the variables to try loading the normal module with insmod normal, but I get the error, error: file '/boot/grub2/i386-pc/normal.r not found. Running ls (hd1)/ shows me nothing! Does that mean there's nothing on the drive I need, or just that the information isn't quite accessible? Hmm. I guess a restart couldn't hurt more; let's try that now that the variables are set.

Actually, you know what, I think I discovered the mistake that caused this whole mess. I decided to check to box to include the hot spare in the installation process. It has no place here; it's managed strictly by the RAID card. It got assigned sda and messed everything up. I'm just gonna turn all this off and redo the installation correctly this time.

### 5.2 Remote ROCKS Servers Inaccessible

Normally, the ROCKS rolls are able to be accessed from the remote ROCKS server in the "ROCKS ROLLS" section of the installation. After the kerfuffle with the boot loader, however, the server seems to be inaccessible even though the CE has internet, verified by pinging through the console. I'm going to use the ability of the installer to remotely obtain the rolls to see if the issue is just with the communicating with the server, or if it's a larger problem. I've placed all the required rolls on NAS-1, and I'm going to try accessing them from there.

To do that, the rolls need to be hosted on an HTTP server on NAS-1. I'm installing and setting up Apache.

When I tried to yum install httpd, none of the mirrors worked, so the installation failed. I tried a yum update and a yum clean all, but the clean just confirmed that there was a serious problem. Now yum reports that mirrors.centos.org cannot be resolved. yum repolist all also runs into the same issue; only the 5 recommended steps are listed.

Turns out /etc/resolv.conf was blank, and, amazingly, adding nameserver 9.9.9.9 to it fixed the problem. I wonder if that same file is messed up in the installer.

On the installer, by changing the kernel parameters from "quiet" to "verbose", or even "debug", the booting up of the GUI installer can be seen and interrupted, providing access to the shell. ifconfig shows the four network ports and the local network, just as it should, but nothing is connected to the internet. The cables are plugged in, so let's see about enabling the internet.

The Arch Linux wiki page for network configuration is very detailed and it seems to be helpful. I'm going through it.

I've gone through the page, setting the ip manually and editing /etc/hosts, but no luck. I'm going to try the /etc/resolv.conf thing that worked on NAS-1.

The ROCKS installation CD on the CE suddenly has internet! The IP is 163.118.42.1/25, the broadcast IP is 163.118.42.127, and the gateway IP is 163.118.42.126 (ip address add 163.118.42.1/25 broadcast + dev enp10s0f0). A route was added: ip route add default via 163.118.42.126 dev enp10s0f0. A nameserver was added to /etc/resolv.conf, nameserver 9.9.9.9. The installer can be restarted with anaconda.

Now the manual installation via anaconda's CLI can begin.

	ROCKS Rolls GUI	/usr/share/anaconda/addo
The locations of several important lines of code:	GUI Function	/usr/share/anaconda/addo
	Actual Function	/opt/rocks/lib/

It is difficult to test the individual lines and functions because of so many references to "self" in the code, which indicates an incredible reliance on being in a special running environment to operate properly.

I'm trying something new. I'm installing ROCKS onto a flash drive on another machine, then I'm going to dd the flash drive image onto the hard drive in the cluster. Maybe that will work.

Make sure the USB is COMPLETELY blank (parted /dev/sd<x> mklabel loop).

To get to the anaconda command line application:

- load the Anaconda GUI like normal
- Ctl-Alt-F2 to drop to the base terminal of the CD
- try to run anaconda
- when X fails to load properly, select the VNC option
- Although Anaconda will continue to not start up properly, the Anaconda environment (with the tmux bar at the bottom) will load.

Just to try something new, I loaded a ubuntu liveCD onto the CE and had a poke around. It looks like everything is where it used to be on the partitions of the original drive, /dev/sdb2, specifically the /root partition. A curious note about how those partitions are organized: /dev/sdb2 is formated as a Linux logical volume, and the logical partitions of that logical volume are found under /dev/rocks\_uscms1/. /dev/rocks\_uscms1/root is the original root file system, and I mounted it with mount /dev/rocks\_uscms1/root/mnt/sdb\_root. Something interesting I found, though, is the contents of /mnt/sdb\_root/etc/redhat-release, which report that CentOS 7 is installed on the system. Hmm. Did the original install do something? Additionally, the /mnt/sdb\_root/boot directory is blank. While THAT boot directory is blank, however, the specific boot partition of /dev/sdb, /dev/sdb1, is fully populated with an el7 image and an updated grub.

To enable ssh on a Ubuntu LiveCD, install openssh-server with sudo apt install openssh-server, and check to make sure the service is running with sudo service ssh status.

BREAK-THROUGH! After fiddling with GRUB from the LiveCD, namely reinstalling it onto the boot partition, the CE still refused to boot! This is because the 3Ware card was not configured to be booted into on the boot order section of the BIOS. This page is accessed by slamming the ¡Delete¿ key immediately upon turning on the CE. The 3Ware card had its boot status elevated, and I was presented with a fully fleshed out GRUB prompt! (In

contrast to the extremely limited rescue GRUB prompt from earlier.) What is available is summarized in Table 5.2.

Figure 1: A list of the partitions available to us at the GRUB prompt.

Partition	Filesystem	Summary of Contents
(proc)	procfs	none
(hd0)	n/a	n/a
(hd0,msdos2)	n/a	n/a
(hd0,msdos1)	ext*	boot partition of CE data drive
(hd1)	ext*	none
(hd1,msdos1)	ext*	misc. config files (namely Squid)
(fd0)	n/a	n/a

Let's try to boot into the boot partition. Following some instructions from online, the first step is to load the ext2 module, insmod ext2. Next, the root of the prompt needs to be set to the boot partition, set root='(hd0,msdos1)'. If the root was set correctly, the output of the ls / command ought to be identical to the output of ls (hd0,msdos1). In the new /, there should be two files that start with vmlinuz. We're only concerned with the one that does not have the word "rescue" in the name. To load the compiled kernel, linux <non-rescuse vmlinuz>, then to boot it, boot.

Unfortunately, the kernel panics when it tries to boot; the rescue kernel was also tried to no avail. The rescue kernel has the panic not syncing: VFS: Unable to mount root fs on unknown-block(0,0). A quick search has revealed that it might be complaining about not having the initramfs loaded beforehand. We have that file, but how do we load it properly?

Running the setup commands in a different order, while throwing in a couple new ones, produces different results, but nothing successful.

```
set pager=1
set root=(hd0,msdos1)
insmod ext2
linux /vmlinuz root=/dev/sda1
initrd /initrd-plymouth.img
boot
```

Load the module for dealing with the boot partition's filesy Load the desired vmlinuz image, usually not the "rescue" of Load the corresponding initrd image.

Attempt to boot into the selected image.

Figure 2: An attempt to boot into the OS from GRUB.

Unfortunately, the pager setting does not page the output from boot, so we still have no clue what's going on after the button's hit.

I wonder what happens if we use one of the initramfs files with initrd instead of just the plain initrd image. Also, I'm gonna try to boot the rescue pair. It worked! I've booted into the rescue image! I think that might mean the images aren't ENTIRELY busted.

Something interesting I've noticed: the /sysroot directory seems to be the miscellaneous configuration files from (hd1,msdos1) from the GRUB. We've also got a /dev directory with two drives, one with one partition (sda) and another with two (sdb). mount reveals that /dev/sda1 is mounted on sysroot, and that its filesystem is ext3. /dev/sdb isn't mounted at all. I've mounted /dev/sdb1 on a directory I created, /mnt/sdb1, and it's the boot partition of the data drive, (hd0,msdos1) from the GRUB. I tried to mount /dev/sdb2, but it complained that its filesystem was of type LVM2b3\_member, which means that it's the root filesystem of the CE. Unlike the Ubuntu LiveCD, however, there is no /dev/rocks directory where those logical partitions would be stored. That's enough poking around for now, let's try to load the proper initramfs-kernel pair.

What I thought was rescue mode is actually emergency mode; the regular images brought me to the same place. What can I do with emergency mode?

The issue with the logical partitions may be a GRUB configuration issue. What if GRUB just needs to be configured to look into and properly load the logical partitions? When the physical boot partition is loaded, the complaint is that the /etc/os-release file is not found. That's fine because that file is found on the root partition. In our case, however, that partition is logical. How can we configure GRUB to boot into a logical partition?

#### 5.3 Nodes not found in insert-ethers

I found the documentation from when Ankit and Christian installed ROCKS 6 on all the nodes back in 2014. They said, after running insert-ethers—cabinet=1 on the CE and selecting *Nodes*, they inserted the ROCKS 6 disc into a node and booted into it. When the disc was loaded, the node sent out a DHCP request that was then picked up by insert-ethers. Let's see about trying that out on compute-1-0. Since we don't have a Jumbo DVD for ROCKS 7.0, I'm trying with the ROCKS 7.0 kernel disc.

The kernel disc booted to the language selection screen as expected. Unfortunately, however, I seem to be stuck here. The screen requires that a mouse be used to select the *Continue* button, but the mouse doesn't work (USB or PS2). \*sigh\* I'm gonna see about restarting the node and interrupting the GUI installer like I did before so I can attempt a command line installation.

To do a command line install, the GUI installer must be interrupted before it can start up. When greeted with the first splash screen, press TAB to edit the kernel settings: change "quiet" to "debug" so that more text will appear on the screen during boot which will allow for more time to cancel the installer startup with control-C. With the GUI installer interrupted, navigate to the shell and run <code>anaconda</code> –T to begin the text-based version of anaconda.

Be sure to choose an appropriate time zone. Change the Software selection from "Minimal Install" to "Compute Node". Select Network configuration, then the correct ethernet device (most likely enp4s0f0). Configure the device to automatically connect after reboot and to apply configuration in the installer. The defaults for the other settings ought to be sufficient. Ensure that the software selection was successful, create a root password, then begin the installation.

The installation failed; it's complaining about an attribute not having the expected data, "AttributeError: 'RocksRollsData' object has no attribute 'info"'. Checking back on insert-ethers, however, something interesting has revealed itself! compute-1-0, the node on which the installation failed, is now visible. The "()" is empty, which indicates that, while the node is visible, it has not requested a kickstart file. I'm guessing, if it worked properly, the "\*" would appear between the "()" on its own. Since that hasn't happened here, I'm assuming it didn't work, which would make sense since the installation failed. Let's try again to see what happens.

Alright, new problem: insert-ethers won't close and tmux window switching won't work. I guess I ought to restart the system (Ctrl-Alt-Delete will bring up a GUI shutdown/restart menu).

After a restart, insert-ethers crashes on startup. It reports "Access denied for user 'root'@'localhost", which is more than a little concerning. What happens if I try a hard restart? Let's find out. No change. Huh, what an interesting problem to have.

Sam did some MySQL nonsense (detailed in the adminlog) to get a new error: "error - unable to download kickstart.". It also suggests to verify that httpd is running; it, in fact, is. She also found a website that recommends a course of action in response to this error. Unfortunately, turns out the site is 6 years old, and not of much help.

Some disappointing news: I read through Ankit's old documentation from when he and Christian were building the cluster with ROCKS 6 back in 2014. They were trying to set up the wiki and the nodes at the same time, and the MySQL didn't like that so much. Sounds familiar! They had to reinstall the CE, so that's what we're gonna go do.

I've backed up the adminlog, thrown in the ROCKS 7 kernel CD, and restarted the machine. I'm going to follow the installation instructions at the beginning of this document.

We've thrown the same ROCKS 7 on the node that's on the CE. We were hoping to get a ROCKS software package "compute node" by pointing the installation source at a specific URL, but the only available one is "minimal install".

We're gonna try installing the node from itself.

As a last ditch effort, I'm going to try to follow the directions exactly on a brand new node. We started insert-ethers, selected "Compute", and booted the new node, compute-1-2 (the real one), into the Kernel Roll CD. We have arrived at the initial ROCKS 7.0 screen where we choose to Install ROCKS or test the media. We've selected the normal "Install ROCKS" option. Upon turning on the network under the "Network Configuration" section of the installer, insert-ethers reports having received a DHCP request from compute-0-1, what compute-1-2 has decided to call itself (this is confirmed by what the installer reports to be the "Current host name". We noticed something very suspicious on the insert-ethers page; it said "Opened kickstart access to 10.1.1.0/255.255.255.0 network". Hmm, what if we point the "Installation Source" of the installer at that address? After trying the URLs 10.1.1.0/255.255.255.0 and 10.1.1.0, we just threw in

255.255.255.0 and it seemed to sit longer than the other ones. While it was doing its thing, I noticed the "Cluster Private Network" section had yet to be configured. I clicked that section and, after verifying that the default values were in fact the proper ones, clicked "Done", which saved the configuration. After that had been completed, the grayed-out progress text for the "Installation Source" changed from "Probing storage..." to "Setting up installation source". It's been sitting at there in that state for quite some time. A'ight, it's been sitting here for far too long; we're gonna try the same thing on the real compute-1-3. This time, we'll configure the private network before messing with the "Installation Source".

Alright, we've started up the new node, and its calling itself compute-0-2. insert-ethers has picked it up. We've selected the "Cluster Network" section, verified that the following settings are acceptable:

Figure 3: The default "Cluster Network" settings.

Private Cluster Interface	enp4s0f1;00:30:48:C2:F4:41
Private Domain Name	local
MTU	1500
IPv4 Address	10.1.1.1
IPv4 Netmask	255.255.255.0

Selecting "Done" saves these settings and completes the configuration. Now let's do the "Installation Source". We're gonna point the node at the full address given to us by insert-ethers using HTTP: 10.1.1.0/255.255.255.0 (the use of HTTP was garnered from miscellaneous brief mentions in online forums). When "Done" is selected, the "Installation Source" attempt to probe the storage, but it ultimately fails. Let's try just 10.1.1.0. That failed too, now just 255.255.255.0. I discovered something interesting: running rocks list network on the CE gives the same network provided by insert-ethers. What if the "Cluster Private Network" section needs to be configured so that it matches THAT network? Let's try that on the real compute-1-4.

This one's calling itself compute-0-3. I've changed the "IPv4 Address" in the "Cluster Private Network" section from 10.1.1.1 to 10.1.1.0. No dice; fails when pointed at 10.1.1.0/255.255.255.0 and 10.1.1.0. Actually, rereading the documentation, it says that kickstart files are transferred over HTTPS rather than HTTP. Let's try that setting. Nope, nothing. I'm

gonna send the

We've made a Hypernews post asking for help. In the mean time, we're putting ROCKS Kernel on a node again to play with for a bit. When we turned it on, it complained of a kernel error and said to run abrt-cli list to view it. The reason it gave was "nobody cared (try booting with the irqpoll option". A quick search revealed that the error means an interrupt was not handled, usually a symptom of buggy firmware. To boot with the irqpoll option, which will, when an interrupt is encountered, poll all interrupt handlers in an attempt to resolve the interruption.

While it doesn't seem like the CE and the ROCKS node can see each other (they have both assigned themselves a local IP of 10.1.1.1), they can both see a machine with local IP 10.1.1.254 (MAC: 00:25:90:33:A3:D8). What is this machine? It's not NAS-0, the SE (which is off), or the network switch. Also, what's compute-0-0? Well, mystery solved; I ssh-ed into 10.1.1.254 to find that it is NAS-1.

We're gonna try wiping all the stuff insert-ethers has done and try again. The command is insert-ethers --remove <host name>, and the list of host names can be found with rocks list host. Now that insert-ethers has been cleared, let's see what we can do with it now. It was also recommended that httpd, dhcpd, and some other services be synced and restarted:

- service dhcpd restart
- service httpd restart
- service foundation-mysql restart
- service autofs restart
- rocks sync config
- rocks sync users

Just to see what would happen, I then ran insert-ethers on the CE and restarted compute-1-0, the node with the ROCKS Kernel on it. Nothing happened with that, so I booted it back into the ROCKS Kernel CD. This time, when we turned networking on, it called itself compute-0-1! That's still not compute-1-0, but it's closer. Also, insert-ethers has seen compute-0-1. In the Anaconda installer we manually changed the host name

from compute-0-1 to compute-1-0, but that change was not reflected in insert-ethers; we're not even sure if that change was real.

Daniel Campos is investigating the cluster. He's gotten into the BIOS of compute-1-0 by spamming DELETE. The nodes DO have support for PXE boot! He changed the boot order to prioritize the ethernet port. On the head node, he set up tcpdump to monitor network traffic to see if the head node will pick up anything from the node. It booted into the Anaconda installer after downloading the kickstart file from the head node, and it said it got all the configurations from the kickstart file.