

# PHY 4210-01 Senior Lab

## Lab P2: Electron Spin Resonance

Sarah Arends  
Jacquelyne Miksanek  
Ryan Wojtyla

Instructor: Jerry Collins

March 28, 2019

### **Abstract**

The Lande factor,  $g_s$ , (or the gyromagnetic ratio of spin) for the electron was determined through the use of electron spin resonance and Helmholtz coils. The g-factor of a diphenyl-picryl-hydrazyl (DPPH) sample was obtained following the measurement of the frequency dependence of the resonance field. The line width of the resonance signal was then calculated.

# Contents

<b>1</b>	<b>Data Analysis</b>	<b>3</b>
1.1	Frequency Dependence of Resonance Field . . . . .	3
1.2	Propagation of Uncertainty in the Frequency Dependence of the Resonance Field . . . . .	3
1.3	Experimental Value of Gyromagnetic Ratio . . . . .	3
1.4	Propagating Uncertainty in Gyromagnetic Ratio . . . . .	3
1.5	Determining Line Width of Resonance Signal . . . . .	4
<b>2</b>	<b>Results</b>	<b>4</b>
2.1	Discrepancy in Gyromagnetic Ratio . . . . .	4
2.2	Discrepancy in Line Width . . . . .	4
<b>3</b>	<b>Conclusion</b>	<b>4</b>
<b>4</b>	<b>Appendices</b>	<b>4</b>
4.1	Appendix A: Data . . . . .	4
4.2	Appendix B: Source Code . . . . .	4

# 1 Data Analysis

## 1.1 Frequency Dependence of Resonance Field

Voltage was compared to frequency to obtain a graphical relationship of the frequency dependence of the resonance field. The amplitude voltage was obtained by measuring the peak-to-peak voltage from the oscilloscope and dividing it in half. The peak of 1 is the specific resonance frequency for the field.

Figure 1: Graphic representation of the frequency dependence of the resonance field.

## 1.2 Propagation of Uncertainty in the Frequency Dependence of the Resonance Field

## 1.3 Experimental Value of Gyromagnetic Ratio

The gyromagnetic ratio is calculated using the following equation, where  $\nu$  is the frequency,  $h$  is Planck's constant,  $\mu_B$  is the Bohr magneton, and  $B_0$  is the magnetic field strength.

$$g_s = \frac{h \times \nu}{\mu_B \times B_0} \quad (1)$$

The magnetic field used in calculating equation 1 must be calculated as well. It is determined from the measured current using equation 2, where  $\mu_0 = 4\pi \times 10^{-7} \frac{Vs}{Am}$ , the number of turns is  $n = 320$ , and the radius of the coils is  $r = 6.8cm$ .

$$B_0 = \mu_0 \left(\frac{4}{5}\right)^{3/2} \times \frac{n}{r} \times I \quad (2)$$

Rather than measuring the current directly, the current is calculated by measuring the voltage drop across a resistor, of which the resistance is also measured. This calculation is shown below in equation.

$$I = \frac{V}{R} \quad (3)$$

By substituting equation 3 into 2, and then substituting equation 2 into equation 1, we arrive at an expression for the gyromagnetic ratio in terms of known constants and measured quantities. This final expression is shown in equation 4.

$$g_s = \frac{h \times \nu}{\mu_B \times \left(\mu_0 \left(\frac{4}{5}\right)^{3/2} \times \frac{n}{r} \times \frac{V}{R}\right)} \quad (4)$$

## 1.4 Propagating Uncertainty in Gyromagnetic Ratio

The error in the experimental value of the gyromagnetic ratio is determined by propagating uncertainty in equation 4.

$$\delta g_s =$$

### **1.5 Determining Line Width of Resonance Signal**

## **2 Results**

### **2.1 Discrepancy in Gyromagnetic Ratio**

### **2.2 Discrepancy in Line Width**

## **3 Conclusion**

## **4 Appendices**

### **4.1 Appendix A: Data**

### **4.2 Appendix B: Source Code**