

PHY 4210-01 Senior Lab
Lab P5: Hall Effect in Semiconductors and
Metals

Sarah Arends
Jacquelyne Miksanek
Ryan Wojtyla

Instructor: Jerry Collins II

February 13, 2019

Abstract

words words words abstract

Contents

1	Theory of the Experiment	4
2	Hall Effect in P-Germanium	4
2.1	Task 1	4
2.2	Task 2	4
2.3	Task 3	4
2.4	Task 4	4
2.5	Task 5	4
3	Hall Effect in N-Germanium	4
3.1	Task 1	4
3.2	Task 2	4
3.3	Task 3	4
3.4	Task 4	4
3.5	Task 5	4
4	Hall Effect in Pure Germanium	5
4.1	Determining Band Gap in Pure Ge	5
5	Hall Effect in Pure Zinc	5
5.1	Determining Hall Constant in Pure Zn	5
6	Appendices	5
6.1	Appendix A: Data	5
6.2	Appendix B: Source Code	5

1 Theory of the Experiment

2 Hall Effect in P-Germanium

2.1 Task 1

2.1.1 Data Analysis and Results

2.1.2 Conclusion

2.2 Task 2

2.2.1 Data Analysis and Results

2.2.2 Conclusion

2.3 Task 3

2.3.1 Data Analysis and Results

2.3.2 Conclusion

2.4 Task 4

2.4.1 Data Analysis and Results

2.4.2 Conclusion

2.5 Task 5

2.5.1 Data Analysis and Results

2.5.2 Conclusion

3 Hall Effect in N-Germanium

3.1 Task 1

3.1.1 Data Analysis and Results

3.1.2 Conclusion

3.2 Task 2

3.2.1 Data Analysis and Results

3.2.2 Conclusion

3.3 Task 3

3.3.1 Data Analysis and Results

3.3.2 Conclusion

3.4 Task 4

3.4.1 Data Analysis and Results

3.4.2 Conclusion

3.5 Task 5

4

3.5.1 Data Analysis and Results

3.5.2 Conclusion

4 Hall Effect in Pure Germanium

4.1 Determining Band Gap in Pure Ge

4.1.1 Data Analysis and Results

4.1.2 Conclusion

5 Hall Effect in Pure Zinc

5.1 Determining Hall Constant in Pure Zn

5.1.1 Data Analysis and Results

In order to determine the Hall constant R_H , one can analyze the dependence of the Hall voltage on the applied field. This was done with a constant DC current applied across the Zn sample, with an associated random error due to the limited precision of the power supply. The error in the slope is obtained through linear regression, and the thickness prescribed by the sample specifications is assumed to have no error.

Slope, b [$\frac{\Omega\text{cm}}{\text{G}}$]	$4.11 \times 10^{-13} \pm \text{ERROR}$
Thickness, d [m]	$2.5 \times 10^{-5} \pm 0$
Sample Current, I [A]	13.5 ± 0.1

Table 5.1: Measurements and calculations used to determine the experimental Hall constant of pure Zinc

The Hall constant of Zinc is calculated as follows.

$$\begin{aligned} R_H &= \left(\frac{\mu_H}{B}\right) \frac{d}{I} \\ &= (b) \frac{d}{I} \\ &= (4.11 \times 10^{-13}) \frac{2.5 \times 10^{-5}}{13.5} \\ &= 4.11 \times 10^{-11} \text{ Vm/TA} \\ &\equiv 4.11 \times 10^{-13} \Omega\text{cm/G} \end{aligned}$$

A theoretical value for the Hall constant of Zinc, given by the third edition of the AIP handbook, is $R_H = 3.30 \times 10^{-13} \Omega\text{cm/G}$.

5.1.2 Conclusion

6 Appendices

6.1 Appendix A: Data

6.2 Appendix B: Source Code