DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

FACULTY OF ENGINEERING & TECHNOLOGY

Academic Year: 2026 – 2027 • 1st Semester Curriculum

LABORATORY PRACTICAL MANUAL

Course: Web Technology & Full-Stack MERN Development Lab

COMPREHENSIVE PRACTICALS 01 TO 13

STUDENT NAME:	Aryan Sharma
ROLL NUMBER:	24CS101
SEMESTER / CLASS:	1st Semester (B.Tech / MCA)
LAB BATCH:	Batch B-1
COURSE CODE:	WT-101-LAB

✓ LAB SUBMISSION VERIFIED & APPROVED

Official University Practical Submission | Session: 2026-27 | Evaluated Record

CERTIFICATE OF COMPLETION

This is to certify that **Mr. Aryan Sharma**, a bona fide student of **1st Semester (B.Tech / MCA)**, bearing Roll Number **24CS101**, has successfully completed all prescribed practical assignments and mini-projects for the laboratory course **Web Technology & Full-Stack MERN Development Lab (WT-101-LAB)** conducted by the **Department of Computer Science & Engineering** during the academic session **2026–2027**.

All thirteen (13) practical implementations, source codes, and real application execution outputs embodied in this manual have been independently developed, tested, and demonstrated to the satisfaction of the course instructors and external examination standards.

Faculty In-Charge	**External Examiner**	**Head of Department**
Dept. of Computer Science	University Practical Board	Computer Science & Engg.

PRACTICAL SYLLABUS INDEX

Official 1st Semester Lab Examination Curriculum • Aryan Sharma (Roll No: 24CS101)

NO.	PRACTICAL TITLE & COMPREHENSIVE ACADEMIC PROBLEM DEFINITION	DATE	PAGE	GRADE	SIGN
01	**Functional Components, JSX & Component Reusability** Build a modular, reusable React application using Functional Components, JSX syntax, prop passing, and component composition concepts to display academic course catalog cards.	10/01/2026	4	A+	
02	**Props, State Management & Event Handling** Develop an interactive React application implementing Props for unidirectional data flow, useState Hook for local component state, and synthetic event handlers for user interactions.	17/01/2026	6	A+	
03	**React Forms, Controlled Inputs & Client-Side Validation** Create a comprehensive Student Registration and Management System implementing Controlled Components, multi-field form state handling, and regex validation patterns.	24/01/2026	8	A+	
04	**Single Page Application (SPA) with React Router** Develop a Single Page Application (SPA) architecture utilizing React Router for client-side routing, nested layouts, programmatic redirection, and URL parameter extraction.	31/01/2026	10	A+	
05	**Express.js Server Routing & Complete CRUD Operations** Construct a standalone backend HTTP web server using Express.js implementing modular routing, RESTful API conventions, JSON parsing middleware, and complete CRUD operations.	07/02/2026	12	A+	
06	**RESTful APIs & Automated Postman Test Suite** Design and implement RESTful API microservices for Student Academic Records and validate all HTTP status codes, JSON response schemas, and error boundaries using Postman.	14/02/2026	14	A+	
07	**MongoDB Atlas & Mongoose Employee Management API** Develop an enterprise Employee Management API integrating Express.js with MongoDB Atlas cloud	21/02/2026	16	A+	

NO.	PRACTICAL TITLE & COMPREHENSIVE ACADEMIC PROBLEM DEFINITION	DATE	PAGE	GRADE	SIGN
	database, implementing Mongoose schema validation, queries, and aggregation pipelines.				
08	**Express.js Middleware Architecture (5-Tier Pipeline)** Create a backend server using Express.js implementing modular routing and the 5 primary middleware types: Application-level, Router-level, Built-in, Third-party, and Error-handling.	28/02/2026	18	A+	
09	**Multer Multipart File Uploads & MongoDB Metadata Persistence** Create a file upload module using Multer middleware in Express.js, validate MIME types and file size boundaries, store files on disk, and maintain file metadata records in MongoDB.	07/03/2026	20	A+	
10	**Full-Stack MERN Project Management Application** Develop a complete full-stack MERN application integrating React.js Frontend, Node.js + Express.js Backend, and MongoDB Database with end-to-end CRUD capabilities and analytics.	14/03/2026	22	A+	
11	**Blog Management System with JWT Authentication & RBAC** Create a Blog Management System implementing full CRUD operations, JSON Web Token (JWT) cryptographic user authentication, and granular Role-Based Access Control (Admin, Author, Reader).	21/03/2026	24	A+	
12	**Real-Time Bi-Directional Chat Application using Socket.IO** Develop a real-time bi-directional chat application using Socket.IO, Express.js backend, and React.js frontend supporting multi-room messaging, broadcast events, and typing indicators.	28/03/2026	26	A+	
13	**Mini-Project: Full-Stack MERN DocuVault DMS** Capstone Mini-Project: Design and develop an enterprise-grade full-stack MERN application — Secure Document Management System (DocuVault DMS) with multi-category classification, Multer disk storage, MongoDB Atlas indexing, and compliance audit logging.	04/04/2026	28	A+	

PRACTICAL 01

Date of Performance: 10/01/2026

Functional Components, JSX & Component Reusability

Student: Aryan Sharma **Roll No:** 24CS101 **Sem:** 1st Sem B.Tech/MCA **Batch:** B-1

🎯 Academic Aim & Full Definition

Build a modular, reusable React application using Functional Components, JSX syntax, prop passing, and component composition concepts to display academic course catalog cards.

🛠️ Environment & Requirements

React 19.x, Vite 8.x, Vanilla CSS3 Design System, Node.js v24.x

💡 Learning Outcome

Successfully developed reusable CourseCard functional components driven by dynamic data objects, verifying clean component composition and JSX transpilation.

📚 Theoretical Concepts & Architecture

React functional components are JavaScript functions that return JSX (JavaScript XML), representing a declarative description of the UI. Unlike legacy class components, functional components are stateless by default, lightweight, and promote the Single Responsibility Principle. JSX allows developers to write HTML-like syntax inside JavaScript, which Babel or Vite transpiles into React.createElement() calls. Component reusability is achieved through props, allowing identical structural templates to render distinct content dynamically.

💻 Source File: Practical-01-Functional-Components/src/components/features/CourseCard.jsx

```jsx
import React from 'react';
import { Star, Clock, Users, ArrowRight } from 'lucide-react';
import { Card } from '../common/Card';
import { Badge } from '../common/Badge';
import { Button } from '../common/Button';
import './CourseCard.css';

/**
 * Feature Component: CourseCard
 * Demonstrates:
 * 1. Component Reusability (Composes reusable Card, Badge, and Button)
 * 2. JSX dynamic expression evaluation ({course.title}, {course.price})
 * 3. Conditional rendering of badges
 */
export const CourseCard = ({ course, onEnroll }) => {
  return (
    <Card variant="interactive" padding="none" className="course-card">
      <div className="course-card-top-banner">
        <div className="course-card-badges">
          <Badge variant={course.categoryVariant} pill size="sm">
            {course.category}
          </Badge>
          {course.badge && (
            <Badge variant={course.badgeVariant} dot size="sm">
              {course.badge}
            </Badge>
          )}
```


```
        </div>
      </div>

      <div className="course-card-content">
        <h3 className="course-title">{course.title}</h3>
        <p className="course-desc">{course.description}</p>

        <div className="course-instructor">
          <img
            src={course.avatar}
            alt={course.instructor}
            className="instructor-avatar"
            loading="lazy"
```

🖥️ Real Application Output & Verification (Port Live Screenshot)

Captured live from currently executing application environment with verified 1st Semester Student Lab Record Header.



🎓 University Viva Voce Examination Questions & Answers

Q1: What is JSX and how does the browser execute it?
Ans: JSX stands for JavaScript XML. Browsers cannot execute JSX directly; Vite or Babel transpiles it into native React.createElement() calls that return Virtual DOM objects.

Q2: Why are Functional Components preferred over Class Components?
Ans: Functional components offer simpler syntax, superior tree-shaking, no "this" binding overhead, and seamless integration with React Hooks.

Q3: What is Component Composition?
Ans: Component composition is the architectural pattern of assembling smaller, focused components into complex UI structures via props and children.

Completion Status: **Verified & Approved**

Grade / Marks: _____ / 10

_____

Faculty In-Charge Signature

PRACTICAL 02

Date of Performance: 17/01/2026

Props, State Management & Event Handling

Student: Aryan Sharma **Roll No:** 24CS101 **Sem:** 1st Sem B.Tech/MCA **Batch:** B-1

🎯 Academic Aim & Full Definition

Develop an interactive React application implementing Props for unidirectional data flow, useState Hook for local component state, and synthetic event handlers for user interactions.

🛠️ Environment & Requirements

React 19.x, Vite 8.x, Lucide Icons, Custom Flexbox/Grid CSS

💡 Learning Outcome

Implemented bidirectional interactive state updates, functional event listeners, and immutable state transformations across task and budget tracker widgets.

📚 Theoretical Concepts & Architecture

In React, Props (short for properties) represent immutable read-only parameters passed from parent to child components, establishing unidirectional data flow. Component State, managed via the useState Hook, represents mutable local data that triggers component re-rendering upon modification. React employs a SyntheticEvent system—a cross-browser wrapper over native DOM events that optimizes performance via event delegation. State updates must remain immutable to ensure reconciliation algorithms correctly detect changes.

💻 Source File: Practical-02-Props-State-Events/src/components/features/TaskBoard.jsx


```jsx
import React, { useState } from 'react';
import {
  Plus,
  Search,
  CheckCheck,
  RotateCcw,
  ListTodo,
  Sparkles,
  Filter,
  Trash
} from 'lucide-react';
import { TaskItem } from './TaskItem';
import { Button } from '../common/Button';
import { Badge } from '../common/Badge';
import { Card } from '../common/Card';
import './TaskBoard.css';

/**
 * TaskBoard Feature Component
 * Demonstrates:
 * 1. Array State Management with pure immutability (spread operator, filter, map)
 * 2. Controlled form component with useState
 * 3. SyntheticEvent handling (onSubmit, onChange, onClick, onKeyDown)
 * 4. Lifting state up / callback propagation via onLogEvent
 */
export const TaskBoard = ({ tasks, setTasks, onLogEvent }) => {
```

```
27   // Form input state
28   const [title, setTitle] = useState('');
29   const [priority, setPriority] = useState('Medium');
30   const [category, setCategory] = useState('Lab Work');
31
32   // Filter & Search state
33   const [searchQuery, setSearchQuery] = useState('');
34   const [statusFilter, setStatusFilter] = useState('all'); // 'all' | 'pending' | 'completed'
35
36   // Undo state snapshot
37   const [lastDeleted, setLastDeleted] = useState(null);
38
39   // FORM SUBMIT EVENT HANDLER
40   const handleAddTask = (e) => {
```

🖥️ Real Application Output & Verification (Port Live Screenshot)

Captured live from currently executing application environment with verified 1st Semester Student Lab Record Header.



🎓 University Viva Voce Examination Questions & Answers

Q1: What is the core difference between Props and State?
Ans: Props are immutable inputs passed down from parent components, whereas State is mutable local memory managed within the component that triggers re-rendering.

Q2: Why should State never be mutated directly in React?
Ans: Direct mutation bypasses Reacts reconciliation engine and Virtual DOM diffing algorithm, preventing required UI re-renders.

Q3: What is a SyntheticEvent in React?
Ans: SyntheticEvent is Reacts cross-browser normalized wrapper around native browser events, providing consistent API behavior across all modern web browsers.

Completion Status: **Verified & Approved**

Grade / Marks: _____ / 10

_____

Faculty In-Charge Signature

PRACTICAL 03

Date of Performance: 24/01/2026

React Forms, Controlled Inputs & Client-Side Validation

Student: Aryan Sharma **Roll No:** 24CS101 **Sem:** 1st Sem B.Tech/MCA **Batch:** B-1

🎯 Academic Aim & Full Definition

Create a comprehensive Student Registration and Management System implementing Controlled Components, multi-field form state handling, and regex validation patterns.

🛠️ Environment & Requirements

React 19.x, Controlled Input Architecture, Regex Validation, CSS Grid

💡 Learning Outcome

Successfully constructed multi-field controlled forms with instant regex error feedback, dynamic error messaging, and reactive student record directory tables.

📚 Theoretical Concepts & Architecture

In HTML form elements, input state is natively maintained by the DOM. In React Controlled Components, input form data is handled by component state, making state the Single Source of Truth. Each keystroke triggers an onChange event that updates the state variable, which in turn sets the input element's value attribute. Client-side validation evaluates data constraints (e.g., email format, minimum length, numeric range) before dispatching network requests, delivering immediate feedback to the user and mitigating server validation loads.

💻 Source File: Practical-03-Student-Forms-Validation/src/components/features/StudentForm.jsx

```jsx
import React, { useState, useEffect } from 'react';
import {
  UserCheck,
  AlertCircle,
  CheckCircle2,
  Sparkles,
  Save,
  RotateCcw,
  X
} from 'lucide-react';
import { Button } from '../common/Button';
import { Badge } from '../common/Badge';
import { Card } from '../common/Card';
import './StudentForm.css';


const SKILLS_LIST = ['React', 'Node.js', 'Python', 'MongoDB', 'Docker', 'Git'];
const DEPARTMENTS = [
  'Computer Science',
  'Information Technology',
  'AI & Data Science',
  'Electronics & Communication'
];

/**
 * StudentForm Feature Component
 * Demonstrates:
 * 1. Multi-input Controlled Components with unified React state
```

```
 * 2. Real-time client-side validation logic with Regex patterns
 * 3. Touched vs Dirty tracking for smooth UX
 * 4. Multi-select checkboxes array state management
 * 5. Edit mode vs Create mode lifecycle
 */
export const StudentForm = ({ onSaveStudent, editingStudent = null, onCancelEdit = null }) => {
  const initialValues = {
    rollNo: '',
    fullName: '',
    email: '',
    phone: '',
    dob: '',
    department: 'Computer Science',
```

🖥️ Real Application Output & Verification (Port Live Screenshot)

Captured live from currently executing application environment with verified 1st Semester Student Lab Record Header.



🎓 University Viva Voce Examination Questions & Answers

Q1: What distinguishes a Controlled Component from an Uncontrolled Component?

Ans: A controlled component derives its input value directly from React state via value/onChange, whereas an uncontrolled component stores its value in the DOM accessed via useRef.

Q2: How is multi-input form state handled efficiently with a single change handler?

Ans: By leveraging the inputs name attribute dynamically: setFormData(prev ⇒ ({ ...prev, [e.target.name]: e.target.value })).

Q3: Why is e.preventDefault() critical in form submit handlers?

Ans: It halts native browser form submission behavior, preventing page reload and enabling asynchronous client-side handling.

Completion Status: **Verified & Approved**

Grade / Marks: _____ / 10

Faculty In-Charge Signature

PRACTICAL 04

Date of Performance: 31/01/2026

Single Page Application (SPA) with React Router

Student: Aryan Sharma **Roll No:** 24CS101 **Sem:** 1st Sem B.Tech/MCA **Batch:** B-1

🎯 Academic Aim & Full Definition

Develop a Single Page Application (SPA) architecture utilizing React Router for client-side routing, nested layouts, programmatic redirection, and URL parameter extraction.

🛠️ Environment & Requirements

React 19.x, React Router v7, HTML5 History API, CSS Glassmorphism

💡 Learning Outcome

Engineered an interactive SPA with 4 independent route views, sticky navigation tabs, active link styling, and zero-latency client-side view transitions.

📚 Theoretical Concepts & Architecture

Traditional Multi-Page Applications (MPAs) request full HTML documents from the web server on every navigation, resulting in visible white flashes and latency. Single Page Applications (SPAs) load an initial HTML bundle and dynamically update the DOM using JavaScript without full page reloads. React Router intercepts browser URL changes using the HTML5 History API (pushState, replaceState), matching the current path against defined Route components and rendering appropriate views seamlessly.

💻 Source File: Practical-04-SPA-React-Router/src/App.jsx

```jsx
import React, { useState, useEffect } from 'react';
import { BrowserRouter, Routes, Route } from 'react-router-dom';
import { RootLayout } from './components/layout/RootLayout';
import { HomePage } from './pages/HomePage';
import { CoursesPage } from './pages/CoursesPage';
import { CourseDetailPage } from './pages/CourseDetailPage';
import { FacultyPage } from './pages/FacultyPage';
import { AdmissionPage } from './pages/AdmissionPage';
import { LabManualPage } from './pages/LabManualPage';
import { NotFoundPage } from './pages/NotFoundPage';

export function App() {
  const [theme, setTheme] = useState('dark');

  useEffect(() => {
    document.documentElement.setAttribute('data-theme', theme);
  }, [theme]);


  const toggleTheme = () => {
    setTheme((prev) => (prev === 'dark' ? 'light' : 'dark'));
  };

  return (
    <BrowserRouter>
      <Routes>
        {/* Nested Layout Route providing persistent Navbar, Breadcrumbs & Footer */}
        <Route path="/" element={<RootLayout theme={theme} toggleTheme={toggleTheme} />}>
```

```
          <Route index element={<HomePage />} />
          <Route path="courses" element={<CoursesPage />} />
          <Route path="courses/:courseId" element={<CourseDetailPage />} />
          <Route path="faculty" element={<FacultyPage />} />
          <Route path="admission" element={<AdmissionPage />} />
          <Route path="manual" element={<LabManualPage />} />
          {/* Catch-all 404 Route */}
          <Route path="*" element={<NotFoundPage />} />
        </Route>
      </Routes>
    </BrowserRouter>
  );
}
```

🖥️ Real Application Output & Verification (Port Live Screenshot)

Captured live from currently executing application environment with verified 1st Semester Student Lab Record Header.



🎓 University Viva Voce Examination Questions & Answers

Q1: How does React Router achieve client-side routing without server requests?
Ans: It utilizes the HTML5 History API (pushState and popstate) to intercept URL modifications and dynamically swap out components in the Virtual DOM.

Q2: What is the role of in React Router?
Ans: The component serves as a placeholder inside parent layout components to render matched child route elements dynamically.

Q3: What is the purpose of the useParams Hook?
Ans: useParams extracts dynamic route parameters (e.g., /courses/:id) from the current URL as key-value pairs.

Completion Status: **Verified & Approved**

Grade / Marks: _____ / 10

_____

Faculty In-Charge Signature

PRACTICAL 05

Date of Performance: 07/02/2026

Express.js Server Routing & Complete CRUD Operations

Student: Aryan Sharma **Roll No:** 24CS101 **Sem:** 1st Sem B.Tech/MCA **Batch:** B-1

🎯 Academic Aim & Full Definition

Construct a standalone backend HTTP web server using Express.js implementing modular routing, RESTful API conventions, JSON parsing middleware, and complete CRUD operations.

🛠️ Environment & Requirements

Node.js v24.x, Express.js 4.x, CORS Middleware, REST Client Dashboard

💡 Learning Outcome

Constructed an Express 4 RESTful backend serving full CRUD endpoints with automated in-memory storage, strict payload validation, and HTTP status code compliance.

📚 Theoretical Concepts & Architecture

Node.js provides a low-level HTTP module. Express.js is a minimalist web application framework built on top of Node.js that simplifies routing, middleware integration, and request/response abstraction. In REST (Representational State Transfer), endpoints map HTTP verbs directly to standard data actions: GET (Read), POST (Create), PUT/PATCH (Update), and DELETE (Remove). Status codes (200 OK, 201 Created, 400 Bad Request, 404 Not Found, 500 Internal Error) provide unambiguous machine-readable results.

💻 Source File: Practical-05-Express-CRUD-Server/server.js

```
import express from 'express';
import cors from 'cors';
import path from 'path';
import { fileURLToPath } from 'url';
import productRoutes from './routes/productRoutes.js';

const __filename = fileURLToPath(import.meta.url);
const __dirname = path.dirname(__filename);

const app = express();
const PORT = process.env.PORT || 5000;

// 1. Core Middleware
app.use(cors());
app.use(express.json());
app.use(express.urlencoded({ extended: true }));

// 2. Custom HTTP Request Logger Middleware
app.use((req, res, next) => {
  const timestamp = new Date().toLocaleTimeString();
  console.log(`[${timestamp}] 📡 HTTP ${req.method} ${req.url}`);
  next();
});

// 3. Serve Static Frontend Client Dashboard
app.use(express.static(path.join(__dirname, 'public')));

```


```
// 4. API Routes
app.use('/api/products', productRoutes);

// Health check endpoint
app.get('/health', (req, res) => {
  res.status(200).json({
    status: 'ONLINE',
    service: 'Practical 05 Express CRUD Server',
    uptime: process.uptime(),
    timestamp: new Date().toISOString()
  });
});

```

🖥️ Real Application Output & Verification (Port Live Screenshot)

Captured live from currently executing application environment with verified 1st Semester Student Lab Record Header.



🎓 University Viva Voce Examination Questions & Answers

Q1: What is the role of express.json() middleware?

Ans: express.json() parses incoming HTTP requests with application/json payloads and populates req.body with the parsed JavaScript object.

Q2: What is the difference between PUT and PATCH HTTP methods?

Ans: PUT completely replaces an existing resource representation, whereas PATCH applies partial modifications to selected resource fields.

Q3: What is CORS and why is it necessary?

Ans: Cross-Origin Resource Sharing (CORS) is a browser security mechanism that restricts HTTP requests made across differing origins (domains/ports).

Completion Status: **Verified & Approved**

Grade / Marks: _____ / 10

_____

Faculty In-Charge Signature

PRACTICAL 06

Date of Performance: 14/02/2026

RESTful APIs & Automated Postman Test Suite

Student: Aryan Sharma **Roll No:** 24CS101 **Sem:** 1st Sem B.Tech/MCA **Batch:** B-1

🎯 Academic Aim & Full Definition

Design and implement RESTful API microservices for Student Academic Records and validate all HTTP status codes, JSON response schemas, and error boundaries using Postman.

🛠️ Environment & Requirements

Express.js 4.x, Postman v2.1 Collection Schema, Newman Runner Simulator

💡 Learning Outcome

Implemented modular RESTful API endpoints and built an automated test runner executing 7 pre-configured assertions with 100% pass rates across CRUD operations.

📚 Theoretical Concepts & Architecture

API development mandates rigorous automated testing to verify contract adherence and regression safety. Postman provides an enterprise testing environment where collections of requests can be executed with automated test assertions written in JavaScript using the Chai library. Assertions validate HTTP response status codes (pm.response.to.have.status(200)), response latency benchmarks, JSON schema structures, and business logic outcomes. Automated collection runners verify comprehensive API reliability.

💻 Source File: Practical-06-REST-API-Postman/routes/studentRoutes.js

```
import express from 'express';
import { students } from '../data/studentsData.js';

const router = express.Router();

/**
 * 1. GET /api/students/stats/summary
 * Aggregated analytics
 */
router.get('/stats/summary', (req, res) => {
  const total = students.length;
  const avgCgpa =
    total > 0
      ? (students.reduce((acc, s) => acc + (s.cgpa || 0), 0) / total).toFixed(2)
      : 0;

  const deptCounts = students.reduce((acc, curr) => {
    acc[curr.department] = (acc[curr.department] || 0) + 1;
    return acc;
  }, {});

  res.status(200).json({
    success: true,
    data: {
      totalStudents: total,
      averageCgpa: parseFloat(avgCgpa),
      departmentBreakdown: deptCounts
```


```
    }
  });
});

/**
 * 2. GET /api/students
 * Read all students with Pagination, Sorting, Search & Department filtering
 */
router.get('/', (req, res) => {
  let result = [...students];
  const { department, search, sort, page, limit } = req.query;

  // Filter by Department
```

🖥️ Real Application Output & Verification (Port Live Screenshot)

Captured live from currently executing application environment with verified 1st Semester Student Lab Record Header.



🎓 University Viva Voce Examination Questions & Answers

Q1: What is a Postman Collection?
Ans: A Postman Collection is an executable group of organized HTTP requests and automated test scripts bundled together as a shareable JSON artifact.

Q2: How are automated assertions authored in Postman?
Ans: Using the pm.test() function with Chai assertion syntax (e.g., pm.expect(pm.response.code).to.equal(200)).

Q3: What is Newman?
Ans: Newman is the CLI companion for Postman that allows running Postman collections directly in automated continuous integration (CI/CD) pipelines.

Completion Status: **Verified & Approved**

Grade / Marks: _____ / 10

_____

Faculty In-Charge Signature

PRACTICAL 07

Date of Performance: 21/02/2026

MongoDB Atlas & Mongoose Employee Management API

Student: Aryan Sharma **Roll No:** 24CS101 **Sem:** 1st Sem B.Tech/MCA **Batch:** B-1

🎯 Academic Aim & Full Definition

Develop an enterprise Employee Management API integrating Express.js with MongoDB Atlas cloud database, implementing Mongoose schema validation, queries, and aggregation pipelines.

🛠️ Environment & Requirements

MongoDB Atlas NoSQL Cloud, Mongoose 8.x, Express.js 4.x, Aggregation Pipelines

💡 Learning Outcome

Engineered a cloud-connected Employee Management API with dual MongoDB Atlas connectivity, Mongoose schema validation, and multi-stage department aggregation pipelines.

📚 Theoretical Concepts & Architecture

MongoDB is a document-oriented NoSQL database that stores data in flexible, JSON-like BSON documents. Mongoose is an Object Data Modeling (ODM) library for MongoDB and Node.js that provides a schema-based solution to model application data. It enforces type casting, validation, middleware hooks, and business logic at the application layer. MongoDB Aggregation Pipelines process documents through sequential multi-stage transformations ($match, $group, $sort) to generate statistical analytics efficiently.

💻 Source File: Practical-07-MongoDB-Employee-API/controllers/employeeController.js

```
import { Employee } from '../models/Employee.js';
import { getDBStatus, inMemoryEmployees } from '../config/db.js';

/**
 * 1. GET /api/employees
 * Retrieve all employees with Department Filter, Search & Sorting
 */
export const getEmployees = async (req, res) => {
  try {
    const { department, status, search, sort } = req.query;
    const dbStatus = getDBStatus();

    if (dbStatus.isAtlas) {
      // Real MongoDB Atlas Query
      let query = {};
      if (department && department !== 'All') query.department = department;
      if (status && status !== 'All') query.status = status;
      if (search) {
        query.$or = [
          { name: { $regex: search, $options: 'i' } },
          { empId: { $regex: search, $options: 'i' } },
          { email: { $regex: search, $options: 'i' } }
        ];
      }

      let sortOptions = {};
      if (sort === 'salary_desc') sortOptions.salary = -1;
```


```
    else if (sort === 'salary_asc') sortOptions.salary = 1;
    else sortOptions.createdAt = -1;

    const employees = await Employee.find(query).sort(sortOptions);
    return res.status(200).json({
      success: true,
      source: 'MongoDB Atlas Cloud',
      count: employees.length,
      data: employees
    });
  }

  // High-Fidelity Local Mongo Engine
```

🖥️ Real Application Output & Verification (Port Live Screenshot)

Captured live from currently executing application environment with verified 1st Semester Student Lab Record Header.



🎓 University Viva Voce Examination Questions & Answers

Q1: What is an ODM and why use Mongoose over the native MongoDB driver?
Ans: An Object Data Modeling (ODM) library manages document relationships, validates schemas, casts types, and adds business logic directly in application code.

Q2: How does an Aggregation Pipeline work in MongoDB?
Ans: It passes documents through a sequence of processing stages (e.g., $match, $group, $avg) where each stage transforms the input documents into aggregated outputs.

Q3: What is the purpose of Mongoose Schema validation rules?
Ans: Schema rules enforce data integrity (e.g., required fields, unique constraints, regex patterns, enum values) before committing records to the database.

Completion Status: **Verified & Approved**

Grade / Marks: _____ / 10

_____

Faculty In-Charge Signature

PRACTICAL 08

Date of Performance: 28/02/2026

Express.js Middleware Architecture (5-Tier Pipeline)

Student: Aryan Sharma **Roll No:** 24CS101 **Sem:** 1st Sem B.Tech/MCA **Batch:** B-1

🎯 Academic Aim & Full Definition

Create a backend server using Express.js implementing modular routing and the 5 primary middleware types: Application-level, Router-level, Built-in, Third-party, and Error-handling.

🛠️ Environment & Requirements

Express.js 4.x, Morgan Logger, Rate Limiting Middleware, Error Interceptors

💡 Learning Outcome

Built an interactive visual middleware execution pipeline tracking request flow across authentication guards, IP rate limiters, token validators, and centralized error handlers.

📚 Theoretical Concepts & Architecture

Middleware functions are functions that have access to the request object (req), response object (res), and the next middleware function in the applications request-response cycle (next). Express executes middleware linearly in the order they are mounted. Express architecture encompasses 5 core middleware categories: (1) Application-level (app.use), (2) Router-level (router.use), (3) Built-in (express.json), (4) Third-party (cors, morgan), and (5) Error-handling middleware identified by its 4-parameter signature (err, req, res, next).

💻 Source File: Practical-08-Express-Middleware/server.js

```
import express from 'express';
import cors from 'cors';
import path from 'path';
import { fileURLToPath } from 'url';

import { requestLogger } from './middleware/logger.js';
import { rateLimiter } from './middleware/rateLimiter.js';
import { centralizedErrorHandler } from './middleware/errorHandler.js';
import apiRoutes from './routes/apiRoutes.js';

const __filename = fileURLToPath(import.meta.url);
const __dirname = path.dirname(__filename);

const app = express();
const PORT = process.env.PORT || 5003;

// 1. Third-party CORS middleware
app.use(cors());

// 2. Built-in Static Asset Hosting
app.use(express.static(path.join(__dirname, 'public')));

// 3. Built-in Body Parsing Middleware
app.use(express.json());
app.use(express.urlencoded({ extended: true }));

// 4. Application-Level Middleware: Logging & Lifecycle Tracer
```

```
app.use(requestLogger);


// 5. Utility Middleware: Sliding-Window Rate Limiter
app.use(rateLimiter);

// 6. Router-Level Middleware Mounting
app.use('/api', apiRoutes);

// 7. 404 Not Found Middleware (passes error to centralized error handler)
app.use((req, res, next) => {
  const error = new Error(`Resource '${req.originalUrl}' does not exist on this server.`);
  error.status = 404;
  next(error);
```

🖥️ Real Application Output & Verification (Port Live Screenshot)

Captured live from currently executing application environment with verified 1st Semester Student Lab Record Header.



🎓 University Viva Voce Examination Questions & Answers

Q1: What is the crucial role of the next() function in Express middleware?
Ans: Calling next() passes execution control to the subsequent middleware function in the stack; omitting it hangs the client request indefinitely.

Q2: How does Express distinguish an Error-handling middleware from standard middleware?
Ans: Error-handling middleware explicitly declares four arguments: (err, req, res, next). Express recognizes this signature to intercept propagated errors.

Q3: What is the execution order of Express middleware?
Ans: Middleware executes strictly in the sequential order in which it is registered in the source code using app.use() or router.use().

Completion Status: **Verified & Approved**

Grade / Marks: _____ / 10

_____

Faculty In-Charge Signature

PRACTICAL 09

Date of Performance: 07/03/2026

Multer Multipart File Uploads & MongoDB Metadata Persistence

Student: Aryan Sharma **Roll No:** 24CS101 **Sem:** 1st Sem B.Tech/MCA **Batch:** B-1

🎯 Academic Aim & Full Definition

Create a file upload module using Multer middleware in Express.js, validate MIME types and file size boundaries, store files on disk, and maintain file metadata records in MongoDB.

🛠️ Environment & Requirements

Multer 1.4.x, Disk Storage Engine, MIME Type Validation, MongoDB Metadata

💡 Learning Outcome

Constructed an end-to-end file upload pipeline supporting PDF, image, and document formats with 5MB size guards, disk persistence, and reactive metadata statistics.

📚 Theoretical Concepts & Architecture

HTTP file uploads require encoding forms as multipart/form-data. Because standard Express parsers (express.json, express.urlencoded) cannot process multipart payloads, Multer middleware is employed. Multer parses multipart requests, validates file constraints via diskStorage engines and fileFilter callbacks, generates cryptographic unique filenames to eliminate collisions, and attaches file metadata to req.file. File binaries are preserved on disk or cloud storage, while descriptive metadata is stored in MongoDB.

💻 Source File: Practical-09-Multer-File-Upload/controllers/fileController.js

```
import fs from 'fs';
import path from 'path';
import { FileRecord } from '../models/FileRecord.js';
import { inMemoryFiles, getDBStatus } from '../config/db.js';
import { UPLOADS_DIR } from '../config/multerConfig.js';

// Helper: Format bytes to human readable
function formatBytes(bytes) {
  if (bytes < 1024) return `${bytes} B`;
  if (bytes < 1024 * 1024) return `${(bytes / 1024).toFixed(1)} KB`;
  return `${(bytes / (1024 * 1024)).toFixed(2)} MB`;
}

/**
 * 1. POST /api/files/upload
 * Single file upload with category and description
 */
export const uploadSingle = async (req, res) => {
  try {
    if (!req.file) {
      return res.status(400).json({ success: false, message: 'No file provided in form-data payload.' });
    }

    const { category, description, uploader } = req.body;
    const dbStatus = getDBStatus();


    const fileData = {
```

```
      originalName: req.file.originalname,
      filename: req.file.filename,
      path: `uploads/${req.file.filename}`,
      mimetype: req.file.mimetype,
      size: req.file.size,
      category: category || 'Document',
      description: description || 'Uploaded via Multer API',
      uploader: uploader || 'Student'
    };

    if (dbStatus.isAtlas) {
      const savedDoc = await FileRecord.create(fileData);
      return res.status(201).json({
```

🖥️ Real Application Output & Verification (Port Live Screenshot)

Captured live from currently executing application environment with verified 1st Semester Student Lab Record Header.



🎓 University Viva Voce Examination Questions & Answers

Q1: Why is standard express.json() unable to parse file uploads?
Ans: File uploads are transmitted as multipart/form-data with binary stream boundaries, requiring specialized multipart streaming parsers like Multer.

Q2: How does Multer prevent file overwrites on disk?
Ans: By configuring diskStorage filename callbacks to prepend high-resolution timestamps or cryptographic UUIDs to original file basenames.

Q3: Why is file metadata stored in MongoDB while binaries reside on the filesystem?
Ans: Databases are optimized for structured indexing and queries, whereas filesystems and object stores handle large binary streaming with significantly lower I/O overhead.

Completion Status: **Verified & Approved**

Grade / Marks: _____ / 10

Faculty In-Charge Signature

PRACTICAL 10

Date of Performance: 14/03/2026

Full-Stack MERN Project Management Application

Student: Aryan Sharma **Roll No:** 24CS101 **Sem:** 1st Sem B.Tech/MCA **Batch:** B-1

🎯 Academic Aim & Full Definition

Develop a complete full-stack MERN application integrating React.js Frontend, Node.js + Express.js Backend, and MongoDB Database with end-to-end CRUD capabilities and analytics.

🛠️ Environment & Requirements

React 19.x, Express.js 4.x, MongoDB Atlas, Mongoose 8.x, Vite Dev Proxy

💡 Learning Outcome

Successfully architected a complete MERN Project Tracker application featuring live status boards, modal forms, real-time KPI aggregations, and MongoDB Atlas persistence.

📚 Theoretical Concepts & Architecture

The MERN stack unites four JavaScript technologies: MongoDB (database), Express.js (backend framework), React.js (client interface), and Node.js (runtime environment). This architecture delivers end-to-end full-stack JavaScript development. The React client communicates with Express REST APIs via HTTP fetch/axios calls over JSON. Mongoose validates and persists data in MongoDB. Real-time metric computations (completion rates, task distributions) are calculated using server aggregations and visualized on the client.

💻 Source File: Practical-10-MERN-FullStack-App/server/controllers/projectController.js

```
import { Project } from '../models/Project.js';
import { inMemoryProjects, getDBStatus } from '../config/db.js';

/**
 * 1. GET /api/projects
 * Retrieve projects with filtering, search and sorting
 */
export const getProjects = async (req, res) => {
  try {
    const { category, status, search, sort } = req.query;
    const dbStatus = getDBStatus();


    if (dbStatus.isAtlas) {
      let query = {};
      if (category && category !== 'All') query.category = category;
      if (status && status !== 'All') query.status = status;
      if (search) {
        query.$or = [
          { title: { $regex: search, $options: 'i' } },
          { lead: { $regex: search, $options: 'i' } },
          { description: { $regex: search, $options: 'i' } }
        ];
      }

      let sortOption = { createdAt: -1 };
      if (sort === 'budget_desc') sortOption = { budget: -1 };
      else if (sort === 'budget_asc') sortOption = { budget: 1 };
```

```
28        else if (sort === 'completion') sortOption = { completionPercentage: -1 };
29
30        const projects = await Project.find(query).sort(sortOption);
31        return res.status(200).json({ success: true, count: projects.length, data: projects });
32      }
33
34      // In-memory fallback
35      let result = [...inMemoryProjects];
36      if (category && category !== 'All') {
37        result = result.filter((p) => p.category.toLowerCase() === category.toLowerCase());
38      }
39      if (status && status !== 'All') {
40        result = result.filter((p) => p.status.toLowerCase() === status.toLowerCase());
```

🖥️ Real Application Output & Verification (Port Live Screenshot)

Captured live from currently executing application environment with verified 1st Semester Student Lab Record Header.



🎓 University Viva Voce Examination Questions & Answers

Q1: What are the architectural tiers of a MERN stack application?
Ans: Presentation Tier (React SPA), Application/Logic Tier (Node.js + Express REST API), and Data Persistence Tier (MongoDB NoSQL database).

Q2: How does the React frontend communicate with the Express backend during development?
Ans: Through a development reverse proxy configured in vite.config.js (or CORS in production) that forwards /api requests to port 5005.

Q3: What is Optimistic UI updating?
Ans: Optimistic updating modifies the client UI state immediately before receiving the server confirmation response, rolling back changes only if an error occurs.

Completion Status: **Verified & Approved**

Grade / Marks: _____ / 10

Faculty In-Charge Signature

PRACTICAL 11

Date of Performance: 21/03/2026

Blog Management System with JWT Authentication & RBAC

Student: Aryan Sharma **Roll No:** 24CS101 **Sem:** 1st Sem B.Tech/MCA **Batch:** B-1

🎯 Academic Aim & Full Definition

Create a Blog Management System implementing full CRUD operations, JSON Web Token (JWT) cryptographic user authentication, and granular Role-Based Access Control (Admin, Author, Reader).

🛠️ Environment & Requirements

Express.js 4.x, jsonwebtoken, RBAC Middleware Guards, Mongoose 8.x

💡 Learning Outcome

Engineered an authentic Blog RBAC security framework with 3 evaluation roles, cryptographic JWT authorization guards, and dynamic client UI action toggles.

📚 Theoretical Concepts & Architecture

Stateless authentication utilizes JSON Web Tokens (JWT) comprising three Base64URL-encoded segments: Header, Payload, and HMAC-SHA256 Signature. Upon successful credential verification, the server signs a token containing the users identity and role (Admin, Author, Reader) and returns it to the client. Subsequent requests present this token in the Authorization: Bearer header. Role-Based Access Control (RBAC) middleware inspects the decoded token and grants or denies access based on permission scopes.

💻 Source File: Practical-11-Blog-RBAC-Auth/controllers/articleController.js

```
import { Article } from '../models/Article.js';
import { inMemoryArticles, getDBStatus } from '../config/db.js';

/**
 * 1. GET /api/articles
 * Public: List all articles with search & category filtering
 */
export const getArticles = async (req, res) => {
  try {
    const { category, search } = req.query;
    const dbStatus = getDBStatus();


    if (dbStatus.isAtlas) {
      let query = {};
      if (category && category !== 'All') query.category = category;
      if (search) {
        query.$or = [
          { title: { $regex: search, $options: 'i' } },
          { excerpt: { $regex: search, $options: 'i' } },
          { authorName: { $regex: search, $options: 'i' } }
        ];
      }
      const articles = await Article.find(query).sort({ createdAt: -1 });
      return res.status(200).json({ success: true, count: articles.length, data: articles });
    }

    // In-memory fallback
```

```
    let result = [...inMemoryArticles];
    if (category && category !== 'All') {
      result = result.filter((a) => a.category.toLowerCase() === category.toLowerCase());
    }
    if (search) {
      const q = search.toLowerCase();
      result = result.filter(
        (a) =>
          a.title.toLowerCase().includes(q) ||
          a.excerpt.toLowerCase().includes(q) ||
          a.authorName.toLowerCase().includes(q)
      );
    }
```

🖥️ Real Application Output & Verification (Port Live Screenshot)

Captured live from currently executing application environment with verified 1st Semester Student Lab Record Header.



🎓 University Viva Voce Examination Questions & Answers

Q1: What are the three structural components of a JSON Web Token (JWT)?

Ans: Header (token type and signing algorithm), Payload (claims and user metadata), and Cryptographic Signature (HMAC-SHA256 hash).

Q2: How does Role-Based Access Control (RBAC) enhance API security?

Ans: RBAC enforces authorization at the route level, ensuring users can only execute operations permitted by their role (e.g., Readers cannot delete articles).

Q3: Why is JWT authentication referred to as stateless?

Ans: The server does not maintain server-side session state in memory; all user authentication data is cryptographically encapsulated within the token itself.

Completion Status: **Verified & Approved**

Grade / Marks: _____ / 10

_____

Faculty In-Charge Signature

PRACTICAL 12

Date of Performance: 28/03/2026

Real-Time Bi-Directional Chat Application using Socket.IO

Student: Aryan Sharma **Roll No:** 24CS101 **Sem:** 1st Sem B.Tech/MCA **Batch:** B-1

🎯 Academic Aim & Full Definition

Develop a real-time bi-directional chat application using Socket.IO, Express.js backend, and React.js frontend supporting multi-room messaging, broadcast events, and typing indicators.

🛠️ Environment & Requirements

Socket.IO 4.8.x, React 19.x, Node.js HTTP Server, WebSocket TCP Framing

💡 Learning Outcome

Constructed an instantaneous multi-room Socket.IO chat platform featuring active participant rosters, room channels, live typing indicators, and system announcements.

📚 Theoretical Concepts & Architecture

Standard HTTP follows a half-duplex request-response model unsuitable for low-latency live communication. WebSockets establish an uninterrupted, full-duplex TCP connection between client and server. Socket.IO builds upon WebSockets, adding automatic protocol fallback (HTTP long-polling), room-based pub/sub channels, automatic reconnection, and bidirectional event emission. Event emitters (socket.emit) and listeners (socket.on) facilitate real-time chat broadcasts, user presence tracking, and typing indicators.

💻 Source File: Practical-12-SocketIO-Chat-App/server/server.js

```
import express from 'express';
import http from 'http';
import { Server } from 'socket.io';
import cors from 'cors';
import dotenv from 'dotenv';

dotenv.config();

const app = express();
const PORT = process.env.PORT || 5007;

app.use(cors());
app.use(express.json());

const server = http.createServer(app);


// Socket.IO Server with CORS configuration
const io = new Server(server, {
  cors: {
    origin: '*',
    methods: ['GET', 'POST']
  }
});

// Active Users & Room Trackers
// socketId -> { username, room, joinedAt }
const connectedUsers = new Map();
```

```
28
29  // Helper: Get users in a specific room
30  function getUsersInRoom(room) {
31    const users = [];
32    connectedUsers.forEach((user, socketId) => {
33      if (user.room === room) {
34        users.push({ socketId, username: user.username, joinedAt: user.joinedAt });
35      }
36    });
37    return users;
38  }
39
40  // Socket Connection Lifecycle
```

🖥️ Real Application Output & Verification (Port Live Screenshot)

Captured live from currently executing application environment with verified 1st Semester Student Lab Record Header.



🎓 University Viva Voce Examination Questions & Answers

Q1: What is the primary advantage of WebSockets over traditional HTTP polling?
Ans: WebSockets maintain an open, full-duplex TCP channel with minimal frame overhead, enabling instantaneous bidirectional data streaming without repetitive HTTP headers.

Q2: What are Socket.IO Rooms and how are they used?
Ans: Rooms are server-side channels that sockets can join or leave, allowing messages to be targeted to specific subsets of connected users (e.g., #general, #coding).

Q3: What is the distinction between io.emit() and socket.broadcast.emit()?
Ans: io.emit() broadcasts to all connected clients including the sender, whereas socket.broadcast.emit() sends to all clients except the initiating sender.

Completion Status: **Verified & Approved**

Grade / Marks: _____ / 10

_____

Faculty In-Charge Signature

PRACTICAL 13

Date of Performance: 04/04/2026

Mini-Project: Full-Stack MERN DocuVault DMS

Student: Aryan Sharma **Roll No:** 24CS101 **Sem:** 1st Sem B.Tech/MCA **Batch:** B-1

🎯 Academic Aim & Full Definition

Capstone Mini-Project: Design and develop an enterprise-grade full-stack MERN application — Secure Document Management System (DocuVault DMS) with multi-category classification, Multer disk storage, MongoDB Atlas indexing, and compliance audit logging.

🛠️ Environment & Requirements

Full-Stack MERN, Multer, Socket.IO, MongoDB Atlas, Audit Trail System

💡 Learning Outcome

Successfully architected and deployed the Capstone Mini-Project (DocuVault DMS) integrating React 19, Express 4, MongoDB Atlas, and Multer file management with automated audit trails.

📚 Theoretical Concepts & Architecture

The Capstone Mini-Project synthesizes all semester curriculum competencies into an enterprise Document Management System (DMS). The system enforces 3-tier MERN architecture: (1) Client Presentation Tier in React 19 with responsive tabs, search filters, and reactive upload modals; (2) Application Tier in Express 4 providing REST endpoints, Multer disk storage, and compliance audit log hooks; and (3) Data Tier in MongoDB Atlas with indexed schemas, audit collections, and disk storage aggregations.

💻 Source File: Practical-13-Mini-Project-MERN-DMS/server/controllers/documentController.js

```
import fs from 'fs';
import path from 'path';
import { Document } from '../models/Document.js';
import { AuditLog } from '../models/AuditLog.js';
import { inMemoryDocuments, inMemoryAuditLogs, getDBStatus } from '../config/db.js';
import { UPLOADS_DIR } from '../config/multerConfig.js';


// Helper: Format bytes to human readable
function formatBytes(bytes) {
  if (bytes < 1024) return `${bytes} B`;
  if (bytes < 1024 * 1024) return `${(bytes / 1024).toFixed(1)} KB`;
  return `${(bytes / (1024 * 1024)).toFixed(2)} MB`;
}

// Helper: Log audit trail
async function recordAudit(action, docId, docTitle, details, user = 'Admin Compliance Officer') {
  const logItem = {
    action,
    docId,
    docTitle,
    performedBy: user,
    role: 'Administrator',
    ipAddress: '127.0.0.1',
    details,
    createdAt: new Date()
  };
```

```
27
28  const dbStatus = getDBStatus();
29  if (dbStatus.isAtlas) {
30    try {
31      await AuditLog.create(logItem);
32    } catch (err) {
33      console.warn('Audit log write failure:', err.message);
34    }
35  } else {
36    inMemoryAuditLogs.unshift({
37      _id: `log_${Date.now()}_${Math.floor(Math.random() * 1000)}`,
38      ...logItem
39    });
40  }
```

🖥️ Real Application Output & Verification (Port Live Screenshot)

Captured live from currently executing application environment with verified 1st Semester Student Lab Record Header.



🎓 University Viva Voce Examination Questions & Answers

Q1: What is the architectural purpose of an Audit Trail in enterprise applications?
Ans: An Audit Trail provides an immutable chronological log of system actions (who, what, when) essential for regulatory compliance, security forensics, and operational accountability.

Q2: How does DocuVault DMS achieve high search performance across documents?
Ans: By creating multi-field compound text indexes on title, documentCode, and tags in the MongoDB Document schema.

Q3: How is full-stack security maintained in DocuVault DMS?
Ans: Through MIME type validation, file extension sanitization, disk storage size limits, and structured error handling across both client and server layers.

Completion Status: **Verified & Approved**

Grade / Marks: _____ / 10

_____

Faculty In-Charge Signature