

Practical File

COMPUTER NETWORKING

Paper Code: CEC013



Bachelor of Engineering

(2016-2020)

COE

Submitted by:

Yash Bansal

2016UCO1639

COE-3

Semester IV

INDEX

1. Implementation of data link layer framing method such as character stuffing and bit stuffing.
2. Implementation of CRC (Cyclic Redundancy Check) error detection method.
3. Implementation of hamming code (7, 4) to limit the noise.
4. Implementation of LZW (Lempel Zip Welch) compression algorithm in C.
5. Program to find shortest path routing between nodes (Dijkstra's Algorithm)
6. Implementation of RSA Algorithm.
7. Write a socket program in C to implement a listener and a talker.

1. Implementation of data link layer framing method such as character stuffing and bit stuffing.

BIT STUFFING :

```
#include <stdio.h>
```

```
#include <string.h>
```

```
int main(){  
    int a[20],b[20],i,j,k,count,n;  
    printf("Enter frame size : ");  
    scanf("%d",&n);  
    printf("Enter the frame in the form of 0s & 1s : ");  
    for(i=0;i<n;i++){  
        scanf("%d",&a[i]);  
    }  
    i=0;  
    count=1;  
    j=0;  
    while(i<n){  
        b[j]=a[i];  
        if(a[i]==1){  
            for(k=i+1;a[k]==1 && count<5 && k<n;k++){  
                j++;  
                b[j]=a[k];  
                count++;  
                if(count==5){
```

```

                                j++;
                                b[j]=0;
                                }
                                i=k;
                                }
                                }
                                i++;
                                j++;
                                }

printf("Afer bit stuffing : ");

for(i=0;i<j;i++){
    printf("%d",b[i]);
}

printf("\n")

return 0;

}

```

OUTPUT:

```

[Sals-MacBook-Pro:Lab yashbansal$ gcc Bitstuffing.c
[Sals-MacBook-Pro:Lab yashbansal$ ./a.out
Enter frame size : 8
Enter the frame in the form of 0s & 1s : 0 1 1 1 1 1 1 0
Afer bit stuffing : 011111010
Sals-MacBook-Pro:Lab yashbansal$ █

```

CHARACTER STUFFING:

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
string charstuff(string s,char start,char end);
```

```
string decodecharstuff(string s,char start,char end);
```

```
int main(){
```

```
    string str;
```

```
    cout<<"Enter Data: ";
```

```
    cin>>str;
```

```
    char start;
```

```
    cout<<"Enter Starting delimiter: ";
```

```
    cin>>start;
```

```
    char end;
```

```
    cout<<"Enter Ending delimiter: ";
```

```
    cin>>end;
```

```
    string result = charstuff(str, start, end);
```

```
    cout<<"Stuffed Data: "<<result<<endl;
```

```
    cout<<"De-Stuffed Data: "<<decodecharstuff(result, start, end)<<endl;
```

```
}
```

```
string charstuff(string s,char start,char end){
```

```
    string res;
```

```
    res += start;
```

```

for(int i=0; i<s.length(); i++) {

    if(s[i] == start) {

        res += s[i];

        res += s[i];

    }

    else if(s[i]==end) {

        res += s[i];

        res += s[i];

    }

    else {

        res+=s[i];

    }

}

res+=end;

return res;

}

```

```

string decodecharstuff(string s,char start,char end){

    string data;

    for(int i=1; i<s.length()-1; i++) {

        if(s[i]==start && i!=s.length()-2) {

            if(s[i+1]==start) {

                data += s[i];

                i++;

            }

        }

    }

}

```

```

    }

    else if(s[i]==end && i!=s.length()-2) {

        if(s[i+1]==end) {

            data += s[i];

            i++;

        }

    }

    else {

        data += s[i];

    }

}

return data;

}

```

OUTPUT:

```

[Sals-MacBook-Pro:Lab yashbansal$ g++ charStuffing.cpp
[Sals-MacBook-Pro:Lab yashbansal$ ./a.out
Enter Data: YashBansal
Enter Starting delimiter: *
Enter Ending delimiter: *
Stuffed Data: *YashBansal*
De-Stuffed Data: YashBansal
Sals-MacBook-Pro:Lab yashbansal$ █

```

2. Implementation of CRC (Cyclic Redundancy Check) error detection method.

```
#include <iostream>

using namespace std;

int main(){

    int disze, dasze, divisor[100], data[100], rem[100], quo[100], temp[100];

    cout<<"Enter the size of divisor : ";

    cin>>disze;

    cout<<"Input divisor : ";

    for (int i = 0; i < disze; ++i){

        cin>>divisor[i];

    }

    cout<<"Enter the size of data : ";

    cin>>dasze;

    cout<<"Input data : ";

    for (int i = 0; i < dasze; ++i){

        cin>>data[i];

    }

    for (int i = 0; i < disze -1; ++i){

        data[dasze+i] = 0;

    }

    int j = 0, k = 0;

    for(int i = 0; i < disze; ++i){

        temp[i] = data[i] ^ divisor[i];

        ++k;

    }
```



```

quo[j++] = 1;

while(k != dasze + disze - 1){

    for(int i = 0; i<disze - 1; ++i){

        temp[i] = temp[i+1];

    }

    temp[disze - 1] = data[k++];

    int ctr = 0;

    while(temp[ctr] != 1){

        for(int i = 0; i<disze - 1; ++i){

            temp[i] = temp[i+1];

        }

        temp[disze - 1] = data[k++];

        quo[j++] = 0;

    }

    for (int i = 0; i < disze; ++i){

        temp[i] = temp[i] ^ divisor[i];

    }

    quo[j++] = 1;

}

for(int i = 0; i < disze - 1; i++){

    data[dasze + i] = temp[i+1];

}

cout<<"Transmitted data is : "<<endl;

for (int i = 0; i < dasze + disze - 1 ; ++i){

    cout<<data[i];

}

```

```

        cout<<endl;

        return 0;

    }

```

OUTPUT:

```

[Sals-MacBook-Pro:Lab yashbansal$ g++ crc.cpp
[Sals-MacBook-Pro:Lab yashbansal$ ./a.out
Enter the size of divisor : 5
Input divisor : 1 1 0 0 1
Enter the size of data : 8
Input data : 1 0 1 0 1 1 0 1
Transmitted data is :
101011011001
Sals-MacBook-Pro:Lab yashbansal$ █

```

3. Implementation of hamming code (7, 4) to limit the noise

```

#include <iostream>

using namespace std;

int main() {

    int data[10];

    int dataatrec[10],c,c1,c2,c3,i;

    cout<<"Enter 4 bits of data one by one:\n";

    cin>>data[0];

    cin>>data[1];

    cin>>data[2];

```

```
cin>>data[4];
```

```
//Calculation of even parity
```

```
data[6]=data[0]^data[2]^data[4];
```

```
data[5]=data[0]^data[1]^data[4];
```

```
data[3]=data[0]^data[1]^data[2];
```

```
cout<<"\nEncoded data is : ";
```

```
for(i=0; i<7; i++)
```

```
    cout<<data[i];
```

```
cout<<"\n\nEnter received data bits one by one : ";
```

```
for(i=0; i<7; i++)
```

```
    cin>>dataatrec[i];
```

```
c1 = dataatrec[6]^dataatrec[4]^dataatrec[2]^dataatrec[0];
```

```
c2 = dataatrec[5]^dataatrec[4]^dataatrec[1]^dataatrec[0];
```

```
c3 = dataatrec[3]^dataatrec[2]^dataatrec[1]^dataatrec[0];
```

```
c = c3*4 + c2*2 + c1 ;
```

```
if(c==0) {
```

```
    cout<<"\nNo error while transmission of data.\n";
```

```
}
```

```
else {
```

```
    cout<<"\nError at position "<<c;
```

```

    cout<<"\nData sent : ";

    for(i=0; i<7; i++)

        cout<<data[i];


    cout<<"\nData received : ";

    for(i=0; i<7; i++)

        cout<<dataatrec[i];


    cout<<"\nCorrect message is : ";


    //if erroneous bit is 0 we complement it, else vice versa
    if(dataatrec[7-c]==0)

        dataatrec[7-c]=1;

    else

        dataatrec[7-c]=0;

    for (i=0; i<7; i++) {

        cout<<dataatrec[i];

    }

}

return 0;

}

```

OUTPUT:

```
[Sals-MacBook-Pro:Lab yashbansal$ g++ hamming.cpp
[Sals-MacBook-Pro:Lab yashbansal$ ./a.out
Enter 4 bits of data one by one:
1 0 1 0

Encoded data is : 1010010

Enter received data bits one by one : 1 0 1 0 0 1 0

No error while transmission of data.
Sals-MacBook-Pro:Lab yashbansal$ █
```

4. Implementation of LZW Compression Algorithm

```
#include <string>

#include <map>

#include <iostream>

#include <iterator>

#include <vector>

using namespace std;

// Compress a string to a list of output symbols.

// The result will be written to the output iterator

// starting at "result"; the final iterator is returned.

template <typename Iterator>

Iterator compress(const string &uncompressed, Iterator result){

    // Build the dictionary.

    int dictSize = 256;
```

```

map<string,int> dictionary;

for (int i = 0; i < 256; i++)

    dictionary[string(1, i)] = i;


string w;

for (string::const_iterator it = uncompressed.begin();
     it != uncompressed.end(); ++it) {

    char c = *it;

    string wc = w + c;

    if (dictionary.count(wc))

        w = wc;

    else {

        *result++ = dictionary[w];

        // Add wc to the dictionary.

        dictionary[wc] = dictSize++;

        w = string(1, c);

    }

}


// Output the code for w.

if (!w.empty())

    *result++ = dictionary[w];

return result;

}


// Decompress a list of output ks to a string.

```

```

// "begin" and "end" must form a valid range of ints

template <typename Iterator>
string decompress(Iterator begin, Iterator end){
    // Build the dictionary.

    int dictSize = 256;

    map<int,string> dictionary;

    for (int i = 0; i < 256; i++)

        dictionary[i] = string(1, i);


    string w(1, *begin++);

    string result = w;

    string entry;

    for ( ; begin != end; begin++) {

        int k = *begin;

        if (dictionary.count(k))

            entry = dictionary[k];

        else if (k == dictSize)

            entry = w + w[0];

        else

            throw "Bad compressed k";


        result += entry;


        // Add w+entry[0] to the dictionary.

        dictionary[dictSize++] = w + entry[0];
    }
}

```

```

        w = entry;

    }

    return result;

}

int main() {

    vector<int> compressed;

    string str;

    cout<<"Enter the string to be compressed: ";

    cin>>str;

    cout<<"String after compression is--> ";

    compress(str, back_inserter(compressed));

    copy(compressed.begin(), compressed.end(), ostream_iterator<int>(cout, ",
));

    cout << endl;

    cout<<"String after Decompression is--> ";

    string decompressed = decompress(compressed.begin(), compressed.end());

    cout << decompressed << endl;

    return 0;

}

```

OUTPUT:

```

[Sals-MacBook-Pro:Lab yashbansal$ g++ lzw.cpp ]
[Sals-MacBook-Pro:Lab yashbansal$ ./a.out ]
Enter the string to be compressed: YashBansal
String after compression is--> 89,      97,      115,      104,      66,      97,      1
10,      115,      97,      108,
String after Decompression is--> YashBansal
Sals-MacBook-Pro:Lab yashbansal$ █

```


5. Program to find shortest path routing between nodes (Dijkstra's Algorithm)

```
import java.util.*;

public class djikstra {

    static final int V = 9 ;

    int min_distance(int dist[] , boolean sptSet[]) {

        int min = Integer.MAX_VALUE;

        int min_index = -1;

        for ( int v = 0 ; v < V ; v++ ) {

            if (sptSet[v]==false && dist[v]<=min) {

                min = dist[v] ;

                min_index = v ;

            }

        }

        return min_index;

    }

    void print_sol(int dist[],int n) {

        System.out.println("Vertex  Distance from Source");

        for (int i = 0; i < V; i++)

            System.out.println(" "+i+"          "+dist[i]);

    }

    void dijk(int graph[][] , int src) {

        int dist[] = new int [V];
```

```

        boolean sptSet[] = new boolean [V];

        for (int i = 0; i < V; i++) {

dist[i] = Integer.MAX_VALUE;

sptSet[i] = false;

        }


dist[src] = 0 ;


for ( int count = 0 ; count < V-1 ; count++) {

        int u = min_distance(dist,sptSet);

        sptSet[u] = true ;


        for (int v = 0 ; v < V ; v++) {

                if (!sptSet[v] && graph[u][v]!=0 && dist[u] !=
                    Integer.MAX_VALUE && dist[u]+graph[u][v]
                    < dist[v]){

                        dist[v] = dist[u] + graph[u][v];

                }

        }

}

print_sol(dist,V);

}

```

```

public static void main (String[] args) {

    int graph[][] = new int[][] { {0, 4, 0, 0, 0, 0, 0, 8, 0},

```

```

        {4, 0, 8, 0, 0, 0, 0, 11, 0},
        {0, 8, 0, 7, 0, 4, 0, 0, 2},
        {0, 0, 7, 0, 9, 14, 0, 0, 0},
        {0, 0, 0, 9, 0, 10, 0, 0, 0},
        {0, 0, 4, 14, 10, 0, 2, 0, 0},
        {0, 0, 0, 0, 0, 2, 0, 1, 6},
        {8, 11, 0, 0, 0, 0, 1, 0, 7},
        {0, 0, 2, 0, 0, 0, 6, 7, 0}
    };

    djikstra t = new djikstra();

    t.dijk(graph, 0);

}
}

```

OUTPUT:

```

[Sals-MacBook-Pro:Lab yashbansal$ javac djikstra.java
[Sals-MacBook-Pro:Lab yashbansal$ java djikstra
Vertex    Distance from Source
0          0
1          4
2         12
3         19
4         21
5         11
6          9
7          8
8         14
Sals-MacBook-Pro:Lab yashbansal$ █

```

6. Implementation of RSA Algorithm.

```
#include <iostream>

using namespace std;

int gcd(int a,int b){
    if(a < b)
        swap(a,b);
    if(b == 0)
        return a;
    return gcd(b,a%b);
}

int modularExponentiation(int a, int b, int c){
    int ans = 1;
    while(b != 0) {
        if((b & 1) == 1)
            ans = (ans%c * a%c)%c;
        a = (a*a)%c;
        b = b/2;
    }
    return ans;
}

int main(){
    string a = "0ABCDEFGHIJKLMNOPQRSTUVWXYZ";
```

```

int p,q;

cout<<"Enter two prime numbers : "<<endl;

cin>>p>>q;

int n = p*q;


while(n<26){

    cout<<"Value of p and q is not large enough."<<endl;

    cout<<"Please enter p and q such that p*q is greater than 26 : "<<endl;

    cin>>p>>q;

    n = p*q;

}


int phi = (p-1)*(q-1);

int e,d;


for(int i=2; i<phi; i++){

    if(gcd(i,phi) == 1){

        e = i;

        break;

    }

}


for(int i=1; i<phi; i++){

    if((e*i)%phi == 1){

        d = i;

        break;

    }

}

```

```
    }  
}
```

```
cout<<"n: "<<n<<endl;  
cout<<"phi: "<<phi<<endl;  
cout<<"e: "<<e<<endl;  
cout<<"d: "<<d<<endl;  
string p1;
```

```
cout<<"Enter the plain text : "<<endl;  
cin>>p1;  
cout<<endl;  
cout<<"Encryption"<<endl;  
int s;  
int* c = new int[p1.length()];
```

```
for(int i=0; i<p1.length(); i++){  
    for(int j=1; j<a.length(); j++){  
        if(a[j] == p1[i]){  
            s = j;  
            break;  
        }  
    }  
    c[i] = modularExponentiation(s,e,n);  
    cout<<s<<endl;  
    cout<<"cipher: "<<c[i]<<endl;
```

```
}
```

```
cout<<endl;
```

```
cout<<"Decryption"<<endl;
```

```
for(int i=0; i<p1.length(); i++) {
```

```
    int m1 = modularExponentiation(c[i],d,n);
```

```
    cout<<a[m1];
```

```
}
```

```
cout<<endl;
```

```
return 0;
```

```
}
```

OUTPUT :

```
[Sals-MacBook-Pro:Lab yashbansal$ g++ rsa.cpp
[Sals-MacBook-Pro:Lab yashbansal$ ./a.out
Enter two prime numbers :
7 11
n: 77
phi: 60
e: 7
d: 43
Enter the plain text :
YASHBANSAL

Encryption
25
cipher: 53
1
cipher: 1
19
cipher: 68
8
cipher: 57
2
cipher: 51
1
cipher: 1
14
cipher: 42
19
cipher: 68
1
cipher: 1
12
cipher: 12

Decryption
YASHBANSAL
Sals-MacBook-Pro:Lab yashbansal$ █
```


7. Write a socket program to implement a listener and a talker.

Server :

```
// Server side C/C++ program to demonstrate Socket programming

#include <stdio.h>
#include <sys/socket.h>
#include <stdlib.h>
#include <netinet/in.h>
#include <string.h>
#define PORT 8080
intmain(intargc, charconst*argv[])
{
    intserver_fd, new_socket, valread;
    structsockaddr_in address;
    intopt = 1;
    intaddrlen = sizeof(address);
    charbuffer[1024] = {0};
    char*hello = "Hello from server";

    // Creating socket file descriptor
    if((server_fd = socket(AF_INET, SOCK_STREAM, 0)) == 0)
    {
        perror("socket failed");
        exit(EXIT_FAILURE);
    }

    // Forcefully attaching socket to the port 8080
    if(setsockopt(server_fd, SOL_SOCKET, SO_REUSEADDR | SO_REUSEPORT,
                  &opt, sizeof(opt)))
    {
        perror("setsockopt");
        exit(EXIT_FAILURE);
    }
    address.sin_family = AF_INET;
    address.sin_addr.s_addr = INADDR_ANY;
    address.sin_port = htons( PORT );

    // Forcefully attaching socket to the port 8080
    if(bind(server_fd, (structsockaddr *)&address,
            sizeof(address))<0)
    {
        perror("bind failed");
        exit(EXIT_FAILURE);
    }
}
```

```

}
if(listen(server_fd, 3) < 0)
{
    perror("listen");
    exit(EXIT_FAILURE);
}
if((new_socket = accept(server_fd, (structsockaddr *)&address,
                        (socklen_t*)&addrlen))<0)
{
    perror("accept");
    exit(EXIT_FAILURE);
}
valread = read( new_socket , buffer, 1024);
printf("%s\n",buffer );
send(new_socket , hello , strlen(hello) , 0 );
printf("Hello message sent\n");
return 0;
}

```

Client :

// Client side C/C++ program to demonstrate Socket programming

```

#include <stdio.h>
#include <sys/socket.h>
#include <stdlib.h>
#include <netinet/in.h>
#include <string.h>
#define PORT 8080

intmain(intargc, charconst*argv[])
{
    structsockaddr_in address;
    intsock = 0, valread;
    structsockaddr_in serv_addr;
    char*hello = "Hello from client";
    charbuffer[1024] = {0};
    if((sock = socket(AF_INET, SOCK_STREAM, 0)) < 0)
    {
        printf("\n Socket creation error \n");
        return-1;
    }

    memset(&serv_addr, '0', sizeof(serv_addr));

    serv_addr.sin_family = AF_INET;

```

```

serv_addr.sin_port = htons(PORT);

// Convert IPv4 and IPv6 addresses from text to binary form
if(inet_pton(AF_INET, "127.0.0.1", &serv_addr.sin_addr)<=0)
{
    printf("\nInvalid address/ Address not supported \n");
    return-1;
}

if(connect(sock, (structsockaddr *)&serv_addr, sizeof(serv_addr)) < 0)
{
    printf("\nConnection Failed \n");
    return-1;
}

send(sock , hello , strlen(hello) , 0 );
printf("Hello message sent\n");
valread = read( sock , buffer, 1024);
printf("%s\n",buffer );
return0;
}

```

Server :

```

pc@pc -Lenovo-G50-80:~$ gcc server.c -o server
server.c: In function 'main':
server.c:53:15: warning: implicit declaration of function 'read'; did you
mean 'fread'? [-Wimplicit-function-declaration]
valread = read( new_socket , buffer, 1024);
^~~~
fread
pc@pc -Lenovo-G50-80:~$ ./server
Hello from client
Hello message sent

```

Client :

```

pc@pc-Lenovo-G50-80:~$ gcc client.c -o client
client.c: In function 'main':
client.c:28:8: warning: implicit declaration of function 'inet_pton' [-
Wimplicit-function-declaration]
if(inet_pton(AF_INET, "127.0.0.1", &serv_addr.sin_addr)<=0)
^~~~~~
client.c:41:15: warning: implicit declaration of function 'read'; did you
mean 'fread'? [-Wimplicit-function-declaration]
valread = read( sock , buffer, 1024);
^~~~
fread
pc@pc -Lenovo-G50-80:~$ ./client
Hello message sent
Hello from server

```

