

# Rajalakshmi Engineering College

Name: Vrithishree V J  
Email: 241901129@rajalakshmi.edu.in  
Roll no: 241901129  
Phone: 9344491726  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 9\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 12

#### Section 1 : MCQ

1. What is the correct way to create an ArrayList in Java?

**Answer**

`ArrayList<String> list = new ArrayList<>();`

**Status : Correct**

**Marks : 1/1**

2. What will be the output of the following code?

```
import java.util.ArrayList;
```

```
public class Main {  
    public static void main(String[] args) {  
        ArrayList<Integer> list = new ArrayList<>();  
        list.add(10);  
    }  
}
```

```
list.add(20);  
list.add(30);  
System.out.println("Size of the list: " + list.size());  
}  
}
```

**Answer**

Size of the list: 3

**Status :** Correct

**Marks :** 1/1

3. What will be the output of the following code?

```
import java.util.*;  
class Main {  
    public static void main(String[] args) {  
        ArrayList<String> list = new ArrayList<>();  
        list.add("Java");  
        list.add("Python");  
        list.add("Java");  
        list.add("C++");  
        System.out.println(list.indexOf("Java"));  
    }  
}
```

**Answer**

0

**Status :** Correct

**Marks :** 1/1

4. What is Collection in Java?

**Answer**

A group of objects

**Status :** Correct

**Marks :** 1/1

5. What will be the output of the following code?

```
import java.util.ArrayList;

public class Main {
    public static void main(String[] args) {
        ArrayList<String> list = new ArrayList<>();
        list.add("Apple");
        list.add("Banana");
        list.remove("Apple");
        System.out.println(list);
    }
}
```

**Answer**

[Banana]

**Status :** Correct

**Marks :** 1/1

6. What will be the output of the following code?

```
import java.util.*;

class Main {
    public static void main(String[] args) {
        ArrayList<Integer> list = new ArrayList<>();
        list.add(1);
        list.add(2);
        list.add(3);
        list.add(4);
        list.add(5);
        System.out.println(list.get(3));
    }
}
```

**Answer**

4

**Status :** Correct

**Marks :** 1/1

7. Which method is used to add an element to the top of the stack?

**Answer**

push()

**Status : Correct**

**Marks : 1/1**

8. Which of the following methods removes and returns the last element from a LinkedList?

**Answer**

removeLast()

**Status : Correct**

**Marks : 1/1**

9. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<Integer> list = new ArrayList<>();
        list.add(1);
        list.add(2);
        list.add(3);
        list.add(4);
        list.set(2, 10);
        System.out.println(list);
    }
}
```

**Answer**

[1, 2, 10, 4]

**Status : Correct**

**Marks : 1/1**

10. What will be the output of the following code?

```
import java.util.*;
```

```
public class Main {  
    public static void main(String[] args) {  
        Stack<Integer> s = new Stack<>();  
        s.push(10);  
        s.push(20);  
        s.push(30);  
        System.out.println(s.peek());  
    }  
}
```

**Answer**

30

**Status :** Correct

**Marks :** 1/1

11. How can you access the first element of an ArrayList named as list?

**Answer**

list.get(0);

**Status :** Correct

**Marks :** 1/1

12. What will be the output of the following code?

```
import java.util.*;  
class Main {  
    public static void main(String[] args) {  
        ArrayList<String> list = new ArrayList<>();  
        list.add("apple");  
        list.add("banana");  
        list.add("cherry");  
        list.add("banana");  
        System.out.println(list.lastIndexOf("banana"));  
    }  
}
```

**Answer**

4

Status : Wrong

Marks : 0/1

13. What does the addFirst() method of LinkedList do?

Answer

Adds an element to the end of the list

Status : Wrong

Marks : 0/1

14. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<Integer> list = new ArrayList<>();
        list.add(10);
        list.add(20);
        list.add(30);
        list.remove(1);
        System.out.println(list);
    }
}
```

Answer

[20]

Status : Wrong

Marks : 0/1

15. What will be the output of the following code?

```
import java.util.*;
public class Main {
    public static void main(String[] args) {
        Stack<Integer> stack = new Stack<>();
        for (int i = 1; i <= 3; i++)
            stack.push(i * 2);
        stack.pop();
        stack.push(10);
    }
}
```

```
        System.out.println(stack.peek());  
    }  
}
```

**Answer**

10


**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: Vrithishree V J  
Email: 241901129@rajalakshmi.edu.in  
Roll no: 241901129  
Phone: 9344491726  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 9\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Bobby is tasked with processing a sequence of numbers from a monitoring system. He needs to extract a strictly increasing subsequence using an ArrayList. The program should dynamically add numbers to the ArrayList only if they are greater than the last number currently stored in the list. Bobby aims to efficiently utilize the dynamic resizing and indexing features of the ArrayList to solve this problem.

Help Bobby implement this solution.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of elements.



The second line consists of N space-separated integers, representing the elements.

### **Output Format**

The output prints the list of integers in increasing sequence, ignoring out-of-order elements.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 7

3 5 9 1 11 7 13

Output: [3, 5, 9, 11, 13]

### **Answer**

```
// You are using Java
import java.util.ArrayList;
import java.util.Scanner;
```

```
public class Main {
    public static void main(String args[]) {
        Scanner scanner = new Scanner(System.in);
        int N = scanner.nextInt();
        ArrayList<Integer> sequence = new ArrayList<>();
        for (int i = 0; i < N; i++) {
            int num = scanner.nextInt();
            if (sequence.isEmpty() || num > sequence.get(sequence.size() - 1)) {
                sequence.add(num);
            }
        }
        System.out.println(sequence);
        scanner.close();
    }
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Vrithishree V J  
Email: 241901129@rajalakshmi.edu.in  
Roll no: 241901129  
Phone: 9344491726  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 9\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Vikram loves listening to music and wants to create a simple playlist manager using Java Collections. The playlist supports the following operations:

"ADD <song>" Adds the song to the end of the playlist. "REMOVE <song>" Removes the first occurrence of the song from the playlist. If the song is not found, do nothing. "SHOW" Displays all songs in the playlist in order. If the playlist is empty, print "EMPTY". "NEXT" Moves to the next song in the playlist and prints its name. If the playlist is empty, print "EMPTY".

The playlist maintains a "current song" position that starts at the first song when it's added. The NEXT command moves to the next song and prints it, wrapping around to the first song after reaching the last song. When removing songs, the current position adjusts accordingly to maintain

proper navigation.

Help Vikram implement this playlist manager.

### ***Input Format***

The first line of the input consists of an integer n, the number of operations.

The next n lines, each containing a command:

- "ADD <song>"
- "REMOVE <song>"
- "SHOW"
- "NEXT"

### ***Output Format***

For each "SHOW" command, print the songs in order, separated by spaces.

For each "NEXT" command, print the next song in the playlist.

If no song exists, print "EMPTY".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 7

ADD song1

ADD song2

SHOW

NEXT

REMOVE song2

SHOW

NEXT

Output: song1 song2

song2

song1

song1

### ***Answer***

```

// You are using Java
import java.util.LinkedList;
import java.util.Scanner;

public class Main {
    public static void main(String args[]) {
        Scanner scanner = new Scanner(System.in);
        int n = scanner.nextInt();
        scanner.nextLine();
        LinkedList<String> playlist = new LinkedList<>();
        int currentIndex = 0;
        for (int i = 0; i < n; i++) {
            String command = scanner.nextLine().trim();
            String[] parts = command.split(" ", 2);
            String operation = parts[0];
            if (operation.equals("ADD")) {
                String song = parts[1];
                playlist.add(song);
                if (playlist.size() == 1) {
                    currentIndex = 0;
                }
            }
            else if (operation.equals("REMOVE")) {
                String song = parts[1];
                int indexToRemove = playlist.indexOf(song);
                if (indexToRemove != -1) {
                    playlist.remove(indexToRemove);
                    if (!playlist.isEmpty()) {
                        if (indexToRemove == currentIndex) {
                            currentIndex = 0;
                        } else if (currentIndex > indexToRemove) {
                            currentIndex--;
                        }
                    }
                    if (currentIndex >= playlist.size()) {
                        currentIndex = 0;
                    }
                }
            }
        }
        else if (operation.equals("SHOW")) {
            if (playlist.isEmpty()) {
                System.out.println("EMPTY");
            }
        }
    }
}

```

```
    } else {
        for (String song : playlist) {
            System.out.print(song + " ");
        }
        System.out.println();
    }
}
else if (operation.equals("NEXT")) {
    if (playlist.isEmpty()) {
        System.out.println("EMPTY");
    } else {
        currentIndex = (currentIndex + 1) % playlist.size();
        System.out.println(playlist.get(currentIndex));
    }
}
}
scanner.close();
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Vrithishree V J  
Email: 241901129@rajalakshmi.edu.in  
Roll no: 241901129  
Phone: 9344491726  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 9\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Assist Pranitha in developing a program that takes an integer N as input, representing the number of names to be read. Then read N names and store them in an ArrayList. Finally, input a search string and output the frequency of that string in the list of names.

Note: Some parts of the code are provided as snippets, and you need to complete the remaining sections by writing the necessary code.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of names to be read.

The following N lines consist of N names, as a string.

The last line consists of a string, representing the name to be searched.

### **Output Format**

The output prints a single integer, representing the frequency of the specified name in the given list.

If the specified name is not found, print 0.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

Alice

Bob

Ankit

Alice

Pranitha

Alice

Output: 2

### **Answer**

// You are using Java

```
import java.util.ArrayList;
```

```
import java.util.Scanner;
```

```
public class Main {  
    public static void main(String args[]) {  
        Scanner scanner = new Scanner(System.in);  
        int N = scanner.nextInt();  
        scanner.nextLine();  
        ArrayList<String> names = new ArrayList<>();  
        for (int i = 0; i < N; i++) {  
            String name = scanner.nextLine();  
            names.add(name);  
        }  
        String searchName = scanner.nextLine();  
        int frequency = 0;  
        for (String name : names) {  
            if (name.equals(searchName)) {
```

```
        frequency++;  
    }  
    }  
    System.out.println(frequency);  
    scanner.close();  
    }  
}
```

**Status :** Correct

**Marks :** 10/10



# Rajalakshmi Engineering College

Name: Vrithishree V J  
Email: 241901129@rajalakshmi.edu.in  
Roll no: 241901129  
Phone: 9344491726  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 9\_PAH

Attempt : 1  
Total Mark : 30  
Marks Obtained : 30

#### Section 1 : Coding

##### 1. Problem Statement

Rekha is a teacher who wants to calculate the average of marks scored by her students in a test. She needs to store all the marks dynamically because the number of students may vary each time. Using an ArrayList allows her to easily add any number of marks without worrying about the initial size.

Help her implement the task.

##### ***Input Format***

The first line of input is an integer n, representing the number of students..

The second line of input consists of n double values, representing the marks of each student, separated by a space.

### Output Format

The output prints: "Average of the list: " followed by the average value formatted to two decimal places.

Refer to the sample output for the formatting specifications.

### Sample Test Case

Input: 5

1.0 2.0 3.0 4.0 5.0

Output: Average of the list: 3.00

### Answer

```
// You are using Java
import java.util.*;
```

```
public class Main {
    public static void main(String args[]) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        ArrayList<Double> marksList = new ArrayList<>();
        for (int i = 0; i < n; i++) {
            double mark = sc.nextDouble();
            marksList.add(mark);
        }
        double sum = 0;
        for (double mark : marksList) {
            sum += mark;
        }
        double average = sum / n;
        System.out.printf("Average of the list: %.2f", average);
    }
}
```

Status : Correct

Marks : 10/10

## 2. Problem Statement

Arun is building a task manager to keep track of tasks using a LinkedList. The task manager supports the following operations:

"ADD <task>" Adds the given task to the end of the list. "REMOVE" Removes the first task from the list. "SHOW" Displays all tasks in the list in order. If the list is empty, print "EMPTY".

Help Arun implement this functionality using a LinkedList.

### ***Input Format***

The first line of the input consists of an integer n, the number of operations.

The next n lines, each containing a command:

- "ADD <task>"
- "REMOVE"
- "SHOW"

### ***Output Format***

For each "SHOW" command, the output prints the tasks in order, separated by spaces.

If no tasks exist, print "EMPTY".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5  
ADD homework  
ADD project  
SHOW  
REMOVE  
SHOW  
Output: homework project  
project

### ***Answer***

// You are using Java

```

import java.util.*;

public class Main {
    public static void main(String args[]) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());
        LinkedList<String> tasks = new LinkedList<>();
        for (int i = 0; i < n; i++) {
            String command = sc.nextLine();
            if (command.startsWith("ADD")) {
                String task = command.substring(4);
                tasks.add(task);
            } else if (command.equals("REMOVE")) {
                if (!tasks.isEmpty()) {
                    tasks.removeFirst();
                }
            } else if (command.equals("SHOW")) {
                if (tasks.isEmpty()) {
                    System.out.println("EMPTY");
                } else {
                    for (int j = 0; j < tasks.size(); j++) {
                        System.out.print(tasks.get(j));
                        if (j != tasks.size() - 1) {
                            System.out.print(" ");
                        }
                    }
                    System.out.println();
                }
            }
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Aditi is analyzing stock market trends and wants to find the Next Greater Element (NGE) for each stock price in a list. The Next Greater Element for an element  $x$  in an array is the first element to the right that is greater than

x. If no greater element exists, return -1 for that position.

Your task is to help Aditi by efficiently computing the Next Greater Element for each element in the given array using a Stack.

Example:

Input:

6

4 5 2 10 8 6

Output:

5 10 10 -1 -1 -1

Explanation:

For each element:

4   5 (next greater element) 5   10 2   10 10   -1 (No greater element) 8   -16   -1

### ***Input Format***

The first line contains an integer  $n$ , representing the number of elements.

The second line contains  $n$  space-separated integers  $arr[i]$ , where  $arr[i]$  is the stock price on the  $i$ -th day.

### ***Output Format***

The output prints  $n$  space-separated integers representing the Next Greater Element for each element in the array.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 6

4 5 2 10 8 6

Output: 5 10 10 -1 -1 -1

### ***Answer***

// You are using Java

```
import java.util.*;
```

```
public class Main {  
    public static void main(String args[]) {  
        Scanner sc = new Scanner(System.in);  
        int n = sc.nextInt();  
        int arr[] = new int[n];  
        for (int i = 0; i < n; i++) {  
            arr[i] = sc.nextInt();  
        }  
        int result[] = new int[n];  
        Stack<Integer> stack = new Stack<>();  
        for (int i = n - 1; i >= 0; i--) {  
            while (!stack.isEmpty() && stack.peek() <= arr[i]) {  
                stack.pop();  
            }  
            if (stack.isEmpty()) {  
                result[i] = -1;  
            } else {  
                result[i] = stack.peek();  
            }  
            stack.push(arr[i]);  
        }  
        for (int i = 0; i < n; i++) {  
            System.out.print(result[i] + " ");  
        }  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Vrithishree V J  
Email: 241901129@rajalakshmi.edu.in  
Roll no: 241901129  
Phone: 9344491726  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 9\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Sanjay is working on a program to merge two sorted linked lists into a single sorted list using Java's LinkedList class from the Collections framework. Given two sorted linked lists, he wants to merge them while maintaining the sorted order.

Write a Java program that:

Reads two sorted linked lists. Merges them into a single sorted linked list. Prints the merged list in ascending order.

##### ***Input Format***

The first line contains an integer m (the size of the first linked list).

The second line contains m space-separated integers (sorted).

The third line contains an integer n (the size of the second linked list).

The fourth line contains n space-separated integers (sorted).

### ***Output Format***

The output prints the merged linked list as space-separated integers.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 2

5 10

3

1 3 8

Output: 1 3 5 8 10

### ***Answer***

```
import java.util.*;
class MergeSortedLinkedLists {
// You are using Java

    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int m = sc.nextInt();
        LinkedList<Integer>list1 = new LinkedList<>();
        for(int i=0;i<m;i++){
            list1.add(sc.nextInt());
        }
        int n = sc.nextInt();
        LinkedList<Integer>list2 = new LinkedList<>();
        for(int i=0;i<n;i++){
            list2.add(sc.nextInt());
        }
        LinkedList<Integer>merged = new LinkedList<>();
        while(!list1.isEmpty() && !list2.isEmpty()){
            if(list1.peekFirst() <= list2.peekFirst()){
                merged.add(list1.removeFirst());
            }
        }
    }
}
```



```

    }
    else{
        merged.add(list2.removeFirst());
    }
}
while(!list1.isEmpty()){
    merged.add(list1.removeFirst());
}
while(!list2.isEmpty()){
    merged.add(list2.removeFirst());
}
for(int num:merged){
    System.out.print(num+" ");
}
//type your code here
}
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Aarav is developing a music playlist application where users can manage their favorite songs. He wants to implement a feature that allows users to reorder the playlist by moving a song from one position to another.

You need to implement a function that performs the following operations using a LinkedList:

Add songs to the playlist in the given order. Move a song from a specified position to another position in the playlist. Print the final playlist after all operations.

### **Input Format**

The first line of the input consists of an integer  $n$  representing the number of songs.

The next  $n$  lines, each containing a string representing a song name.

After the songs are given the next line contains an integer  $m$ , the number of

move operations.

The next m lines, each containing two integers x and y representing the move operation where the song at position x (0-based index) should be moved to position y.

### **Output Format**

The output prints the final playlist, each song on a new line.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

SongA

SongB

SongC

SongD

SongE

2

2 4

0 3

Output: SongB

SongD

SongE

SongA

SongC

### **Answer**

// You are using Java

```
import java.util.*;
```

```
public class Main{
```

```
    public static void main(String[] args){
```

```
        Scanner sc = new Scanner(System.in);
```

```
        int n = Integer.parseInt(sc.nextLine().trim());
```

```
        LinkedList<String>playlist = new LinkedList<>();
```

```
        for(int i=0;i<n;i++){
```

```
            playlist.add(sc.nextLine().trim());
```

```
        }
```

```

int m = Integer.parseInt(sc.nextLine().trim());
for(int i=0;i<m;i++){
    String[] move = sc.nextLine().split(" ");
    int x = Integer.parseInt(move[0]);
    int y = Integer.parseInt(move[1]);
    String song = playlist.remove(x);
    playlist.add(y,song);
}

for(String song:playlist){
    System.out.println(song);
}
}
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

A teacher is filtering a list of words provided by students. Some words contain too many vowels, making them difficult for a spelling competition. The teacher decides to remove all words that contain more than two vowels.

Help the teacher to implement it using ArrayList.

#### **Input Format**

The first line contains an integer N, representing the number of words in the list.

The next N lines contain a string representing the words (one per line).

#### **Output Format**

The output consists of words that contain two or less than two vowels, printed in the same order they appeared in the input. Each word is printed on a new line.

Refer to the sample output for the formatting specifications.

### Sample Test Case

Input: 1

sri

Output: sri

### Answer

```
import java.util.ArrayList;
import java.util.Scanner;

// You are using Java
class VowelFilter {
    //Type your code here
    public static void filterWords(int n,Scanner sc){
        ArrayList<String> words = new ArrayList<>();
        for(int i=0;i<n;i++){
            words.add(sc.nextLine());
        }
        for(String word:words){
            if(countVowels(word)<=2){
                System.out.println(word);
            }
        }
    }
    public static int countVowels(String word){
        int count=0;
        for(char c: word.toCharArray()){
            if("aeiou".indexOf(c)!=-1){
                count++;
            }
        }
        return count;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        sc.nextLine();
        VowelFilter.filterWords(n, sc);
        sc.close();
    }
}
```

```
}
```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Raman, a computer science teacher, is responsible for registering students for his programming class. To streamline the registration process, he wants to develop a program that stores students' names and allows him to retrieve a student's name based on their index in the list.

Raman has decided to use an ArrayList to store the names of students, as it provides efficient dynamic resizing and indexing.

Write a program that enables Raman to input the names of students and fetch a student's name using the specified index. If the entered index is invalid, the program should return an appropriate message.

##### **Input Format**

The first line of input consists of an integer  $n$ , representing the number of students to register.

The next  $n$  lines of input consist of the names of each student, one by one.

The last line of input is an integer, representing the index (0-indexed) of the element to retrieve.

##### **Output Format**

If the index is valid (within the bounds of the ArrayList), print "Element at index [index]: " followed by the element (student name as string).

If the index is invalid, print "Invalid index".

Refer to the sample output for formatting specifications.

##### **Sample Test Case**

Input: 5

Alice

Bob

Ankit

Alice

Prajit

2

Output: Element at index 2: Ankit

**Answer**

// You are using Java

import java.util.\*;

public class Main{

public static void main(String[] args){

Scanner sc = new Scanner(System.in);

int n = Integer.parseInt(sc.nextLine());

ArrayList<String> students = new ArrayList<>();

for(int i=0;i<n;i++){

students.add(sc.nextLine());

}

int index = Integer.parseInt(sc.nextLine());

if(index>=0 && index<students.size()){

System.out.println("Element at index "+index+": "+students.get(index));

}

else{

System.out.println("Invalid index");

}

}

}

**Status : Correct**

**Marks : 10/10**