

Library Table

```
CREATE TABLE Library (  
    book_id VARCHAR(10) PRIMARY KEY,  
    title VARCHAR(50) NOT NULL,  
    author VARCHAR(40),  
    category VARCHAR(30),  
    price DECIMAL(8,2) CHECK (price > 0),  
    issued CHAR(1) DEFAULT 'N'  
);
```

```
INSERT INTO Library (book_id, title, author, category, price, issued) VALUES  
( 'B101', 'Database Systems', 'Navathe', 'Education', 600, 'Y'),  
( 'B102', 'Python Programming', 'Mark Lutz', 'Education', 750, 'N'),  
( 'B103', 'Digital Circuits', 'Morris Mano', 'Engineering', 500, 'Y'),  
( 'B104', 'AI Basics', 'Russell', 'Technology', 900, 'N'),  
( 'B105', 'SQL Cookbook', 'Alex', 'Education', 800, 'Y');
```

-- 3. Display all books from category 'Education'.

```
SELECT * FROM Library WHERE category = 'Education';
```

-- 4. Find average price of books.

```
SELECT AVG(price) AS average_price FROM Library;
```

-- 5. Count total issued books.

```
SELECT COUNT(*) AS issued_books_count FROM Library WHERE issued = 'Y';
```

-- 6. List books with price BETWEEN 600 AND 900.

```
SELECT * FROM Library WHERE price BETWEEN 600 AND 900;
```

-- 7. Display books ordered by price ASC.

```
SELECT * FROM Library ORDER BY price ASC;
```

-- 8. Find titles starting with 'S'.

```
SELECT * FROM Library WHERE title LIKE 'S%';
```

-- 9. Update 'AI Basics' issued status to 'Y' (Fixed typo in raw question from 'V' to logical 'Y').

```
UPDATE Library SET issued = 'Y' WHERE title = 'AI Basics';
```

-- 10. Delete books priced < 600.

```
DELETE FROM Library WHERE price < 600;
```