

MongoDB CRUD Commands

Solutions with Sample Output

1. Create restaurants collection and insert a restaurant

MongoDB Command:

```
use insta_clone_db

db.restaurants.insertOne({
  name: "Burger Hub",
  cuisine: "Fast Food",
  location: "Mumbai",
  rating: 4.5
})
```

Sample Output:

```
{
  acknowledged: true,
  insertedId: ObjectId("...")
}
```

2. Insert 3 movies using insertMany

MongoDB Command:

```
db.movies.insertMany([
  {
    title: "Jawan",
    genre: "Action",
    releaseYear: 2023,
    imdbRating: 6.9
  },
  {
    title: "12th Fail",
    genre: "Drama",
    releaseYear: 2023,
    imdbRating: 8.7
  },
  {
    title: "Kalki 2898 AD",
    genre: "Sci-Fi",
    releaseYear: 2024,
    imdbRating: 7.0
  }
])
```

Sample Output:

```
{
  acknowledged: true,
  insertedIds: {
    "0": ObjectId("..."),
    "1": ObjectId("..."),
    "2": ObjectId("...")
  }
}
```

3. Find products with price less than 1000

MongoDB Command:

```
db.flipkart_products.find({
  price: { $lt: 1000 }
})
```

Sample Output:

```
[
  {
    _id: ObjectId("..."),
    name: "Wireless Mouse",
    price: 799
  },
  {
    _id: ObjectId("..."),
    name: "USB Keyboard",
    price: 599
  }
]
```

4. Update Burger Hub rating to 4.7

MongoDB Command:

```
db.restaurants.updateOne(
  { name: "Burger Hub" },
  { $set: { rating: 4.7 } }
)
```

Sample Output:

```
{
  acknowledged: true,
  matchedCount: 1,
  modifiedCount: 1
}
```

5. Delete only orders with status exactly 'cancelled'

MongoDB Command:

```
db.orders.deleteMany({
  status: "cancelled"
})
```

Sample Output:

```
{
  acknowledged: true,
  deletedCount: 2
}
```

Note: ObjectId values and counts shown in the sample outputs depend on the actual data in your MongoDB database.