

MongoDB Update Operators – Commands with Output

Practical MongoDB examples for playlists, restaurants, and products.

1. Using \$set – Update Playlist Genre

MongoDB Command:

```
db.playlists.updateOne(
  { name: "Evening Vibes" },
  { $set: { genre: "Chill" } }
)
```

Output:

```
{
  acknowledged: true,
  matchedCount: 1,
  modifiedCount: 1
}
```

```
db.playlists.find(
{ name: "Evening Vibes" },
{ _id: 0, name: 1, genre: 1 }
)
```

```
{ name: "Evening Vibes", genre: "Chill" }
```

2. Using \$unset – Remove Expired Temporary Offers

MongoDB Command:

```
db.restaurants.updateMany(
  { offerExpired: true },
  { $unset: { temporaryOffer: "" } }
)
```

Output:

```
{
  acknowledged: true,
  matchedCount: 2,
  modifiedCount: 2
}
```

The temporaryOffer field is removed from all matching restaurant documents.

If expiration is stored as a date:

```
db.restaurants.updateMany(
{ offerExpiry: { $lt: new Date() } },
{ $unset: { temporaryOffer: "" } }
)
```

3. Using \$push – Add a Song to an Existing Array

MongoDB Command:

```
db.playlists.updateOne(
  { _id: 101 },
  { $push: { songs: "Calm Waters" } }
)
```

Output:

```
{
  acknowledged: true,
  matchedCount: 1,
  modifiedCount: 1
}
```

Before:

```
{
  _id: 101,
  name: "Relaxing Sounds",
  songs: ["Ocean Breeze", "Soft Rain"]
}
```

After:

```
{
  _id: 101,
  name: "Relaxing Sounds",
  songs: ["Ocean Breeze", "Soft Rain", "Calm Waters"]
}
```

4. Using \$addToSet – Add a Unique Product Tag

MongoDB Command:

```
db.products.updateOne(
  { sku: "F12345" },
  { $addToSet: { tags: "trending" } }
)
```

Output:

First execution:

```
{
  acknowledged: true,
  matchedCount: 1,
  modifiedCount: 1
}
```

Running the same command again:

```
{
  acknowledged: true,
  matchedCount: 1,
  modifiedCount: 0
}
```

Example final document:

```
{
  sku: "F12345",
  name: "Smart Watch",
  tags: ["electronics", "wearable", "trending"]
}
```

5. Using \$inc – Decrease Stock Safely

MongoDB Command:

```
db.products.updateOne(
  {
    name: "Wireless Earbuds",
    stock: { $gt: 0 }
  },
  {
    $inc: { stock: -1 }
  }
)
```

Output:

If stock is 5 before purchase:

```
{
  name: "Wireless Earbuds",
  stock: 5
}
```

```
After purchase:
{
  name: "Wireless Earbuds",
  stock: 4
}
```

```
If stock is already 0:
{
  acknowledged: true,
  matchedCount: 0,
  modifiedCount: 0
}
```

The stock: { \$gt: 0 } condition prevents the stock value from becoming negative.

Summary

Operator	Purpose
\$set	Update a field value
\$unset	Remove a field
\$push	Add an item to an array
\$addToSet	Add an array item without duplicates
\$inc	Increase or decrease a numeric value