REQUETES SQL

1)
```
select *
from revend;
```

NR	NOMR	VILLER
R1	MENARDEAU	PARIS
R2	MACCIONE	ROME
R3	SCHULTZ	COLOGNE
R4	MUELLER	COLOGNE
R5	WADDLE	LONDRES
R6	OLAF	OSLO
R7	HIGGINS	LONDRES

2)
```
select *
from revend
where viller='LONDRES';
```

NR	NOMR	VILLER
R5	WADDLE	LONDRES
R7	HIGGINS	LONDRES

3)
```
select nf
from fvr
where nr='R1';
```

NF
F1
F2
F3

4)
```
select nf
from fvr
where nv='V1' and nr='R1';
```

NF
F1

5)
```
select nomr
from revend
where nr in (select nr
             from fvr
             nf='F1');
```

RNOM
MENARDEAU
MUELLER

6)
```
select rnom
from revend
where nr not in (select nr
                 from fvr);
```

no records selected

7)
```
select nf
from fvr
where nr='R1' and nf in (select nf
                         from fvr
                         where nr='R2');
```

NF
F2
F3

8)
```
select distinct nf
from fvr, voiture
where fvr.nv=voiture.nv and nr='R1' and
                            voiture.couleur='ROUGE';
```

NF
F1

9.1)
```
select nv
from fvr
where nr in (select nr
             from revend
             where viller='LONDRES');
```

NV
V3
V5
V3
V5
V6

9.2) SELECT Distinct FVR.NV V1
FROM FVR WHERE
FVR.NR NOT IN (
SELECT FVR.NR FROM FVR, REVEND R
WHERE FVR.NR = R.NR
AND R.Ville = "Lon"
AND (*))

10)
```
select nf
from fvr
where nr in (select nr
             from revend
             where viller='LONDRES' or viller='PARIS'
               and nv in (select nv
                          from voiture
                          where couleur='ROUGE'));
```

NF
F1
F2
F2
F4
F5
F5

AND NR IN
(SELECT NR FROM REVEND
WHERE Viller = 'LONDRES')

(*) NOT EXISTS (SELECT NR
FROM FVR WHERE
FVR.NR = R.NR and

11)

```
select fvr.nv
from fvr,revend,fourn
where fvr.nr=revend.nr and fvr.nf=fourn.nf
                       and revend.viller=fourn.villef;
```

```
NV
--
V3
V3
V2
V4
V5
V6
V3
V1
V6
```

12)

```
select fvr.nr
from fvr, revend, fourn
where fvr.nr=revend.nr and fvr.nf=fourn.nf
      and revend.viller<>fourn.villef;
```

```
NR
--
R1
R2
R2
R2
R2
R2
R3
R3
R4
R4
R5
R5
R6
R7
R7
```

13)

```
select nr
from revend
where not exists (select *
                  from fourn,voiture,fvr
                  where fourn.villef='LONDRES' and
                        voiture.couleur=rouge and
                        fourn.nf=fvr.nf and
                        voiture.nv=fvr.nv and
                        revend.nr=fvr.nr);
```

```
NR
--
R2
R5
R6
```

14)

```
select nf
from fourn
where villef<>'PARIS' and code in (select code
                                   from fourn
                                   where villef='PARIS');
```

```
NF
--
F5
```

15)

```
select nv
from fvr x
where not exists (select *
                  from revend
                  where viller='LONDRES' and not exists
                        (select *
                         from fvr
                         where nr=revend.nr and
                               nv=x.nv));
```

```
NV
--
V3
V3
V3
V3
V3
V3
V3
V5
V3
V5
V5
V3
V5
```

16)

```
select nr
from fvr x
where not exists (select *
                  from fvr y
                  where nf='F1' and not exists
                        (select *
                         from fvr z
                         where nr=x.nr and
                               nv=y.nv));
```

```
NR
--
R1
R4
R1
R4
R1
R4
R4
R4
R4
R4
R4
```

17)
```
select nr
from fvr
where nv in (select nv
             from fvr
             where nf='F1' and
             nv not in (select nv
                        from fvr
                        where nf<>'F1'));
```

no records selected

Nenhuma
nr