

[Home](#) > [My Courses](#) > [OCAJP 8 Training Course -1Z0 808](#) > [Practice Test II](#) > **Report**

Search Courses



## Practice Test II

**Attempt**

1

**Completed on**

Wednesday , 04 September 2019 , 06:42 PM

**Marks Obtained**

0 / 70

**Time Taken**

00 H 00 M 15 S

**Your score is**

0.0%

**Result**

Fail

**Mode**

Exam

## Domains wise Quiz Performance Report

<b>No</b>	1
<b>Domain</b>	Creating and Using Arrays
<b>Total Question</b>	10
<b>Correct</b>	0
<b>Incorrect</b>	0
<b>Unattempted</b>	10
<b>Marked for review</b>	0

No	2
Domain	Working with Methods and Encapsulation
Total Question	9
Correct	0
Incorrect	0
Unattempted	9
Marked for review	0
No	3
Domain	Handling Exceptions
Total Question	4
Correct	0
Incorrect	0
Unattempted	4
Marked for review	0
No	4
Domain	Working with Inheritance
Total Question	12
Correct	0
Incorrect	0
Unattempted	12
Marked for review	0
No	5
Domain	Java Basics
Total Question	6
Correct	0
Incorrect	0
Unattempted	6
Marked for review	0

No	6
Domain	Using Operators and Decision Constructs
Total Question	1
Correct	0
Incorrect	0
Unattempted	1
Marked for review	0
No	7
Domain	Using Operators and Decision Constructs
Total Question	11
Correct	0
Incorrect	0
Unattempted	11
Marked for review	0
No	8
Domain	Using Loop Constructs
Total Question	5
Correct	0
Incorrect	0
Unattempted	5
Marked for review	0

No	9
Domain	Working With Java Data Types
Total Question	8
Correct	0
Incorrect	0
Unattempted	8
Marked for review	0
No	10
Domain	Working with Selected classes from the Java API
Total Question	4
Correct	0
Incorrect	0
Unattempted	4
Marked for review	0
Total	Total
All Domain	All Domain
Total Question	70
Correct	0
Incorrect	0
Unattempted	70
Marked for review	0

### Review the Answers

Sorting by


All

#### Question 1

Unattempted

Domain :Creating and Using Arrays

Which of the following is valid array declaration?

- A. `String strs[][] = new String[][1];`
- B. `String strs[][] = new String[3][];` 
- C. `String strs[2][] = new String[][];`
- D. `String strs[][] = new String[3];`

E. `String strs[][] = new String[][];`

**Explanation:**

**Explanation:**

Option B is the correct answer.

When we create multi-dimensional arrays, we need to give first dimension size. So, when you create a two-dimensional array, we must give the number of rows when we initialize it. So, here options A and E are incorrect.

Option B is correct since it creates a two-dimensional array without passing the size for columns which is legal, then we can define a different number of columns for each row.

**Reference** :<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/arrays.html>

Ask our Experts

Rate this Question? 😊 😞


Question 2

Unattempted

Domain :Creating and Using Arrays

What is the total number of integers that array nums can hold in this code fragment?

```
int nums[][] = new int[3][3];  
nums[0] = new int[2];
```

- A. 6
- B. 8 
- C. 9
- D. Not valid array statement

**Explanation:**

**Explanation:**

Option B is the correct answer.

Here we have created a two-dimensional array with three rows and each of row will have three columns, so nums array can hold total 9 values. But then we have changed the first row of the two-dimensional array to refer array which can hold only two values. So, now total elements allowed will be 8. Hence, option B is correct.

**Reference** :<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/arrays.html>

Ask our Experts

Rate this Question? 😊 😞

Question 3

Unattempted

Domain :Creating and Using Arrays

Which of the following is a correct anonymous array?

- A. `new Integer[4]{1,2,3,4};`
- B. `new Integer{1,2,3,4};`
- C. `new Integer[3]{1,2,3,4};`
- D. `new Integer[]{1,2,3,4};` ✓
- E. None of the above.

**Explanation:**

**Explanation:**

**Option D is the correct answer.**

Following is the correct syntax for creating the anonymous array.

```
type[[ elements separated by comma.]
```

Remember that you do not specify a size when using anonymous array creation syntax. The size is derived from the number of items (comma-separated) between the curly braces. So, option D is correct.

As explained above options A and C incorrect.

Option B is incorrect as [] is missing.

## Reference

[:http://docs.oracle.com/javase/tutorial/java/nutsandbolts/arrays.html](http://docs.oracle.com/javase/tutorial/java/nutsandbolts/arrays.html)

Ask our Experts

Rate this Question? 😊 😞


## Question 4

Unattempted

Domain :Creating and Using Arrays

What will be the output of this program?

```
1    public class Whiz{  
2        public static void main(String[] args) {  
3  
4            final int [] ints = new int[3];  
5            int len = ints.length;  
6            ints[1]++;  
7            for(int i : ints)  
8                System.out.print(i);  
9        }  
10    }
```

- A. 000
- B. 100
- C. 010 
- D. An Exception is thrown.
- E. Compilation fails due to an error at line 6.

## Explanation:

**Explanation:**

Option C is the correct answer.

At line 4, we have defined an integer array with final, but it doesn't mean that all values in the array are final. It means only the reference is final, so at line 6, there won't be any error. All array elements are initialized to their default values when array initialized, hence all elements of the array will be 0, at line 6 second element will be increased by one. So, when using enhanced for loop, 010 will be printed. Hence, option C is correct.

**Reference** :<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/arrays.html>

---

Ask our Experts

Rate this Question? 😊 😞


**Question 5****Unattempted****Domain :Creating and Using Arrays**

What will be the output of this program?

```
1    public class Whiz{  
2.  
3        public static void main(String[] args) {  
4.  
5            int [][]ints = new int[3][2];  
6            ints[0] = new int[3];  
7            ints[2] = {1,2,3};  
8            System.out.print(ints[0].length + ints[2].length);  
9        }  
10    }
```

A. 4



- B. 5
- C. 6
- D. An `ArrayIndexOutOfBoundsException` is thrown
- E. Compilation fails 

---

**Explanation:**

Explanation:

Option E is the correct answer.

This code fails to compile due to an error at line 7, because the array constants can only be used in initializers. So, we can't use "{1,2,3}" at line 7.

**Reference** : <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/arrays.html>

---

Ask our Experts

Rate this Question?  

---

**Question 6**


Unattempted

Domain :Creating and Using Arrays

What will be the output of this program?

```
1    import java.util.Arrays;
2
3    public class Whiz {
4        public static void main(String[] args) {
5            int [ ][ ] ints = new int[2][1];
6
7            Arrays.sort(ints[1]);
8
9            System.out.print(Arrays.toString(ints[1]));
10        }
```

11.     }

- A.   [0, 0, 0]
- B.   [null,null,null]
- C.   null
- D.   NullPointerException 
- E.   Compilation fails

---

**Explanation:**

Explanation:

Option D is the correct answer.

Methods in the Arrays class throw a NullPointerException, if the specified array reference is null. So, here we haven't initialized the ints[1], so it is null. Hence, passing it to Arrays sort method throws a NullPointerException. So, option D is correct.

**Reference:**

<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/arrays.html>

---

Ask our Experts


Rate this Question?  

**Question 7****Unattempted****Domain :Creating and Using Arrays**

What will be the output of this program?

```
1      import java.util.Arrays;
2
3      public class Program{
4          public static void main(String[] args) {
5
```

```
6.      int[] ints = {2,-1,4,5,3};  
7.      Arrays.sort(ints);  
8.      System.out.print(Arrays.binarySearch(ints, -1));  
9.      }  
10.    }
```

- A. 0 
- B. 1
- C. -1
- D. true
- E. Compilation fails

---

**Explanation:**

Explanation:

Option A is the correct answer.

Arrays class has binary Search method which can use to search elements in a sorted array.

```
public static int binarySearch(int[] a,int key)
```

This method searches the specified array of ints for the specified value using the binary search algorithm. The array must be sorted (as by the sort(int[]) method) prior to making this call. If it is not sorted, the results are undefined.

Since we have sorted the array, binary search will function properly. Since the array is sorted, index position of -1 will be 0, so the binary search will return 0. Hence, option A is correct.

**Reference** : <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/arrays.html>

Ask our Experts

Rate this Question? 😊 😞

## Question 8

Unattempted

Domain :Working with Methods and Encapsulation

What will be the output of this program?

```
1    class Whiz{  
2        public static void main(String args[]){  
3            new Whiz().meth();  
4        }  
5  
6        public void meth()throws Exception{  
7            for(int x=0;x>5;x++)  
8                System.out.print(x);  
9        }  
10    }
```

- A. 01234
- B. An exception is thrown at runtime.
- C. Code will cause a never ending loop
- D. Compilation fails ✓
- E. No output

**Explanation:**

Explanation:

Option D is the correct answer.

The method `meth()` is declared as an exception, so when we call that method within another method, the calling method must handle or declare the exception. Otherwise, compilation will not succeed.

## REFERENCE

:<http://docs.oracle.com/javase/tutorial/essential/io/fileOps.html#exception>

Ask our Experts

Rate this Question? 😊 😞

Question 9


Unattempted

Domain :Handling Exceptions

What will be the output of this program?

```
1      class Whiz {  
2          public static void main(String args[]){  
3              int x = 5, y=10;  
4              try {  
5                  y /=x;  
6              }  
7              catch(Exception e){  
8                  System.out.print("error");  
9              } finally {  
10                 System.out.print("finally");  
11             }  
12         }  
13     }
```

- A. error finally
- B. error
- C. Compilation fails

- D. finally 
- E. No output

---

**Explanation:**

Option D is the correct answer.

If we write catch block for checked exceptions and if there is no chance of that checked exception from the try block, we get compile time error. But this rule is not applicable for Exception class even though it is checked exception. There will be no exception occurred in try block, so catch clause won't run but finally runs as always. Hence, finally will be printed; so option D is correct

---

Ask our Experts

Rate this Question?  


---

**Question 10**

Unattempted

Domain :Handling Exceptions

Which of the following exception is thrown by JVM when code uses a negative size while initializing an array?

- A. NullPointerException
- B. NumberFormatException
- C. IllegalArgumentException
- D. NegativeArraySizeException 
- E. ArrayIndexOutOfBoundsException

---

**Explanation:**

Explanation:

Option D is the correct answer.

Option D is correct since the NegativeArraySizeException is thrown when we tried to initialize an array with negative size.

The NullPointerException is thrown by the JVM when there is a null reference where an object is required. So, option A is incorrect.

The NumberFormatException thrown by the programmer when an attempt is made to convert a string to a numeric type but the string doesn't have an appropriate format. So option B is incorrect.

Option C is incorrect since the IllegalArgumentException thrown by the programmer to indicate that a method has been passed an illegal or inappropriate argument.

#### REFERENCE:

<http://docs.oracle.com/javase/8/docs/api/java/lang/Exception.html>

Ask our Experts

Rate this Question? 😊 😞

#### Question 11


Unattempted

Domain :Handling Exceptions

What will be the output of this program?

```
1      class Whiz {  
2          public static void main(String args[] ) {  
3              try {  
4                  new Whiz().meth();  
5              } catch(ArithmeticException e) {  
6                  System.out.print("Arithmetic");  
7              } finally {  
8                  System.out.print("final 1");  
9              } catch(Exception e) {  
10                 System.out.print("Exception");  
11             } finally {  
12                 System.out.print("final 2");  
13             }  
14         }  
}
```

```
15.  
16.      public void meth()throws ArithmeticException {  
17.          for(int x = 0; x < 5; x++) {  
18.              int y = (int) 5/x;  
19.              System.out.print(x);  
20.          }  
21.      }  
22.  }
```

- A. Arithmetic final 1
- B. Exception final 2
- C. Arithmetic final 2
- D. Exception
- E. Compilation fails 

---

**Explanation:**

Explanation:

Option E is the correct answer.

You can't have multiple finally clauses. In this code, the first finally clause causes the end of the try clause. So, other catch clause appeared like a catch clause without a try clause, so compilation fails.

**REFERENCE**    :<http://docs.oracle.com/javase/tutorial/essential/exceptions/catch.html>

---


Ask our Experts

Rate this Question?  



What will be the output of this program?

```
1      interface I{
2          void meth();
3      }
4
5      class A implements I{
6          void A(String s){
7              }
8          public void meth(){
9              System.out.print("A");
10         }
11     }
12
13     class C extends A implements I{
14         public void meth(){
15             System.out.print("C");
16         }
17     }
18
19     class Whiz{
20         public static void main(String args[]){
21             A a = new A();
22             C c1 = (C)a;
23             c1.meth();
24         }
25     }
```

- A. A
- B. C
- C. An exception will be thrown at runtime 
- D. Compilation fails due to an error at line 6
- E. Compilation fails due to multiple errors

---

**Explanation:**

Explanation:

Option C is the correct answer.

Here, we try to cast a superclass reference to lower class reference, but superclass reference refers to the superclass object. So, casting will cause a ClassCastException.

**REFERENCE** :<http://docs.oracle.com/javase/tutorial/essential/exceptions/catch.html>

---

Ask our Experts

Rate this Question?  


---

**Question 13**

Unattempted

Domain :Java Basics

Java source code will be compiled in to \_ \_ \_ \_ \_ file.

- A. .java
- B. .class 
- C. .exe
- D. .byte
- E. None of the above

---

**Explanation:**

**Explanation:**

Option B is the correct answer.

When we compile the java source we get the bytecode. Java bytecode is the instruction set of the Java virtual machine. Each bytecode is composed by one, or in some cases two, bytes that represent the instruction (opcode), along with zero or more bytes for passing parameters. So, option B is correct.

**REFERENCE** :<https://docs.oracle.com/javase/tutorial/getStarted/application/index.html>

---

Ask our Experts


Rate this Question? 😊 😞

Question 14

Unattempted

Domain :Java Basics

Which of the following command can be used to compile the code?

- A. javac 
- B. java
- C. javadoc
- D. jar
- E. compile

**Explanation:**

Explanation:

Option A is the correct answer.

The compiler is invoked by the javac command. When compiling a java class, you must include the filename with java extension. Hence, the option A is correct.

To execute java program we can use java command but can't use it for compiling.

**REFERENCE:**

<https://docs.oracle.com/javase/tutorial/getStarted/application/index.html>

---

Ask our Experts

Rate this Question? 😊 😞


## Question 15

Unattempted

Domain :Using Operators and Decision Constructs

What will be the output of this program?

```
1 public class Whiz{  
2  
3     public static void main(String args[]){  
4         int x = 10, y = 12;  
5         System.out.println("Answer is :"+ x +y);  
6     }  
7 }
```

- A. Answer is : 22
- B. Answer is : 1012 
- C. Answer is :
- D. Compilation fails

---

**Explanation:****Explanation:**

Option B is the correct answer.

In the printing statement at line 5, we have used the string value first, so the + will work as the concatenation operator in "x+y" hence 1012 will be printed. So, option B is correct.

**REFERENCE** :<https://docs.oracle.com/javase/tutorial/getStarted/application/index.html>

[Ask our Experts](#)

Rate this Question? 😊 😞

## Question 16

Unattempted

Domain :Java Basics

Which of the following statement is true?

- A. class declaration should come before import statement.
- B. Package statement should come after class statement.
- C. Comments can come before package statement. ✓
- D. Constructor should appear before any other statement of a class.
- E. None of the above.

**Explanation:**

Explanation:

Option C is the correct answer.

The correct order of the statements should be

package statement

import statement

class statement

Except above comments can be appeared on any place. So option C is correct.

Option D is incorrect since we can place constructors before or after other statements, also middle of other statements.

**REFERENCE** :<https://docs.oracle.com/javase/tutorial/getStarted/application/index.html>

Ask our Experts

Rate this Question? 😊 😞

## Question 17

Unattempted

Domain :Java Basics

which of the following statement compiles successfully?

- A. `final int / array[] = {1,2,3};`
- B. `final int // array[] = {1,2,3};`
- C. `final int /** */ array[] = {1,2,3};` ✓
- D. All of the above
- E. None of the above

**Explanation:**

Explanation:

Option C is the correct answer.

We can have following comments in java

`/* text */` - The compiler ignores everything from `/*` to `*/`.

`// text` - The compiler ignores everything from `//` to the end of the line.

`/** documentation */`

This is a documentation comment and in general, it's called doc comment. The JDK javadoc tool uses doc comments when preparing automatically generated documentation.

Option C is correct since it doesn't affect the complete statement. Option A is incorrect since using `/` for comments is invalid in java. Option B is incorrect since because of `//` the statement will be incomplete.

**REFERENCE** :<https://docs.oracle.com/javase/tutorial/getStarted/application/index.html>

Ask our Experts

Rate this Question? 😊 😞


## Question 18

Unattempted

Domain :Using Operators and Decision Constructs

What will be the output of this program?

```
1 public class Whiz{  
2  
3     static int x = 2;  
4     public static void main(String args[]){  
5         if( x > 1){  
6             x++;  
7             int x = 4;  
8         }  
9         System.out.println(x);  
10        final int x = 10;  
11    }  
12 }
```

- A. 2
- B. 3 
- C. 4
- D. 10
- E. Compilation fails

---

Explanation:

**Explanation:**

**Option B is the correct answer.**

In the given code, we have defined a static variable x with value 2 hence at line 5 if block will be executed, and increment the value of x by one, at line 7, defining new integer with the same name will shadow the class variable x, but the scope of that variable is limited to the if block. Hence, the value of the class variable will be printed which is 3. So, option B is correct.

The integer variable x at line 10 is declared after the printing statement, so it won't affect any statement above the line 10, but if there was more code after line 10, then that x would shadow the class variable x.

**REFERENCE** :<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/variables.html>

---

Ask our Experts

Rate this Question? 😊 😞

Question 19

Unattempted

Domain :Working with Methods and Encapsulation

What will be the output of this program?

```
1 public class Whiz{
2
3     static int x = 2;
4     static int z;
5     public static void main(String args[]){
6         System.out.println(x+z);
7     }
8
9     static{
10         int x = 3;
11         Z = X;
```



12.        }

13. }

A.    2

B.    4

C.    5 

D.    6

E.    Compilation fails

---

**Explanation:**

Explanation:

Option C is the correct answer.

At line 10, we have defined new integer with value 3, it shadows the class variable x. Hence, the value of z will be 3. So, 2+3 will print 5 as the output. Hence, option C is correct.

**REFERENCE**     : <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/variables.html>

---

Ask our Experts

Rate this Question?  

Question 20

Unattempted


Domain :Working with Methods and Encapsulation

You need to create a class to store information about Books contained in a library. The library class has provided a static method to add Book. When each book is added, the library should update the number of books field, which records the total number of books.

Which of the following variable scope is best suited for that field?

A.    Method parameter

B.    Instance variable

- C. Static variable 
- D. Global variable
- E. Local variable

---

**Explanation:****Explanation:**

Option C is the correct answer.

To store the number of books in the library, you can't use an instance variable. Because Library class uses a static method to add a book in the library. The static method can't access the instance variable. So, you must take static variable to store the number of books in the library. The static variable in Library class will be incremented when static method of Library class gets called. when you create an object for Book class, Book class constructor calls Library class static method which adds a book to the library and updates the number of the books. To know the number of books in library, just call static variable of Library class which gives the number of books. So, option C is correct.

**REFERENCE :** <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/variables.html>

---

Ask our Experts


Rate this Question?  

Question 21

Unattempted

Domain :Java Basics

Which of the following is correct static import statement?

- A. `import java.lang.Math.*;`
- B. `import static java.lang.Math.abs();`
- C. `static import java.lang.Math.abs();`
- D. `static import java.lang.Math;`
- E. `import static java.lang.Math.abs;` 

---

**Explanation:****Explanation:**

**Option E is the correct answer.**

Correct syntax for static import is

```
import static [class member/s]
```

Option A is incorrect since it is non-static import as we haven't used static there.

Option B is incorrect since to import a specific static method it is illegal to use parentheses, a just name should be used.

Options C and D are incorrect since we have used static before import there, which makes them invalid.

Option E is correct since we have followed correct syntax there.

**Reference** :<http://docs.oracle.com/javase/tutorial/java/javaOO/classes.html>

Ask our Experts

Rate this Question? 😊 😞

Question 22

Unattempted


Domain :Using Loop Constructs

Given :

```
1    class Whiz {  
2        public static void main(String args[] ) {  
3            int [] a = {1,2,3,4,5,6};  
4            int i = a.length - 1;  
5  
6            while (i >= 0) {  
7                if (i == 2) continue;  
8                System.out.print(a[i]);  
9                i--;  
10           }  
11       }
```

12.     }

What is the output?

- A.   65
- B.   654
- C.   123
- D.   Compilation fails
- E.   Will print 654 and then goes to never ending loop. 

**Explanation:**

**Explanation:**

Option E is the correct answer.

When the value of i is 2, the "if statement" will call continue. After that, every time the value of i will be 2 as it can't reach to i-- statement, where it cause a never ending loop.

**Reference :** <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/branch.html>

Ask our Experts

Rate this Question?  

Question 23


Unattempted

Domain :Using Loop Constructs

What will be the output of this program?

```
1     class Whiz {  
2         public static void main(String args[ ]) {  
3             int [ ] a = {1,2,3};  
4  
5             for(int j : a) {
```

```
6.          if (j == 2) continue;
7.          for(int x = 0; x < 3; System.out.print(x)) {
8.              x++;
9.          }
10.         }
11.     }
12. }
```

- A. 123
- B. 123123 
- C. 123123123
- D. Compilation fails
- E. Will print 123 and then goes to never ending loop

---

**Explanation:****Explanation:**

Option B is the correct answer.

This is a nested loop. When j is equal to two, current iteration stops as if calls continue. So, there will be 123 on first and third iteration process.

**Reference**

:<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/branch.html>

---

Ask our Experts

Rate this Question?  


Question 24

Unattempted

Domain :Using Loop Constructs

Which of the following will print all the elements of the array when inserted at line 10?

```
1  class Whiz{  
2      public static void main(String args[]){  
3  
4          int array[][] = {{3,2,1},{5,4,2},{0,8,7}};  
5  
6              outer:for(int x = 0, k=0; x<3; x++){  
7                  k=0;  
8                  inner:while(true){  
9                      System.out.print(array[x][k++]);  
10                     // insert here  
11                 }  
12             }  
13         }  
14     }
```

- A. if (k == 3) break outer;
- B. if (k == 3) break inner ; 
- C. if (k > 3) break;
- D. break;
- E. None of the above.

---

**Explanation:**

Explanation:

Option B is the correct answer.

Option B is correct as it will print all the elements of the array. As every array has three elements we should break the inner loop as soon as k becomes 3, as then it will cause an exception.

Option A is incorrect as the output will only contain elements of the array[0] because it breaks the outer loop.

Options C and E are incorrect as they cause an `ArrayIndexOutOfBoundsException`.

Option D is incorrect as the output will only contain the first elements for each array.

**Reference :** <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/branch.html>

---

Ask our Experts

Rate this Question? 😊 😞

Question 25

Unattempted

Domain :Using Loop Constructs

Which of the following statement is true?

- A. When we need to execute a certain section, we can use the "while" or the "for" statements.
- B. The "do/while" loop allows to define any number of possible execution paths.
- C. The "while" and the "do-while" are equivalent.
- D. The "while" evaluates its conditional expression at the bottom of the loop
- E. The "for" loops has two forms, one of them was designed for looping through collections and arrays



---

**Explanation:**

**Explanation:**

**Option E is the correct answer.**

Option E is correct as "for" loops has two forms, for and enhanced for. The later one is designed to iterate through elements of a collection or array.

Option A is incorrect because to execute a certain section of code then we have to use "if" of "switch".

Option B is incorrect as we can't use loops to select different execution paths, for that we need to use control statements like if, switch.

Option C is incorrect as "while" and "do-while" are not same.

Option D is incorrect since the "while" loop evaluates its expression at the top of the loop.

**Reference** :<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/while.html>

Ask our Experts

Rate this Question? 😊 😞

### Question 26

Unattempted

Domain :Using Loop Constructs


What will be the output of this program?

```
1  class Whiz{  
2      public static void main(String args[]){  
3          int []a = {1,2,3,4};  
4          int i = a.length - 1;  
5  
6          while(true){  
7              while(i>=0){  
8                  System.out.print(a[i]);  
9                  i--;  
10             }  
11         }  
12     }  
13 }
```

A. 1234

B. 4321



- C. 4321 and will create never ending loop 
- D. No output
- E. Compilation fails

---

**Explanation:****Explanation:**

Option C is the correct answer.

Using "while(true)" at line 6, will create an endless loop, but in its first iteration, all the elements of the array will be printed in descending order since the initial value of the variable "i" is 3.

Option C is correct as the output will be 4321 followed by endless loop because of "while(true)".

Options A and B are incorrect since a never ending loop is created.

Option D is incorrect as "4321" is produced in the first iteration of the first while loop.

Option E is incorrect as the code compiles successfully.

**Reference:**

<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/while.html>

---

Ask our Experts

Rate this Question?  


---

**Question 27****Unattempted****Domain :Using Operators and Decision Constructs**

What will be the output of this program?

```
1    public class Whiz {  
2        public static void main(String [ ] args) {  
3            int x = 1;  
4            int y = 10;  
5
```

```
6.          if((x*=3) == y) {  
7.                      System.out.println(y);  
8.          } else {  
9.                      System.out.println(x);  
10.         }  
11.     }  
12. }
```

- A. 1
- B. 3 
- C. 10
- D. Compilation fails due to an error at line 6.
- E. Compilation fails due to multiple errors.

---

**Explanation:**

Explanation :

Option B is the correct answer.

At line 6, we have used parentheses to change the value of x. Inside the parentheses, we have used assignment operator which will result in x multiplied by 3. But the condition of the if block won't be true since the value of y, is 10. Hence, else block executes and print 3, so option B is correct.

**REFERENCE** : <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/if.html>

---

Ask our Experts

Rate this Question?  

Question 28


Unattempted

Domain :Using Operators and Decision Constructs

Which of the following will compile successfully when inserted at line 4?

```
1 public class Whiz {
```

```
2.      public static void main(String args[] ) {  
3.  
4.          // insert here  
5.          final int y = 2;  
6.  
7.          switch(x+y) {  
8.              case x+1 : {System.out.print("A");}  
9.              case 1   : System.out.print("B");  
10.             default  : System.out.print("default"); break;  
11.             case y    : System.out.print("C");  
12.          }  
13.      }  
14.  }
```

- A. final int x = -1; 
- B. int x = -1;
- C. int x = 1;
- D. final int x = 1;
- E. All of the above

---

**Explanation:**

Explanation:

Option A is the correct answer.

If we use a variable for the case, it needs to be a compile time constant, so options B and C are incorrect.

Option D is incorrect as there is a case with value 2, so if we use 1 as the value of x then there will be two cases with value 2, which is illegal.

Option A is correct since there if we use -1 then the case x+1 will be 0, so there won't be any duplicate cases.

**Reference** :<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/switch.html>

Ask our Experts

Rate this Question? 😊 😞

Question 29


Unattempted

Domain :Using Operators and Decision Constructs

What will be the output of this program?

```
1 public class Whiz {  
2     public static void main(String args[]) {  
3  
4         final int array [] = {1,2,3};  
5  
6         switch(2) {  
7             case array[0] : {System.out.print("A");}  
8             case array[1] : System.out.print("B");  
9             default      : System.out.print("default"); break;  
10            case array[2] : System.out.print("C");  
11        }  
12    }  
13 }
```

A. ABdefault

- B. default
- C. Bdefault
- D. C
- E. Compilation fails 

---

**Explanation:**

Explanation:

Option E is the correct answer.

Option E is correct as the code fails to compile due to line case statements. When using a primitive or reference type variables as case constants, we should keep in mind that they should be compile-time constant. But in given code, we have used variables from the primitive array, even the array is final, the elements of the array are not final hence code fails to compile.

**Reference** : <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/switch.html>

---

Ask our Experts

Rate this Question?  

Question 30

Unattempted

Domain :Using Operators and Decision Constructs

What will be the output of this program?

```
1 public class Whiz {  
2     public static void main(String [ ] args) {  
3         String out = "0";  
4         int i = -1, j = -5;  
5         if (i < 5)  
6             if (j > 0)  
7                 if (i > j)
```

```
8.         out += "1";

9.         else out += "2";


10.        else out += "3";

11.        else out += "4";

12.        System.out.println(out);

13.    }

14. }
```

- A. 01
- B. 02
- C. 03 
- D. 04
- E. Compile time error.

---

**Explanation:**

Explanation :

Option C is the correct answer.

While using if, we need to remember when there is no curly braces to group the if statements. The if consider only the next line as statement related to the if. So, in given code, first if consider next if condition as its statement, and that if at line 6 consider if at line 7 as its statement to execute.

At line 5, if test becomes true hence next if at line 6 is tested and it becomes false, so its else block at line 10 is executed and concat 3 to string. So, option C is correct.

**REFERENCE** : <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/if.html>

---

Ask our Experts

Rate this Question?  


## Question 31

Unattempted

Domain :Using Operators and Decision Constructs

What will be the output of this program?

```
1 public class Whiz {  
2     public static void main(String args[] ) {  
3  
4         int whiz = 0;  
5  
6         if (whiz > 0) {  
7             System.out.print("A");  
8         }  
9         System.out.println();  
10        else  
11        System.out.print("B");  
12    }  
13 }
```

- A. A
- B. B
- C. A B
- D. No output
- E. Compile fails 

**Explanation:**

Explanation:

Option E is the correct answer.

This code fails to compile since we can't include other statements between if and else. So, line 9 printing statement included between if and else results in a compile time error.

**REFERENCE** :<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/if.html>

Ask our Experts

Rate this Question? 😊 😞

Question 32

Unattempted

Domain :Using Operators and Decision Constructs

What will be the output of this program?

```
1 public class Whiz{  
2     public static void main(String args[]){  
3         int marks = 60;  
4  
5         if(marks >= 40) System.out.println("C");  
6         else if(marks >= 60) System.out.println("B");  
7         else if(marks >= 75) System.out.println("A");  
8         else System.out.println("D");  
9     }  
10 }
```

A. A

B. B

C. C 

D. D

E. Compilation fails



**Explanation:**

Explanation:

Option C is the correct answer.

This code compiles successfully and prints C as the output so option C is correct. But if you have a look carefully you can see that logic of using if else here is incorrect since any value greater than 40 will end up printing C which it is not supposed to. To fix this we need to use check for greater values first.

**REFERENCE** :<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/if.html>

---

Ask our Experts

Rate this Question? 😊 😞

**Question 33****Unattempted**

Domain :Using Operators and Decision Constructs

Given the variable "point" is an integer and based on its value you need to print "n" or "p", here "n" for negative number while "p" for positive number, which of the following printing statement you can use for that?

Assume zero is a positive integer.

- A. `System.out.println(point >= 0 ? "p": "n");` ✓
- B. `System.out.println(point >= 0 : "p"? "n");`
- C. `System.out.println(if(point >= 0 ) "p";else "n");;`
- D. `System.out.println(point >= 0 : "p"; "n");`
- E. None of the above.

**Explanation:**

Explanation:

Option A is the correct answer.

The correct syntax of using the ternary operator is

[condition]?[statement to execute when true]:[statement to execute when false]

So, option A is correct since it follows the correct syntax.

Options B and D are incorrect since we have used incorrect syntax for the ternary operator.

Option C is incorrect since we are not allowed to use if inside a printing statement.

**REFERENCE** :<https://docs.oracle.com/javase/tutorial/java/nutsandbolts/if.html>

Ask our Experts

Rate this Question? 😊 😞

### Question 34

Unattempted

Domain :Using Operators and Decision Constructs

Which of the following will produce output 8 when inserted at line 7?

```
1 public class Whiz {  
2     public static void main(String args[] ) {  
3         int x = 1;  
4         int y = 2;  
5         int z = 3;  
6  
7         // insert here  
8     }  
9 }
```

- A. `System.out.println((z / y) + z*2);`
- B. `System.out.println(z / (y + z)*2);`
- C. `System.out.println((z / y + z)*2);` ✓
- D. `System.out.println(z / y + z*2);`
- E. Compilation fails.

**Explanation:****Explanation:**

**Option C is the correct answer.**

In given code, we need to use parentheses to change the operator's precedence.

Option A is incorrect since  $(z/y)$  will result in 1 and then  $z*2$  will result in 6, so 7 will be printed.

Option B is incorrect since  $(y+z)$  will happen first and then it will divide  $z$  which returns 0. So, the final output will be 0.

Option C is correct since it will print 8. In statement  $(z / y + z)*2$ ,  $(z / y + z)$  will result 4,  $(1+3)$  and then it will be multiplied by 2 which result 8.

**REFERENCE** :<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/expressions.html>

Ask our Experts


Rate this Question? 😊 😞

**Question 35****Unattempted****Domain :Working With Java Data Types**

What will be the output of this program?

```
1 public class Whiz{
2     public static void main(String args[]){
3         Integer i = 10;
4         Double d = 10.0;
5         int ii = 10;
6         double dd = 10.0;
7
8         System.out.print(i.equals(d) + " ");
```

```
9.          System.out.print(ii == dd);  
10.      }  
11. }
```

- A. true true
- B. true false
- C. false false
- D. false true 
- E. Compilation fails

---

**Explanation:**

Explanation:

Option D is the correct answer.

While using equals method of wrappers, it checks the wrapper type and the wrapper primitive value. Hence, line 8 will result in false since i and d are not the same types. Comparison of primitives using '==' will check the actual value of the variable refer not the type. Hence, at line 9, true will be printed. Hence, option D is correct.

**Reference** : <http://docs.oracle.com/javase/tutorial/java/landl/objectclass.html>

---

Ask our Experts

Rate this Question?  

Question 36


Unattempted

Domain :Creating and Using Arrays

What will be the output of this program?

```
1  class Whiz {  
2      public static void main(String args[]) {  
3          new Whiz().iterator(new int [ ]{10,12,13});
```

```
4.     }  
5.     void iterator(int [] li) {  
6.         for(int x=0;x<i.length;System.out.print(i[x] + " "))x++;  
7.     }  
8. }
```

- A. 10 12 13
- B. 12 13
- C. 10 12
- D. 12 13 followed by an exception 
- E. Compilation fails

---

**Explanation:**

Explanation:

Option D is the correct answer.

We have passed the anonymous array to the iterator method which uses a for loop to iterate through array elements and print them. In given for loop, we have used the printing statement in update part and we have done the increment part inside the loop. So, in the first iteration, it will increase the value of x and then print the second element. But when it does two iteration value of x will become 3, so in final iteration trying to access element will index position 3, will result in an exception. Hence, option D is correct.

**Reference** : <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/for.html>

---

Ask our Experts

Rate this Question?  

Question 37

Unattempted


Domain :Creating and Using Arrays

Consider this given program:

```
1      class Whiz {  
2  
3          public static void main(String args[] ) {  
4  
5              int [ ] a = {1,2,3,4,5,6};  
6  
7              // insert code here  
8              System.out.print(i + " ");  
9              }  
10         }  
11     }
```

Which of the following statement will compile successfully when inserted at line 5?

- I. for (int i = 0, j = 0; i < a.length; j++) { i = a[j];
- II. for (int i : a) {
- III. for (a : int i) {

- A. I only
- B. II only
- C. III only
- D. I and II only 
- E. All the statements will compile successfully.

---

#### Explanation:

#### Explanation:

Option D is the correct answer.

The first one is the correct way of using for loop to iterate the array elements and the second one is called an enhance for loop. It can also be used to iterate the array elements. The third one is the incorrect use of the enhance for loop since the variable declaration should come before the collection inside for.

## Reference

[:http://docs.oracle.com/javase/tutorial/java/nutsandbolts/for.html](http://docs.oracle.com/javase/tutorial/java/nutsandbolts/for.html)

Ask our Experts

Rate this Question? 😊 😞

## Question 38

Unattempted

Domain :Working with Selected classes from the Java API

Which of the following is true regarding this given program code?

- I. String s2 = "Rekha";  
II. String s2 = new String("Rekha");

```
1      public class Whiz{  
2.  
3      public static void main(String[] args) {  
4          String s1 = "Rekha";  
5          //insert here  
6.  
7          System.out.print(s1.equals(s2)+" ");  
8          System.out.print(s1 == s2);  
9.  
10     }  
11 }
```

- A. Inserting the code statement II at line 6, will produce output "true true"  
B. Inserting the code statement I at line 6, will produce output "true false"  
C. Inserting the code statement I at line 6, will produce output "false false"  
D. Inserting the code statement II at line 6, will produce output "true false" ✓  
E. None of the above.

**Explanation:****Explanation:**

Option D is the correct answer.

When creating Strings without using "new" keyword, compiler search for equal String literal in the String pool, if equal found then the reference will refer to it without creating new String. So, in this case with the statement I, new String won't be created, so both "s1" and "s2" refer to the same String object. Therefore with the statement I, we will have "true true" as result. So, options B and C are incorrect.

When using "new" to create a String, a new String object will be created even there is an equal String literal in the pool, so here "==" check will return false since "s1" and "s2" refer to two different objects. But the "equals()" method will return true since the String literal are equal. So, the option A is incorrect and D is correct.

**Reference** : <http://docs.oracle.com/javase/tutorial/java/landl/objectclass.html>

Ask our Experts


Rate this Question? 😊 😞

Question 39

Unattempted

Domain :Using Operators and Decision Constructs

Which of the following statement is correct about switch?

- A. Switch statement is more efficient than a set of if-then-else statement. 
- B. Two case constants in the same switch might be identical.
- C. Switch uses equalsIgnoreCase method when working with strings.
- D. It is not possible to create a nested switch statements.
- E. None of the above.

**Explanation:**

Option A is the correct answer.



Option A is correct since the switch is efficient than if, as it will directly execute the statements based on the input, where ifs have to check one by one till match found.

Option B is incorrect as in a switch all cases should be unique.

Option C is incorrect as the switch uses equals method when working with Strings.

Option D is incorrect since we can have nested switches.

**Reference** : <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/switch.html>

---

Ask our Experts

Rate this Question? 😊 😞

Question 40

Unattempted

Domain :Working with Methods and Encapsulation

Which of the following will override the method run correctly when inserted at line 8?

```
1      class A{  
2          private void run(){  
3              System.out.print("A");  
4          }  
5      }  
6  
7      class B extends A{  
8          //override method() here  
9      }
```

- A. `private void run(){System.out.print("B");}`
- B. `void run(){System.out.print("B");}`
- C. `public void run(){System.out.print("B");}`

D. `private void run(String s){System.out.print(s);}`

E. We can't override the method run 

---

**Explanation:**

Explanation:

Option E is the correct answer.

To override a method, that method needs to be inherited. So, in this case, we have defined the method `run` as `private` hence we can't override the method `run` at line 8. Hence, option E is correct.

**Reference** : <http://docs.oracle.com/javase/tutorial/java/landl/polymorphism.html>

---

Ask our Experts

Rate this Question?  

Question 41


Unattempted

Domain :Working with Inheritance

What will be the output of this program?

```
1  abstract class Animal{
2      void run(){
3          System.out.print("Animal run");
4      }
5  abstract void sound();
6  }
7
8  class Dog extends Animal{
9
10     void sound(){
11         System.out.print("Bark");
12     }
```

```
13.  
14.     public void run(){  
15.         System.out.print(" Dog runs");  
16.     }  
17. }  
18. public class Whiz{  
19.     public static void main(String [] args){  
20.         Animal dog = new Dog();  
21.         dog.sound();  
22.         dog.run();  
23.     }  
24. }
```

- A. Bark Dog runs 
- B. Bark Animal runs
- C. Compilation fails due to an error at line 10
- D. Compilation fails due to an error at line 21
- E. Compilation fails due to multiple errors

---

**Explanation:**

Explanation:

Option A is the correct answer.

Here at line 20, we have created Dog instance and have used a superclass Animal reference, so we can invoke any method of superclass Animal even the actual object is Dog. When invoking the overridden method at run time, the overridden version of the actual object will be invoked, so sound and run method of Dog class will be invoked. So, option A is correct.

**Reference:**

<http://docs.oracle.com/javase/tutorial/java/javaOO/objectcreation.html>

<http://docs.oracle.com/javase/tutorial/java/javaOO/usingobject.html>

Ask our Experts

Rate this Question? 😊 😞

Question 42


Unattempted

Domain :Handling Exceptions

What will be the output of this program?

```
1  class Animal {  
2      public void eat() throws Exception { System.out.print("Animal eats");}  
3  }  
4  
5  class Dog extends Animal{  
6      public void eat() { System.out.print("Dog eats");}  
7  
8      public static void main(String [] args) {  
9          Animal a = new Dog();  
10         Dog d = new Dog();  
11         d.eat();  
12         a.eat();  
13     }  
14 }
```

- A. Animal eats Animal eats
- B. Dog eats Animal eats
- C. Dog eats Dog eats

- D. Compilation fails due to an error at line 6
- E. Compilation fails due to an error at line 12 

---

**Explanation:**

Explanation:

Option E is the correct answer.

If a method is overridden but we use a polymorphic (super type) reference to refer to the subtype object with the overriding method, the compiler assumes we are calling the supertype version of the method. If the supertype version declares a checked exception but the overriding subtype method does not, the compiler still thinks you are calling a method that declares an exception.

So, above code fails to compile due to line 12 since compiler sees calling the eat method of superclass and fails to catch or declare the exception.

**Reference** :<http://docs.oracle.com/javase/tutorial/java/javaOO/objectcreation.html>

---

Ask our Experts


Rate this Question?  

Question 43

Unattempted

Domain :Working with Methods and Encapsulation

Choose the option that has correct method signature for overridden version of this method.  
`abstract Number number();`

- A. `private Number number()`
- B. `public void number()`
- C. `public Integer number()throws NumberFormatException` 
- D. `public Integer number(Integer i)`
- E. None of the above

---

**Explanation:**

**Option C is the correct answer.**

Option A is incorrect since we can't use more restrictive access level when overriding methods so using private is incorrect.

Option B is incorrect since we can't change the return type of overriding method except for covariant types. (Subtype of superclass method return type)

Option C is correct since there we have used Integer as return type which is a subtype of Number, and also it is legal to throw a new or broader unchecked exception in overriding method. Hence, option C is correct.

While overriding, we can't change the argument list. Hence, option D is incorrect.

**Reference** :<http://docs.oracle.com/javase/tutorial/java/javaOO/objectcreation.html>

---

Ask our Experts


Rate this Question? 😊 😞

Question 44

Unattempted

Domain :Working with Inheritance

Which of the following is an advantage of using inheritance?

- A. It increases reusability
- B. We can access both super class content and sub class content at the same time
- C. It increases the extensibility
- D. All of the above 

---

**Explanation:**

Explanation:

**Option D is the correct answer.**

Inheritance can also make application code more flexible to change because classes that inherit from a common superclass can be used interchangeably. If the return type of a method is superclass

Reusability -- facility to use public methods of base class without rewriting the same

Extensibility -- extending the base class logic as per business logic of the derived class

Overriding-- With inheritance, we will be able to override the methods of the base class so that meaningful implementation of the base class method can be designed in the derived class.

**Reference** :<http://docs.oracle.com/javase/tutorial/java/landl/subclasses.html>

---

Ask our Experts

Rate this Question? 😊 😞

Question 45

Unattempted

Domain :Working with Inheritance

Which of the following can be inserted at line 10 to invoke the read method?

```
1    class Person{}
2
3    class Student extends Person{
4
5        public void read(){System.out.println("Reading");}
6    }
7
8    public class Whiz{
9
10       public static void main(String [] args){
11
12           Person stu = new Student();
13
14           //insert here
15
16       }
17 }
```

A. stu.read();

B. (Student)stu.read();

C. `(Student)(stu).read();`

D. `((Student)stu).read();` 

E. None of the above.

---

### Explanation:

### Explanation:

Option D is the correct answer.

At line 9, we have created a Student instance with reference Person, so it is impossible to invoke the read method using that reference directly even the actual object is Student compiler tries to find the read method of reference type. Hence, the option A is incorrect. Options B and C will do the same thing since the "." operator has higher precedence if we use them then it will try to see the return value of the read method and tries to cast it which is illegal.

Option D is correct since we have correctly cast the object to Student using correct order of parentheses.

**Reference :** <http://docs.oracle.com/javase/tutorial/java/landl/subclasses.html>

---

Ask our Experts

Rate this Question?  

Question 46

Unattempted


Domain :Working with Inheritance

Which of the following will produce the output "Cat" when inserted at line 5?

```
1  class Animal {  
2      Animal(String s){ super(); }  
3  }  
4  class Cat extends Animal {  
5      // insert code here  
6  }  
7
```



```
8. public class Whiz {  
  
9.     public static void main(String [] args) {  
  
10.         Animal ab = new Cat();  
  
11.     }  
  
12. }
```

- A. Cat(String s) { super();System.out.print(s); }Cat(){ this("Cat"); }
- B. Cat(String s) { super(null);System.out.print(s); } Cat(){ this("Cat"); } 
- C. Cat(String s) { super(" ");System.out.print(s); }Cat(){ super("Cat"); }
- D. Cat(String s) { super(null);System.out.print("Cat"); }
- E. None of the above.

---

**Explanation:**

Explanation:

Option B is the correct answer.

Option B is correct as we have used the keyword "this" to invoke the "Cat(String s)" constructor. And the print statement in that constructor produces the expected output.

Option A is incorrect as the superclass has only one constructor which can take String as the argument so calling "super()" with empty parameters causes a compile time error.

Option C is incorrect as the expected output can only be achieved by invoking the "Cat(String s)" constructor so using super will skip the needed constructor and will invoke the super class constructor. Therefore, the expected output won't produce.

Option D will cause compile time error as we need to have "Cat()" constructor which doesn't take any parameter as we used "new Cat()" at line 10.

**Reference :** <http://docs.oracle.com/javase/tutorial/java/javaOO/thiskey.html>

[Ask our Experts](#)


Rate this Question? 😊 😞

## Question 47

Unattempted

Domain :Working with Inheritance

Which of the following statement is true?

- A. Abstract classes can contain default methods
- B. Abstract classes can be final
- C. Abstract classes do not have constructors
- D. Abstract classes can't be instantiated 
- E. None of the above

**Explanation:**

Explanation:

Option D is the correct answer.

Option A is incorrect as only interfaces can have default method.

Option B is incorrect as abstract classes can't be final, they meant to be extended and concreted, so if we could mark them final then there will be no way to concrete them.

Option C is incorrect as every class abstract or not should have a constructor.

Option D is correct, it is illegal to instantiate abstract classes.

Reference :<http://docs.oracle.com/javase/tutorial/java/landl/usinginterface.html>

[Ask our Experts](#)

Rate this Question? 😊 😞

## Question 48

Unattempted

Domain :Working with Inheritance

What will be the output of this program?

```
1      interface I{  
2          default boolean equals(Object O){  
3              return true;  
4          }  
5      }  
6  
7      class A implements I{  
8          public boolean equals(Object O){  
9              return false;  
10         }  
11     }  
12  
13     public class Whiz{  
14         public static void main(String [] args){  
15             A a = new A();  
16             I ia = new A();  
17             I i = new I(){};  
18  
19             System.out.println(a.equals(ia) + " " + i.equals(ia));  
20         }  
21     }
```

- A. true true
- B. false false
- C. true false

D. An Exception

E. Compilation fails 

**Explanation:**

**Explanation:**

Option E is the correct answer.

From java se 8, we can have default and static non-abstract methods in interfaces but there are some rules, such a rule is we can't override Object class methods using default method, it will result in a compile time error. Hence at line 2 trying to override equals method of the Object class results into a compile time error.

**Reference** : <http://docs.oracle.com/javase/tutorial/java/landl/abstract.html>

Ask our Experts

Rate this Question?  

Question 49


Unattempted

Domain :Working with Inheritance

What will be the output of this program?

```
1      interface I{  
2          public default void print(){  
3              System.out.print("I");  
4          }  
5  
6          static void method(){  
7              System.out.print("Static");  
8          }
```

```
9.     }  
10.  
11.  
12.  
13. public class WhizI  
14.     public static void main(String [] args){  
15.         I i = new I();  
16.         i.print();  
17.         I.method();  
18.     }  
19. }
```

- A. IStatic 
- B. An exception is thrown
- C. Compilation fails due to an error at line 2
- D. Compilation fails due to an error at line 15
- E. Compilation fails due to multiple errors

---

**Explanation:**

Explanation:

Option A is the correct answer.

From java se 8, we can have default and static non-abstract methods in interfaces but there are some rules. Both static and default methods in interfaces are public. At line 15, we have initialized an instance of type I. So, using it we can invoke the default method, which prints "I". Then we can invoke the static method using the interface name or using the object reference, here we have to use Interface name to invoke its static method, which will print "Static". Hence, option A is correct.

**Reference :** <http://docs.oracle.com/javase/tutorial/java/landI/abstract.html>

---

Ask our Experts

Rate this Question? 😊 😞

Question 50

Unattempted

Domain :Java Basics

Which of the following is a valid long literal?

- A. `0x99ffCl` ✓
- B. `12`
- C. `12.8`
- D. `11.2l`
- E. None of the above.

---

**Explanation:**

Explanation:

Option A is the correct answer.

Using L suffix will make literal long, as long as it is valid non-fraction number hence option D is incorrect. Also, we can use decimal, hexadecimal, octal or binary literals, so option A is correct.

Option B is a valid integer literal but it can be assigned to long since long can store integers.

**REFERENCE** : <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/variables.html>

---

Ask our Experts

Rate this Question? 😊 😞

Question 51

Unattempted

Domain :Working With Java Data Types

Which operator is used by Java run time implementations to free the memory of an object when it is no longer needed?

- A. delete
- B. free
- C. new
- D. clear
- E. None of the above



---

**Explanation:**

Explanation:

Option E is the correct answer.

Java handles deallocation of memory automatically, we do not need to explicitly clear an element. The GC only occurs during execution of the program. When no references to the object exist, that object is assumed to be no longer needed, and the memory occupied by the object can be reclaimed.

**REFERENCE** : <http://docs.oracle.com/javase/tutorial/java/javaOO/usingobject.html>

---

Ask our Experts

Rate this Question? 😊 😞

---


**Question 52**

Unattempted

Domain :Working With Java Data Types

What will be the output of this program?

```
1 public class Whiz{  
2  
3     static int x = 0b1;  
4     static int y = 0xF;  
5     static int z = 018;  
6  
7     public static void main(String args[]){  
8
```

9.                    `System.out.println(x+z+y);`
10.                `}`
- 11.
12. `}`
- A.    31
- B.    32
- C.    34
- D.    Compilation fails due to an error on line 4.
- E.    Compilation fails due to an error at line 5 

---

**Explanation:**

Explanation:

Option E is the correct answer.

We can use various literal types for numeric type variables, i.e.

binary literal – 0b11

Octal literal – 012

Decimal literal – 11

Hexadecimal literal – 0xff

At line 5, we have used octal literal, for an octal literal, we can use only 0-7 digits, so using 8 will result in compile time error. Hence option E is correct.

**REFERENCE** : <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/variables.html>

---

Ask our Experts

Rate this Question?  



What will be the output of this program?

```
1  class Whiz {  
2      public static void main(String args[]) {  
3          int array[] = {1,2,3};  
4          double dbls[] = array;  
5          double sum = 0;  
6          for (int i = 0; i < array.length; ++i)  
7              sum += dbls[i];  
8          System.out.println(sum);  
9      }  
10 }
```

- A. 6
- B. 6.0
- C. 3.0
- D. An exception is thrown
- E. Compilation fails 

**Explanation:**

Explanation:

Option E is the correct answer.

At line 3, we have defined an integer array. Then at line 4, we have tried to assign array at line 3 to double type array so code fails to compile. So, option E is correct.

**REFERENCE** : <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/variables.html>

<http://docs.oracle.com/javase/tutorial/java/javaOO/usingobject.html>

[Ask our Experts](#)

Rate this Question? 😊 😞


## Question 54

Unattempted

Domain :Working With Java Data Types

How many objects are eligible for GC when line 10 is reached?

```
1  class Wrap {  
2      Double d = 10.0;  
3      int x = 10;  
4      int [ ] s = new int[10];  
5  }  
6  public class Whiz {  
7      public static void main(String [] args){  
8          Wrap w =new Wrap();  
9          w = null;  
10     }  
11 }
```

- A. 1
- B. 2
- C. 3 
- D. 4
- E. Compilation fails

**Explanation:****Explanation:**

**Option C is the correct answer.**

At line 8, we have created a wrap instance, in that wrapper, there are two objects, one is an array of ints and other is a Double. So, making w reference null will result in Wrap object unreachable and also its enclosing two objects. Hence, total three objects eligible for GC. Hence, option C is correct.

**REFERENCE** : <http://docs.oracle.com/javase/tutorial/java/javaOO/usingobject.html>

Ask our Experts

Rate this Question? 😊 😞


Question 55

Unattempted

Domain :Working with Methods and Encapsulation

Which of the following will compile successfully when inserted at line 4?

```
1  class Program{
2
3      public static void main(String args[]){
4
5          Print p = new Print();
6
7          //insert here
8
9      }
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299
2300
2301
2302
2303
2304
2305
2306
2307
2308
2309
2310
2311
2312
2313
2314
2315
2316
2317
2318
2319
2320
2321
2322
2323
2324
2325
2326
2327
2328
2329
2330
2331
2332
2333
2334
2335
2336
2337
2338
2339
2340
2341
2342
2343
2344
2345
2346
2347
2348
2349
2350
2351
2352
2353
2354
2355
2356
2357
2358
2359
2360
2361
2362
2363
2364
2365
2366
2367
2368
2369
2370
2371
2372
2373
2374
2375
2376
2377
2378
2379
2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391
2392
2393
2394
2395
2396
2397
2398
2399
2400
2401
2402
2403
2404
2405
2406
2407
2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2418
2419
2420
2421
2422
2423
2424
2425
2426
2427
2428
2429
2430
2431
2432
2433
2434
2435
2436
2437
2438
2439
2440
2441
2442
2443
2444
2445
2446
2447
2448
2449
2450
2451
2452
2453
2454
2455
2456
2457
2458
2459
2460
2461
2462
2463
2464
2465
2466
2467
2468
2469
2470
2471
2472
2473
2474
2475
2476
2477
2478
2479
2480
2481
2482
2483
2484
2485
2486
2487
2488
2489
2490
2491
2492
2493
2494
2495
2496
2497
2498
2499
2500
2501
2502
2503
2504
2505
2506
2507
2508
2509
2510
2511
2512
2513
2514
2515
2516
2517
2518
2519
2520
2521
2522
2523
2524
2525
2526
2527
2528
2529
2530
2531
2532
2533
2534
2535
2536
2537
2538
2539
2540
2541
2542
2543
2544
2545
2546
2547
2548
2549
2550
2551
2552
2553
2554
2555
2556
2557
2558
2559
2560
2561
2562
2563
2564
2565
2566
2567
2568
2569
2570
2571
2572
2573
2574
2575
2576
2577
2578
2579
2580
2581
2582
```

- A. `Print.p2();`
- B. `p.p2(6);` 
- C. `System.out.print(p.print(6));`
- D. `Print.print(3);`
- E. None of the above

---

**Explanation:**

**Option B is correct.**

We can invoke a static method using a class name or via an instance of the class. So, here option B is correct since we have used an object reference to invoke the p2 method by passing an integer as the argument.

Option A is incorrect since the p2 method expects an integer as the argument.

Option C is incorrect since print returns nothing so using it in printing statement is invalid.

The print method is an instance method so we can't invoke it using a class name. So, option D is incorrect.

**EXAM OBJECTIVE** : Working with Java Data Types - Know how to read or write to object fields

**REFERENCE** : <http://docs.oracle.com/javase/tutorial/java/javaOO/usingobject.html>

---

Ask our Experts

Rate this Question?  

Question 56

Unattempted


Domain :Working With Java Data Types

Which of the following will print true?

`Double d = 10.0;`

`int i = 10;`

`Integer wi = 10;`

- A. `System.out.print((wi == d));`
- B. `System.out.print(d == i);` 
- C. `System.out.print(d.equals(i));`
- D. `System.out.print(d.equals(wi));`
- E. `System.out.print(wi.equals(d));`

---

**Explanation:****Explanation:**

Option B is the correct answer.

Option B is correct since it returns true. Comparison of Wrapper and primitive using "==" will unwrap the wrapper to primitive and compare, hence "d==i" return true.

Option A is incorrect since it results in a compile-time error because we can't use "==" with two different wrappers.

Other options are incorrect since equals method of the wrapper will first check if the wrapper is of the same type, hence others will return false.

**REFERENCE** : <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/variables.html>

---

Ask our Experts


Rate this Question?  

Question 57

Unattempted

Domain :Working With Java Data Types

Which of the following can be used to get the maximum possible value for an integer?

- A. `Integer.max;`
- B. `Integer.MAX_VALUE;` 

- C. `new Integer().max();`
- D. `new Integer().MAX;`
- E. None of these

---

**Explanation:**

**Explanation:**

Option B is the correct answer.

Integer wrapper as a static field called MAX\_VALUE which represents the maximum value of Integer type can hold. Hence, option B is correct.

**REFERENCE** : <https://docs.oracle.com/javase/8/docs/api/java/lang/Integer.html>

---

Ask our Experts

Rate this Question? 😊 😞


Question 58

Unattempted

Domain :Working With Java Data Types

What will be the output of this program?

```
1  class Whiz {  
2      public static void main(String args[]) {  
3          Double d = 10;  
4          int i = 10;  
5          Integer wi = 10;  
6          System.out.print((wi == i) + " ");  
7          System.out.print(d == i);  
8      }  
9  }
```

- A. true false
- B. false false
- C. true true
- D. Compilation fails due to an error at line 3 
- E. Compilation fails due to an error at line 7

---

**Explanation:**

Explanation:

Option D is the correct answer.

While assigning literals to wrapper we need to assign wrapper or primitive in wrapper type since assignment can't unwrap and then wide the literal. So, here at line 3, we have tried to assign an integer primitive literal to the Double wrapper which results in a compile time error. So, option D is correct.

**REFERENCE** : <https://docs.oracle.com/javase/8/docs/api/java/lang/Double.html>

---

Ask our Experts

Rate this Question?  


Question 59

Unattempted

Domain :Using Operators and Decision Constructs

What will be the output of this program?

```
1  class Whiz {  
2      public static void main(String args[]) {  
3          char a = 'C';  
4          a++;  
5          System.out.print(a);  
6      }  
7  }
```

- A. C
- B. D 
- C. 68
- D. An Exception is thrown
- E. Compilation fails due to an error at line 5

---

**Explanation:**

Explanation:

Option B is the correct answer.

Primitive char type is int-compatible, so at line 4 using increment operator will change it is ASCII value by one, which will result in the next character. Hence, D will be printed, so option B is correct.

**REFERENCE** : <http://docs.oracle.com/javase/tutorial/java/nutsandbolts/variables.html>

---

Ask our Experts

Rate this Question?  

Question 60


Unattempted

Domain :Working With Java Data Types

What will be the output of this program?

```
1  class Whiz {  
2      public static void main(String args[]) {  
3          Double d = 0.0;  
4          System.out.print(d.BYTES);  
5          System.out.print(d.SIZE);  
6      }  
7  }
```



- A. 00
- B. 80
- C. 88
- D. 864 
- E. Compilation fails due to an error at line 5

---

**Explanation:**

Explanation:

Option D is the correct answer.

This code shows usage of BYTES, SIZE are the constant fields in Double class.

BYTES : The number of bytes used to represent a double value which is 8 .

SIZE : The number of bits used to represent a double value.

**REFERENCE** : <https://docs.oracle.com/javase/8/docs/api/java/lang/Double.html>

---

Ask our Experts

Rate this Question?  

Question 61


Unattempted

Domain :Working with Inheritance

What will be the output of this program?

```
1    class Whiz{  
2        public static void main(String args[]){  
3            A ab = new B();  
4            ab.print();  
5            ab.print("C");  
6        }
```

```
7.     }  
8.  
9.     class A{  
10.         public void print(){  
11.             System.out.print("A");  
12.         }  
13.     }  
14.  
15.     class B extends A{  
16.         public void print(String s){  
17.             System.out.print(s);  
18.         }  
19.     }
```

- A. AA
- B. CC
- C. AC
- D. An exception is thrown
- E. Compilation fails 

---

**Explanation:**

Explanation:

Option E is the correct answer.

When compiling the code, Compiler looks only at the reference and sees that A doesn't have a print() method that takes a String. The compiler doesn't care that the actual object might be a B at runtime. So, it will result in a compile-time error, so option E is correct.

REFERENCE :<http://docs.oracle.com/javase/tutorial/java/javaOO/returnvalue.html>

---

Ask our Experts

Rate this Question? 😊 😞

Question 62

Unattempted

Domain :Working with Inheritance

You are asked to create a method which should satisfy the following requirements.  
The method should be a non-abstract method. It should take no parameters. It shouldn't return anything. Name of the method should be "print". And it should be an instance Method. This method is defined in an interface  
Which is the correct method signature?

- A. void print()
- B. static void print()
- C. default void print() ✓
- D. public void print()
- E. public abstract print()

---

**Explanation:**

Option C is the correct answer.

According to the given requirement, the method should be a default method since the method supposed to be defined in an interface and it should be a non-abstract and an instance method. Since we used the method in an interface it is implicitly public, so option C is correct.

**Reference:**

<http://docs.oracle.com/javase/tutorial/java/javaOO/returnvalue.html>

---

Ask our Experts


Rate this Question? 😊 😞

Question 63

Unattempted

## Domain :Working with Methods and Encapsulation

Which of the following is not a part of the method signature?

- A. Return type 
- B. Method name
- C. Type of parameters
- D. Number of parameters
- E. Order of the parameters

**Explanation:**

Explanation:

Option A is the correct answer.

The signature of a method is used to uniquely identify a method. A signature consists of:

- Method name
- Number of parameters
- Type of the parameters
- Order of the parameter

Even a return type is not part of the method signature. The return type is a must for a method, if a method doesn't expect to return anything then we need to use void. So, option A is correct.

**Reference :** <http://docs.oracle.com/javase/tutorial/java/javaOO/returnvalue.html>

Ask our Experts

Rate this Question?  


Question 64

Unattempted

Domain :Working with Methods and Encapsulation

What will be the output of this program?

```
1    public class Program{  
2        int x = 10;  
3  
4        public static void main(String args[]){  
5            int y = 12;  
6            System.out.print(y+x);  
7            int x = 11;  
8        }  
9    }
```

- A. 21
- B. 22
- C. 23
- D. Compilation fails due to an error at line 6 
- E. Compilation fails due to multiple errors

---

**Explanation:**

Explanation:

Option D is the correct answer.

We can't access non-static content from static content, it will result in a compile-time error. So, at line 6, trying to access variable x in main method results compile-time error, since the variable x is not static.

**Reference** : <http://docs.oracle.com/javase/tutorial/java/javaOO/classvars.html>

---

Ask our Experts

Rate this Question?  

## Question 65


Unattempted

Domain :Working with Inheritance

What is the output while compiling class B?

```
1    package one;
2
3    class A{
4        protected int j = 12;
5    }
6
7
```

```
1    package two;
2    import one.*;
3    class B extends A{
4        public static void main(String [ ] args) {
5            A a = new A();
6        }
7    }
```

- A. Compilation succeeds
- B. Compilation fails due to an error at line 3 of class B
- C. Compilation fails due to an error at line 5 of class B
- D. Both option B and C 

**Explanation:**

**Option D is the correct answer.**

Class A in package one has default access level so when the code tried to extends class A and to create an instance of class A in class B of package two, it cause compilation failure since class A can be only accessed within the one package. So option D is correct.

Options A is incorrect as the code fails to compile, if we mark class A as public then class A can be accessed within package two, so then the code will compile fine.

**Reference :** <http://docs.oracle.com/javase/tutorial/java/javaOO/accesscontrol.html>

Ask our Experts

Rate this Question? 😊 😞

Question 66

Unattempted

Domain :Working with Inheritance

Which of the following statement(s) is/are correct?

- I. Private members of a class can only be accessed by the members of the same class.
- II. Protected members of a class can be inherited only by a subclass of another package.
- III. Protected members of a class can be inherited by a subclass of an another package, and become private members of that subclass.

- A. I only ☒
- B. II only ☐
- C. I and II only ☐
- D. I and III only ☐
- E. None of the statement is true ☐

**Explanation:**

Explanation:

**Option A is the correct answer.**

The statement I is correct as the private members can be only accessed by the members of the enclosing class.

Statement III is incorrect . Let us consider Test1 is in package one, Test2 is in package two and Test3 is in package three. Test2 is a subclass of Test1 and Test3 is a subclass of Test2. Here both Test2, Test3 can access Test1 class protected members. Here statement III is not valid.

Statement II is incorrect since protected members are inherited by subclasses for same package as well as other packages.

Option A is correct since only the statement I is correct.

**Reference :** <http://docs.oracle.com/javase/tutorial/java/javaOO/accesscontrol.html>

Ask our Experts

Rate this Question? 😊 😞

#### Question 67

Unattempted

Domain :Working with Methods and Encapsulation

What will be the output of this program?

```
1  class Whiz {  
2      public static void main(String args[]){  
3          int x = 1;  
4          int y = new Whiz().change(x);  
5          System.out.print(x+y);  
6      }  
7      int change(int x) {  
8          x = 2;  
9          return x;  
10     }  
11 }
```

A. 2

B. 3 

C. 4



- D. Compilation fails
- E. An exception is thrown at runtime

---

**Explanation:**

Explanation:

Option B is the correct answer.

When you are passing a primitive variable, you are passing a copy of the bits representing the variable. Here we have passed the variable x to change method which will pass the bit pattern of 1, not the reference, so the value of x in the main method will remain unchanged. So, the output will be 3, hence option B is correct.

**Reference** : <http://docs.oracle.com/javase/tutorial/java/javaOO/arguments.html>

---

Ask our Experts

Rate this Question? 😊 😞


Question 68

Unattempted

Domain :Working with Selected classes from the Java API

What will be the output of this program?

```
1 public class Whiz{
2
3     public static void main(String[] args) {
4         char[] chars = {'1','Z','0','-','8','1'};
5         StringBuilder sb = new StringBuilder();
6         sb.append(chars,0,chars.length-1);
7         sb.append('0');
8         sb.append("8");
9         System.out.print(sb);
10    }
11 }
```

- A. 1Zo-8o8 
- B. 1Zo-81o8
- C. 1Zo-81o
- D. Compilation fails due to an error at line 6
- E. Compilation fails due to an error at line 7

---

**Explanation:**

Explanation:

Option A is the correct answer.

At line 6, we have used one of the overloaded version of the append method.

```
public StringBuilder append(char[] str, int offset, int len)
```

Appends the string representation of a subarray of the char array argument to this sequence. Characters of the char array str, starting at index offset, are appended in order to the contents of this sequence. The length of this sequence increases by the value of len.

So at line 6, the content of the builder will be "1Zo-8". Then in next two lines, we have added o and 8, which makes it "1Zo-8o8". Hence, option A is correct.

**REFERENCE** : <http://docs.oracle.com/javase/7/docs/api/java/lang/StringBuilder.html>

---

Ask our Experts

Rate this Question?  

Question 69


Unattempted

Domain :Working with Selected classes from the Java API

What will be the output of this program?

```
1 class Whiz {
```

```
2.      public static void main(String [ ] args) {  
3.          StringBuilder sb = new StringBuilder("Whiz");  
4.          sb.append("Labs");  
5.          System.out.print(sb.length() + sb.capacity());  
6.      }  
7. }
```

- A. 16
- B. 40
- C. 28 
- D. 24
- E. Compilation fails

---

**Explanation:**

Explanation:

Option C is the correct answer.

As the length of the String "WhizLabs" is eight, so the length method will return 8. And we have used StringBuilder class' "public StringBuilder(String str)" constructor, when we construct a string builder initialized to the contents of the specified string. The initial capacity of the string builder is 16 plus the length of the string argument. So, here we have initially passed "Whiz" to constructor and length of it; is 4. Therefore, the initial capacity is 20. So, 20 will be returned when capacity method invoked and output will be 28. Hence, option C is correct.

**REFERENCE :** <http://docs.oracle.com/javase/7/docs/api/java/lang/StringBuilder.html>

---

Ask our Experts

Rate this Question?  


## Question 70

Unattempted

Domain :Working with Selected classes from the Java API

What will be the output of this program?

```
1  class Whiz {  
2      public static void main(String args[]) {  
3          String s = "1Z";  
4          s.concat("0");  
5          s += "1";  
6          System.out.println(s + "-808");  
7      }  
8  }
```

- A. 1Z01-808
- B. 1Z0-808
- C. 1Z1-808 
- D. An Exception is thrown at runtime
- E. Compilation fails

**Explanation:**

Explanation:

Option C is the correct answer.

Strings are immutable, so at line 4 concatenating "0" will not add "0" to s, instead it will return new String with value "1Z0". At line 5, using assignment operator will add "1" to s, so output will be 1Z1-808. Hence, option C is correct.

**REFERENCE** : <http://docs.oracle.com/javase/7/docs/api/java/lang/StringBuilder.html>

Ask our Experts

Rate this Question?  

## Finish Review

### Certification

[Cloud Certification](#)

[Java Certification](#)

[PM Certification](#)

[Big Data Certification](#)

### Company

[Support](#)

[Discussions](#)

[Blog](#)

### Follow us



---

© Copyright 2019. Whizlabs Software Pvt. Ltd. All Right Reserved.