

```
#include <stdlib.h>
#include <string.h>
#include <ctype.h>
```

```
#define MAXPAROLA 30
#define MAXRIGA 80
```

```
int main(int argc, char *argv[])
```

```
{
    int freq[MAXPAROLA]; /* vettore di contatori
delle frequenze delle lunghezze delle parole */
    char riga[MAXRIGA];
    int i, inizio, lunghezza;
    FILE * f;
```

```
    for(i=0; i<MAXPAROLA; i++)
        freq[i]=0;
```

```
    if(argc != 2)
```

```
    {
        fprintf(stderr, "ERRORE: serve un parametro con il nome del file\n");
        exit(1);
    }
```

```
    f = fopen(argv[1], "rt");
    if(f==NULL)
```

```
    {
        fprintf(stderr, "ERRORE: impossibile aprire il file %s\n", argv[1]);
        exit(1);
    }
```

```
    while( fgets( riga, MAXRIGA, f ) != NULL )
```

# Threads

## Pthread library

Stefano Quer and Pietro Laface

Dipartimento di Automatica e Informatica

Politecnico di Torino

## Thread libraries

- ❖ It provides the programmer the interface to use the threads
- ❖ The management can be done
  - A user level (by functions)
  - A kernel level (via system calls)
- ❖ The most used thread libraries are
  - POSIX threads
  - Windows 32/64
  - Java

Implemented at user  
and kernel level

Implemented at  
kernel level

Implemented by means of a thread library  
of the system hosting Java (Pthread POSIX  
or Windows 32/64)

# Pthreads

## ❖ POSIX threads or Pthreads

- Is the standard UNIX library for threads
  - IEEE POSIX 1003.1 2004 Edition
- Defined for C language, but available in other languages (e.g., FORTRAN)

## ❖ Using Pthreads

- A thread is a function that is executed in concurrency with the main thread

A process with multiple threads = a set of independently executing functions that share the process resources

## Pthreads

- ❖ The Pthreads library allows
  - Creating and manipulating threads
  - Destroying thread
  - Synchronizing threads
  - Protection of resources shared by threads
  - Thread scheduling
- ❖ It defines more than 60 functions
  - All functions have a **pthread\_** prefix
    - `pthread_equal`, `pthread_self`,  
`pthread_create`, `pthread_exit`,  
`pthread_join`, `pthread_cancel`,  
`pthread_detach`

## Library linkage

- ❖ The Pthread system calls are defined in
  - `pthread.h`
  - Thus you have to insert in the `.c` files
    - `#include <pthread.h>`
  - Compile your program linking the `pthread` library
    - `gcc -Wall -g -o <exeName> <file.c> -lpthread`

## Thread Identifier

- ❖ A thread is uniquely identified
  - By a type identifier **pthread\_t**
  - Similar to the PID of a process (**pid\_t**)
  - The type **pthread\_t** is opaque
    - Its definition is implementation dependent
    - Can be used only by functions specifically defined in Pthreads
    - It is not possible compare directly two identifiers or print their values
  - It has meaning only within the process where the thread is executed
    - Remember that the PID is global within the system

## pthread\_equal system call

```
int pthread_equal (  
    pthread_t tid1,  
    pthread_t tid2,  
);
```

- ❖ Compares two thread identifiers
- ❖ Arguments
  - Two thread identifiers
- ❖ Return value
  - Nonzero if the two threads are equal
  - Zero otherwise

## pthread\_self system call


```
pthread_t pthread_self ( void );
```

- ❖ Returns the thread identifier of the calling thread
  - It can be used by a thread (with **pthread\_equal**) to self-identify



## pthread\_create system call

- ❖ At run-time a program consists of one process and one thread
- ❖ **pthread\_create** allows creating a new thread
  - The maximum number of thread that can be created is undefined and implementation dependent



## pthread\_create system call

```
int pthread_create (  
    pthread_t *tid,  
    const pthread_attr_t *attr,  
    void *(*startRoutine)(void *),  
    void *arg );
```

### ❖ Arguments

- Identifier of the generated thread (**tid**)
- Thread attributes (**attr**)
- NULL is the default attribute
- C function executed by the thread (**startRoutine**)
- Argument passed to the start routine (**arg**)
- **NULL** if no argument

A single argument

## pthread\_create system call

```
int pthread_create (  
    pthread_t *tid,  
    const pthread_attr_t *attr,  
    void *(*startRoutine)(void *),  
    void *arg  
);
```

### ❖ Return value

- 0 on success
- Error code on failure

## pthread\_exit system call

- ❖ A process (with all its threads) terminates if
  - Its thread calls **exit** (or **\_exit** or **\_Exit**)
  - The main thread execute **return**
  - The main thread receives a signal whose action is to terminate
- ❖ A single thread can terminate (without affecting the other process threads)
  - Executing **return**
  - Executing **pthread\_exit**
  - Receiving a cancellation request performed by another thread using **pthread\_cancel**

## System call pthread\_exit

```
void pthread_exit (  
    void *valuePtr  
);
```

- ❖ It allows a thread to terminate returning a termination status
- ❖ Arguments
  - The **valuePtr** value is kept by the kernel until a thread calls **pthread\_join**
  - This value is available to the thread that calls **pthread\_join**

## Example

Thread  
creation

```
void *tF () {  
    ...  
    pthread_exit (NULL);  
}
```

Attributes

Arguments

```
pthread_t tid;  
int rc;  
rc = pthread_create (&tid, NULL, tF, NULL);  
if (rc) {  
    // Error ...  
    exit (-1);  
}  
...  
pthread_exit (NULL);  
// exit (0);  
// return (0); (in main)
```

Terminates only  
the main thread

Terminates the  
process  
(all its threads)

## Example

Creation of N  
threads with 1  
argument

Collects the tids

```
void *tF (void *par) {  
    int *tidP, tid;  
    ...  
    tidP = (int *) par;  
    tid = *tidP;  
    ...  
    pthread_exit (NULL);  
}
```

```
pthread_t th[NUM_THREADS];  
int rc, t;  
  
for (t=0; t<NUM_THREADS; t++) {  
    rc = pthread_create (&th[t], NULL, tF,  
        (void *) &t);  
    if (rc) {...}  
}  
pthread_exit(NULL);
```

Address of t

## Example

Creation of N  
threads with 1  
argument

A thread can be  
executed when t is  
changed

```
void *tF (void *par) {  
    int *tidP, tid;  
    ...  
    tidP = (int *) par;  
    tid = *tidP;  
    ...  
    pthread_exit (NULL);  
}
```

The content is  
being modified by  
the main thread

```
pthread_t th[NUM_THREADS];  
int rc, t;
```

```
for (t=0; t<NUM_THREADS; t++) {  
    rc = pthread_create (&th[t], NULL, tF,  
        (void *) &t);  
    if (rc) {...}  
}  
pthread_exit(NULL);
```

**ERROR**

&t is the address of a variable,  
the main thread changes its content in  
concurrency with the created threads  
that read its value



## Example

Creation of N  
threads with 1  
argument

Cast of a value  
`void * ↔ long int`

```
void *tF (void *par) {  
    long int tid;  
    ...  
    tid = (long int) par;  
    ...  
    pthread_exit(NULL);  
}
```

```
pthread_t th[NUM_THREADS];  
int rc; long int t;  
  
for (t=0; t<NUM_THREADS; t++) {  
    rc = pthread_create (&th[t], NULL, fF,  
        (void *) t);  
    if (rc) { ... }  
}  
pthread_exit (NULL);
```

Tricky:

We pass a `long int` as it were an address, because `pthread_create` requires an address as its last argument

## Example

Creation of N  
threads with 1  
argument

Cast of vector  
void \*  $\leftrightarrow$  **long** int

```
void *tF (void *par) {  
    long int tid;  
    ...  
    tid = (long int) par;  
    ...  
    pthread_exit(NULL);  
}
```

```
long int tA[NUM_THREADS];  
for (t=0; t<NUM_THREADS; t++) {  
    tA[t] = t;  
    rc = pthread_create (&th[t], NULL, tF,  
        (void *) tA[t]);  
    if (rc) { ... }  
}  
pthread_exit (NULL);
```

Argument stored in a  
vector element

## Example

Creation of N  
threads with 1  
argument

Cast of a vector of  
pointers  
 $\text{void}^* \leftrightarrow \text{int}$

```
void *tF (void *par) {  
    int *tid, taskid;  
    ...  
    tid = (int *) par;  
    taskid = *tid;  
    ...  
    pthread_exit(NULL);  
}
```

```
int tA[NUM_THREADS];  
for (t=0; t<NUM_THREADS; t++) {  
    tA[t] = t;  
    rc = pthread_create (&th[t], NULL, tF,  
        (void *) &tA[t]);  
    if (rc) { ... }  
}  
pthread_exit (NULL);
```

The pointer to a  
vector element

## Example

Creation of N  
threads with 1  
**struct**

```
struct tS {  
    int tid;  
    char str[N];  
};
```

```
void *tF (void *par) {  
    struct tS *tD;  
    int tid; char str[L];
```

```
    tD = (struct tS *) par;  
    tid = tD->tid; strcpy (str, tD->str);  
    ...
```

Cast to a vector  
of **structs**

```
pthread_t t[NUM_THREADS];  
struct tS v[NUM_THREADS];  
...  
for (t=0; t<NUM_THREADS; t++) {  
    v[t].tid = t;  
    strcpy (v[t].str, str);  
    rc = pthread_create (&t[t], NULL, tF, (void *) &v[t]);  
    ...  
}  
...
```

Address of a **struct**

## pthread\_join system call

❖ At its creation a thread can be declared

➤ Joinable

- Another thread may "wait" (**pthread\_join**) for its termination, and collect its exit status

➤ Detached

- No thread can explicitly wait for its termination (not joinable)


## pthread\_join system call

- ❖ If a thread
  - is **joinable**, its termination status is retained until another thread performs a **pthread\_join** for that thread
  - is **detached** its termination status is immediately released
- ❖ A thread calling **pthread\_join** waits until the required thread calls **pthread\_exit**

## pthread\_join () system call

```
int pthread_join (  
    pthread_t tid,  
    void **valuePtr  
);
```

- ❖ Used by a thread to wait the termination of another thread



## pthread\_join system call

```
int pthread_join (  
    pthread_t tid,  
    void **valuePtr  
);
```

**valuePtr** can be set to **NULL** if you are not interested in the return value

### ❖ Arguments

- Identifier (**tid**) of the waited-for thread
- The void pointer **valuePtr** will obtain the value returned by thread **tid**
  - Returned by **pthread\_exit**
  - Returned by **return**
  - **PTHREAD\_CANCELED** if the thread was deleted



## pthread\_join () system call

```
int pthread_join (  
    pthread_t tid,  
    void **valuePtr  
);
```

### ❖ Return value

- 0 on success
- Error code on failure
  - If the thread was detached **pthread\_join** should fail
  - If it fails, it returns the constant **EINVAL** or **ESRCH**

## Example

Returns the exit status  
(**tid** in this example)  
Tricky: tid is an int

```
void *tF (void *par) {  
    long int tid;  
    ...  
    tid = (long int) par;  
    ...  
    pthread_exit ((void *) tid);  
}
```

```
void *status;  
long int s;  
...  
/* Wait for threads */  
for (t=0; t<NUM_THREADS; t++) {  
    rc = pthread_join (th[t], &status);  
    s = (long int ) status;  
    if (rc) { ... }  
}  
...
```

th[t] collects the **tids**

Waits each thread,  
and collects its exit  
status

## Example

```
int myglobal;

void *threadF (void *arg) {
    int *argc = (int *) arg;
    int i, j;
    for (i=0; i<20; i++) {
        j = myglobal;
        j = j + 1;
        printf ("t");
        if (*argc > 1) sleep (1);
        myglobal = j;
    }
    printf ("(T:myglobal=%d)", myglobal);
    return NULL;
}
```

Use of a  
shared global  
variable

The global variable is  
incremented by  
means of a copy on  
j

The thread can sleep  
or not

## Example

```
int main (int argc, char *argv[]) {
    pthread_t mythread;
    int i;
    pthread_create (&mythread, NULL, threadF, &argc);
    for (i=0; i<20; i++) {
        myglobal = myglobal + 1;
        printf ("m");
        sleep (1);
    }
    pthread_join (mythread, NULL);
    printf ("(M:myglobal=%d)", myglobal);
    exit (0);
}
```

## Example

The thread executes immediately  
No loss of increments

```
> ./pgrm
mttttttttttttttttttttttttttttt(T:myglobal=21)mmmmmmmmmmmmmmmmmmmmmmmmmmmm
m(M:myglobal=40)
```

Thread and main thread alternates their execution every second. The increments of the thread are lost

```
> ./pgrm 1
mtmtmtmtmtmtmtmtmtmtmtmtmtmtmtmt (T:myglobal=21)
M:myglobal=21)
```

2sec waiting for the main thread  
Only some increments are lost

```
> ./pgrm 1  
mttmtttmtttmtttmtttmtttmtttmtttmmmmmmmmmm  
m(M:myglobal=30)
```

## pthread\_cancel system call

```
int pthread_cancel (  
    pthread_t tid  
);
```

- ❖ Terminates the target thread
  - The effect is similar to a call to `pthread_exit(PTHREAD_CANCELED)` performed by the target thread
- ❖ The thread calling `pthread_cancel` does not wait for termination of the target thread (it continues)

## pthread\_cancel () system call

```
int pthread_cancel (  
    pthread_t tid  
);
```

- ❖ Arguments
  - Target thread (tid) identifier
- ❖ Return value
  - 0 on success
  - Error code on failure

## pthread\_detach system call

```
int pthread_detach (  
    pthread_t tid  
);
```

The **attribute** of the **pthread\_create** allows creating a detached thread

- ❖ Declares thread **tid** as detached
  - The status information will not be kept by the kernel at the termination of the thread
  - No thread can join with that thread
  - Calls to **pthread\_join** should fail with error code **EINVAL** or **ESRCH**



## pthread\_detach system call

```
int pthread_detach (  
    pthread_t tid  
);
```

### ❖ Arguments

- Thread (**tid**) identifier

### ❖ Return value

- 0 on success
- Error code on failure

## Example

```
pthread_t tid;
int rc;
void *status;

rc = pthread_create (&tid, NULL, PrintHello, NULL);
if (rc) { ... }

pthread_detach (tid);

rc = pthread_join (tid, &status);
if (rc) {
    // Error
    exit (-1);
}

pthread_exit (NULL);
```

Detach a thread

Error if try to join

## Example

```
pthread_attr_t attr;  
void *status;
```

```
pthread_attr_init (&attr);  
pthread_attr_setdetachstate (&attr,  
    PTHREAD_CREATE_DETACHED);  
//PTHREAD_CREATE_JOINABLE);
```

```
rc = pthread_create (&t[t], &attr, tF, NULL);  
if (rc) {...}
```

```
pthread_attr_destroy (&attr);
```

```
rc = pthread_join (thread[t], &status);  
if (rc) {  
    // Error  
    exit (-1);  
}
```

Creates a detached  
thread using the  
attribute of  
`pthread_create`


Creates a detached  
thread

Destroys the attribute  
object

Error if try to join

## Exercise

- ❖ Implement, using threads, this precedence graph




## Solution

```
void waitRandomTime (int max){  
    sleep ((int)(rand() % max) + 1);  
}
```


```
int main (void) {  
    pthread_t th_cf, th_e;  
    void *retval;
```

```
    srand (getpid());  
    waitRandomTime (10);  
    printf ("A\n");
```




## Solution

```
waitRandomTime (10);  
pthread_create (&th_cf, NULL, CF, NULL);  
waitRandomTime (10);  
printf ("B\n");  
waitRandomTime (10);  
pthread_create (&th_e, NULL, E, NULL);  
waitRandomTime (10);  
printf ("D\n");  
pthread_join (th_e, &retval);  
pthread_join (th_cf, &retval);  
waitRandomTime (10);  
printf ("G\n");  
return 0;  
}
```




## Solution

```
static void *CF () {  
    waitRandomTime (10);  
    printf ("C\n");  
    waitRandomTime (10);  
    printf ("F\n");  
    return ((void *) 1); // Return code  
}  
static void *E () {  
    waitRandomTime (10);  
    printf ("E\n");  
    return ((void *) 2); // Return code  
}
```



## Exercise

- ❖ Implement, using threads, this precedence graph





## Exercise

- ❖ Given a text file, passed as an argument of the command line
- ❖ Implement a concurrent program using three threads ( $T_1$ ,  $T_2$ ,  $T_3$ ) that process the file content in pipeline
  - $T_1$ : Read from file the next character
  - $T_2$ : Transforms the character read by  $T_1$  in uppercase
  - $T_3$ : Displays the character produced by  $T_2$

## Solution

```
static void *GET (void *arg) {
    char *c = (char *) arg;
    *c = fgetc (fg);
    return NULL;
}
static void *UPD (void *arg) {
    char *c = (char *) arg;
    *c = toupper (*c);
    return NULL;
}
static void *PRINT (void *arg) {
    char *c = (char *) arg;
    putchar (*c);
    return NULL;
}
```

## Solution

```
FILE *fg;
char next, this, last;

int main (int argc, char ** argv) {
    int retC;
    pthread_t tGet, tUpd, tPrint;
    void *retV;

    if ((fg = fopen(argv[1], "r")) == NULL){
        perror ("Errore fopen\n");
        exit (0);
    }
    this = ' ';
    last = ' ';
    next = ' ';
```

## Solution

```
while (next != EOF) {  
    pthread_create (&tGet, NULL, GET, &next);  
    pthread_create (&tUpd, NULL, UPD, &this);  
    pthread_create (&tPrint, NULL, PRINT, &last);  
    pthread_join (tGet, &retV);  
    pthread_join (tUpd, &retV);  
    pthread_join (tPrint, &retV);  
    last = this;  
    this = next;  
}
```

## Solution

```
// Last two chars processing

pthread_create(&tUpd,NULL,UPD,&this);
pthread_create(&tPrint,NULL,PRINT,&last);
pthread_join (tUpd, &retV);
pthread_join (tPrint, &retV);
pthread_create(&tPrint,NULL,PRINT,&this);

return 0;
}
```