

1. Установите СУБД MySQL. Создайте в домашней директории файл .my.cnf, задав в нем логин и пароль, который указывался при установке.

```
Vaceslavs-MacBook-Pro:~ vaceslavroznov$ ls -la | grep .my.cnf
-rw-r--r--  1 vaceslavroznov  staff   38  9 авг 16:34 .my.cnf
Vaceslavs-MacBook-Pro:~ vaceslavroznov$
```

2. Создайте базу данных example, разместите в ней таблицу users, состоящую из двух столбцов, числового id и строкового name.

```
[mysql> CREATE DATABASE example;
Query OK, 1 row affected (0,00 sec)
```

```
[mysql> show databases;
+-----+
| Database |
+-----+
| example |
| information_schema |
| mysql |
| performance_schema |
| sys |
+-----+
5 rows in set (0,00 sec)
```

```
[mysql> use example;
Database changed
```

```
[mysql> create table user (id int not null, user char(150) not null);
Query OK, 0 rows affected (0,01 sec)
```

```
[mysql> show tables;
+-----+
| Tables_in_example |
+-----+
| user |
+-----+
1 row in set (0,00 sec)
```

3. Создайте дамп базы данных example из предыдущего задания, разверните содержимое дампа в новую базу данных sample.

```
-----
Vaceslavs-MacBook-Pro:~ vaceslavroznov$ sudo /usr/local/mysql/bin/mysqldump example > ~/example.sql
Vaceslavs-MacBook-Pro:~ vaceslavroznov$ vim ~/example.sql
Vaceslavs-MacBook-Pro:~ vaceslavroznov$ clear
```

```
[mysql> create database sample;  
Query OK, 1 row affected (0,01 sec)
```

```
mysql>  
[10]+  Stopped /usr/local/mysql/bin/mysql  
[Vaceslavs-MacBook-Pro:~ vaceslavroznov$ mysql sample < ~/example.sql  
[Vaceslavs-MacBook-Pro:~ vaceslavroznov$ mysql  
Welcome to the MySQL monitor.  Commands end with ; or \g.  
Your MySQL connection id is 26  
Server version: 8.0.17 MySQL Community Server - GPL
```

Copyright (c) 2000, 2019, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

```
[mysql> show databases;  
+-----+  
| Database |  
+-----+  
| example |  
| information_schema |  
| mysql |  
| performance_schema |  
| sample |  
| sys |  
+-----+  
6 rows in set (0,00 sec)
```

```
[mysql> use sample;  
Reading table information for completion of table and column names  
You can turn off this feature to get a quicker startup with -A  
  
Database changed  
mysql> █
```

```
[mysql> use sample  
Reading table information for completion of table and column names  
You can turn off this feature to get a quicker startup with -A  
  
Database changed  
[mysql> show tables;  
+-----+  
| Tables_in_sample |  
+-----+  
| user |  
+-----+  
1 row in set (0,00 sec)
```