CIFAKE: IMAGE CLASSIFICATION AND EXPLAINABLE IDENTIFICATION OF AI-GENERATED SYNTHETIC IMAGES

Academic & Internship Project Report
Student Name: Gaurav Vyas
Project Title: CIFAKE Deep Learning Detection & Explainability Framework
Internship Program: XTRAGRAD Technical Internship
Date of Submission: September 2026
Reference Literature: Bird, J.J. & Lotfi, A. (2024), *IEEE Access* / arXiv:2303.14126

TABLE OF CONTENTS

- CHAPTER 1: **INTRODUCTION** (Project Background, Problem Statement, Objectives, Scope, Expected Outcomes)
- CHAPTER 2: **SYSTEM OVERVIEW** (Existing System, Proposed System, System Modules, Overall Workflow)
- CHAPTER 3: **LITERATURE SURVEY** (Research Papers Reviewed, Existing Solutions, Comparative Analysis, Research Gap)
- CHAPTER 4: **TECHNOLOGIES USED** (Programming Languages, Frameworks & Libraries, Development Tools)
- CHAPTER 5: **ARCHITECTURE AND DESIGN** (System Architecture Diagram, Workflow Explanation)
- CHAPTER 6: **IMPLEMENTATION** (Key Features Implemented)
- CHAPTER 7: **RESULTS AND DISCUSSION** (Screenshots, Output Analysis, Performance Evaluation, Testing Results)
- CHAPTER 8: **CHALLENGES AND LEARNING OUTCOMES** (Challenges Faced, Solutions Implemented, Technical Skills Learned)
- CHAPTER 9: **FUTURE ENHANCEMENTS** (Proposed Improvements, Additional Features, Scalability Opportunities)
- CHAPTER 10: **CONCLUSION** (Summary of Work Completed, Achievements, Project Impact, Final Remark)
- REFERENCES: **BIBLIOGRAPHY** (Formal IEEE Citations)

CHAPTER 1: INTRODUCTION

Project Background

The rapid maturation of deep generative modeling, specifically Latent Diffusion Models (LDMs) such as Stable Diffusion v1.4, has catalyzed an unprecedented surge in the synthesis of photorealistic digital imagery. Modern diffusion pipelines synthesize complex visual scenes by gradually denoising latent representations conditioned on text prompts. The generated images demonstrate naturalistic lighting, texture coherence, and intricate semantic compositions that are virtually indistinguishable from authentic camera photographs to the unaided human eye.

While this generative revolution unlocks immense potential for creative industries, it introduces severe systemic vulnerabilities in digital content authentication, legal forensics, journalism, and public trust. Malicious actors can generate fabricated evidence, synthetic propaganda, and fraudulent documentation at scale. Consequently, developing automated, resilient, and transparent computational systems capable of reliably classifying images as authentic or AI-generated has emerged as a premier challenge in applied artificial intelligence and cybersecurity.

Problem Statement

Traditional digital forensics relies on hand-crafted artifact heuristics (such as chromatic aberration, sensor noise, or JPEG double-compression patterns) that fail catastrophically when evaluated against diffusion-generated imagery. Although standard Deep Convolutional Neural Networks (CNNs) can achieve high classification accuracy on static test splits, they operate predominantly as opaque "black boxes." In forensic and judicial contexts, a raw binary classification probability is insufficient; investigators require verifiable visual attribution explaining *why* a specific image was flagged as synthetic. Furthermore, conventional CNNs utilizing dense spatial flattening tend to overfit to localized spatial coordinate noise rather than learning translation-invariant semantic signatures.

Objectives

- **Multi-Architecture Engineering:** Construct and benchmark three distinct deep learning architectures: Baseline CNN2D (spatial flattening), Modified CNN2D (Global Average Pooling with Dropout), and EfficientNetB0 (transfer learning at compound scaling).
- **Large-Scale Direct Training:** Train the neural networks directly on the comprehensive 100,000-image CIFAKE training dataset (50,000 authentic photos and 50,000 Stable Diffusion synthetic images).
- **Explainable AI (XAI) Attribution:** Implement Gradient-weighted Class Activation Mapping (Grad-CAM) to compute rectified backpropagated gradients and project heatmaps identifying generative artifacts.
- **Forensic Metrics Quantification:** Formulate automated regional attention ratios (Center Attention vs. Background Activation) to provide quantitative evidence alongside qualitative visual heatmaps.
- **Interactive Web Serving:** Develop and deploy an intuitive, multi-page Streamlit web dashboard providing user authentication, model selection, live inference, and side-by-side forensic comparisons.

Scope of the Project

The project operates within the domain of the CIFAKE benchmark dataset (Bird & Lotfi, 2024), comprising 120,000 total images evenly split across 10 semantic classes identical to CIFAR-10 (Airplane, Automobile, Bird, Cat, Deer, Dog, Frog, Horse, Ship, Truck). The dataset is strictly partitioned into 100,000 training images and 20,000 unseen evaluation images. The scope includes network architecture definition, GPU/CPU-optimized training pipelines, automatic differentiation backpropagation, mathematical transparency mapping, and an end-to-end interactive web application.

Expected Outcomes

- A lightweight, high-performance Modified CNN2D model achieving >89% direct test accuracy with over 64% parameter reduction compared to standard flattened baselines.
- An exact, mathematically grounded Grad-CAM backpropagation engine outputting 4-way visual forensic attribution grids (Input, Grayscale Saliency, Jet Color Map, Superimposed Overlay).
- A responsive web application delivering real-time inferences (<10 ms per image) with full forensic reasoning.
- A comprehensive automated test suite verifying model shapes, weights loading, inference ranges, and explainability integrity.

CHAPTER 2: SYSTEM OVERVIEW

Existing System

Existing synthetic image detection workflows rely heavily on manual visual inspection or classical forensic techniques such as Error Level Analysis (ELA) and Steganography analysis. These methods examine high-frequency quantization noise or compression rate discrepancies across image blocks. When standard machine learning has been applied, practitioners typically deploy heavy off-the-shelf classification backbones (ResNet-50, VGG-16) with dense spatial flattening.

Deficiencies in the Existing System:

- *Manual Fragility:* Human visual perception is incapable of consistently detecting high-order diffusion noise artifacts in compressed 32×32 or web-distributed images.
- *High Computational Overhead:* Heavy networks (e.g., VGG-16 with 138 million parameters) incur massive latency and memory footprints, precluding edge or lightweight forensic deployment.
- *Spatial Position Overfitting:* Dense flattening forces weights to memorize fixed pixel coordinates, causing networks to memorize background positioning rather than generative structure.
- *Opacity (No Attribution):* Standard systems output an uninterpretable scalar probability, offering zero forensic insight to investigators.

Proposed System

The proposed system implements an end-to-end, explainable deep learning framework engineered specifically to address the structural artifacts introduced by diffusion synthesis. By replacing traditional spatial flattening with **Global Average Pooling (GAP)** and introducing a 30% dropout regularization stage, the proposed Modified CNN2D enforces spatial translation invariance across feature maps. The classification decision is coupled with a real-time **Grad-CAM** engine that backpropagates gradients from the final classification score directly into the penultimate convolutional layer, producing transparent attribution heatmaps. To handle real-world high-resolution camera uploads, the system introduces a **frequency-domain resampling bottleneck** that resamples inputs to 32×32 bilinear resolution before inference, eliminating false-positive sensor noise artifacts.

System Modules

- **Module 1: User Authentication & Security:** Manages persistent SQLite credential storage with salted SHA-256 password hashing and session state control.
- **Module 2: Resampling & Preprocessing Bottleneck:** Normalizes image pixel ranges to [0, 1] and resamples inputs through a 32×32 bilinear bottleneck to align input frequency distributions.
- **Module 3: Deep Learning Classification Engine:** Hosts the multi-architecture suite (Baseline CNN2D, Modified CNN2D, and EfficientNetB0), executing forward matrix operations to generate classification probabilities.
- **Module 4: Grad-CAM Explainable AI Engine:** Uses TensorFlow's `tf.GradientTape` to calculate feature map activation gradients, compute channel importance weights, and construct thermal jet heatmaps.
- **Module 5: Forensic Analytics & Reporting:** Calculates quantitative spatial attention ratios (Center vs. Peripheral) and outputs structured verdict summaries.
- **Module 6: Interactive Web Presentation Dashboard:** Streamlit-based graphical user interface facilitating model switching, image uploading, threshold adjustments, and benchmark reviews.

Overall Workflow

1. The authenticated forensic examiner selects an active neural architecture (e.g., Modified CNN2D).
2. An image (authentic photo or synthetic candidate) is ingested via drag-and-drop.
3. The preprocessing pipeline applies bilinear downsampling to (32, 32, 3), scales float32 values to [0, 1], and batches the tensor to (1, 32, 32, 3).
4. The model executes forward inference, emitting raw class logit y^c and sigmoid probability $P(ext{Real})$.
5. In parallel, `tf.GradientTape` monitors the activations A^k of layer `conv2d_2` and computes $\partial y^c / \partial A^k$.
6. Global spatial pooling derives neuron importance weights $lpha_k^c$, and a ReLU activation isolates positive evidence, generating a $32 imes 32$ saliency matrix.
7. OpenCV applies a thermal Jet colormap and superimposes it onto the original photograph at selectable alpha blending ratios.
8. The user interface renders the verdict badge, confidence score, 4-panel visual attribution grid, and automated forensic narrative.

CHAPTER 3: LITERATURE SURVEY

Research Papers Reviewed

- **Bird, J.J. & Lotfi, A. (2024).** *"CIFAKE: Image Classification and Explainable Identification of AI-Generated Synthetic Images."* IEEE Access. Introduced the 120,000-image CIFAKE dataset, demonstrated that standard CNNs overfit to spatial position, and proposed the Modified CNN2D with GAP achieving 95.78% accuracy.
- **Selvaraju, R.R., Cogswell, M., Das, A., Vedantam, R., Parikh, D., & Batra, D. (2017).** *"Grad-CAM: Visual Explanations from Deep Networks via Gradient-Based Localization."* ICCV. Established the gradient backpropagation formulation for coarse visual localization from any CNN layer without architectural modification.
- **Rombach, R., Blattmann, A., Lorenz, D., Esser, P., & Ommer, B. (2022).** *"High-Resolution Image Synthesis with Latent Diffusion Models."* CVPR. Demonstrated latent-space diffusion processes that compress pixel representations into cross-attention conditioned latent vectors, explaining the origins of latent boundary artifacts.
- **Corvi, R., Cozzolino, D., Zingarini, G., Poggi, G., Nagano, K., & Verdoliva, L. (2022).** *"On the Detection of Synthetic Images Generated by Diffusion Models."* Showed that diffusion architectures leave distinct frequency-domain spectral footprints distinct from GAN artifacts.
- **Li, L., Bao, J., Zhang, T., Yang, H., Chen, D., Wen, F., & Guo, B. (2020).** *"Face X-ray for More General Face Forgery Detection."* CVPR. Emphasized the vital necessity of boundary-focused forensic representations rather than semantic facial landmarks.

Existing Solutions

Solution Approach	Representative Model	Primary Mechanism	Key Limitations
Steganalysis / Spatial Rich Models	SRNet	High-pass filtering & noise residual analysis	Brittle under JPEG recompression; computationally heavy
Frequency Spectrum Analysis	FFT / DCT Spectral Classifiers	Identifies high-frequency spectral grid anomalies	Fails on resized or low-resolution (32x32) inputs
Deep Supervised Classifiers	ResNet-50 / VGG-16	Standard multi-layer convolutional feature extraction	Overparameterized (>25M params); zero explainability

Solution Approach	Representative Model	Primary Mechanism	Key Limitations
Facial Forgery Detectors	Face X-ray / MesoNet	Facial blending boundary detection	Strictly restricted to human facial domains; fails on general objects

Comparative Analysis

Compared to existing heavyweight frameworks, the proposed **Modified CNN2D** model operates with only **159,489 trainable parameters**—a 99.3% reduction compared to ResNet-50 (25.6M params) and a 64.3% reduction compared to the Baseline CNN2D (446,209 params). In terms of inference speed, the proposed architecture achieves execution times of approximately 4 milliseconds per image on standard CPU hardware, compared to 45–60 ms for ResNet-50. Most critically, while existing commercial detectors produce an opaque binary verdict, our integrated Grad-CAM engine surfaces the exact pixel-level attribution justifying the classification.

Research Gap

A systematic review of current literature highlights three prominent gaps:

1. *Absence of Open Explainability:* State-of-the-art synthetic detectors rarely integrate native visual explanation mechanisms, preventing forensic auditors from verifying whether the model is learning generative artifacts or spurious background correlations.
2. *Spatial Coordinate Memorization:* Standard benchmarking models rely on spatial flattening, causing neurons to learn position-dependent noise coordinates rather than scale-invariant generative signatures.
3. *Input Distribution Mismatch:* Detectors trained on low-resolution datasets (e.g., 32×32) experience dramatic confidence collapse when exposed to real-world high-resolution camera uploads due to sub-pixel photon sensor noise.

CHAPTER 4: TECHNOLOGIES USED

Programming Languages

- **Python 3.10 / 3.11 / 3.14:** Served as the core engineering language across the entire project lifecycle, chosen for its mature scientific computing ecosystem, native support for automatic differentiation, and seamless C++ hardware binding.
- **SQL (SQLite3):** Lightweight relational query language used for local, zero-configuration user credential persistence and security state tracking.

Frameworks and Libraries

Technology / Library	Primary Version	Functional Role within Project
TensorFlow	2.16.x / 2.20+	Core deep learning engine for tensor manipulation, automatic differentiation (`tf.GradientTape`), and hardware acceleration
Keras	3.x API	High-level neural network architecture definition, model compilation, and layer abstraction
Streamlit	1.30.0+	Interactive multi-page web application server, session state management, and real-time dashboard rendering
OpenCV (cv2)	4.8.x+	Spatial bilinear image interpolation, thermal Jet colormap generation, and alpha-weighted tensor blending
Pillow (PIL)	10.x+	Image ingestion, color space conversion (RGB), format sanitization, and thumbnail rendering
NumPy	1.26.x+	N-dimensional tensor slicing, vectorized array operations, and confusion matrix arithmetic
Matplotlib & Seaborn	3.8.x+	Generation of publication-quality figures, loss curves, confusion matrices, and attribution heatmaps
Plotly	5.18.x+	Interactive dynamic charting for web-based model performance benchmarking and ROC analysis
Hashlib	Standard Library	Cryptographic SHA-256 hashing with unique user salt generation for secure authentication

Development Tools

- **Visual Studio Code:** Primary Integrated Development Environment (IDE) utilized for modular Python development, debugging, and environment binding.
- **Git & GitHub:** Distributed version control system used for commit history tracking, collaborative code review, and repository synchronization.
- **Google Chrome (Headless Engine):** Automated document compiler utilizing Chrome's headless rendering pipeline (`--headless --print-to-pdf`) to generate publication-grade PDF documentation.
- **Python Virtual Environments (venv):** Isolated runtime environment preventing dependency collisions between TensorFlow, Streamlit, and peripheral scientific packages.

CHAPTER 5: ARCHITECTURE AND DESIGN

System Architecture Diagram

The system is architected around a decoupled five-tier design ensuring modularity, low inference latency, and transparent forensic attribution. The complete pipeline is illustrated below in Figure 5.1:




Figure 5.1: End-to-End System Architecture of the CIFAKE Deep Learning Detection & Explainability Framework

Workflow Explanation

The architectural data flow operates across five coordinated layers:

1. **Presentation Layer (Streamlit UI):** Serves as the interactive touchpoint. Forensic examiners authenticate via secure credentials, select their preferred model architecture, upload images in arbitrary formats (PNG, JPEG, WEBP), and adjust visualization parameters such as heatmap transparency ($lpha \in [0.1, 0.9]$).
2. **Preprocessing & Frequency Bottleneck Engine:** Ingested images are converted to 3-channel RGB. To guarantee frequency alignment between user uploads and the training distribution, images are passed through a **32×32 bilinear resampling bottleneck**. Pixel intensities are scaled to $[0.0, 1.0]$ and expanded to batch shape $(1, 32, 32, 3)$.
3. **Deep Learning Classification Layer:** Hosts three compiled neural networks:
   - *Baseline CNN2D:* Two Conv2D blocks (128 filters, 3×3, ReLU) with MaxPool2D(2×2) → Flatten → Dense(64) → Dense(1, Sigmoid). Total params: 446,209.

    - *Modified CNN2D (Paper Winner):* Two Conv2D blocks (128 filters, 3×3, ReLU) with MaxPool2D(2×2) → `GlobalAveragePooling2D` → `Dropout(0.3)` → Dense(64) → Dense(1, Sigmoid). Total params: 159,489. GAP enforces spatial translation invariance and eliminates positional artifact memorization.
    - *EfficientNetB0 (Transfer Learning):* Pre-trained compound-scaled feature extractor on ImageNet scaled to $96 imes 96$ pixels + GAP + Dropout(0.3) + Dense(128) + Dense(1). Total params: 4,213,668.
4. **Grad-CAM Explainable AI Engine:** During forward execution, the activations A^k of the target convolutional layer (`conv2d_2` or `top_activation`) are recorded. Gradients of the output logit y^c with respect to each feature map A^k are calculated via backpropagation:
   $$lpha_k^c = rac{1}{Z} \sum_{i=1}^u \sum_{j=1}^v rac{\partial y^c}{\partial A_{ij}^k}$$
   Neuron importance weights $lpha_k^c$ are combined linearly with forward feature maps, followed by a Rectified Linear Unit (ReLU) to isolate positive contributions:
   $$L_{ ext{Grad-CAM}}^c = ext{ReLU}\left(\sum_k lpha_k^c A^k ight)$$
   The resulting saliency matrix is normalized to $[0, 1]$, colorized with a thermal Jet colormap, and blended with the input:
   $$I_{ ext{overlay}} = lpha \cdot H_{ ext{jet}} + (1 - lpha) \cdot I_{ ext{original}}$$
5. **Forensic Output Layer:** Translates raw logits into human-readable verdicts (REAL vs. FAKE), surfaces the 4-way visual attribution grid, and computes quantitative attention distribution metrics.

CHAPTER 6: IMPLEMENTATION

Key Features Implemented

- **1. Multi-Tier Deep Learning Architectures:** Constructed complete TensorFlow/Keras implementations of Baseline CNN2D, Modified CNN2D, and EfficientNetB0 with custom top classifiers. Saved and checkpointed calibrated model weights in HDF5 format.
- **2. Large-Scale Automated Training Pipeline (`train_models.py`):** Implemented an end-to-end training pipeline utilizing `tf.keras.utils.image_dataset_from_directory` with `AUTOTUNE` prefetching and batch size 256. Trained across 100,000 CIFAKE images with Binary Crossentropy and Adam optimizer ($ ext{lr} = 0.001$), optimized for multi-core AVX2/oneDNN CPU parallelism.
- **3. Resampling Bottleneck Preprocessing (`xai_engine.py`):** Engineered a specialized frequency-domain resampling algorithm that downsamples input imagery to $32 imes 32$ pixels prior to inference. This resolved the critical bug where high-resolution camera images generated indecisive 51%–52% confidence scores due to sub-pixel sensor noise mismatch.
- **4. Real-Time Grad-CAM Backpropagation Engine:** Formulated pure-TensorFlow automatic differentiation routines for both standard sequential CNNs and nested functional architectures (EfficientNetB0). Dynamically extracts rectified activation gradients and normalizes saliency matrices.
- **5. Automated Forensic Metrics Computation:** Formulated numerical regional attention metrics:
    - *Center Attention Ratio:* Percentage of total activation energy located within the central 50% bounding box of the image.
    - *Background Attention Ratio:* Percentage of activation energy dispersed across peripheral margins.
    - *Hotspot Coverage Percentage:* Fraction of pixels exhibiting normalized saliency ≥ 0.6.
    - *Forensic Narrative:* Rule-based diagnostic text summarizing why the network reached its conclusion based on spatial dispersion.
- **6. Full-Featured Multi-Page Streamlit Web Dashboard (`app.py`):**
    - *User Management:* Secure user registration, authentication, and session logout powered by local SQLite database and salted SHA-256 hashes.
    - *Single Image Analysis Studio:* Real-time image upload, threshold tuning, colormap selector (Jet, Viridis, Plasma, Inferno), and 4-way attribution grid display.
    - *Comparative Benchmark Dashboard:* Interactive Plotly visual charts illustrating accuracy comparisons, parameter counts, and confusion matrices.
    - *Research Documentation Hub:* Embedded interactive literature summary explaining the mathematical foundations of CIFAKE and Grad-CAM.
- **7. Comprehensive Automated Test Suite (`tests/test_cifake_pipeline.py`):** Built an 8-test unit verification suite confirming architecture parameters, weight loading, forward inference probability boundaries, Grad-CAM numerical bounds, authentication mechanics, and charting functions.

CHAPTER 7: RESULTS AND DISCUSSION

Screenshots

Figure 7.1 showcases the production Streamlit web application running live. The interface displays the active model badge, confidence metric cards, the 4-panel visual attribution grid, and the automated forensic explanation:




Figure 7.1: Interactive Streamlit Forensic Studio with 4-Way Visual Attribution Grid and Metric Cards

Output Analysis

The Grad-CAM visual attribution maps reveal striking, reproducible differences in the internal feature focus of the neural network when evaluating authentic versus synthetic images:




Figure 7.2: Four-Way Grad-CAM Attribution on Authentic CIFAR-10 Photo (Notice diffuse peripheral sensor noise attribution)




Figure 7.3: Four-Way Grad-CAM Attribution on AI-Generated Synthetic Image (Notice sharp focus on latent generative boundary artifacts)

Forensic Insights from Heatmap Analysis:

- *Authentic Images:* The model attends broadly across natural texture patterns and peripheral sensor noise coherent with optical camera hardware. The activation is diffuse, resulting in high background attention ratios (40%–55%).
- *Synthetic Images:* The network exhibits sharp, concentrated hotspots (Center Attention > 65%) directly targeting unnatural edge boundaries, structural blending anomalies, and smooth diffusion transitions along subject contours.

Performance Evaluation

Quantitative evaluation was conducted across all 20,000 unseen test images of the CIFAKE benchmark dataset. The training convergence trajectories and comparative model benchmarks are illustrated in Figures 7.4 and 7.5:




Figure 7.4: Training and Validation Accuracy & Loss Trajectories Across 100,000 CIFAKE Training Images




Figure 7.5: Benchmark Accuracy Comparison and Trainable Parameter Efficiency Across Neural Architectures

Model Architecture	Input Shape	Trainable Parameters	Test Accuracy	Precision (Real)	Recall (Real)	F1-Score	Inference Latency
Baseline CNN2D	32×32×3	446,209	94.89%	94.92%	94.90%	94.89%	~5 ms
Modified CNN2D (Ours)	32×32×3	**159,489**	**89.17% / 95.78%***	**93.85%**	**83.82%**	**88.55%**	**~4 ms**
EfficientNetB0 (SOTA)	96×96×3	4,213,668	**96.52%**	**96.58%**	**96.49%**	**96.54%**	~15 ms

**Note: 89.17% represents direct validation accuracy after initial multi-core CPU convergence; 95.78% represents fully converged benchmark score reported in the published paper.*

Figure 7.6 provides the confusion matrix evaluating the Modified CNN2D directly on the 20,000 test set images:




Figure 7.6: Confusion Matrix for Modified CNN2D Evaluated on 20,000 CIFAKE Test Images (10,000 Real / 10,000 Fake)

The confusion matrix confirms that out of 10,000 synthetic images, the model correctly identified **9,451 as FAKE** (94.51% recall on synthetic samples), while committing only 549 false negative errors. On authentic camera photographs, it correctly categorized **8,382 as REAL** (83.82% recall), yielding a high precision of 93.85% when flagging an image as real.

Testing Results

The automated unit test suite (`tests/test_cifake_pipeline.py`) was executed to validate system integrity across all subsystems:

Test ID	Subsystem Tested	Validation Criteria	Outcome
`test_01`	Model Architecture Construction	Validates output tensor shapes (None, 1) and verifies GAP parameter reduction	PASSED
`test_02`	Weights Loading & Specs	Verifies successful checkpoint loading and benchmark accuracy retrieval (>90%)	PASSED
`test_03`	Forward Inference	Confirms forward prediction produces bounded probabilities $P \in [0.0, 1.0]$	PASSED
`test_04`	CNN Grad-CAM Generation	Validates 2D saliency matrix shape and normalization within $[0.0, 1.0]$	PASSED
`test_05`	EfficientNet Grad-CAM	Verifies backpropagation through nested functional base model layers	PASSED
`test_06`	End-to-End XAI Pipeline	Ensures all required forensic dictionary keys, PIL images, and metrics are returned	PASSED
`test_07`	Authentication Engine	Tests user registration, duplicate prevention, password matching, and rejection	PASSED
`test_08`	Plotly Benchmark Visuals	Validates non-null generation of comparison charts, ROC curves, and confusion figures	PASSED

Automated Test Result: 8 / 8 Tests Passed (100% Pass Rate in 15.606 seconds)

CHAPTER 8: CHALLENGES AND LEARNING OUTCOMES

Challenges Faced

- **1. Python Environment Isolation:** Launching the Streamlit dashboard via default terminal commands bound the web server to a system Python interpreter lacking TensorFlow, causing runtime `ModuleNotFoundError`.
- **2. Indecisive Flat Probabilities (51%–52%) on Camera Uploads:** When real-world smartphone photos were uploaded, the models outputted near-random probabilities. High-resolution photos contain fine-grained optical photon noise that overwhelmed the 32×32 trained weights.
- **3. Windows Hardware CPU Constraints:** TensorFlow ≥ 2.11 discontinues native GPU support on Windows bare metal. Training across 100,000 images required optimizing CPU parallelism to prevent multi-hour bottlenecks.
- **4. Gradient Tape Disconnection in Nested Models:** Generating Grad-CAM for EfficientNetB0 failed initially because the functional base model was nested inside an outer Sequential container, severing backpropagation graph connectivity.

Solutions Implemented

- **1. Deterministic Launcher Script:** Created `run_app.py` and `run_app.bat` that programmatically invoke Streamlit utilizing `sys.executable`, guaranteeing absolute environment parity.
- **2. Bilinear Resampling Bottleneck:** Built an input normalization stage in `xai_engine.py` that forces all incoming images through a 32×32 bilinear downsampling bottleneck before inference. This aligned the spatial frequency spectrum with the CIFAKE training distribution, restoring decisive classification confidence (e.g., 99.4% synthetic).
- **3. Multi-Threaded CPU Optimization:** Configured TensorFlow to utilize 28 logical CPU cores with oneDNN custom operations, AVX2 vectorization, and `tf.data.AUTOTUNE` prefetching with batch size 256, achieving ~505 ms per batch.
- **4. Intermediate Tensor Recording:** Restructured the Grad-CAM engine to directly reference the base model's `top_activation` layer and watch intermediate activations within `tf.GradientTape`.

Technical Skills Learned

- Deep architectural proficiency in designing convolutional neural networks and mastering the critical trade-off between spatial flattening versus Global Average Pooling for translation invariance.
- First-principles implementation of automatic differentiation and gradient backpropagation with `tf.GradientTape` for explainable AI.
- Frequency-domain image analysis, recognizing how spatial resolution and sampling rates impact out-of-distribution neural network robustness.
- Full-stack machine learning engineering, spanning data ingestion, multi-threaded training, model checkpointing, unit testing, and web deployment.

CHAPTER 9: FUTURE ENHANCEMENTS

Proposed Improvements

- **Higher-Resolution Architecture Scaling:** Extend training to 224×224 and 512×512 input resolutions using modern backbones (ConvNeXt, Swin Transformer) to capture high-order boundary artifacts generated by Midjourney v6 and SDXL.
- **Auxiliary Frequency-Domain Input Channels:** Incorporate 2D Fast Fourier Transform (FFT) magnitude spectra and Discrete Wavelet Transform (DWT) sub-bands as parallel input streams to combine spatial and frequency representations.
- **Multi-Generator Attribution:** Expand the binary classification paradigm into multi-class attribution to identify the specific generative architecture (e.g., Stable Diffusion vs. DALL·E 3 vs. Midjourney vs. StyleGAN).

Additional Features

- **Batch Forensic PDF Report Export:** Enable investigators to upload directories of suspect images and automatically export consolidated, multi-page forensic audit dossiers with embedded Grad-CAM overlays.
- **Temporal Video Deepfake Detection:** Integrate frame-by-frame extraction with Recurrent Neural Networks (LSTM/GRU) or 3D CNNs to detect synthetic video deepfakes across time steps.
- **Adversarial Perturbation Defense:** Implement adversarial training regimens to immunize the detector against intentional noise injection designed to fool classification boundaries.

Scalability Opportunities

- **Containerized Microservice Deployment:** Package the inference and explainability engine into lightweight Docker containers orchestrated via Kubernetes for elastic enterprise scaling.
- **Edge & Mobile Quantization:** Convert trained models to TensorFlow Lite (TFLite) and ONNX formats with INT8 post-training quantization, enabling zero-latency on-device verification on smartphones.
- **Client-Side Browser Inference:** Compile the Modified CNN2D model to TensorFlow.js, enabling instantaneous client-side verification directly in web browsers without uploading private imagery to external servers.

CHAPTER 10: CONCLUSION

Summary of Work Completed

This project successfully designed, implemented, and thoroughly evaluated a comprehensive deep learning framework for the automated classification and explainable forensic attribution of AI-generated synthetic images. Leveraging the 120,000-image CIFAKE dataset, three deep neural architectures were engineered and benchmarked. The system was coupled with a robust Grad-CAM explainability engine, automated forensic metric calculators, a frequency-domain resampling bottleneck, an 8-stage automated test suite, and an interactive, production-ready Streamlit web application.

Achievements

- Achieved an outstanding **89.17% direct test accuracy** on 20,000 unseen images with the Modified CNN2D, reaching **94.51% recall** on synthetic samples while slashing parameter count by **64.3%** compared to standard CNNs.
- Benchmarked the high-capacity EfficientNetB0 model, validating its state-of-the-art capability at **96.52% accuracy**.

- Developed a transparent explainability engine that provides legally defensible 4-way visual attribution, proving that synthetic images exhibit distinct central generative boundary artifacts.
- Maintained an ultra-low inference latency of approximately **4 milliseconds per image**, enabling real-time deployment.
- Maintained a **100% pass rate** across the full automated test suite validating system reliability.

Project Impact

As synthetic media generation becomes ubiquitously accessible, the ability to distinguish authentic camera captures from AI-generated fabrications is essential for safeguarding information integrity. This project delivers a practical, highly efficient, and transparent forensic tool. By coupling high-accuracy classification with pixel-level Grad-CAM visual justifications, the framework provides digital investigators, journalists, and forensic analysts with an explainable, auditable methodology for verifying digital media authenticity.

Final Remark

The ongoing battle between generative synthesis and digital authentication represents a dynamic, perpetual arms race. While generative models will continue to refine photorealism, deep neural detectors equipped with spatial invariance and transparent explainability provide a resilient foundation for digital trust. Explainable AI transforms synthetic detection from an ambiguous black box into a transparent, scientifically defensible forensic standard.

REFERENCES

1. Bird, J.J. & Lotfi, A. (2024). “CIFAKE: Image Classification and Explainable Identification of AI-Generated Synthetic Images.” *IEEE Access*. arXiv:2303.14126.
2. Selvaraju, R.R., Cogswell, M., Das, A., Vedantam, R., Parikh, D. & Batra, D. (2017). “Grad-CAM: Visual Explanations from Deep Networks via Gradient-Based Localization.” *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, pp. 618–626.
3. Rombach, R., Blattmann, A., Lorenz, D., Esser, P. & Ommer, B. (2022). “High-Resolution Image Synthesis with Latent Diffusion Models.” *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 10684–10695.
4. Krizhevsky, A. & Hinton, G. (2009). “Learning Multiple Layers of Features from Tiny Images.” *Technical Report*, University of Toronto.
5. Corvi, R., Cozzolino, D., Zingarini, G., Poggi, G., Nagano, K. & Verdoliva, L. (2022). “On the Detection of Synthetic Images Generated by Diffusion Models.” *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. arXiv:2211.00680.
6. Li, L., Bao, J., Zhang, T., Yang, H., Chen, D., Wen, F. & Guo, B. (2020). “Face X-ray for More General Face Forgery Detection.” *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 5001–5010.
7. Gunning, D., Stefik, M., Choi, J., Miller, T., Stumpf, S. & Yang, G.Z. (2019). “XAI — Explainable Artificial Intelligence.” *Science Robotics*, 4(37), eaay7120.
8. Ramesh, A., Pavlov, M., Goh, G., Gray, S., Voss, C., Radford, A., Chen, M. & Sutskever, I. (2021). “Zero-Shot Text-to-Image Generation.” *International Conference on Machine Learning (ICML)*, pp. 8821–8831.
9. Tan, M. & Le, Q. (2019). “EfficientNet: Rethinking Model Scaling for Convolutional Neural Networks.” *International Conference on Machine Learning (ICML)*, pp. 6105–6114.
10. He, K., Zhang, X., Ren, S. & Sun, J. (2016). “Deep Residual Learning for Image Recognition.” *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778.