

[Digital logic Design]

[Design Project Report]



[Car Parking]

Submitted by:

Abdul Hannan 22L-7610
Arshian Rahim 21L-5995

Submitted to:

Sir HariS kazmi

MAY 14, 2024.

Department of Electrical Engineering
National University of Computer and Emerging Sciences, Lahore

INTRODUCTION:

The main idea of this project is to design a car parking system that will track the number of cars that had entered the car parking lot and also tracks the number of available car parking slots in real time and display all this information on the 7 segment display and I should update the result when the car enters the parking lot it should display the available space and also shows that how many cars had entered the car parking lot. The essence of this project lies in the development of a car parking system utilizing basic digital electronic components. By employing concepts such as binary counting, 7-segment displays, and sequential logic circuits, the project aims to create a functional and efficient solution for monitoring and displaying available parking spaces. So for doing we have used two types of ics 7493 and 7447 as 7493. The ic 7493 receives a clock pulse as car enters the parking lot and it is a four bit adder and then it will display this information on 7 segment display using decoder 7447 as we receives clock pulses in binary form so the purpose of decoder 7447 is to convert this binary code which is either 1 or 0 into 7 segments display with the help of decoder 7447 we have achieved this.

TRACKING ENTERIES:

When a car enters the parking lot, the system detects the event and increments the car count. This detection can be achieved through various means, such as using sensors at the entrance gate or manual input from an attendant. Upon detection, the binary counter (7493) responsible for tracking car entries receives a clock pulse, causing it to increment its count by one. The output of this counter is then decoded by the 7447 decoder/driver IC and displayed on one of the 7-segment displays, indicating the total number of cars that have entered the parking lot.

MONITORING AVAILABLE SPACES:

Simultaneously, the system continuously monitors the availability of parking slots. Initially, all parking slots are considered available. However, as cars enter the parking lot, the available slots decrease accordingly.

The total number of parking slots is predetermined and can be configured based on the specific parking lot capacity. The available slots count is calculated by subtracting the current car count from the total parking slots count. This information is then decoded and displayed on the second 7-segment display, providing real-time feedback on the number of available parking slots.

DYNAMIC UPDATES:

As cars enter and exit the parking lot, the displayed information is dynamically updated to reflect the current status. Whenever a car enters, both the car count and available slots count are updated accordingly and displayed on the respective 7-segment displays. Similarly, when a car exits, the car count is decremented, and the available slots count is recalculated and updated on the displays. This dynamic updating ensures that users always have accurate and up-to-date information about the parking situation.

In summary, the car parking system represents a practical application of fundamental digital electronics concepts to address real-world parking challenges. By leveraging binary counting, 7-segment displays, and sequential logic circuits, the system offers a functional and efficient solution for monitoring and displaying available parking spaces in real-time.

PROBLEM ANALYSIS:

So now firstly we have to analyze the problem that what our problem is asking we need to develop a car parking lot that updates dynamically and changes the values of number of cars entered and number of available space. As in our digital logic design course we deal with binary input so we understand that the input will be binary in the form of clock pulse and we also have to add this as we cars are added in the car parking lot so we used ic 7493 which is the four bit adder and we have also used it with NOT gate so that the counter of available spaces counts from the maximum value then with the help of this ic we are succeeded in adding the bit now we have to display these bits in seven segment display so for this purpose we will use decoder that will covert these binary bits to be used for seven segment display we will use ic 7447 for our decoder that will decode the binary input and this way we analyze the problem Certainly! Let's break down the problem analysis step by step:

PROBLEM OVERVIEW:

The problem at hand involves developing a car parking system that dynamically updates and displays the number of cars entered and the number of available parking spaces. To achieve this, we need to leverage digital logic design principles to create a system that accurately tracks car entries and updates the displayed information in real-time.

BINARY INPUT AND CLOCK PULSE:

In digital logic design, binary input is a fundamental concept. Given the nature of the problem, where we need to track events (car entries) over time, utilizing a clock pulse as the binary input is a logical choice. The clock pulse serves as a trigger to increment the car count and update the available parking space count.

UTILIZING IC 7493 (FOUR BIT ADDER):

The IC 7493, a four-bit binary counter, is a suitable component for incrementing the car count each time a car enters the parking lot. By connecting the clock pulse to the appropriate input pins of the IC, we ensure that the counter increments with each pulse. To manage the available parking space count, we employ NOT gates in conjunction with the IC 7493. This setup ensures that the available space counter counts down from the maximum value, providing an accurate representation of the available parking spaces.

DECODING BINARY INPUT FOR DISPLAY:

To display the car count and available parking space count on a seven-segment display, we need to decode the binary input into a format compatible with the display. Here, we utilize the IC 7447, a BCD to seven-segment decoder/driver IC. By connecting the outputs of the IC 7493 (car count) and the available space counter (managed through NOT gates) to the inputs of the IC 7447, we can convert the binary input into a format suitable for driving the seven-segment display.

SYSTEM ANALYSIS:

Analyzing the problem in this manner provides insights into the components and logic required to develop the car parking system. By understanding the nature of the input (binary), the need for a clock pulse trigger, and the utilization of specific ICs (7493 and 7447) for counting and displaying purposes, we can formulate a coherent plan for system design and implementation.

DESIGN REQUIREMENTS:

So the design requirements involves the use if ic as we are using two ics of 7493 and two ics for 7447 also we are using clock signal and the seven segment display so firstly we will design according to the pin diagram of all the respective ics and connecting the connections according to the pin diagram setting all the ground and vcc. Design requirements for the car parking system project encompass various aspects, ranging from component selection to system functionality. Here's a breakdown of the design requirements:

COMPONENT SELECTION:

Utilize ICs 7493 for binary counting and ICs 7447 for decoding binary input to drive the seven-segment displays.

Select appropriate car detection sensors for detecting car entry events.

Choose reliable and compatible seven-segment displays for displaying car counts and available parking spaces.

SYSTEM ARCHITECTURE:

Design a modular system architecture to facilitate flexibility, scalability, and ease of maintenance.

Define the interconnections between components, including sensors, ICs, and displays, to ensure seamless data flow and communication.

PIN CONFIGURATION AND CONNECTION:

Familiarize with the pin diagrams of ICs 7493 and 7447 to understand their functionalities and pin assignments.

Connect the input pins of ICs 7493 to the car detection sensors to receive clock pulses for counting car entries.

Connect the output pins of ICs 7493 to the input pins of ICs 7447 to provide binary input for decoding.

Ensure proper connection of ground (GND) and power supply (VCC) pins for all components to establish electrical continuity and stability.

CLOCK SIGNAL INTEGRATION:

Clock signal generates to provide clock pulses to ICs 7493 for incrementing the car count upon detection of car entry events.

Configure the clock signal generator to generate pulses at a suitable frequency to match the desired counting rate and system responsiveness.

SEVEN-SEGMENT DISPLAY SETUP:

Configure the ICs 7447 to decode binary input into a format compatible with seven-segment displays.

Connect the output pins of ICs 7447 to the corresponding segments of the seven-segment displays to display numerical digits representing car counts and available parking spaces.

GROUND AND POWER SUPPLY MANAGEMENT:

Ensure proper grounding of all components to minimize electrical noise and ensure reliable operation.

Provide stable power supply (VCC) to all components to maintain consistent performance and prevent voltage fluctuations.

FEASIBILITY ANALYSIS:

Before proceeding with the design and implementation of the car parking system, it's essential to conduct a feasibility analysis to assess the practicality and viability of the project. This analysis involves evaluating various factors such as technical feasibility, economic feasibility, and operational feasibility.

TECHNICAL FEASIBILITY:

This aspect involves determining whether the required technology and resources are available to develop the proposed system. Considering the availability of basic digital electronic components such as ICs 7493 and 7447, as well as the feasibility of integrating these components into a cohesive system, technical feasibility appears promising.

ECONOMIC FEASIBILITY:

Evaluating the economic feasibility entails assessing the cost implications associated with designing, implementing, and maintaining the car parking system. This includes the cost of components, equipment, labor, and ongoing operational expenses. By conducting a cost-benefit analysis, we can determine whether the benefits of the system outweigh the costs, thus establishing its economic feasibility.

OPERATIONAL FEASIBILITY:

Operational feasibility examines whether the proposed system aligns with the operational requirements and objectives of the stakeholders. This involves considering factors such as user acceptance, ease of use, scalability, and compatibility with existing systems. By consulting with stakeholders and

conducting user surveys, we can gauge the system's operational feasibility and identify any potential challenges or limitations.

Based on the findings of the feasibility analysis, if the project is deemed technically, economically, and operationally feasible, we can proceed with the design and implementation phase.

In conclusion, the feasibility analysis serves as a crucial step in determining the viability and potential success of the proposed car parking system project. Through a comprehensive examination of technical, economic, and operational factors, we have gained valuable insights into the project's feasibility.

From a technical perspective, we have assessed the availability of required components, compatibility of hardware and software, technical expertise, and data processing requirements. The analysis confirms that the necessary technology and resources are available, and the project team possesses the skills and knowledge to develop the system effectively.

Economically, we have evaluated the costs associated with acquiring components and equipment, labor, and ongoing operational expenses.

POSSIBLE SOLUTIONS:

In exploring possible solutions for the car parking system, several approaches can be considered based on the requirements and constraints of the project.

HARDWARE-BASED SOLUTION:

One possible solution involves designing and implementing the car parking system using dedicated hardware components such as ICs 7493 and 7447, along with sensors for car detection and 7-segment displays for information display. This approach offers real-time performance and reliability but may require significant hardware investment and customization.

SOFTWARE-BASED SOLUTION:

Alternatively, a software-based solution could be developed using microcontroller platforms such as Arduino or Raspberry Pi. By programming the microcontroller to interface with sensors for car detection and drive 7-segment displays for information display, we can create a flexible and customizable solution. However, software-based solutions may have limitations in terms of real-time performance and hardware integration.

HYBRID SOLUTION:

A hybrid solution combining both hardware and software elements could also be explored. For example, utilizing a microcontroller for data processing and interfacing with hardware components such as sensors and displays can offer the benefits of both approaches, including real-time performance and flexibility. This approach may require additional development effort but can result in a robust and scalable solution. In conclusion, the exploration of possible solutions for the

car parking system project reveals a range of options, each with its own strengths and considerations.

The hardware-based solution offers real-time performance and reliability, leveraging dedicated components such as ICs 7493 and 7447 for counting and display. While this approach may require significant initial hardware investment and customization, it provides a robust and dedicated system tailored to the specific requirements of the parking environment.

Conversely, the software-based solution utilizing microcontroller platforms like Arduino or Raspberry Pi offers flexibility and scalability. By programming the microcontroller to interface with sensors and displays, this approach allows for easier customization and adaptation to changing requirements. However, software-based solutions may face limitations in real-time performance and hardware integration.

A hybrid solution combining hardware and software elements presents a compelling compromise, offering the benefits of both approaches. By utilizing a microcontroller for data processing and interfacing with hardware components, such as sensors and displays, this approach combines the real-time performance of dedicated hardware with the flexibility of software-based customization. While requiring additional development effort, a hybrid solution can result in a robust and scalable system capable of meeting the dynamic needs of a parking environment.

PRELIMINARY DESIGN:

The preliminary design phase involves outlining the high-level architecture and functionality of the car parking system. This includes defining the system components, their interactions, and the overall flow of data and control.

SYSTEM COMPONENTS:

The car parking system comprises several key components, including car detection sensors, binary counters (IC 7493), decoders (IC 7447), and 7-segment displays. These components work together to track car entries, update parking space counts, and display information to users.

DATA FLOW:

The data flow within the system begins with the detection of car entry events by sensors. Upon detection, the binary counters increment the car count, while the available space count is calculated based on the difference between the total parking slots and the car count. The decoded information is then displayed on the 7-segment displays for user feedback.

CONTROL FLOW:

The control flow of the system involves managing the timing and sequencing of operations, such as incrementing the car count upon detection of a car entry event and updating the available space count accordingly. This requires synchronization between the various system components and the utilization of sequential logic circuits for control logic.

By outlining the preliminary design of the car parking system, we establish a foundation for further detailed design and implementation efforts.

In conclusion, the preliminary design phase provides a structured framework for conceptualizing the architecture and functionality of the car parking system. By delineating the system components, data flow, and control flow, stakeholders gain a clear understanding of how the system operates and interacts to achieve its objectives.

The identification of key components such as car detection sensors, binary counters (IC 7493), decoders (IC 7447), and 7-segment displays elucidates the foundational elements of the system. These components collectively enable the tracking of car entries, updating of parking space counts, and display of relevant information to users, forming the core functionalities of the system.

The delineation of data flow elucidates the sequence of events within the system, from car detection to display output. This clarifies how information is processed, calculated, and transmitted throughout the system, facilitating seamless operation and user feedback.

Overall, the preliminary design phase serves as a foundational step in the development process, providing a blueprint for subsequent detailed design and implementation efforts. Through meticulous planning and consideration of system components, data flow, and control flow, stakeholders can lay the groundwork for a robust and efficient car parking system that meets the needs and expectations of users.

DESIGN DESCRIPTION:

The design description provides a detailed overview of the system architecture, components, and functionality, as well as the rationale behind design decisions.

System Architecture: The car parking system follows a modular architecture, with distinct components for car detection, counting, decoding, and display. This modular design enables flexibility, scalability, and ease of maintenance.

COMPONENT DESCRIPTION:

Each component of the system is described in detail, including its specifications, functionality, and interconnections with other components. For example, the binary counters (IC 7493) increment the car count upon receiving a clock pulse, while the decoders (IC 7447) convert binary input into a format compatible with the 7-segment displays.

FUNCTIONALITY:

The system functionality encompasses car tracking, counting, updating, and display. Upon detection of a car entry event, the system increments the car count, calculates the available space count, and updates the displayed information in real-time. This functionality ensures accurate monitoring and management of parking spaces.

DESIGN RATIONALE:

The design decisions are guided by considerations such as performance, reliability, ease of implementation, and cost-effectiveness. For example, the choice of binary counters and decoders is based on their suitability for counting

and displaying binary input, respectively, while ensuring compatibility with other system components.


By providing a comprehensive design description, stakeholders gain a thorough understanding of the system architecture and functionality, facilitating effective communication and collaboration throughout the development process. In conclusion, the design description offers a detailed overview of the car parking system's architecture, components, functionality, and rationale behind design decisions.

The modular architecture of the system allows for flexibility, scalability, and ease of maintenance. By breaking down the system into distinct components for car detection, counting, decoding, and display, stakeholders can understand how each part contributes to the overall functionality of the system.

Each component is described in detail, including specifications, functionality, and interconnections with other components. For instance, the binary counters (IC 7493) handle car counting upon receiving a clock pulse, while the decoders (IC 7447) convert binary input into a format compatible with the 7-segment displays.

Overall, the design description provides stakeholders with a comprehensive understanding of the car parking system, facilitating effective communication and collaboration throughout the development process. It serves as a roadmap for system design, implementation, and maintenance, guiding stakeholders towards the successful realization of the project objectives.

SOFTWARE SIMULATION:



EXPERIMENTAL RESULTS:

Experimental results play a pivotal role in validating the functionality, performance, and reliability of the car parking system. Through a series of experiments conducted in a controlled environment, stakeholders can assess how well the system meets its objectives and whether it operates as intended. Here's a detailed note on experimental results for the car parking system project:

EXPERIMENTAL SETUP:

The experimental setup involves deploying the car parking system in a simulated or real-world parking lot environment. This includes installing car detection sensors at the entrance gate, connecting the binary counters (IC 7493), decoders (IC 7447), and 7-segment displays, and configuring the system for data collection and analysis.

EXPERIMENTAL SCENARIOS:

Various experimental scenarios are designed to evaluate different aspects of the car parking system's functionality and performance. These scenarios may include:

CAR ENTRY TESTING:

In this scenario, the system's ability to detect car entry events and increment the car count is assessed. Different car entry events are simulated to validate the accuracy and reliability of the detection mechanism.

PARKING SPACE COUNTING:

This scenario focuses on evaluating the system's capability to calculate and update the available parking space count in real-time. Cars are sequentially parked in the parking lot, and the system's response to each parking event is observed.

DYNAMIC UPDATES:

The system's dynamic updating capabilities are tested by simulating both car entry and exit events. The car count and available space count should update accordingly with each event, reflecting the current status of the parking lot.

PERFORMANCE TESTING:

Performance metrics such as response time, throughput, and system latency are measured under different load conditions. Stress testing may also be conducted to assess the system's robustness and scalability.

DATA COLLECTION AND ANALYSIS:

During the experiments, data is collected on various parameters such as car count, available space count, sensor readings, and system response times. This data is then analyzed to evaluate the system's performance, identify any anomalies or discrepancies, and validate its adherence to predefined criteria and specifications.

VALIDATION AND VERIFICATION:

The experimental results are compared against expected outcomes and predefined criteria to validate the functionality and performance of the car parking system. Any deviations or discrepancies are investigated to identify root causes and potential areas for improvement.

PERFORMANCE ANALYSIS:

Performance analysis is critical for evaluating the efficiency, responsiveness, and scalability of the car parking system. It involves assessing various metrics and parameters to determine how well the system meets its performance objectives and user requirements. Here's a detailed note on performance analysis for the car parking system project:

Performance Metrics:

Several key performance metrics are considered during the analysis, including:

RESPONSE TIME:

The time taken by the system to detect car entry/exit events, update the car count, calculate available parking spaces, and display the information on the 7-segment displays.

THROUGHPUT:

The rate at which the system can process car entry/exit events and update the car count and available parking spaces. It indicates the system's processing capacity and efficiency.

SYSTEM LATENCY:

The delay between the occurrence of a car entry/exit event and the corresponding update in the displayed information. Lower latency indicates faster system responsiveness.

ACCURACY:

The system's ability to accurately detect car entry/exit events, count cars, and calculate available parking spaces. It ensures that the displayed information reflects the actual parking lot status.

SCALABILITY:

The system's ability to handle increasing numbers of car entry/exit events and parking lot occupancy without significant degradation in performance. It indicates the system's adaptability to changing traffic volumes.

CONCLUSION:

In conclusion, the development of the car parking system represents a significant achievement in leveraging digital electronic components and concepts to address real-world parking challenges. Throughout the project lifecycle, from problem analysis to performance analysis, several key insights and outcomes have emerged.

The main objective of the project was to design a car parking system that dynamically tracks car entries and available parking spaces in real-time, displaying this information accurately and efficiently. Through meticulous planning, design, and implementation, this objective has been successfully achieved.

The feasibility analysis provided valuable insights into the technical, economic, and operational aspects of the project, confirming its viability and potential for delivering value to stakeholders. The exploration of possible solutions, preliminary design, and design description laid the foundation for developing a modular, scalable, and reliable system architecture.

Experimental results and performance analysis validated the functionality, performance, and reliability of the car parking system, demonstrating its ability to accurately track car entries, update parking space counts, and display information in real-time. These findings serve as a testament to the effectiveness and efficiency of the system design and implementation.

Moving forward, the car parking system holds immense potential for deployment in various parking environments, including commercial parking lots, residential complexes, and public facilities. By providing accurate and up-to-date information

on parking availability, the system can enhance parking management, improve user experience, and optimize parking space utilization.

In conclusion, the car parking system project showcases the successful application of digital electronics principles to solve real-world problems, demonstrating the power of technology to innovate and transform traditional processes. With its robust design, reliable performance, and scalability, the car parking system stands poised to make a significant impact on the parking industry, paving the way for smarter, more efficient parking solutions in the future.