

資料庫管理 HW03

B12508026 戴偉璿

1. (a) Left join all advisors(e) and their advisees(s), if someone has no advisee, then s would be NULL.

```
1 select e.id, e.name from employee as e
2 left join employee s on e.id=s.supervisor_id
3 where s.supervisor_id is null;
```

- (b) Find the latest store id of each employee before 2025-01-05 and left join to the employee table.

```
1 select e.id as employee_id, h.store_id
2 from employee e
3 left join employee_store_history h
4 on e.id = h.employee_id
5 and h.start_date_time=(
6     select max(h2.start_date_time)
7     from employee_store_history h2
8     where h2.employee_id = e.id
9         and h2.start_date_time <= '2025-01-05'
10 );
```

- (c) Using limit 1 to obtain the first store id and limit 1 offset 1 to obtain the second store id (after skipping the first one), then join them to produce the final result.

```
1 select e.id as employee_id,
2     (select h1.store_id from employee_store_history h1 where h1.employee_id=e.id order by
3     ↪ h1.start_date_time limit 1) as first_store_id,
4     (select h2.store_id from employee_store_history h2 where h2.employee_id=e.id order by
5     ↪ h2.start_date_time limit 1 offset 1) as second_store_id
6 from employee e;
```

- (d) Calculating the total quantity purchased for each product, then ordering by total quantity and product_id, using limit 2 offset 3 to find the 4th and 5th products. Finally, joining with purchase_detail and purchase tables to get the required information.

```
1 with total_qty as(
2     select pd.product_id as product_id, sum(pd.qty) as total_qty, count(*) as purchase_count
3     from purchase_detail pd
```

```

4     group by pd.product_id
5 ),
6 target_product as(
7     select product_id
8     from total_qty
9     order by total_qty desc, product_id asc
10    limit 2 offset 3
11 )
12 select p.id as product_id, p.name as product_name, pu.store_id as store_id, count(*) as
    ↪ purchase_count, sum(pd.qty) as total_qty
13 from target_product tp
14 join product p on tp.product_id = p.id
15 join purchase_detail pd on pd.product_id = p.id
16 join purchase pu on pd.purchase_no = pu.purchase_no
17 group by p.id, p.name, pu.store_id
18 order by p.id, pu.store_id;

```

- (e) First choose the target product ids by ranking the total purchased quantity, then cross join with store table to get all combinations of target products and stores. Finally, left join with purchase and purchase_detail tables to get the required information.

```

1 with total_qty as(
2     select pd.product_id as product_id, row_number() over(order by sum(pd.qty) desc,
    ↪ pd.product_id asc) as rnk
3     from purchase_detail pd
4     group by pd.product_id
5 ),
6 target as(
7     select product_id
8     from total_qty
9     where rnk >= 4 and rnk <= 5
10 )
11 select t.product_id as id, p.name as name, s.id as store_id, coalesce(sum(pd.qty), 0) as amount,
    ↪ coalesce(count(distinct pu.purchase_no), 0) as cnt
12 from target t --target store id
13 cross join store s
14 left join purchase pu on pu.store_id = s.id
15 left join purchase_detail pd on pu.purchase_no = pd.purchase_no and t.product_id = pd.product_id
16 join product p on p.id = t.product_id
17 group by s.id, t.product_id, p.name
18 order by t.product_id, s.id;

```

- (f) Calculate the total spending of each member in each store, then rank them within each store based on the total spending. Using `rank()` instead of `row_number()` to handle ties in spending amounts. While ranking, using `partition by` to separate rankings for each store.

```

1 select sa.store_id as store_id, sa.member_id as member_id, sum(sd.unit_price*sd.qty) as amount,
    ↪ rank() over(partition by sa.store_id order by sum(sd.unit_price*sd.qty) desc) as rnk
2
3 from sales sa
4 join sales_detail sd on sd.receipt_no = sa.receipt_no
5 where member_id is not null

```

```

6 group by sa.store_id, sa.member_id
7 order by sa.store_id, rnk;

```

2. (a) First, I identified the hard questions based on the number of total answers and correct answers. Then, for each hard question, I found each user's first correct submission and ranked the users by cost time and submission timestamp. Finally, I counted the number of hard questions where each user ranked in the top 3 and kept only those who appeared in at least two questions.

Fig. 1 shows the leaderboard of top users appearing in at least two hard questions.




Figure 1: Leaderboard of Top Users Appearing in at Least Two Hard Questions

Following is my source code, I used DuckDB to execute the SQL query and Matplotlib to visualize the results.

```

1 import duckdb
2 import matplotlib.pyplot as plt
3
4 con = duckdb.connect('my_database.db')
5
6 df = con.sql("""
7 -- list the hard questions
8 with hard_questions as(
9     select question_id as id, count(*) as total_ans, sum(is_correct) as total_ac
10    from answers
11   group by question_id
12   having total_ans >= 1000 and total_ac <= 500
13 ),-- list the rank for all users
14 first_correct_pre as(
15     select question_id, user_id, cost_time, created_at, rank() over(partition by question_id,
16     ↪ user_id order by created_at asc) as rnk
17    from answers
18   where is_correct = 1
19 ),-- first correct for each user
20 first_correct as(
21     select question_id, user_id, cost_time, created_at

```

```

21     from first_correct_pre
22     where rnk = 1
23 ),--rank users for hard questions
24 usr_rnk as(
25     select question_id, user_id, rank() over(partition by question_id order by cost_time asc,
26         ↪ created_at asc) as rnk
27     from first_correct fc
28     join hard_questions hq on hq.id = fc.question_id
29 )
29 select user_id, count(distinct question_id) as appr_cnt
30 from usr_rnk
31 where rnk <= 3
32 group by user_id
33 having appr_cnt >= 2
34 order by appr_cnt desc, user_id asc;
35 """).df()
36 print(df)
37
38 plt.figure(figsize=(12,6))
39 plt.bar(df["user_id"].astype(str), df["appr_cnt"])
40 plt.xlabel("User ID")
41 plt.ylabel("Number of Ranked Hard Questions")
42 plt.title("Leaderboard Top Users (Appearing in >= 2 Hard Questions)")
43 plt.tight_layout()
44 plt.savefig("2a_leaderboard.png")
45 plt.show()

```

- (b) Using the same CTEs as in 2a to find the users who ranked in the top 3 for hard questions. Then I calculated their scores based on the given scoring system. Finally, I kept only those users with a total score of at least 5.

Fig. 2 shows the leaderboard of top users with a score of at least 5.




Figure 2: Leaderboard of Top Users with a Score of at Least 5

Following is my source code:

```

1 import duckdb
2 import matplotlib.pyplot as plt

```

```
3
4 con = duckdb.connect('my_database.db')
5
6 df = con.sql("""
7 -- list the hard questions
8 with hard_questions as(
9     select question_id as id, count(*) as total_ans, sum(is_correct) as total_ac
10    from answers
11   group by question_id
12   having total_ans >= 1000 and total_ac <= 500
13 ),-- list the rank for all users
14 first_correct_pre as(
15     select question_id, user_id, cost_time, created_at, rank() over(partition by question_id,
16     ↪ user_id order by created_at asc) as rnk
17    from answers
18   where is_correct = 1
19 ),-- first correct for each user
20 first_correct as(
21     select question_id, user_id, cost_time, created_at
22    from first_correct_pre
23   where rnk = 1
24 ),--rank users for hard questions
25 usr_rnk as(
26     select question_id, user_id, rank() over(partition by question_id order by cost_time asc,
27     ↪ created_at asc) as rnk
28    from first_correct fc
29   join hard_questions hq on hq.id = fc.question_id
30 )
31 select user_id,
32        sum(
33            cast(rnk = 1 as int) * 5 +
34            cast(rnk = 2 as int) * 2 +
35            cast(rnk = 3 as int) * 1
36        ) as score
37 from usr_rnk
38 where rnk <= 3
39 group by user_id
40 having score >= 5
41 order by score desc, user_id asc;
42 """).df()
43 print(df)
44
45 plt.figure(figsize=(12,6))
46 plt.bar(df["user_id"].astype(str), df["score"])
47 plt.xlabel("User ID")
48 plt.ylabel("Score")
49 plt.title("Leaderboard Top Users (Score >= 5)")
50 plt.tight_layout()
51 plt.savefig("2b_leaderboard.png")
52 plt.show()
```