

- 1) Write a command that puts the following values, in their given order, into the salespeople table:  
city – San Jose, name – Blanco, comm – NULL, cnum – 1100.

```
W1_84109_Sumit>INSERT INTO SALESPEOPLE (City,Sname,Comm,Snum)
-> VALUES('San Jose','Blanco',NULL,1100);
Query OK, 1 row affected (0.01 sec)
```

- 2) Write a command that removes all orders from customer Clemens from the Orders table.

```
W1_84109_Sumit>Select * from ORDERS;
+-----+-----+-----+-----+
| Onum | Amt   | Odate   | Cnum | Snum |
+-----+-----+-----+-----+
| 3001 | 18.63 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-05 | 2006 | 1001 |
| 3010 | 1309.95 | 1990-10-06 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-06 | 2006 | 1001 |
+-----+-----+-----+-----+
10 rows in set (0.00 sec)
```

2) Write a command that removes all orders from customer Clemens from the Orders table.

```
W1_84109_Sumit>DELETE
-> FROM ORDERS
-> Where Cnum IN
-> (Select Cnum
-> from CUSTOMER
-> Where Cname='Clemens');
Query OK, 2 rows affected (0.02 sec)

W1_84109_Sumit>Select * from ORDERS
-> ^C
W1_84109_Sumit>Select * from ORDERS;
+-----+-----+-----+-----+-----+
| Onum | Amt      | Odate      | Cnum | Snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.63    | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19   | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10  | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45  | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16  | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23  | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75    | 1990-10-04 | 2004 | 1002 |
| 3010 | 1309.95  | 1990-10-06 | 2004 | 1002 |
+-----+-----+-----+-----+-----+
8 rows in set (0.00 sec)
```