

- 1) Write two different queries that would produce all orders taken on October 3rd or 4th, 1990.

```
W1_84109_Sumit>Select * from ORDERS Where Odate =1990-10-03 or Odate = 1990-10-04;
Empty set, 2 warnings (0.00 sec)

W1_84109_Sumit>Select * from ORDERS Where Odate = '1990-10-03' or Odate = '1990-10-04';
+-----+-----+-----+-----+-----+
| Onum | Amt   | Odate   | Cnum | Snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.63 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
+-----+-----+-----+-----+-----+
7 rows in set (0.00 sec)
```

```
W1_84109_Sumit>Select * from ORDERS Where Odate Between '1990-10-03' and '1990-10-04';
+-----+-----+-----+-----+-----+
| Onum | Amt   | Odate   | Cnum | Snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.63 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
+-----+-----+-----+-----+-----+
7 rows in set (0.00 sec)
```

- 2) Write two different queries that would produce all orders taken on October 3rd or 4th, 1990.

```
W1_84109_Sumit>Select * from CUSTOMER where Snum =1001 or Snum= 1004;
+-----+-----+-----+-----+-----+
| Cnum | Cname   | City   | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2001 | Hoffman | London | 100    | 1001 |
| 2006 | Clemens | London | 100    | 1001 |
| 2007 | Pereira | Rome   | 100    | 1004 |
+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

- 3) Write a query that will produce all the customers whose names begin with a letter from 'A' to 'G'.

```
W1_84109_Sumit>Select * from CUSTOMER where Cname regexp '^[A-G]';
+-----+-----+-----+-----+-----+
| Cnum | Cname   | City   | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome   | 200    | 1003 |
| 2004 | Grass    | Berlin | 300    | 1002 |
| 2006 | Clemens  | London | 100    | 1001 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
+-----+-----+-----+-----+-----+
4 rows in set (0.01 sec)
```

- 4) Write a query that selects all customers whose names begin with the letter 'C'.

```
W1_84109_Sumit>Select * from CUSTOMER where Cname LIKE 'C%';
+-----+-----+-----+-----+-----+
| Cnum | Cname   | City    | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2006 | Clemens | London  | 100    | 1001 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
+-----+-----+-----+-----+-----+
2 rows in set (0.00 sec)

W1_84109_Sumit>
```

- 5) Write a query that selects all orders except those with zeroes or NULLs in the amt field.

```
W1_84109_Sumit>Select * from ORDERS Where Amt !='0' OR Amt !=NULL;
+-----+-----+-----+-----+-----+
| Onum | Amt      | Odate      | Cnum | Snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.63    | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19   | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10  | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45  | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16  | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23  | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75    | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00  | 1990-10-05 | 2006 | 1001 |
| 3010 | 1309.95  | 1990-10-06 | 2004 | 1002 |
| 3011 | 9891.88  | 1990-10-06 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
10 rows in set, 1 warning (0.00 sec)
```