

## Assignment -6

### Using Special Operators in Conditions.

1) Write two different queries that would produce all orders taken on October 3<sup>rd</sup> or 4<sup>th</sup>, 1990.

**Select \* from Orders where odate between '1990-10-03' and '1990-10-04';**

```
W1_89793_Saurabh>Select * from Orders
-> where odate between '1990-10-03' and '1990-10-04';
+-----+-----+-----+-----+-----+
| Onum | Amt      | Odate      | Cnum | Snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69    | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19   | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10  | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45  | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16  | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23  | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75    | 1990-10-04 | 2004 | 1002 |
+-----+-----+-----+-----+-----+
7 rows in set (0.00 sec)
```

**Select \* from Orders where odate in('1990-10-03','1990-10-04');**

```
W1_89793_Saurabh>Select * from Orders
-> where odate in('1990-10-03','1990-10-04') ;
+-----+-----+-----+-----+-----+
| Onum | Amt      | Odate      | Cnum | Snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69    | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19   | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10  | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45  | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16  | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23  | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75    | 1990-10-04 | 2004 | 1002 |
+-----+-----+-----+-----+-----+
7 rows in set (0.00 sec)
```

2) Write a query that selects all of the customers serviced by Peel or Motika.  
(Hint: the snum field relates the two tables to one another).

**Select \* from Customers where snum in(1001, 1004);**

```
W1_89793_Saurabh>Select * from Customers
-> where snum in(1001, 1004);
+-----+-----+-----+-----+-----+
| Cnum | Cname   | City    | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2001 | Hoffman | London  | 100    | 1001 |
| 2006 | Clemens | London  | 100    | 1001 |
| 2007 | Pereira | Rome    | 100    | 1004 |
+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

3) Write a query that will produce all the customers whose names begin with a letter from 'A' to 'G'.

**Select \* from Customers where cname between 'A%' and 'H%';**

```
W1_89793_Saurabh>Select * from Customers
-> where cname between 'A%' and 'H%';
+-----+-----+-----+-----+-----+
| Cnum | Cname   | City    | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome    | 200    | 1003 |
| 2004 | Grass    | Berlin  | 300    | 1002 |
| 2006 | Clemens  | London  | 100    | 1001 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

4) Write a query that selects all customers whose names begin with the letter 'C'.

**Select \* from Customers where cname like 'C%';**

```
W1_89793_Saurabh>Select * from Customers
-> where cname like 'C%';
+-----+-----+-----+-----+-----+
| Cnum | Cname   | City    | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2006 | Clemens | London  | 100    | 1001 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
+-----+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```



5) Write a query that selects all orders except those with zeroes or NULLs in the amt field.

```
Select * from Orders where Amt>0 or Amt != Null;
```

```
W1_89793_Saurabh>Select * from Orders
-> where Amt>0 or Amt != Null;
+-----+-----+-----+-----+
| Onum | Amt      | Odate      | Cnum | Snum |
+-----+-----+-----+-----+
| 3001 | 18.69    | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19   | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10  | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45  | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16  | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23  | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75    | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00  | 1990-10-05 | 2006 | 1001 |
| 3010 | 1309.95  | 1990-10-06 | 2004 | 1002 |
| 3011 | 9891.88  | 1990-10-06 | 2006 | 1001 |
+-----+-----+-----+-----+
10 rows in set (0.00 sec)
```