ASSIGNMENT NO 2

Objective: To learn and practice the "mkdir,rm,rmdir" commands in Linux.

1.Open the terminal in your Linux system.

2.Use the "cd" command to navigate to a directory where you would like to create a new directory.

3.Use the "mkdir" command to create a new directory. The syntax for the "mkdir" command is as follows: mkdir [options] directory_name

4. Try out the following examples and write down the commands you used to create each directory:

a. Create a directory named "my_directory".

mkdir my_directory

```
Ragini@Ragini99500W1:~$ mkdir my_directory
```

b. Create a directory named "our_directory" inside the "my_directory" directory.

mkdir my_directory/our_directory

```
Ragini@Ragini99500W1:~$ mkdir my_directory/our_directory
```

c. Create a directory named "new_directory" and make it hidden.

mkdir .new_directory

```
Ragini@Ragini99500W1:~$ mkdir .new_directory
```

d. Create a directory named "pictures" with multiple subdirectories named "vacation", "family", and "friends".

mkdir -p pictures/vacation pictures/family pictures/friends

```
Ragini@Ragini99500W1:~$ mkdir -p pictures/vacation pictures/family picture
s/friends
```

e. Create a directory named “dir1”

mkdir dir1

```
Ragini@Ragini99500W1:~$ mkdir dir1
mkdir: dir1: File exists
```

5.Use the "ls" command to verify that the new directories have been created successfully.

Ls

```
Ragini@Ragini99500W1:~$ ls
backup  my_directory   my_music           new_demo.txt
dir1    my_file.txt    my_old_files       new_file.txt
dir2    my_files       my_other_file.txt  pictures
dir3    my_files_copy  my_third_file.txt  testdir
```

TO SEE HIDDEN DIR=

ls -a

```
Ragini@Ragini99500W1:~$ ls -a
.               .lesshst        dir3           my_other_file.txt
..              .motd_shown     my_directory   my_third_file.txt
.bash_history   .new_directory  my_file.txt    new_demo.txt
.bash_logout    .profile        my_files       new_file.txt
.bashrc         backup          my_files_copy  pictures
.cache          dir1            my_music       testdir
.config         dir2            my_old_files
```

6.Use tree Command to see the above directory structure. (If it is not installed in your system, install it with the command “sudo apt-get install tree”

Tree RUN=(sudo apt-get install tree)

```
Ragini@Ragini99500W1:~$ tree
.
├── backup
│   ├── file1.txt
│   └── file2.txt
├── dir1
├── dir2
├── dir3
├── my_directory
│   └── our_directory
├── my_file.txt
├── my_files
│   ├── backup
│   │   ├── file1.txt
│   │   └── file2.txt
│   ├── demo.txt
│   ├── file1.txt
│   ├── file2.txt
│   └── file3.txt
├── my_files_copy
│   ├── backup
│   │   ├── file1.txt
│   │   └── file2.txt
│   ├── file1.txt
│   ├── file2.txt
│   └── file3.txt
├── my_music
│   ├── new_song_3.mp3
│   └── old_music
│       └── song_1.mp3
├── my_old_files
│   ├── backup
│   │   ├── file1.txt
│   │   └── file2.txt
│   ├── file1.txt
│   ├── file2.txt
│   └── file3.txt
├── my_other_file.txt
├── my_third_file.txt
├── new_demo.txt
├── new_file.txt
├── pictures
│   ├── family
│   ├── friends
│   └── vacation
└── testdir

20 directories, 25 files
```

7. Try out some of the additional options for the "mkdir" command (e.g., -p, -m, -v).

mkdir -p folder1/folder2/folder3

```
Ragini@Ragini99500W1:~$ mkdir -p folder1/folder2/folder3
```

mkdir -v demo_folder

```
Ragini@Ragini99500W1:~$ mkdir -v demo_folder
mkdir: created directory 'demo_folder'
```

mkdir -m 777 public_folder

```
Ragini@Ragini99500W1:~$ mkdir -m 777 public_folder
```

8. Try to delete the directory named “dir1”

rmdir dir1

```
Ragini@Ragini99500W1:~$ rmdir dir1
```

9. Try to delete the directory named “pictures”

rm -r pictures

