Chmod ASSIGNMENT

1. Create a file named student.txt.

touch student.txt

```
Ragini@Ragini99500W1:~$ touch student.txt
```

2. Check the current permissions of student.txt.

ls -l student.txt

```
Ragini@Ragini99500W1:~$ ls -l student.txt
-rw-r--r-- 1 Ragini Ragini 0 Oct 24 07:10 student.txt
```

3. Set the permissions of student.txt to 755 using numeric notation.

chmod 755 student.txt

```
Ragini@Ragini99500W1:~$ chmod 755 student.txt
```

4. Set the permissions of student.txt to 644 using numeric notation.

chmod 644 student.txt

```
Ragini@Ragini99500W1:~$ chmod 644 student.txt
```

5. Using symbolic notation: Add execute permission for the owner. Remove write permission from the group. Remove all permissions from others.

chmod u+x student.txt

```
Ragini@Ragini99500W1:~$ chmod u+x student.txt
```

chmod g-w student.txt

```
Ragini@Ragini99500W1:~$ chmod g-w student.txt
```

chmod o= student.txt

```
Ragini@Ragini99500W1:~$ chmod o= student.txt
```

6. Set student.txt permissions so that: Owner: Read, Write, Execute Group: Read, Execute Others: Read

chmod 754 student.txt

```
Ragini@Ragini99500W1:~$ chmod 754 student.txt
```

7. Create a directory named project.

mkdir project

```
Ragini@Ragini99500W1:~$ mkdir project
```

8. Set the permission of project to 750.

chmod 750 project

```
Ragini@Ragini99500W1:~$ chmod 750 project
```

9. Create a file inside project and apply the required permission using symbolic notation.

touch project/report.txt && chmod u+x,g+r,o-rwx project/report.txt

```
Ragini@Ragini99500W1:~$ touch project/report.txt && chmod u+x,g+r,o-rwx pro
ject/report.txt
```

10. Verify all permission changes using ls -l. 1 /

ls -l student.txt

```
Ragini@Ragini99500W1:~$ ls -l student.txt
-rwxr-xr-- 1 Ragini Ragini 0 Oct 24 07:10 student.txt
```

ls -ld project && ls -l project/

```
Ragini@Ragini99500W1:~$ ls -ld project && ls -l project/
drwxr-x--- 2 Ragini Ragini 4096 Oct 24 07:12 project
total 0
-rwxr----- 1 Ragini Ragini 0 Oct 24 07:12 report.txt
```