

BMI / CS 771 Fall 2025:

Homework Assignment 3

Oct 2025

1 Overview

One of the central problems in computer vision is to recognize and localize object instances in an input image. This problem, widely known as object detection, often requires orchestrated model design and implementation. In this assignment, you will implement FCOS — a fully convolutional one-stage object detector using PyTorch and with our helper code. You will train and evaluate FCOS on PASCAL VOC 2007 [1] and COCO [4] datasets using your implementation. The conference version of FCOS [5] is listed as our reading material, while this assignment follows its **journal version** [6], which introduces improved design choices and provides more detailed explanations. Although the FCOS model is conceptually simple, the implementation requires some careful thoughts to ensure efficiency in training.

This assignment is team-based and requires cloud computing. A team should have 2-3 students, unless otherwise approved by the instructor. The assignment has a total of 12 points. Details are described in Section 4.

2 Setup

- We recommend using Conda to manage your packages.
- The following packages are needed: PyTorch (≥ 2.0 with GPU support), torchvision, pycocotools, PyYaml, NumPy, Pillow, and Tensorboard. Again, you are in charge of installing them.
- You can install any common packages that are helpful for the implementation. **If a new package is required for your implementation, a description must be included in the writeup.**
- **Using an open source implementation of FCOS is not permitted in this assignment**, including the one in torchvision. Feel free to take some inspiration from an existing implementation.

- You can debug your code and run experiments on CPUs. However, full training is very expensive on CPUs. GPU computing is thus required for this project. Please setup your team’s cloud instance. **Do remember to shut down the instance when it is not used!**
- For most part of this assignment, you will work with PASCAL VOC 2007 dataset. We provide a bash script to download this dataset. Simply run `sh ./download_dataset.sh`
- To complete the assignment, you will need to fill in the missing code in: `./code/libs/model.py`
- You are allowed to modify any part of the code in order to improve the model design or the training / inference of the model, **except the evaluation code**, including `./code/eval.py` and the `evaluate` function in `./code/libs/engine.py`.
- Your submission should include the code, results, trained models (see Sec. 6), and a writeup. The submission can be generated using:
`python ./zip_submission.py`
- If you encounter any font related errors when visualizing detection results on GCP, the missing fonts can be installed by
`sudo apt install fonts-freefont-ttf`

3 Overview of the Implementation

Our helper code and the implementation (located under `./code`) are more complicated than the first two assignments. Here we include an overview of the FCOS model and our implementation. **You are required to go through our helper code before attempting this assignment.** You might also want to review our lecture materials for some of the concepts here.

The FCOS Model. FCOS, as the name suggested, provides a one-stage object detector. The key idea is to decode an object candidate (including its categorical label and bounding box) at every spot on the feature maps, where the box is represented as its center (located at the spot) plus offsets to four borders. In doing so, object detection is simplified as a dense image labeling problem. Specifically, the model design, as shown in Figure 1, consists of (a) a backbone (e.g., ResNet [2]) to extract a pyramid of image features; (b) a feature pyramid network [3] (FPN) to refine these image features; and (c) shared classification and regression heads that are applied to the refined feature maps for decoding object labels and boxes.

Code Organization. The helper code are organized into three parts.

- Source code for input pipeline, model architecture, and training/inference utilities are located under `./code/libs/`.




Figure 1: Overview of FCOS from [6]. The model consists of a backbone network, a feature pyramid, and shared classification / regression heads.

- Configuration files (in YAML format) for the model architecture, training, and inference are stored under `./code/configs/`.
- Training and evaluation interfaces are exposed in `./code/train.py` and `./code/eval.py`.

Input Pipeline (`./code/libs/dataset.py` and `./code/libs/transforms.py`). Unlike image classification, object detection requires predicting structured labels such as bounding box coordinates, which are inherently tied to the spatial layout of the image. Therefore, any data augmentation that alters pixel locations, such as flipping, cropping, or resizing, must also adjust the corresponding bounding box labels to remain consistent. Moreover, images within the same mini-batch may have varying aspect ratios, making it nontrivial to batch them together efficiently during training.

Our helper code has provided a standard input pipeline for training object detection models. The dataset class (*VOCDetection*) provides a wrapper to load and process the VOC dataset. The *GeneralizedRCNNTransform* class implements common data augmentations for object detection, including horizontal flipping, scale jitters. Proper padding is also included after these augmentations, so that their outputs share a common size and thus can be easily batched.

Model Architectures (`./code/libs/model.py`). This is the implementation of the FCOS model, including the backbone, FPN, and heads. The classification and regression heads are implemented in *FCOSClassificationHead* and *FCOSRegressionHead*, while all other parts are encapsulated in the *FCOS* class. The current implementation (`./libs/model.py`) misses several critical pieces in order to function properly. **You will need to complete the code here.**

Training, Inference, and Other Utilities (all other files under `./code/libs`). These files implement utility functions that are necessary for the assignment, including training and inference pipelines, loss functions, visualizations, and

others. Two of the key components worth noting are (a) the training and inference pipeline (`./code/libs/engine.py`); and (b) the centralized parameter configuration (`./libs/config.py`). Specifically, `engine.py` includes functions to train the model, and to evaluate a trained-model. `config.py` specifies model architecture, model parameters, as well as hyperparameters used in training, which can be overwritten using an external configuration file (in yaml format e.g., `./code/configs/voc_fcos.yaml`).

To modify the model architecture or training hyperparameters, we can now replace the corresponding fields and their values in a separate yaml config file, without the need to touch the code. **See `./code/configs/voc_fcos.yaml` for an example.** This design allows us to separate the implementation and configuration, and is particularly helpful for our experiments.

Training and Evaluation Interface. Our helper code provides the full training and inference interface as follows (assuming `./code` as the current directory). *To be able to run the code, you will need to finish necessary code for training and inference.*

- To train the model, run
`python ./train.py ./configs/voc_fcos.yaml`
- By default, the training logs and checkpoints will be saved under a folder in `../logs`. Each run will have a separate folder that ends with the time stamp of the experiment. You can monitor and visualize these training logs using TensorBoard. Similar to our previous assignment, we recommend copying the logs and plotting the curves locally.
`tensorboard --logdir=../logs/your_exp_folder`
- To evaluate a trained model, run
`python ./eval.py ./configs/voc_fcos.yaml ../logs/your_exp_folder`
- This evaluation will automatically grab the last checkpoint and save all results (e.g., `eval_results.json` and `./viz` folder for visualization) under the experiment folder. Additionally, you can specify which checkpoint to evaluate (using “-e”) or visualize the detection results (using “-v”). See `eval.py` for more details.
- Our help code also supports resuming training from a previous checkpoint. This is mostly unnecessary for VOC, as with proper implementation training should finish well within half an hour.
`python ./train.py ./configs/voc_fcos.yaml`
`--resume=../logs/your_exp_folder/epoch_x.pth.tar`

4 Details

This assignment has two parts. An autograder will be used to grade certain parts of the assignment. **Please follow the instructions closely.**

4.1 Model Inference

Our first step is to implement the inference procedure of FCOS.

Classification and Regression Heads (2 pts). You will need to complete the implementation of the classification and regression heads in the FCOS model. Specifically, our helper code provides definitions of the heads in the class of *FCOSClassificationHead* and *FCOSRegressionHead* under `./code/libs/model.py`. Once you implement the forward pass of these two classes, the backward pass will be handled by automatic differentiation. Some hints are provided in the comments. Note that the choices you make here will impact other parts of your implementation.

Decoding the Objects (3 pts). The next task is to complete the FCOS inference procedure. You will need to implement the *inference* function in the class of *FCOS*. A high-level sketch of this implementation is described in the comments, though the details can be a bit involved.

Testing your Inference Code and Reporting Results (1 pt). To test the implementation of model inference, we have included a pre-trained FCOS model (using ResNet18 as the backbone) and its config file in the assignment under `./pretrained`. You can test your code using this pretrained model by running `python ./eval.py ../pretrained/voc_res18.yaml ../pretrained/voc_res18.pth.tar`

The inference should run for a few minutes with an expected $\text{mAP}@0.5 = 60.9\%$. If you could not match this inference speed or mAP score, your implementation will probably need some further scrutiny. **Please include the mAP scores, inference time, and sample detection results (e.g., using “-v” option during evaluation) in the writeup.**

4.2 Model Training

Our second step is to implement the training procedure of FCOS.

Training with the Multitask Loss Functions (3 pts). The key component of training lies in computing the multitask loss. This loss combines a classification loss, a regression loss, and a center-ness loss. Computing this loss involves the assignment of targets (e.g., positive/negative labels, offsets), given the feature maps and the ground truth object annotations. While our helper code handles most part of the training, you will need to implement the computation of the multitask loss by filling in the *compute_loss* function within the class of *FCOS*. This implementation can be a bit tricky. Again, comments in our helper code provide some hints.

An important aspect of your implementation is its efficiency. A “sloppy” implementation will lead to a major increase in training time. As a reference, training on VOC 2007 using the default configuration (e.g., ResNet 18 with 10 epochs) should take well under 30 minutes using a single T4 GPU. *Full credit will be awarded only if the training completes within a reasonable time frame and the mAP scores align with the results of a reference implementation.*

Once your implementation is complete, you will train your own FCOS model following our previous instructions. You can refer to the configuration file of our pretrained model and the journal paper for hints on choosing training parameters. That said, it's also fun and instructive to experiment with different hyperparameters (e.g., learning rate, data augmentation, etc.).

To reduce turnaround time, we recommend starting with a lightweight model and/or a shortened training schedule when exploring hyperparameter settings. Once you identify a promising configuration, you can retrain using a more powerful backbone (e.g., ResNet-34) and the full training schedule.

In your writeup, please include (a) training curves of your model; (b) testing mAP scores; (c) sample object detection results on the test set; and (d) key parameters of the model / training. Your final model should also be included in the submission (see Sec. 6).

Training and Inference on the COCO dataset (3 pts). Moving beyond the VOC dataset, we will also experiment with training and inference using COCO dataset [4]. This will require downloading the dataset, modifying *dataset.py* (and other parts of the helper code if necessary), as well as creating a new config file. Although these modifications are relatively minor, they require a solid understanding of the codebase.

To reduce training time, we recommend using a **lightweight backbone** (e.g., ResNet-18) and a **small number of epochs** (e.g., 4). You can also use a subset of the training data to further cut down the training time. Extensive hyperparameter tuning is not required, as long as you can demonstrate the feasibility of your implementation.

You are expected to (1) describe your implementation (in the writeup) and include the code and trained model in the submission (see Sec. 6); (2) describe necessary procedures of your experiments including data preparation (in the writeup); and (3) demonstrate the performance in terms of accuracy and efficiency (in the writeup).

5 Writeup

For this assignment, and all other assignments, you must submit a project report in PDF. Every team member should send the same copy of the report. Please clearly identify the contributions of all members. For this assignment, you will need to include (a) a description of your implementation for model inference and some demonstration of the results (Sec 4.1); (b) a description of your implementation for model training and some demonstration of the results (Sec 4.2); and (c) a description of your implementation and experimental procedure on the COCO dataset, and some demonstration of the results (Sec 4.2). You can also discuss anything extra you did. Feel free to add other information you feel is relevant.

6 Handing in

This is very important as you will lose points if you do not follow instructions. Every time after the first that you do not follow instructions, you will lose 5%. The folder you hand in must contain the following:

- code/ - directory containing all your code for this assignment
- writeup/ - directory containing your report for this assignment.
- results/ - directory containing your results. **Please copy your final model (model_final.pth.tar in your experiment folder) and its corresponding config file (yaml format) into the designated folders.** Only one model for each dataset is needed.
 - For the VOC dataset, place the files under results/voc/.
 - For the COCO dataset, place the files under results/coco/.

Visuals including sample detection results, training curves should be included in the writup and not in this folder.

Do not use absolute paths in your code (e.g. /user/classes/proj1). Your code will break if you use absolute paths and you will lose points because of it. Simply use relative paths as the starter code already does. **Do not turn in the data / logs / models folder.** Hand in your project as a zip file through Canvas. You can create this zip file using *python zip_submission.py*.

References

- [1] M. Everingham, L. Van Gool, C. K. Williams, J. Winn, and A. Zisserman. The pascal visual object classes (voc) challenge. *International journal of computer vision*, 88(2):303–338, 2010.
- [2] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.
- [3] T.-Y. Lin, P. Dollár, R. Girshick, K. He, B. Hariharan, and S. Belongie. Feature pyramid networks for object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2117–2125, 2017.
- [4] T.-Y. Lin, M. Maire, S. Belongie, J. Hays, P. Perona, D. Ramanan, P. Dollár, and C. L. Zitnick. Microsoft coco: Common objects in context. In *Computer Vision–ECCV 2014: 13th European Conference, Zurich, Switzerland, September 6–12, 2014, Proceedings, Part V 13*, pages 740–755. Springer, 2014. <https://cocodataset.org/>.
- [5] Z. Tian, C. Shen, H. Chen, and T. He. Fcos: Fully convolutional one-stage object detection. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 9627–9636, 2019.

- [6] Z. Tian, C. Shen, H. Chen, and T. He. Fcos: A simple and strong anchor-free object detector. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2020.