

1. Create 'spj' database'. (Database for suppliers, parts and jobs) 2. use spj database; 3. Create following tables in spj database.

```
W2_99546_Pratiksha>SHOW DATABASES;
```

Database
classwork_db
hr_db
information_schema
joins_db
performance_schema
sales_db
spj_db

```
+-----+  
7 rows in set (0.00 sec)
```

```
W2_99546_Pratiksha>USE SPJ_DB;
```

```
Database changed
```

```
W2_99546_Pratiksha>SHOW TABLES;
```

Tables_in_spj_db
j
k
p
s
sp

```
+-----+  
5 rows in set (0.00 sec)
```

Q.CREATE TABLE sp (S# CHAR(4) NOT NULL, P# CHAR(4) NOT NULL, J# CHAR(4) NOT NULL, QTY INT);

```
W2_99546_Pratiksha>SELECT*FROM SP;
```

S#	P#	J#	QTY
S1	P1	J1	200
S1	P1	J4	700
S2	P3	J1	400
S2	P3	J2	200
S2	P3	J3	200
S2	P3	J4	500
S2	P3	J5	600
S2	P3	J6	400
S2	P3	J7	800
S2	P3	J2	100
S3	P3	J1	200
S3	P4	J2	500
S4	P6	J3	300
S4	P6	J7	300
S5	P2	J2	200
S5	P2	J4	100
S5	P5	J5	500
S5	P5	J7	100
S5	P6	J7	200
S5	P6	J2	200
S5	P1	J4	100
S5	P3	J4	200
S5	P4	J4	800
S5	P5	J4	400
S5	P6	J4	500

```
25 rows in set (0.00 sec)
```

Q.CREATE TABLE P (P# CHAR(6) NOT NULL, Pname CHAR(20), color CHAR(6), weight SMALLINT, city CHAR(15));

```
W2_99546_Pratiksha>SELECT *FROM P;
```

P#	Pname	color	weight	city
P1	Nut	Red	12	Paris
P2	Bolt	Green	17	Paris
P3	Screw	Blue	17	Rome
P4	Screw	Red	14	London
P5	Cam	Blue	12	Paris
P6	Cog	Red	19	London

6 rows in set (0.00 sec)

Q.CREATE TABLE K(k# CHAR(4) NOT NULL, Jname CHAR(10), City CHAR(15));

```
W2_99546_Pratiksha>SELECT*FROM K;
```

K#	Jname	CITY
K1	Sorter	Paris
K2	Punch	Rome
K3	Reader	Anthens
K4	Console	Anthens
K5	Collator	London
K6	Terminal	Oslo
K7	Tape	London

7 rows in set (0.00 sec)

Q. CREATE TABLE S (S# CHAR(5) NOT NULL, Sname CHAR(20), status SMALLINT, city CHAR(15));

```
W2_99546_Pratiksha>SELECT*FROM S;
```

S#	Sname	status	city
S1	Smith	20	London
S2	Jones	10	Paris
S3	Blake	30	Paris
S4	Clark	20	London
S5	Adams	300	Athens

5 rows in set (0.00 sec)