

1) Which of these views are updateable (will allow DML operations)?

1 ) Create View Dailyorders as Select Distinct cnum, snum, onum, odate from Orders;

Ans : not allow

2) Create View Custotals as Select cname, Sum (amt) Sum\_Amt from Orders, Customers where Orders.cnum=Customers.cnum Group by cname;

Ans : will allow

3) Create view Thirddorders as Select \* from Dailyorders where odate='1990-10-03';

Ans : not allow

4) Create view Nullcities as Select snum, sname, city from Salespeople where city is NULL OR sname BETWEEN 'A' and 'MZ';

Ans : will allow

2) Create a view of the Salespeople table called Commissions. This view will include only the snum and comm fields. Through this view, someone could enter or change commissions, but only to values between .10 and .20.

```
w3_93119_sushant>
w3_93119_sushant>create view commissions as select snum,comm from salespeople where comm between 0.10 and 0.20 with che
ck option;
Query OK, 0 rows affected (0.00 sec)
w3_93119_sushant>
```

3) Some SQL implementations have a built-in constant representing the current date, sometimes called “CURDATE” or “SYSDATE”. The word SYSDATE can therefore be used in a SQL statement, and be replaced by the current date when the value is accessed by

commands such as Select or Insert. We will use a view of the Orders table called Entryorders to insert rows into the Orders table. Create the Orders table, so that SYSDATE is automatically inserted for odate if no value is given. Then create the Entryorders view so that no values can be given.

```
w3_93119_sushant>
w3_93119_sushant>CREATE TABLE Orders (
  ->   onum INT PRIMARY KEY,
  ->   amt DECIMAL(10, 2),
  ->   odate DATETIME NOT NULL DEFAULT CURRENT_TIMESTAMP,
  ->   cnum INT,
  ->   snum INT
  -> );
```

```
Query OK, 0 rows affected (0.03 sec)
```

```
w3_93119_sushant>CREATE VIEW Entryorders AS
```

```
  -> SELECT onum, amt, cnum, snum
```

```
  -> FROM Orders;
```

```
ERROR 1050 (42S01): Table 'Entryorders' already exists
```

```
w3_93119_sushant>DROP VIEW ENTRYORDERS;
```

```
Query OK, 0 rows affected (0.02 sec)
```

```
w3_93119_sushant>FROM Orders;^C
```

```
w3_93119_sushant>^C
```

```
w3_93119_sushant>CREATE VIEW Entryorders AS
```

```
  -> SELECT onum, amt, cnum, snum
```

```
  -> FROM Orders;
```

```
Query OK, 0 rows affected (0.02 sec)
```

```
w3_93119_sushant>
```