

CSS FUNDAMENTALS

Styling Modern Websites with CSS, Bootstrap, and Tailwind CSS

Prepared for:

Get Techy With Lucky / Tech Pulse Insider

Instructor: Lucky Nakola

A Comprehensive Guide to Web Design Fundamentals

Version 1.0 | 2025

TABLE OF CONTENTS

- Chapter 1: Introduction to CSS
- Chapter 2: Ways of Adding CSS to HTML
- Chapter 3: CSS Syntax and Format
- Chapter 4: CSS Selectors
- Chapter 5: Colors, Backgrounds, and Typography
- Chapter 6: CSS Box Model
- Chapter 7: Display, Positioning, and Alignment
- Chapter 8: Flexbox Layout System
- Chapter 9: CSS Grid Layout System
- Chapter 10: Responsive Design and Media Queries
- Chapter 11: Modern Web Design Principles
- Chapter 12: Introduction to CSS Frameworks
- Chapter 13: Tailwind CSS Foundation
- Chapter 14: CSS Best Practices
- Glossary of CSS Terms

CHAPTER 1: INTRODUCTION TO CSS

What is CSS?

CSS stands for Cascading Style Sheets. It is a language used to style and layout web pages. While HTML provides the structure and content of a website, CSS makes it look beautiful and professional.

HTML, CSS, and JavaScript: The Web Trinity

To understand CSS better, think of a website like a person:

- HTML = Structure and Skeleton (the bones of a website)
- CSS = Appearance and Design (the clothes and makeup)
- JavaScript = Behavior and Interaction (the actions and movements)

Why CSS is Important

CSS plays a critical role in modern web development:

- Improves Visual Appeal: Makes websites attractive and engaging
- Enhances User Experience: Guides users through clear design
- Ensures Branding Consistency: Maintains company colors and style
- Enables Responsiveness: Works across devices (mobile, tablet, desktop)
- Separates Concerns: Keeps structure (HTML) separate from styling (CSS)
- Improves Maintainability: Changes to style don't affect HTML structure

Key Concepts for Beginners

Structure vs. Styling

- Structure (HTML): What the content is (heading, paragraph, button)
- Styling (CSS): How it looks (color, size, spacing)

Chapter Summary

- CSS means Cascading Style Sheets
- CSS is used to style and layout web pages
- HTML provides structure; CSS provides appearance
- CSS is essential for modern web development
- CSS improves user experience and brand consistency

CHAPTER 2: WAYS OF ADDING CSS TO HTML

There are three main ways to add CSS to your HTML pages. Each method has its advantages and disadvantages.

Method 1: Inline CSS

What is Inline CSS?

Inline CSS is written directly inside an HTML element using the style attribute. The CSS rules apply only to that specific element.

```
<h1 style="color: blue; font-size: 32px;">Welcome to CSS</h1>
```

When to Use Inline CSS

- Quick styling for a single element
- Testing and experimenting
- Small one-off changes

Advantages

- Easy and quick for simple changes
- Works immediately
- Good for learning

Disadvantages

- Not reusable for other elements
- Makes HTML code harder to read
- Difficult to maintain in large projects
- Cannot use advanced CSS features like media queries

Method 2: Internal CSS

What is Internal CSS?

Internal CSS is written inside a `<style>` tag in the `<head>` section of your HTML document. It applies to all matching elements on that page.

```
<head>
  <style>
    h1 {
      color: blue;
      font-size: 32px;
      text-align: center;
    }
  </style>
</head>
```

When to Use Internal CSS

- Single HTML page projects
- Class demonstrations and learning
- Quick prototypes

Advantages

- Easier to read than inline CSS
- Reuses styles across multiple elements on the same page
- Supports all CSS features
- Good for small projects

Disadvantages

- Cannot be shared with other HTML files
- Style sheet is mixed with HTML
- Not ideal for websites with multiple pages

Method 3: External CSS (Recommended)

What is External CSS?

External CSS is written in a separate .css file and linked to your HTML document using a `<link>` tag. This is the industry standard for professional web development.

```
<head>
  <link rel="stylesheet" href="style.css">
</head>
```

In your style.css file:

```
h1 {
  color: blue;
  font-size: 32px;
  text-align: center;
}
```

When to Use External CSS

- All professional projects
- Websites with multiple pages
- Team development
- Production websites
-

Best Practice

For this course and professional development, always use External CSS. This approach follows industry standards and creates clean, maintainable code.

Chapter Summary

- Inline CSS: Styles applied directly in HTML tags
- Internal CSS: Styles in `<style>` tag in HTML head
- External CSS: Styles in separate .css file
- External CSS is the recommended approach for all projects
- Always keep HTML and CSS separate in professional work

CHAPTER 3: CSS SYNTAX AND FORMAT

Understanding CSS syntax is fundamental. CSS has a simple but powerful structure that you need to master.

Basic CSS Syntax

Every CSS rule follows this basic structure:

```
selector {  
  property: value;  
  property: value;  
}
```

Breaking Down the Syntax

1. Selector

The selector targets which HTML elements you want to style.

```
p { /* p is the selector */ }
```

2. Declaration Block

The declaration block contains all styling rules, enclosed in curly braces { }.

3. Property

A property is what you want to change (e.g., color, font-size, margin).

4. Value

A value is what you're setting the property to (e.g., blue, 16px, center).

5. Semicolon (;)

Each property-value pair must end with a semicolon.

Complete Example

```
p {  
  color: black;  
  font-size: 16px;  
  line-height: 1.5;  
  text-align: left;  
}
```

CSS Comments

Comments are notes you write in your CSS to explain your code.

```
/* This is a CSS comment */
```

CHAPTER 4: CSS SELECTORS

CSS selectors are patterns used to target and style specific HTML elements on a webpage. They act as the bridge between your HTML structure and your CSS visual rules.

Basic Selectors

Basic selectors form the foundation of CSS targeting. [\[1\]](#)

- ❖ Universal Selector (*): Matches every single element on the page.
- ❖ Type Selector (element): Targets elements matching the specific HTML tag name.
- ❖ Class Selector (.classname): Targets elements containing the specific class attribute.
- ❖ ID Selector (#idname): Targets a single, unique element matching the specific id attribute.

Combinator Selectors

Combinators define spatial and structural relationships between multiple elements.

- Descendant Selector (space): Targets an element nested anywhere inside a specified parent element.
- Child Selector (>): Targets elements that are immediate, direct children of the parent element.
- Adjacent Sibling Selector (+): Targets an element placed immediately after another specific element at the same hierarchy level.
- General Sibling Selector (~): Targets all sibling elements that follow a specific element, regardless of precise proximity.

Attribute Selectors

Attribute selectors match elements based on the presence, exact value, or partial matching of their HTML attributes.

- Presence ([attr]): Matches any element possessing the specified attribute.
- Exact Match ([attr="val"]): Matches elements with the exact attribute value specified.
- Starts With ([attr^="val"]): Matches elements whose attribute value begins with the specified string.
- Ends With ([attr\$="val"]): Matches elements whose attribute value ends with the specified string.
- Contains Substring ([attr*="val"]): Matches elements whose attribute value contains the specified substring anywhere within it.

CHAPTER 5: COLORS, BACKGROUNDS, AND TYPOGRAPHY

Backgrounds

Website backgrounds set the visual tone, group content, and guide user focus. Below are the complete, structured notes on mastering backgrounds in web design.

1. Core Types of Visual Backgrounds

- **Solid Colors:** Uses a single hex code to create a clean, minimalist look.
- **Color Gradients:** Blends two or more colors. Linear gradients move in a straight line, while radial gradients radiate from a central point.
- **Textured Backgrounds:** Subtle patterns like grain, noise, or grid lines that add depth without distracting readers.
- **Static Images:** High-resolution photography or illustrations that instantly communicate a brand's identity.
- **Video Backgrounds:** Short, looping, muted videos used primarily in hero sections to create high emotional engagement.
- **Abstract Animations:** Lightweight CSS or JavaScript animations (like floating particles) that make a site feel dynamic.

2. Functional Roles of Backgrounds

- **Visual Hierarchy:** Darker or contrasting backgrounds separate headers, features, and footers from the main content.
- **Readability:** Backgrounds must provide high contrast against text to ensure legible copy.
- **Brand Identity:** Warm tones feel inviting, dark themes feel premium, and bright colors feel energetic.
- **Spatial Depth:** Layering light elements on dark backgrounds (or vice versa) creates a sense of physical depth.

3. Implementation Technicalities (CSS Guide)

To control how backgrounds behave on different screens, developers use specific CSS properties:

- **background-color:** Defines the solid color base using HEX, RGB, or HSL values.
- **background-image:** Links to the file path of your image or video asset.
- **background-size: cover:** Scales the image so the background area is completely covered.
- **background-size: contain:** Scales the image to fit entirely inside the box, leaving blank space if ratios differ.
- **background-position: center:** Centers the image so cropping happens equally on all edges during resizing.
- **background-attachment: fixed:** Creates a parallax effect where the background stays still while text scrolls over it.

4. Critical Design Best Practices

- **Accessibility First:** Maintain a minimum contrast ratio of 4.5:1 for normal text against the background (WCAG AA standard).
- **Overlay Text Protection:** Add a semi-transparent dark or light color overlay (`rgba`) over busy images to keep text readable.
- **Performance Optimization:** Compress image files (use modern formats like WebP or AVIF) to prevent slow page load speeds.
- **Mobile Adaptation:** Switch complex desktop backgrounds or heavy videos to simple solid colors on mobile screens to save data and space.
- **Avoid Tiling Defects:** Set `background-repeat: no-repeat` unless you are explicitly using a seamless, tileable pattern.

Typography

Typography in web design is the art of selecting, arranging, and styling text to make digital interfaces readable, accessible, and visually engaging.

As famously argued, "95% of web design is typography," making it a crucial component that establishes brand personality, guides user behavior, and defines the overall user experience (UX).

Key Principles of Web Typography

- **Readability & Legibility:** The primary goal is ensuring text is easy to read. Digital text should be broken into scan-friendly chunks, typically using 16px or larger for body copy.
- **Visual Hierarchy:** Using variations in size, weight, and color to guide users through content, defining what to read first. A typical structure uses `(H_{1})` (largest) down to `(H_{6})`, with body text below.
- **Accessibility:** Adhering to WCAG 2.1 guidelines, which require a minimum contrast ratio of 4.5:1 for normal text and 3:1 for large text.
- **Responsiveness:** Using relative units (`em`), (`rem`), (`vw`)) to allow text to scale appropriately across mobile, tablet, and desktop devices.
- **Font Pairing:** Limiting to 2–3 typefaces maximum to prevent visual noise. A common strategy is pairing a sans-serif for body text (like Roboto or Open Sans) with a distinct serif or display font for headings.

Key Components & Technical Terms

- **Alignment:** Left-aligned text improves readability, whereas justified text should generally be avoided for long content.
- **Leading (Line Height):** The spacing between lines, typically recommended to be $\backslash(1.4)$ to $\backslash(1.6)$ times the font size.
- **Spacing:** Tracking (letter-spacing) is the uniform gap between letters, while kerning refers to the adjustment of space between specific character pairs, which is vital for headlines.
- **Line Length (Measure):** The ideal width for comfortable reading is generally considered to be 45–75 characters per line.

Typeface Classifications & Modern Formats

- Classifications: Serif (traditional) and sans-serif (modern) are common for body text, while slab serif and script/display fonts are often used for headlines.
- Variable Fonts: A single font file that allows for fluid adjustments to weight, width, and style, improving performance

Hex color codes

Hex color codes are six-digit hexadecimal numbers (0-9, A-F) used to define colors in digital design and web development, structured as **#RRGGBB** to represent Red, Green, and Blue intensities.


Common Hex Code Examples

- | | |
|-------------------------|--------------------------|
| ● White: #FFFFFF | ● Blue: #0000FF |
| ● Black: #000000 | ● Yellow: #FFFF00 |
| ● Red: #FF0000 | ● Teal: #008080 |
| ● Green: #008000 | ● Purple: #800080 |

How Hex Codes Work

- Structure: `#RRGGBB` - The first two characters (RR) are red, the middle two (GG) are green, and the last two (BB) are blue.
- Intensity: Values range from `00` (lowest intensity) to `FF` (highest intensity).
- Shorthand: 3-digit codes (e.g., `#369`) are shorthand for 6-digit codes (e.g., `#336699`).
- Transparency: An 8-digit code (`#RRGGBBAA`) can include an alpha channel for transparency, ranging from `00` (fully transparent) to `FF` (fully opaque).

Example of Hex Color Codes



RGB COLOR SCHEME

An RGB color scheme is a digital color model that creates millions of colors by mixing Red, Green, and Blue light. It is an additive color model used exclusively for digital screens like phones, TVs, and computers.

Primary, Secondary, and Tertiary Colors

- Primary: Red (255,0,0), Green (0,255,0), Blue (0,0,255).
- Secondary: Yellow (255,255,0), Cyan (0,255,255), Magenta (255,0,255).
- Tertiary: Created by mixing primary and secondary colors (e.g., Orange, Violet).

RGB
Color theme



CHAPTER 6: CSS BOX MODEL

The CSS Box Model is the core foundational standard of web layout that treats every HTML element as a rectangular box. Browsers calculate the exact physical dimensions and screen positioning of elements by nesting four structural layers: Content, Padding, Border, and Margin.

The Four Core Layers

- **Content:** The central area containing text, images, or child nodes. Controlled using **width** and **height**.
- **Padding:** Transparent spacing inside the element that cushions the content from its perimeter. Controlled via the **padding** property.
- **Border:** A structural edge surrounding the padding and content layers. Styled using thickness, color, and texture via **border**.
- **Margin:** Invisible spacing outside the border that pushes adjacent layout boxes away. Configured using **margin**

Padding

```
.box { padding: 20px; }
```

Border

```
.box { border: 2px solid #333; }
```


Margin

```
.box { margin: 20px; }
```

Box Sizing

```
* { box-sizing: border-box; }
```

Always use this to include padding and border in width/height.



CHAPTER 7: DISPLAY, POSITIONING, AND ALIGNMENT

Display Property

```
div { display: block; } /* Full width */  
span { display: inline; } /* Side-by-side */  
img { display: inline-block; }
```

Position Property

```
.box { position: relative; }  
.box { position: absolute; }  
.navbar { position: fixed; top: 0; }
```

CHAPTER 8: FLEXBOX LAYOUT

```
.container { display: flex; }  
.container { justify-content: center; }  
.container { align-items: center; }  
.container { gap: 20px; }
```



CHAPTER 9: CSS GRID LAYOUT

CSS Grid Layout is a highly powerful, **two-dimensional layout** engine built directly into native CSS. Unlike Flexbox (which is primarily one-dimensional, handling either rows or columns), Grid handles both rows and columns simultaneously. This allows you to build complex, asymmetrical web architectures without relying on messy positioning hacks or floating elements.

The Core Mechanics: Grid Container vs. Grid Items


To start using CSS Grid, you must establish a structural relationship between a parent element and its direct children.

- Grid Container: The parent element that has `display: grid;` applied to it. This initializes the grid context.
- Grid Items: All direct child elements inside the Grid Container. They automatically place themselves into the grid tracks.

Essential Container Properties

These properties are applied to the parent container to define the layout blueprint: [\[1\]](#)

- `grid-template-columns`: Defines the number and widths of the vertical columns.
- `grid-template-rows`: Defines the number and heights of the horizontal rows.
- `gap` (or `grid-gap`): Sets the spacing between grid tracks (rows and columns) without adding margins to the outer edges.



CHAPTER 10: RESPONSIVE DESIGN

Responsive Web Design (RWD) is a development approach where a website automatically adjusts its layout, images, and content to fit the screen size of any device, from desktop monitors to smartphones.

The Three Pillars of Responsive Design

- **Fluid Grids:** Layout elements use relative units (percentages % or viewport units vw/vh) instead of fixed pixels (px) to resize proportionally.
- **Flexible Images:** Media files scale dynamically within their containers using CSS properties like `max-width: 100%` and `height: auto`.
- **CSS Media Queries:** Directives that apply specific styling blocks only when a device meets targeted conditions, such as a maximum or minimum screen width.

The Technical Essentials

The Viewport Meta Tag: This mandatory HTML tag forces mobile browsers to scale pages to the actual device width rather than simulating a desktop screen.

html

```
<meta name="viewport" content="width=device-width, initial-scale=1.0">
```

- Use code with caution.
- Breakpoints: The specific screen-width thresholds where a website's layout shifts.

Common breakpoints target standard sizes:

- Mobile: 640px
- Tablet: 768px
- Laptop: 1024px
- Desktop: 1280px

Modern Layout Techniques

- **CSS Flexbox:** A one-dimensional layout system ideal for aligning items in rows or columns and distributing space dynamically.
- **CSS Grid:** A two-dimensional layout system that handles both rows and columns simultaneously, perfect for complex page architectures.
- **Mobile-First Workflow:** The industry-standard practice of writing styles for the smallest screens first, then using media queries to add complexity as the screen expands.

Chapter 11: Modern Web Design Principles

1. Simplicity and Clarity

Modern web design prioritizes the user's focus by removing unnecessary visual noise. A clear design helps users find information quickly and complete tasks without confusion.

- **Minimalist Aesthetics:** Emphasize content by stripping away decorative elements that do not serve a functional purpose.
- **White Space (Negative Space):** Use intentional empty areas around text and images to allow the layout to breathe.
- **Microcopy:** Keep buttons, labels, and forms short, direct, and universally easy to understand.
- **Single Focal Points:** Design pages so that users are drawn to one primary action (like a "Sign Up" button) at a time.

2. Visual Hierarchy

Visual hierarchy is the arrangement of elements in a way that implies importance. It guides the user's eye across the page in a specific, intentional order.

- **Size and Scale:** Make critical elements (like main headers) significantly larger than supporting elements.
- **Color and Contrast:** Use bright or highly contrasting colors to draw immediate attention to Call-to-Action (CTA) buttons.
- **Reading Patterns:** Layout key information along natural scanning paths, such as the F-Pattern (for text-heavy blogs) or the Z-Pattern (for landing pages).
- **Element Isolation:** Give highly important items more surrounding space to make them stand out from the rest of the layout.

3. Consistent Spacing

Consistency in spacing creates a predictable rhythmic flow, making a website feel polished, professional, and stable.

- **The Spacing Scale:** Stick to a strict geometric scale (e.g., multiples of 4px or 8px) for all margins and paddings.
- **Tailwind Alignment:** Use standard utilities like `p-4` (16px) or `m-8` (32px) to automatically enforce design constraints.
- **Proximity Principle:** Place related items (like a headline and its paragraph) closer together, while pushing unrelated sections further apart.
- **Component Uniformity:** Ensure that card components, buttons, and form fields share identical internal padding across all pages.

4. Responsive Design

A continuation of Chapter 10, modern responsive design ensures that the user experience is identical in quality across all screen boundaries.

- **Fluid Adaptability:** Layouts must fluidly morph, not just break or snap at specific screen sizes.
- **Touch-Friendly Targets:** Interactive elements must scale up on mobile screens to a minimum size of 44x44px to accommodate finger taps.
- **Content Prioritization:** Drop non-essential sidebars or background decorations on smaller screens to keep the mobile viewport functional.
- **Performance Control:** Optimize asset delivery so mobile data networks can load the responsive layout instantly.

Chapter 12-13: CSS Frameworks

What is a CSS Framework?

A CSS framework is a library of pre-written, ready-to-use code that simplifies styling websites. Instead of writing custom CSS rules from scratch for every element, developers use framework files to build consistent, responsive layouts quickly.

The 3 Main Types of CSS Frameworks

1. Component-Based Frameworks

- Concept: Provide fully styled UI elements like buttons, navbars, and cards.
- Examples: Bootstrap, Bulma, Foundation.
- Pros: Incredibly fast for prototyping and building admin dashboards.
- Cons: All websites built with them tend to look identical.

2. Utility-First Frameworks

- Concept: Provide low-level styling classes (like padding, margins, and colors) to build custom layouts in HTML.
- Examples: Tailwind CSS, Tachyons.
- Pros: Complete design freedom without writing a single line of custom CSS.
- Cons: HTML code can look cluttered with dozens of classes.

3. Minimal / Classless Frameworks

- Concept: Style standard HTML tags (`<h1>`, `<button>`, `<p>`) automatically without requiring class names.
- Examples: Pico.css, MVP.css.
- Pros: Perfect for text-heavy sites, blogs, and fast documentation.
- Cons: Highly restrictive and difficult to customize for unique designs.

Why Tailwind CSS is Often Considered the Best

- No Arbitrary Class Names: You never waste time naming classes like `.main-wrapper-inner`.
- Zero Custom CSS Bloat: The final production CSS file stays extremely small (usually under 10KB) because it only includes classes you actually used.
- Complete Design Freedom: Unlike Bootstrap, Tailwind does not lock you into a specific visual look. You can build any design system easily.
- Lightning-Fast Changes: You can adjust responsive layouts, hover states, and dark modes right inside your HTML file without switching tabs.

Chapter 14: CSS Best Practices

1. Use External CSS

Separating content from presentation is a fundamental rule of web development. External stylesheets keep your code clean, manageable, and highly efficient.

- Separation of Concerns: HTML handles the page structure, while the external `.css` file manages the design and visual layout.
- Global Consistency: Linking a single external stylesheet to multiple HTML pages ensures your entire website looks uniform.
- Cached Performance: Browsers download the external CSS file only once during the first page load and cache it, making subsequent pages load much faster.
- Avoid Inline Styles: Inline styles (`style="..."`) clutter HTML, make global updates a nightmare, and override external rules due to high CSS specificity.

2. Organize Styles Logically

As websites grow, stylesheets can easily turn into unmanageable "spaghetti code." Logical organization keeps your codebase clean for collaboration and future updates.

Commented Architecture: Use clear section banners inside your CSS file to group styles by function:

```
/* =====  
1. GLOBAL RESETS & VARS  
===== */  
/* =====  
2. LAYOUT & CONTAINERS  
===== */  
/* =====  
3. COMPONENTS (Buttons, Cards, etc.)  
===== */
```

- CSS Variables (Custom Properties): Define global styles (colors, fonts, spacing) at the top of your document using the `:root` selector to make site-wide changes trivial.
- Naming Conventions: Use structured naming systems like BEM (Block, Element, Modifier) to make your class names intuitive (e.g., `.card`, `.card__title`, `.card__button--disabled`).
- Tailwind Approach: If using Tailwind, organize your HTML classes consistently (e.g., dimensions first, then positioning, layout, typography, and states).

3. Test on Multiple Devices

A website might look flawless on your personal laptop but completely break on a different screen, browser, or operating system.

- **Cross-Browser Testing:** Validate that your layout functions identically across modern engines: Blink (Chrome/Edge), Gecko (Firefox), and WebKit (Safari).
- **Device Diversification:** Test on actual hardware representing different eco-systems (iOS vs. Android) and screens (high-DPI Retina vs. standard monitors).
- **Browser DevTools:** Use the responsive design mode in Chrome or Firefox to quickly simulate varied device viewports and throttling networks.
- **Real-world Interaction:** Verify that touch elements are easy to tap, scroll behaviors are fluid, and dynamic components work without a mouse hover.

4. Optimize Performance

Efficient CSS ensures your web pages render instantly, directly lowering bounce rates and boosting SEO search rankings.

- **Minification:** Remove all unnecessary whitespaces, line breaks, and comments from production CSS files using automated build tools (like cssnano or Esbuild).
- **Eliminate Unused CSS:** Use purging tools to scan your HTML and remove code blocks that are never used on your site. (Tailwind does this automatically via its JIT compiler).
- **Critical CSS Injection:** Inline only the essential CSS required to render the top part of your page (above-the-fold content) directly in the HTML `<head>`, then load the rest asynchronously.
- **Modern CSS File Formats:** Leverage natively optimized layout systems like CSS Grid and Flexbox, which require significantly less code than old float-based layout hacks.

GLOSSARY OF CSS TERMS

1. Core Concepts

- **CSS (Cascading Style Sheets)**
 - Definition: A stylesheet language used to describe the presentation, layout, and formatting of a document written in HTML or XML. The word "Cascading" refers to the specific rules that determine which style wins when multiple layout rules conflict.

Example:

CSS

```
/* The browser cascades down from global rules to specific rules */  
p { color: black; }  
  
.highlight { color: red; } /* This wins for paragraphs with  
class="highlight" */
```

- **Selector**
 - Definition: The structural part of a CSS rule that tells the browser exactly which HTML elements to target and apply styles to.
 - Example: `h1`, `p`, `.card`, `#submit-btn`, `div > p`. In `h1 { color: blue; }`, `h1` is the selector.
- **Property**
 - Definition: The specific visual characteristic or behavior of an HTML element that you want to alter (such as its size, color, spacing, or alignment).
 - Example: `background-color`, `font-size`, `margin-top`, `border-radius`, `opacity`.
- **Value**
 - Definition: The precise setting, measurement, or keyword assigned to a CSS property.
 - Example: `24px`, `bold`, `#ff0000`, `center`, `0.8`. In `font-size: 16px;`, `16px` is the value.
- **Class**
 - Definition: A reusable identifier that can be assigned to multiple HTML elements simultaneously. It is targeted in CSS using dot (.) notation.

Example:

CSS

```
.btn-primary { background: blue; color: white; }  
/* HTML: <button class="btn-primary">Click</button> */
```

- ID
 - Definition: A strictly unique identifier assigned to exactly one single HTML element per page. It is targeted in CSS using hash (#) notation and carries very high specificity.

Example:

CSS

```
#main-navigation { background: #111; }  
/* HTML: <nav id="main-navigation">...</nav> */
```

- Specificity
 - Definition: The mathematical weight and matching algorithm browsers use to determine which CSS rule is applied when an element matches multiple conflicting selectors.
 - Example: An inline style overrides an ID selector (#id); an ID selector overrides a class selector (.class); a class overrides an element selector (div).

2. Layout & Box Model

- Box Model
 - Definition: The foundational design architecture of the web, where every HTML element is treated as a rectangular box consisting of four distinct concentric layers: Content, Padding, Border, and Margin.

Example:

CSS

```
.box {  
    width: 300px;      /* Content Layer */  
    padding: 20px;     /* Padding Layer (Inside border) */  
    border: 5px solid; /* Border Layer */  
    margin: 15px;      /* Margin Layer (Outside border) */  
}
```

- **Flexbox (Flexible Box Layout)**
 - **Definition:** A one-dimensional CSS layout engine designed for distributing space and aligning items along a single axis (either a row horizontally or a column vertically), even when their dimensions are dynamic or unknown.

Example:

CSS

```
.flex-container {  
    display: flex;  
    justify-content: space-between; /* Horizontal spacing alignment */  
    align-items: center;           /* Vertical alignment */  
}
```

- **Grid (CSS Grid Layout)**
 - **Definition:** A highly powerful two-dimensional structural layout engine that handles both horizontal rows and vertical columns simultaneously, allowing complex web interfaces to be built with explicit track coordinates.

Example:

CSS

```
.grid-container {  
  display: grid;  
  grid-template-columns: repeat(3, 1fr); /* 3 equal-width columns */  
  gap: 20px;                             /* Space between grid cells */  
}
```

- Display
 - Definition: The property that dictates how an element behaves structurally on a web page and how it interacts layout-wise with its surrounding neighbor elements.
 - Example:
 - `display: block;` (Takes up full width, starts on a new line; e.g., `<div>`)
 - `display: inline;` (Takes only necessary width, sits side-by-side with text; e.g., `<span>`)
 - `display: inline-block;` (Sits side-by-side like inline, but accepts height/width)
 - `display: none;` (Completely removes element from rendering tree)
- Position
 - Definition: The property that sets the coordinate system and baseline anchor used to place an element exactly where you want it within the viewport or parent wrappers.
 - Example:
 - `position: static;` (Default flow of the document)
 - `position: relative;` (Offset relative to its original default position)
 - `position: absolute;` (Placed exactly relative to its nearest positioned ancestor element)
 - `position: fixed;` (Locked directly to the viewport window; stays put when scrolling)
 - `position: sticky;` (Acts static until it hits a specified scroll threshold, then locks fixed)
 -

- Z-Index
 - Definition: Controls the precise vertical stacking order of elements along the virtual Z-axis (depth). It dictates which element appears on top when objects overlap. Only works on positioned elements.
 - Example: `.modal { position: fixed; z-index: 9999; }` (Ensures the modal sits on top of all other elements).

3. Responsive Design

- Responsive Design
 - Definition: A web creation approach where fluid layouts, scaling media, and programmatic styling adapt dynamically to look flawless across all user screen footprints, from massive smart TVs down to small smartphones.
 - Example: Changing a 4-column layout into a single-column block layout when viewed on a phone.
- Media Query
 - Definition: A functional CSS block syntax that acts like an "IF statement" in code, running block styles only if the active browser environment satisfies specific rules (like minimum viewport width).

Example:

CSS

```
@media (max-width: 768px) {  
  body { background-color: lightgray; } /* Only runs on screens 768px  
wide or smaller */  
}
```

- Breakpoint
 - Definition: The critical width thresholds pixel-wise where a website's default layout layout breaks or snaps into a completely new column or structural presentation to fit a different class of device.
 - Example: Common industry breakpoints include `640px` (mobile), `768px` (tablets), `1024px` (laptops), and `1280px` (desktops).

- Viewport
 - Definition: The literal visible canvas area of a web page that a user can see inside their active browser app window, exclusive of browser user interface toolbars.
 - Example: Measured using viewport CSS units where `100vw` equals 100% of viewport width, and `100vh` equals 100% of viewport height.

4. Typography & Colors

- Typography
 - Definition: The global discipline and styling ecosystem governing how text layouts are arranged, sized, spaced, and styled to optimize visual interest and clear reading hierarchy.
 - Example: Combining font styling choices, character tracking, clear hierarchies, and optimal reading lengths to make articles effortless to digest.
- Font Family
 - Definition: A fallback list prioritizing which specific typeface fonts the browser should choose to display text copy on screen.
 - Example: `font-family: 'Inter', Helvetica, Arial, sans-serif;` (If the user does not have 'Inter' installed, the browser falls back to Helvetica, then Arial, then any default generic sans-serif).
- Font Weight
 - Definition: Dictates the literal thickness, boldness, or stroke density of text characters. It is typically expressed in keywords or numeric steps from 100 to 900.
 - Example: `font-weight: bold;` or numeric variables like `font-weight: 400;` (Regular text) and `font-weight: 700;` (Bold header).
- Line Height
 - Definition: Determines the exact vertical distance or breathing space between baseline rows of body text paragraphs, serving as a core factor in professional reading legibility.
 - Example: `line-height: 1.6;` (Sets the line heights to 1.6 times the active text font size, highly recommended for body text readability).

- Color (and Formats)
 - Definition: Sets the foreground color tint of textual content, using various underlying programmatic standard formats.
 - Example:
 - Hexadecimal: `color: #3b82f6;`
 - RGB (Red, Green, Blue): `color: rgb(59, 130, 246);`
 - RGBA (with Alpha transparency layer): `color: rgba(59, 130, 246, 0.5);`
 - HSL (Hue, Saturation, Lightness): `color: hsl(217, 91%, 60%);`
- Text Transform
 - Definition: Explicitly controls the capitalization and grammatical formatting case rules of text blocks independently of how the text was typed in raw HTML.
 - Example: `text-transform: uppercase;` (Converts string data to all caps), `text-transform: capitalize;` (Capitalizes the initial letter of every single word).

**KEEP PRACTICING EVERY DAY
GOOD LUCK**

END OF TRAINING GUIDE