

Separation Performance Evaluation

Copyright 2025 Hiroko Watarai, Kazuki Matsumoto, Kohei Yatabe.

Table of Contents

Introduction	1
Download dataset	1
Run	1
Reference	2

Introduction

This script reproduces the result of the experiment described in Section 5.2. of our paper [1].

Download dataset

Please download [Impulse_response_Acoustic_Lab_Bar-Ilan_University_\(Reverberation_0.160s\)_3-3-3-8-3-3-3.zip](#) [2] and place it in your current directory.

Run

```
% unzip dataset
if ~exist("Impulse_response_Acoustic_Lab_Bar-
Ilan_University_(Reverberation_0.160s)_3-3-3-8-3-3-3","dir")
    mkdir Impulse_response_Acoustic_Lab_Bar-
Ilan_University_(Reverberation_0.160s)_3-3-3-8-3-3-3
    unzip("Impulse_response_Acoustic_Lab_Bar-
Ilan_University_(Reverberation_0.160s)_3-3-3-8-3-3-3.zip",...
        "Impulse_response_Acoustic_Lab_Bar-
Ilan_University_(Reverberation_0.160s)_3-3-3-8-3-3-3")
end

% install BSS-eval
if ~exist("bss_eval-master\","dir")
    unzip("https://gitlab.inria.fr/bass-db/bss_eval/-/archive/master/bss_eval-
master.zip")
end
addpath("bss_eval-master\v3.0\)")

% run
addpath(genpath("IVA"));
util_loadSampleMixture; % download SiSEC
SDRi = nan(4*56,6);
mixtureIdx = 0;
count = 0;
wb = waitbar(count);
for mixingSystemIdx = 1:4
    for sourcePairIdx = 1:56
        mixtureIdx = mixtureIdx + 1;
```

```

[x,s,fs] = util_reproduceExperiment1Mixture(mixingSystemIdx,
sourcePairIdx);

SDRi(mixtureIdx,1) = util_calcSDRi(s,x,run_IVA_FastADMM(x));
SDRi(mixtureIdx,2) = util_calcSDRi(s,x,run_IVA_ADMM(x));
SDRi(mixtureIdx,3) = util_calcSDRi(s,x,run_IVA_PDS(x));
SDRi(mixtureIdx,4) = util_calcSDRi(s,x,run_IVA_AuxIP2(x));
SDRi(mixtureIdx,5) = util_calcSDRi(s,x,run_IVA_AuxISS(x));
SDRi(mixtureIdx,6) = util_calcSDRi(s,x,run_IVA_AuxIP(x));

waitbar(count/224,wb,count+" / 224");
count = count + 1;

boxchart(SDRi);
xticklabels(["FastADMM","ADMM","PDS","IP","ISS","IP2"]);
ylabel("SDRi [dB]");
drawnow
end
end
close(wb)

% visualize the result
boxchart(SDRi);
xticklabels(["FastADMM","ADMM","PDS","IP","ISS","IP2"]);
ylabel("SDRi [dB]");

```

Reference

1. H. Watarai, K. Matsumoto, and K. Yatabe, "Fast and flexible algorithm for determined blind source separation based on alternating direction method of multipliers" (2025).
2. E. Hadad, F. Heese, P. Vary, and S. Gannot, "Multichannel audio database in various acoustic environments", in International Workshop on Acoustic Signal Enhancement (2014).