


eZ publish Installation Guide



9th March 2001

 eZ systems The double squares and eZ are trademarks belonging to eZ systems of Norway, registration number NO 981 601 564 (<http://www.brreg.no/oppslag/enhet/detalj.ssc?orgnr=981601564>).

All images and text herein is Copyright 2001 eZ systems.

eZ publish is a software package released under the GPL lisence (<http://www.gnu.org/copyleft/gpl.html>), its primary point of distribution and information is <http://devel.ez.no/>

Contents

1	Introduction	4
2	Pre-requisites	5
2.1	Needed Privileges	5
2.2	Needed Software	5
2.3	Which Software is Already Installed?	6
2.3.1	Systems Using RPM	6
2.4	FreeBSD	6
2.5	IRIX	6
2.6	RAQ 3	6
2.7	Windows	6
2.8	Other Systems	7
2.9	Installation of Required Software	7
3	Compile Configuration	8
3.1	PHP	8
3.1.1	Unpacking	8
3.1.2	Configuration	8
3.1.2.1	Common	8
3.1.2.2	Command Line	9
3.1.2.3	Apache Module	9
3.1.2.4	Other Web Servers	9
3.1.2.5	Creating the Configuration	9
3.1.3	Compilation	9
3.1.4	Installation	9
4	Apache Configuration	10
4.1	Dual Virtual Host	10
4.1.1	Configuring Through httpd.conf	10
4.1.1.1	User Site	10
4.1.1.2	Admin Site	10
4.1.2	Configuring Through .htaccess	11
4.1.2.1	User Site	12
4.1.2.2	Admin Site	12

5	eZ publish Installation	13
5.1	Database	13
5.2	Program Files	13
6	Now What?	15
6.1	Post Install Checklist	15
7	Installing on RAQ 3	16
8	Installing on Windows	20
8.1	Programs to Install	20
8.2	Configuration of PHP	20
8.3	Apache Configuration	20
8.4	Configuration of Virtual Host for win2000	21
8.4.1	User Site	21
8.4.2	Admin Site	21
8.5	eZ publish Installation	21

Chapter 1

Introduction

“He who asks is a fool for five minutes, but he who does not ask remains a fool forever.”

-

eZ publish is a content management system, among a lot of other things. This installation manual will try to cover the job of installing eZ publish on your server.

This manual covers installation on a Red Hat Linux system; most of what is described here can also be applied to other installations, especially if your system uses RPM for installation. For other systems you would need to do a lot of compiling yourself to make this work, or apply the system's own package manager.

Finding packages can be done directly from vendor sites, though you might not be guaranteed that you'll find the package you need. In such instances you need to download the source directly from the software developer.

Different distribution sites for different Unix systems are:

- Debian <http://www.debian.org/distrib/ftplist>
- IRIX <http://freeware.sgi.com/>
- Red Hat Linux <http://www.redhat.com/apps/download>
- SuSE Linux <http://www.suse.com/us/support/download/index.html>
- Sun <http://www.sunfreeware.com/>

The addresses to the software developers will be given where appropriate in the text.

A line starting with a hash-sign “#” are input from the user to the shell.

Chapter 2

Pre-requisites

2.1 Needed Privileges

For the standard installation (and for the moment the only method) of eZ publish you will need to have the following privileges on your system:

- Access to Apache's httpd.conf
- Access to compiler
- Access to Apache's modules
- Access to a MySQL database
- You might also need the privilege to add new libraries to your system.

You might also use other web servers than apache, but then you're on your own since we haven't tested eZ publish on other configurations. If you do try another web server, please keep a log of what you do and submit it to us (pkej@ez.no) for inclusion in future versions of this manual.

2.2 Needed Software

You also need to download and install the following packages, if they aren't present on your system already:

- MySQL (<http://www.mysql.com>) version 3.23 or later.
- libXml (<http://xmlsoft.org/#Downloads>) version 2.2.7
- libQdom () version
- ImageMagick (<http://www.imagemagick.org/>) newest version
- Apache (<http://httpd.apache.org/>) latest 1.3 release.
- Any and all modules you need for apache in addition to mod_php. (<http://modules.apache.org/>)
- PHP (<http://www.php.net/>) version 4.0.4p11 or later, you need the source code version.
- eZ publish (<http://developer.ez.no/>) version 2.0 or later stable releases.

The libraries and php will appear pre-compiled for Linux i386 on <http://developer.ez.no> in the future. The software is listed in the order of installation.

2.3 Which Software is Already Installed?

2.3.1 Systems Using RPM

RPM is a system for distributing pre-compiled software. The packages also contain pre-configured settings and initialisation files, leaving almost nothing to the user, except deciding what to install.

To check if a package is available on your system you can run the following command (RPM based systems “rpm -qa | grep <name of program/library>”). If you need to know where you can find the different files from that package you can follow up on the previous command with the following “rpm -ql <rpm name>”. RPM name is one of the returned names from the previous command, example:

```
# pkej@vogel:/etc/httpd > rpm -qa | grep libxml
libxml-1.8.7-80
libxmld-1.8.7-80
# pkej@vogel:/etc/httpd > rpm -ql libxml-1.8.7-80
/usr/bin/xml-config
/usr/lib/libxml.so.1
/usr/lib/libxml.so.1.8.7
/usr/share/doc/packages/libxml
/usr/share/doc/packages/libxml/AUTHORS
/usr/share/doc/packages/libxml/COPYING
/usr/share/doc/packages/libxml/COPYING.LIB
/usr/share/doc/packages/libxml/NEWS
/usr/share/doc/packages/libxml/README
/usr/share/doc/packages/libxml/TOD0
```

2.4 FreeBSD

When installing and compiling PHP on a FreeBSD system you might encounter an error when using `-with-dom` which says you have a configure error on the lib. It turns out that the current port of libxml installs itself as `/usr/local/lib/libxml2.a` so and it goes unrecognised by configure. You can easily get around this problem by linking the libs to `libxml.a` so.

2.5 IRIX

By accessing the software manager (you must be root) you can get a list of installed software, scroll or search that list to find the packages you’re interested in. Double click on the tabs to the left to get information about where specific files are installed.

2.6 RAQ 3

There is a separate chapter (7) in this manual describing installation on a RAQ 3 server. It was kindly provided by Chris Mason,

2.7 Windows

Windows installation is described in its own chapter (8).

2.8 Other Systems

On other systems you should read the documentation for that system to learn how to find out what software is already installed.

You could try to use the command “find” to find the software. It is used thus: “find . -name *<program name>*” from the /usr/, /local/, /lib/, /share/ directories. In extreme cases you could try from the root of the system, but this will take a long time and will also hog resources on your computer. Therefore we urge you to learn how to use the proper installation features of your system to find the software already installed.

2.9 Installation of Required Software

If you’ve found pre-compiled versions of all the software packaged for use with an installation tool, you just have to install that software using the tool. Instructions for its usage is often found using the command “man <installation tool name>” or by reading your system’s documentation or the supplier’s website.

If you’ve had to download source code you will find instructions on how to compile and install the software you’ve downloaded at the software developer’s website. This requires a bit of knowledge and you should only undertake this if you feel confident about the job.

This manual will only cover configuration of the software needed and compilation of PHP to use the other software.

Chapter 3

Compile Configuration

3.1 PHP

3.1.1 Unpacking

After you have downloaded PHP you need to unpack it somewhere where you can compile and configure the software. To unpack run the command:

```
# tar zxvf php-4.0.x.tar.gz
```

Where the x is the version of php you've downloaded. Then you need to move into the directory you extracted php into:

```
# cd php-4.0.x
```

3.1.2 Configuration

You'll need either an apache module or a command line version of PHP to use eZ publish on your website. We recommend you use PHP as an apache module. You will also need the command line version if you want to use the cron jobs for periodical updates of the eZ news feed module.

Thus for our recommended installation of PHP you need both the command line and module versions of PHP.

3.1.2.1 Common

Both the command line and apache module versions need to have the following configurations added to the configuration tool:

–enable-trans-sid This lets PHP use session id's which don't rely on cookies. It does not disable normal cookie based sessions.

(<http://www.php.net/manual/en/install.configure.php#install.configure.enable-trans-sid>)

–with-mysql This tells PHP that the mysql functionality should be used.

(<http://www.php.net/manual/en/install.configure.php#install.configure.with-mysql>)

–enable-magic-quotes This tells PHP to enable magic quotes by default. you can also turn this feature on and off on a directory by directory basis in either the “.htaccess” files (if you use them) or in the setup of the virtual server in “httpd.conf”.

(<http://www.php.net/manual/en/install.configure.php#install.configure.enable-magic-quotes>)

-with-dom This configures PHP to include libxml.
(<http://www.php.net/manual/en/install.configure.php#install.configure.with-dom>)

-with-qtldom This configures PHP to include libqtdom. It isn't up on the PHP site with a link, but it works as -with-dom.

You should also go through the web page: <http://www.php.net/manual/en/install.configure.php> and make sure that there isn't other functionality you would like to have included.

3.1.2.2 Command Line

The default is to create a command line version of PHP. Therefore you don't need to add more configuration options for this.

3.1.2.3 Apache Module

To build an apache module you need to add:

-with-apxs This compiles PHP as an apache module.
(<http://www.php.net/manual/en/install.configure.php#install.configure.with-apxs>)

3.1.2.4 Other Web Servers

We haven't tested our software with other web servers than apache. If you need to try out other web servers, read this document <http://www.php.net/manual/en/install.configure.php#install.configure.servers> to learn how you configure for the web server you will be using.

3.1.2.5 Creating the Configuration

Now you just have to run the “./configure” program with the appropriate configuration directives which we discussed in the preceeding sections, for an apache module you'd do the following:

```
# ./configure --enable-trans-sid --with-mysql --with-magic-quotes
--with-apxs --with-dom --with-qtldom
```

Remember that to compile a script/cgi version you'd need to change that line to:

```
# ./configure --enable-trans-sid --with-mysql --with-magic-quotes
--with-dom --with-qtldom
```

3.1.3 Compilation

To compile you need to run the command “make”:

```
# make
```

3.1.4 Installation

To install your new PHP package you need to run the following command:

```
# make install
```

Chapter 4

Apache Configuration

For the moment we have only one solution for configuring apache.

4.1 Dual Virtual Host

4.1.1 Configuring Through httpd.conf

This set up is based on having two different virtual hosts for your administration back-end and the main site. The main site would typically be known as “www.yoursite.com” and the administration would be “admin.yoursite.com”; the names are up to you, theoretically you could have different names, for example “mysite.yoursite.com” and “administration.mysite.com”.

The virtual host is configured through the “httpd.conf” file which is the main configuration of Apache. Following is an example of such a host, remember to exchange everything within brackets (“[“ and “]”) with your preferred and local settings and also remove the brackets.

4.1.1.1 User Site

```
# User site
<VirtualHost [your.domain.com]>
  <Directory [/your/apache/documentroot/publish_dist]>
    Options FollowSymLinks Indexes ExecCGI
    AllowOverride None
  </Directory>
  RewriteEngine On
  RewriteRule ^/filemanager/filedownload/([^\s]+)/(.*)$
  [/your/apache/documentroot]/publish_dist/ezfilemanager/files/$1
  [T="application/octet-stream",S=1]
  # The lines above should appear on the same
  # line in your configuration file!
  RewriteRule !\.(gif|css|jpg|png)$ [/your/apache/documentroot]/publish_dist/index.php
  ServerAdmin [your e-mail address]
  DocumentRoot [/your/apache/documentroot]/publish_dist
  ServerName [your.domain.com]
  ServerAlias publish
</VirtualHost>
```

4.1.1.2 Admin Site

```
# Admin site
```

```
<VirtualHost admin.yourdomain.org>
  <Directory [/your/apache/documentroot/admin]>
    Options FollowSymLinks Indexes ExecCGI
    AllowOverride None
  </Directory>
  RewriteEngine On
  RewriteRule !\.(gif|css|jpg|png)$ [/your/apache/documentroot/admin/index.php]
  ServerAdmin [your_mail@domain.no]
  DocumentRoot [/your/apache/documentroot/admin]
  ServerName [admin.yourdomain.org]
  ServerAlias [admin.yourdomain.org]
</VirtualHost>
```

The format of the “httpd.conf” file is covered at <http://httpd.apache.org/docs/> for a complete understanding of the above information you’ll need to read that documentation.

The rewrite rules does the following:

```
RewriteRule ^/filemanager/filedownload/([^\.]*)$
[/your/apache/documentroot]/publish_dist/ezfilemanager/files/$1
[T="application/octet-stream",S=1]
```

This says that everything served from “/filemanager/filedownload/” should be redirected to fetch information from “publish_dist/ezfilemanager/files”. In other words, when people downloads a file from the filemanager, the file is served from the directory specified in the second part.

The “^” just after “RewriteRule” says that everything which starts with this, in other words it is a start of line marker. When working with an URL that is from the root of your site, ie. the part from the first slash after your domain name.

The “\$” sign is used to mark the end of line, in order to remember the full line.

The part “[T=“application/octet-stream”,S=1]” means that everything which is matched shall be of the specific mime type (“application/octet-stream”, ie. binary download). The “S=1” part means that if we match this rule, we should skip one rule ahead before trying to match again.

The next rewrite rule:

```
RewriteRule !\.(gif|css|jpg|png)$ [/your/apache/documentroot]/publish_dist/index.php
```

is found in both sites (admin and user). This means that every file, except gif, css, jpg and png (and files matched against the previous rule when in the user site) should be redirected to the file in the second part, ie. the index.php file. The reason for this is that we don’t want anyone trying to get direct access to anything which might be sensitive, or revealing about the site’s operation.

If you didn’t compile PHP with magic quotes; or other software relies on PHP not using magic quotes you can add the following line into each virtual host section:

```
php_value magic_quotes_gpc 1
```

NOTE: It isn’t possible to use the form <http://mysite.com/admin> at all; since the admin module assumes that the url “/” is the start of the admin pages. If you do change eZ publish code in order to do this anyway; please send the code to bf@ez.no for future inclusion.

4.1.2 Configuring Through .htaccess

Instead of using httpd.conf and rewrite rules in the virtual hosts, you can also do the rewrite rules in the .htaccess files in directory specific configuration files.

Note: You must set up apache to accept this. You still need two domains for this operation!

4.1.2.1 User Site

In your main directory (/path/to/index.php/) create a file called ".htaccess" containing the following text:

```
Options FollowSymLinks Indexes ExecCGI
RewriteEngine On
RewriteRule ^/filemanager/filedownload/([^\./]+)/(.*)$
/path/to/website/ezfilemanager/files/$1
[T="application/octet-stream",S=1]
# The lines above should appear on the same
# line in your configuration file!
RewriteRule !\.(gif|css|jpg|png)$ /path/to/website/index.php
```

4.1.2.2 Admin Site

In your admin subdomain home directory, create a file with the following text:

```
RewriteEngine On
RewriteRule !\.(gif|css|jpg|png)$ /path/to/website/admin/index.php
```

Note the extra "\" in the rewrite rule. Its slightly different to the line used in the httpd.conf method.

Chapter 5

eZ publish Installation

5.1 Database

Now you need to create a database in MySQL, the default name we use is publish, but you can change that to whatever pleases you.

```
# mysql -uroot -p publish < sql/publish.sql
```

Add a publish user in MySQL. To add a user you can use the MySQL client to log on to mysql and then create the user:

```
# mysql>grant all on publish.* to publish@localhost
identified by "secret";
```

where secret is your password. Then you need to add the default eZ publish data into your newly created database:

```
# mysql -uroot -p publish < sql/publish.sql
```

5.2 Program Files

The next step is to install the eZ publish package in your document root directory. First you need to unpack the software in a temporary directory:

```
# cd /tmp
# tar zxvf /path/to/ezpublish-2.0.tar.gz
```

The next step is to move the files to your document root:

```
# mv /tmp/publish_dist /your/apache/documentroot
```

When all this is done you need to tell eZ publish a little about the site you're running. You'll need to edit the "site.ini" file which you will find in the document root:

```
# cd /your/apache/documentroot
# vi site.ini
```

Instead of vi you can use your preferred text editor. You'll need to add information about the username, hostname and password of your database. More information on what you can do with "site.ini" can be found in the "eZ publish Customisation Guide".

The next important step is to run the script modfix. This script will create symbolic links needed and set permissions.

```
# ./modfix.sh
```

Chapter 6

Now What?

After installing eZ publish you can test your site through the URL <http://www.yoursite.com/> and you can administrate your site from the URL <http://admin.yoursite.com/>, of course, if you did anything different the names of the admin and the public site might be different.

NOTE: The default user name and password for your site will be admin/publish. Remember to change the password.

The next manual you should read is the “eZ publish Customisation Guide”, it tells you how to configure the software to use the functionality you want, as well as how you change the templates to suit your needs.

When you’re finished with the design and the initial testing you can head over to <http://zez.org/> for articles about community building as well as programming, or you can visit <http://developer.ez.no> for updates, articles about eZ publish and how to work with it, as well as keeping abreast of new developments.

6.1 Post Install Checklist

1. Consider this: all eZ publish sites has an admin site, perhaps you should call the admin host something different than admin?
2. Check that you’ve downloaded and read the configuration manual. A quick tip is to read through the file “site.ini” and change any e-mail addresses, passwords etc. to fit your own choices.
3. Log in on your admin site (<http://admin.yoursite.com/>). You will be presented with a page which will list any install problems. If any problems appear read the error message presented and follow any instructions. If that fails, read the FAQ. Then go to <http://developer.ez.no> and search the forum for anyone who have had the same problem. Also check the bug list for any open bugs covering your problem. Finally you should register to the mailing list and try asking for help there.
4. If everything is okay go to the “user” module and change the e-mail address of the site administrator immediatly.
5. Change the password of the administration user to something only you know.
6. Start browsing the public part of your site, just to check that everything is working; some of the articles supplied as default will inform you about features of the software.

Chapter 7

Installing on RAQ 3

Installing ezPublish on raq3 without messing up the GUI or voiding the warranty.

This is untested by eZ systems, and we provide this “as is” without any form of guarantee or endorsement, either explicitly or implicitly.

First, add the domain into the DNS, but do not create a virtual site.

Log in by telnet (install SSH unless you are desperate to get hacked).

Put the publish files in the directory you want to use, I used /home/sites/extrasites/mysite/web

Install mysql 3.23 or later by rpm, there is one out there. MySQL (<http://www.mysql.com>) version 3.23 or later if you want to compile

Now you need to create a database in MySQL, the default name we use is publish, but you can change that to whatever pleases you.

```
# mysql -uroot -p publish < sql/publish.sql
```

Add a publish user in MySQL. To add a user you can use the MySQL client to log on to mysql and then create the user:

```
# mysql>grant all on publish.* to publish@localhost
identified by "secret";
```

where secret is your password. Then you need to add the default eZ publish data into your newly created database:

```
# mysql -uroot -p publish < sql/publish.sql
```

Then get:

- <http://www.freesoftware.com/pub/infozip/zlib/> (zlib.tar.gz)
- <http://www.boutell.com/gd/> (gd-1.8.4.tar.gz)
- <ftp://ftp.uu.net/graphics/jpeg/jpegsrc.v6b.tar.gz> (jpegsrc.v6b.tar.gz)
- <http://www.php.net> (php-4.0.4pl1.tar.gz)

Delete all gd.h files on your system. You can find them using:

```
# find / -name gd.h
```

If there are more than one, then delete all of them.

Now add the following line to the `/etc/ld.so.conf` file:

```
/usr/local/lib
```

Save the file, and run:

```
# /sbin/ldconfig
```

This was an important part, because Apache needs this dir to find the correct modules.

Extract the zlib archive:

```
# tar -zxvf zlib.tar.gz # cd zlib-1.1.3
```

And install it:

```
# ./configure --shared
# make
# make install
```

Now install the JPEG-6b, doing the following:

```
# tar -zxvf jpegsrc.v6b.tar.gz
# cd jpeg-6b
# ./configure --enable-shared
# make
# make install
```

Install the PNG library

```
# wget http://www.libpng.org/pub/png/src/libpng-1.0.9.tar.gz
```

Then compile the package.

Get ImageMagick ImageMagick (<http://www.imagemagick.org/>) newest version Download and then:

```
# tar -zxvf Imagemagick-xxx
# cd Imagemagick-xxx
# ./configure
# make
# make install
```

Then go one directory back, and extract the GD archive using:

```
# tar -zxvf gd-xxx
# cd gd-xxx
```

Now edit the Makefile (using `vi` or `pico`) and check which modules you want. I removed the Freetype Library (`-DHAVE_LIBFREETYPE / -lfreetype`). After making the changes save the file and go back to the shell. Now compile GD:

```
# make
```

```
# make install
```

If this is giving any errors, just remove the modules you don't have (but don't remove the JPEG lib - we need that one ! :))

Now go back one dir, and extract PHP4:

```
# tar -zxvf php-4.0.4pl1.tar.gz
# cd php-4.0.4pl1
```

First remove any cache:

```
# rm config.cache
# make clean
# ./configure --with-xml --with-mysql \
--with-apxs=/usr/sbin/apxs \
--with-system-regex \
--with-zlib \
--enable-safe-mode \
--with-gdbm \
--enable-sysvsem \
--with-ftp \
--with-config-file-path=/etc/httpd/conf/ \
--enable-magic-quotes \
--with-exec-dir=/usr/sbin/httpd \
--with-dom \
--enable-trans-sid
# make
# make install
```

run /sbin/ldconfig again.

Apache: (Your mileage may vary, be wary of paths)

edit /etc/httpd/conf/httpd.conf and add the Loadmodules lines like this:

```
# Extra Modules
LoadModule php_module modules/mod_php.so
LoadModule php3_module modules/libphp3.so
LoadModule perl_module /usr/lib/apache/libperl.so
LoadModule php4_module /usr/lib/apache/libphp4.so
LoadModule php4_module lib/apache/libphp4.so
```

Reconstruction of the complete module list from all available modules

(static and shared ones) to achieve correct module execution order.

[WHENEVER YOU CHANGE THE LOADMODULE SECTION ABOVE UPDATE THIS, TOO]

```
ClearModuleList
# Extra Modules
AddModule mod_php.c
AddModule mod_php3.c
AddModule mod_perl.c
AddModule mod_php4.c
```

Add the second line below line below the rewrite stuff, above the <Virtualhost> directives.

NameVirtualHost 216.97.67.4 Include /etc/httpd/conf/extrasites.conf <VirtualHost 216.97.67.4>

create this include file and in it put the apache virtual server directives for your site.

For example:

```
# User site
<VirtualHost yourIP>
    ServerName [yourdomain.org]
    ServerAlias [www.yourdomain.org]
    <Directory [/your/site/root/]>
        Options FollowSymLinks Indexes ExecCGI
        AllowOverride None
    </Directory>
    RewriteEngine On
    RewriteRule !\.(gif|css|jpg|png)$ [/your/site/root/index.php]
    ServerAdmin [your_mail@domain.no]
    DocumentRoot [/your/site/root/]
</VirtualHost>

# Admin site
<VirtualHost admin.yourdomain.org>
    <Directory [/your/site/root/admin]>
        Options FollowSymLinks Indexes ExecCGI
        AllowOverride None
    </Directory>
    RewriteEngine On
    RewriteRule !\.(gif|css|jpg|png)$ [/your/site/root/admin/index.php]
    ServerAdmin [your_mail@domain.no]
    DocumentRoot [/your/site/root/admin]
    ServerName [admin.yourdomain.org]
    ServerAlias [admin.yourdomain.org]
</VirtualHost>
```

restart apache:

```
# /etc/rc.d/init.d/httpd stop
```

wait a few seconds then

```
# /etc/rc.d/init.d/httpd start
```

Then chown httpd.httpd * on both the domain and admin.domain directories to get it to work.

If all is well, your site should work.

Chapter 8

Installing on Windows

eZ publish on a Windows System Running Apache

Thanks to Øyvind Wærendskjold <werenskjold@disippel.net> for giving us this information. You can find a file called “install_ezpublish_win.zip” at the eZ publish site (<http://developer.ez.no>).

This is untested by eZ systems, and we provide this “as is” without any form of guarantee or endorsement, either explicitly or implicitly.

8.1 Programs to Install

Install Apache1.3.x (<http://httpd.apache.org/dist/binaries/win32/>)

Install PHP 4.0.x (<http://www.php.net/downloads.php>)

Install MySQL 3.23.x (<http://www.mysql.com/downloads/os-win32.html>)

8.2 Configuration of PHP

Remember to place php_domxml.dll in the "extension_dir" directory of apache. Modify php.ini:

```
session.save_path=\WinNT\temp
extension=php_domxml.dll # remove the comment on this line in the ini file.
extension_dir=C:\Program Files\Apache Group\Apache\extensions
```

8.3 Apache Configuration

Create the virtual hosts for apache. Use the file virtualhosts.conf in this package as a template

If you don't want to include the virtualhost config directly in httpd.conf, remember to use the include directive instead. Copy your virtualhost file to the apache configure directory and add the following line at the bottom of httpd.conf should do the trick:

```
include conf/virtualhosts.conf
```

Also remember to enable the rewrite module in httpd.conf:

```
LoadModule rewrite_module modules/ApacheModuleRewrite.dll
```

8.4 Configuration of Virtual Host for win2000

8.4.1 User Site

```
# User site
Options FollowSymLinks Indexes ExecCGI
RewriteEngine On
RewriteRule ^/filemanager/filedownload/([^\|+)]/(.*)$
[/your/apache/documentroot]/ezfilemanager/files/$1
[T="application/octet-stream",S=1]
RewriteRule !(\.(gif|css|jpg|png)$) [/your/apache/documentroot]/index.php
DocumentRoot [/your/apache/documentroot] ServerName [yourdomain.org]
ServerAlias [www.yourdomain.org]
```

8.4.2 Admin Site

```
# Admin site
Options FollowSymLinks Indexes ExecCGI
#If the following value is set directly in the
#php.ini file it will affect all domains on your
#site and create problems
php_value include_path \
"./;[/your/apache/documentroot]; \
[/your/apache/documentroot]/admin/"
RewriteEngine On
RewriteRule !.(gif|jpg|css|png)$ \
[/your/apache/documentroot]/admin/index.php
RewriteRule ^/ez(.*(gif|jpg|png)$) \
[/your/apache/documentroot]/ez$1
DocumentRoot [/your/apache/documentroot]/admin
ServerName [admin.yourdomain.org]
ServerAlias [admin.yourdomain.org]
```

8.5 eZ publish Installation

Decompress eZ publish to "c:\ezpublish", then run "modfix.bat" from the "ezpublish-win.files.zip" distribution in that catalog.

Add the file "winINIFile.php" from the "ezpublish-win.files.zip" distribution to "c:\ezpublish\classes":

- replace c:\ezpublish\classes\INIFile.php with the file from the "ezpublish-win.files.zip" distribution.
- replace c:\ezpublish\classes\eztemplate.php with the file from the "ezpublish-win.files.zip" distribution.
- replace c:\ezpublish\admin\index.php with the file from the "ezpublish-win.files.zip" distribution.